

Directory Privacy

For cPanel & WHM version 68

(cPanel >> Home >> Files >> Directory Privacy)

Overview


This interface allows you to protect specific directories in your cPanel account's files. After you enable this feature for a directory, when users attempt to view that directory via a website, the system prompts them to log in.

Note:


- This feature modifies `htaccess` and `htpasswd` configurations in order to restrict access to files on your websites.
- This feature does **not** protect directories that users access via FTP, SFTP, Web Disk, or other services, or when they access files locally.

Select a directory

To use this interface, select a directory to manage.

- To select a directory, click the desired directory's name.
- To view and select subdirectories, click the parent directory's folder icon (). Then, click the desired subdirectory name.

Notes:

- A protected directory's subdirectories inherit their parent directory's password protection.
- The lock icon () indicates that *Directory Privacy* configurations already exist for that directory.

Security Settings

Important:

You **must** perform these steps and click *Save* in order to enable this feature.

To password protect the selected directory, perform the following steps:

1. Select the *Password protect this directory* checkbox.

Note:

To remove password protection from a directory, deselect the *Password protect this directory* checkbox. Then, click *Save*.

2. Enter a display label for the directory in the *Enter a name for the protected directory* text box.

Note:

This name **only** functions as a label for the directory. Do **not** confuse it with the directory's actual name.

3. Click *Save*. A confirmation message will appear. Click *Go Back* to return to the directory's configuration.

In This Document

Related Documentation

- [Directory Privacy](#)
- [SSL TLS Wizard](#)
- [HTML Editor](#)
- [SSL TLS](#)
- [File Manager](#)

For Hosting Providers

- [Web Template Editor](#)
- [Skeleton Directory](#)
- [Security Advisor](#)
- [Security Questions](#)
- [Shell Fork Bomb Protection](#)

Important:

After you complete this process, you **must** create a user that can access this directory.

Create User

To create an authorized user for the selected directory, perform the following steps:

1. Enter the desired username in the *Username* text box.
2. Enter and confirm the new password in the appropriate text boxes.

Notes:

- The system evaluates the password that you enter on a scale of 100 points. 0 indicates a weak password, while 100 indicates a very secure password.
- Some web hosts require a minimum password strength. A green password *Strength* meter indicates that the password is equal to or greater than the required password strength.
- Click *Password Generator* to generate a strong password. For more information, read our [Password & Security](#) documentation.

3. Click *Save*. A confirmation message will appear. Click *Go Back* to return to the directory's configuration.

Note:

To change an existing user's password, enter the user's information and the new desired password. Then, click *Save*.

Authorized Users

The *Authorized Users* menu lists the directory's existing authorized users. To delete a user, select that user and click *Delete User*. A confirmation message will appear. Click *Go Back* to return to the directory's configuration.