

cPanel API 1 Functions - SpamAssassin::config

Guide to cPanel API 1

Return Data

cPanel Tags
(deprecated)

Bandwidth:
displaybandwidth

er

Bandwidth::displaybandwidth

Bandwidth::displaybandwidth

Bandwidth::displaybandwidth

▼ BoxTrapper

BoxTrapper::change_status

BoxTrapper::cleanconfigfilelist

BoxTrapper::editmsg

BoxTrapper::fetchconfigfile

BoxTrapper::getboxconfdir

BoxTrapper::listmsgsgs

BoxTrapper::logcontrols

BoxTrapper::messageaction

BoxTrapper::multimessageaction

BoxTrapper::resetmsg

BoxTrapper::saveconfigfile

BoxTrapper::saveconf

BoxTrapper::showautowhitelist

BoxTrapper::showemails

BoxTrapper::showfromname

BoxTrapper::showlog

Description

This function prints the cPanel account's Apache SpamAssassin's™ default values.

Warning:

cPanel API 1 is **deprecated**. Do not use this function. Instead, we **strongly** recommend that you use the following newer functions:

- **UAPI (recommended)** — `Email::get_spam_settings` — This function retrieves the Apache SpamAssassin™ settings for the account.
- **cPanel API 2** — `None`.

Examples

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
$print_config =  
$cpanel->api1('SpamAs  
sassin', 'config');  
// Call the function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Function information

About this module

The SpamAssassin module modifies Apache SpamAssassin settings.

About cPanel API 1

BoxTrapper:: show message

BoxTrapper:: show queue

BoxTrapper:: show queuesearch

BoxTrapper:: show queuetime

BoxTrapper:: status

BoxTrapper:: statusbutton

Branding

Branding:: file

Branding:: image

Branding:: killing

Branding:: setbrandingpkg

Branding:: setmyacctspkg

Branding:: setupdirs

Branding:: tempsetbrandingpkg

Cgi

Cgi:: backuplink

Cgi:: displayurchin

Cgi:: phpmyadminlink

Chkservd

Chkservd:: getximport

Chkservd:: getximport_ssl

ClamScanner

ClamScanner:: bars

cPAddons

cPAddons:: mainpg

Cron

Cron:: crontab_perms

CustInfo

CustInfo:: getemail

Denylp

Denylp:: adddenyip

Denylp:: deldenyip

Denylp:: listdenyips

LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
my $save_config =  
$cpliveapi->apil('SpamAssassin',  
'config'); # Call the  
function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

cPanel Tag System (deprecated)

Warning:

In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We provide this example to help developers move from the old cPanel tag system to our [LiveAPI](#) system. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs.

```
<cpanel  
Module="SpamAssassin:  
:config()">
```

cPanel API 1 accesses information about cPanel accounts.

Warning: cPanel API deprecated. We strongly recommend cPanel API or UAPI instead.

Notes:

- Th
Fe
- Ur
mi
us
20
or
20
) . `
- 20
or
20
) .

Find a function

- DiskUsage: show manager
- Email: addautoresponder
 - Email: addforward
 - Email: addfilter
 - Email: addlist
 - Email: addmx
 - Email: addpop
 - Email: addspam
 - Email: addspambox
 - Email: addspamfilter
 - Email: changemx
 - Email: checkfastmail
 - Email: checkpipewd
 - Email: clearspambox
 - Email: delautoresponder
 - Email: deldforward
 - Email: delfilter
 - Email: dellist
 - Email: delmx
 - Email: delpop
 - Email: delspam
 - Email: delspambox
 - Email: disable_spam_autodelete
 - Email: editquota
 - Email: enable_spam_autodelete
 - Email: getaging
 - Email: getsarsbody
 - Email: getsarscharset
 - Email: getsarsfrom
 - Email: getsarshtml
 - Email: getsarsinterval

Command Line

```
cpapil
--user=username
SpamAssassin config
```

Notes:

- You **must** URI-encode these values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to cPanel API 1](#) documentation or run the `cpapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapil` command:

```
/usr/local
/cpanel/bin/cpapil
```

Output (HTML)

HTML output that displays a user's Apache SpamAssassin configuration.

Parameters

This function does not accept parameters.

Returns

This function returns HTML output that displays a user's Apache SpamAssassin configuration.

- cPanel API 1 Functions - Email: addspambilter — This function modifies the minimum Apache SpamAssassin™ spam score.
- cPanel API 1 Functions - Email: delspam — This function disables Apache SpamAssassin™ for a cPanel account.

Email: getarsstart
Email: getarsstop
Email: getarssubject
Email: getmailserver
Email: getmailserveruser
Email: getpopquota
Email: has_spam_as_acl
Email: has_spam_autodelete
Email: listmaildomains
Email: listmaildomainsopt
Email: listmaildomainsoptndef
Email: mainacctdiskused
Email: passwdlist
Email: passwdpop
Email: setmxaccept
Email: spamboxstatus
Email: spamstatus
Email: tracefilter

▼ Fileman

Fileman: changeperm
Fileman: delfile
Fileman: dofileop
Fileman: emptytrash
Fileman: extractfile
Fileman: fileimg
Fileman: fmmkdir
Fileman: fmmkfile
Fileman: fmpushfile
Fileman: fmrename
Fileman: fmsavefile
Fileman: fmsaveht

- cPanel API 1 Functions - Email::spamboxstatus — This function checks whether Apache SpamAssassin™ Spam Box is enabled.
- cPanel API 1 Functions - Email::spamstatus — This function checks whether Apache SpamAssassin™ is enabled.

mfile

Fileman:: fullbacku
p

Fileman:: getfile

Fileman:: htmledito
r

Fileman:: killdir

Fileman:: listfiles

Fileman:: listfullba
ckups

Fileman:: listtempl
ates

Fileman:: restoreaf

Fileman:: restored
b

Fileman:: restorefil
e

Fileman:: restorefil
es

Fileman:: savehtml
file

Fileman:: showper
m

Fileman:: uploadfil
es

Fileman:: viewfile

▼ Frontpage

FrontPage:: addfp

FrontPage:: delfp

FrontPage:: fpstat
us

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: ftpquota

Ftp:: ftpservernam
e

Ftp:: ftpstatslogin

Ftp:: get_anonftp

Ftp:: get_anonftpin

Ftp:: get_welcome
msg

Ftp:: getftpquota

Ftp:: kill_ftp_sessi
on

Ftp:: listftpstatsurl

Ftp:: passwdftp

Ftp:: set_anonftp

Ftp:: set_anonftpin

Ftp:: set_welcome
msg

▼ Gpg

Gpg:: deletekey

Gpg:: exportkey

Gpg:: exportsecret
key

Gpg:: genkey

Gpg:: importkeys

▼ Htaccess

Htaccess:: checkpr
otected

Htaccess:: del_use
r

Htaccess:: getinde
x

Htaccess:: htdirls

Htaccess:: number
_of_users

Htaccess:: phpsele
ctable

Htaccess:: resnam
e

Htaccess:: set_pas
s

Htaccess:: set_pro
tect

Htaccess:: setinde
x

Htaccess:: setphpr
eference

Htaccess:: showus
ers

▼ ImageManager

ImageManager:: c
onvert

ImageManager:: di
mensions

ImageManager:: h
dimension

ImageManager:: s
cale

ImageManager:: th
umbnail

ImageManager:: w
dimension

▼ LastLogin

LastLogin:: lastlogi
n

▼ LeechProtect

LeechProtect:: disable

LeechProtect:: enable

LeechProtect:: setup

LeechProtect:: showpasswdfile

LeechProtect:: status

▼ LogManager

LogManager:: listdownloads

LogManager:: save settings

LogManager:: show settings

▼ MagicRevision

MagicRevision:: uri

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: del_handler

Mime:: del_hotlink

Mime:: del_mime

Mime:: del_redirect

Mime:: linkallownull

Mime:: linkenable

Mime:: linkexts

Mime:: linkrurl

Mime:: linkurls

▼ Mysql

Mysql:: adddb

Mysql:: addhost

Mysql:: adduser

Mysql:: adduserdb

Mysql:: checkdb

Mysql:: deldb

Mysql:: delhost

Mysql:: deluser

Mysql:: deluserdb

Mysql:: gethost
Mysql:: initcache
Mysql:: listdbs
Mysql:: listdbsopt
Mysql:: listusers
Mysql:: listusersopt
Mysql:: number_of
_dbs
Mysql:: number_of
_users
Mysql:: repairdb
Mysql:: routines
Mysql:: updatepriv
s

▼ Net

Net:: dnslookup
Net:: dnszone
Net:: sethastracero
ute

▼ News

News:: displaynew
s

▼ NVData

NVData:: set

▼ OptimizeWS

OptimizeWS:: load
optimizesettings
OptimizeWS:: load
optimizesettings (b
ytes)
OptimizeWS:: opti
mizews

▼ Park

Park:: disabledir
ect
Park:: getredirectu
rl
Park:: park
Park:: setredirectur
l
Park:: unpark

▼ Postgres

Postgres:: adddb
Postgres:: adduser
Postgres:: adduser
db
Postgres:: deldb
Postgres:: deluser

Postgres:: deluser
db

Postgres:: initcach
e

Postgres:: listdbso
pt

Postgres:: listusers
opt

Postgres:: number
_of_dbs

Postgres:: number
_of_users

▼ ProxyUtils

ProxyUtils:: proxya
ddress

▼ Resellers

Resellers:: accoun
tlistopt

Resellers:: themeli
stopt

▼ Serverinfo

Serverinfo:: servic
estatus

▼ SetLang

SetLang:: listlangs
opt

SetLang:: setlang

▼ SpamAssassin

SpamAssassin:: co
nfig

SpamAssassin:: sa
veconfig

▼ SSH

SSH:: getport

▼ SSL

SSL:: delete

SSL:: deletectr

SSL:: deletecsr

SSL:: deletekey

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcabundle

SSL:: getcname

SSL:: install

SSL:: installedhost

SSL:: listkeysopt

SSL:: showcrt

SSL:: showcsr

SSL:: showkey

SSL:: sslsharedsta
tus

SSL:: uploadcrt

SSL:: uploadkey

▼ StatManager

StatManager:: doF
orm

StatManager:: upd
ateUserConfig

▼ Stats

Stats:: analoglist

Stats:: awstats

Stats:: bwbar

Stats:: errlog

Stats:: lastvisitors

Stats:: showbandw
idth

Stats:: webalizer

Stats:: webalizerftp

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: cplist
subdomains

SubDomain:: disab
lesubrd

SubDomain:: listsu
bdomainsop

SubDomain:: setsu
burl

▼ UI

UI:: confirm

UI:: redirect

UI:: showresult