

UAPI Functions - PostgreSQL::revoke_all_privileges

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup::
fullbackup

p_to_ftp

Backup:: fullbacku
p_to_homedir

Backup:: fullbacku
p_to_scp_with_key

Backup:: fullbacku
p_to_scp_with_pa
ssword

Backup:: list_back
ups

Bandwidth

Bandwidth:: get_e
nabled_protocols

Bandwidth:: get_re
tention_periods

Bandwidth:: query

Batch

Batch:: strict

Brand

Brand:: read

Branding

Branding:: file

Branding:: get_app
lications

Branding:: get_app
lication_informatio
n

Branding:: get_ava
ilable_applications

Branding:: get_info
rmation_for_applic
ations

Description

This function revokes all privileges for a PostgreSQL® database from a database user.

Important:

In cPanel & WHM version 76 and later, when you disable the `Postgres` role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.exam  
ple.com:2083/cpsess##  
#####/execute/Post  
gresql/revoke_all_pri  
vileges?user=example_  
dbuser&database=examp  
le_database
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

Func tion infor mati on

About this mod ule

The `Postgresql` module manages PostgreSQL database users.

About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster
 - CacheBuster:: read
 - CacheBuster:: update
- Chkservd
 - Chkservd:: get_external_ports
 - Chkservd:: get_external_ports_ssl
- Chrome
 - Chrome:: get_domain
- Contactus
 - Contactus:: is_enabled
- cPAddons
 - cPAddons:: get_available_addons
 - cPAddons:: get_instance_settings
 - cPAddons:: list_addon_instances
- cPGreyList
 - cPGreyList:: disable_all_domains
 - cPGreyList:: disable_domains
 - cPGreyList:: enable_all_domains
 - cPGreyList:: enable_domains
 - cPGreyList:: has_reylisting_enabled
 - cPGreyList:: list_domains
- DAV
 - DAV:: disable_shared_global_addressbook
 - DAV:: enable_shared_global_addressbook
 - DAV:: get_calendar_contacts_config
 - DAV:: has_shared_global_addressbook
 - DAV:: is_dav_service_enabled

LiveAPI PHP Class

```

$cpanel = new
CPANEL(); // Connect
to cPanel - only do
this once.

// Revokes all
privileges from
PostgreSQL database
user "example_dbuser"
for database
"example_database"
$grant_all =
$cpanel->uapi(
    'Postgresql',
    'revoke_all_privilege
s',
    array(
        'user' =>
        'example_dbuser',
        'database'=>
        'example_database',
    )
);

```

Note:
For more information, read our [Guide to the LiveAPI System](#).

Notes:

- The *Fe*
- Ur
mu
us
20
or
20
)
'
20
or
20
)

**Find
a
funct
ion**

Post
gres
ql m
odul
e
man
ages
Post
greS
QL®
data
base
s
and
user
s.

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

Email:: add_spam_filter

▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# Revokes all  
privileges from  
PostgreSQL database  
user "example_dbuser"  
for database  
"example_database"  
my $grant_all =  
$cpliveapi->uapi(  
    'Postgresql',  
    'revoke_all_privileges',  
    {  
        'user' =>  
        'example_dbuser',  
        'database' =>  
        'example_database',  
    }  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

- UAPI Functions - PostgreSQL: create_database — This function creates a PostgreSQL database.
- UAPI Functions - PostgreSQL: create_user — This function creates a PostgreSQL database user.
- UAPI Functions - PostgreSQL: delete_database — This function deletes a PostgreSQL database.

Email: browse_mailbox
Email: change_mx
Email: check_fast_mail
Email: check_pipe_forwarder
Email: delete_auto_responder
Email: delete_do_main_forwarder
Email: delete_filter
Email: delete_forwarder
Email: delete_held_messages
Email: delete_list
Email: delete_mx
Email: delete_pop
Email: disable_filter
Email: disable_mailbox_autocreate
Email: disable_spam_assassin
Email: disable_spam_autodelete
Email: disable_spam_box
Email: dispatch_client_settings
Email: edit_pop_quota
Email: enable_filter
Email: enable_mailbox_autocreate
Email: enable_spam_assassin
Email: enable_spam_box
Email: fetch_charmaps
Email: fts_rescan_mailbox
Email: generate_mailman_opt
Email: get_auto_responder
Email: get_chase

▼ cPanel Template Toolkit

```
<!-- Revokes all
privileges from
PostgreSQL database
user "example_dbuser"
for database
"example_database"
-->
[% data = execute(
'Postgresql',
'revoke_all_privileges', { user =>
'example_dbuser',
database =>
'example_database' }
); %]
```

Note:

For more information, read our [Guide to Template Toolkit](#) documentation.

- UAPI Functions - PostgreSQL: get_restrictions — This function retrieves the PostgreSQL® user and database name length restrictions.

ts

Email: get_client_settings

Email: get_default_email_quota

Email: get_default_email_quota_mib

Email: get_disk_usage

Email: get_filter

Email: get_held_message_count

Email: get_mailbox_autocreate

Email: get_mailman_delegates

Email: get_main_account_disk_usage

Email: get_main_account_disk_usage_bytes

Email: get_max_email_quota

Email: get_max_email_quota_mib

Email: get_pop_quota

Email: get_spam_settings

Email: get_webmail_settings

Email: has_delegated_mailman_lists

Email: has_plaintext_authentication

Email: hold_outgoing

Email: is_integer

Email: list_autoresponders

Email: list_default_address

Email: list_domain_forwarders

Email: list_filters

Email: list_filters_backups

Email: list_forwarders

Email: list_forward

Command Line

```
uapi --user=username
Postgresql
revoke_all_privileges
user=example_dbuser
database=example_data
base
```

Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

Output (JSON)

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "metadata": {
  },
  "data": null
}
```

Note:

Use cPanel's *API Shell* interface (`cPanel >> Home >> Advanced >> API Shell`) to directly test cPanel API calls.

Parameters

ers_backups
 Email:: list_lists
 Email:: list_mail_domains
 Email:: list_mx
 Email:: list_pops
 Email:: list_pops_with_disk
 Email:: list_system_filter_info
 Email:: passwd_list
 Email:: passwd_pop
 Email:: release_outgoing
 Email:: remove_mailman_delegates
 Email:: reorder_filters
 Email:: set_always_accept
 Email:: set_default_address
 Email:: set_list_privacy_options
 Email:: stats_db_status
 Email:: store_filter
 Email:: suspend_incoming
 Email:: suspend_login
 Email:: suspend_outgoing
 Email:: trace_filter
 Email:: unsuspend_incoming
 Email:: unsuspend_login
 Email:: unsuspend_outgoing
 Email:: verify_password

Parameter	Type	Description	Possible values	Example
name	string	Required The database user's name.	A valid string. <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> Note : If database prefixing is enabled, this value must include the database prefix for the account. </div>	example_dbuser
database	string	Required The database's name.	A valid string. <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> Note : If database prefixing is enabled, this value must include the database prefix for the account. </div>	example_database

Returns

This function only returns metadata.

✓ EmailAuth
 EmailAuth:: disable_dkim
 EmailAuth:: enable_dkim
 EmailAuth:: ensure_dkim_keys_exist

EmailAuth:: fetch_
dkim_private_keys

EmailAuth:: install
_dkim_private_key
s

EmailAuth:: install
_spf_records

EmailAuth:: validat
e_current_dkims

EmailAuth:: validat
e_current_ptrs

EmailAuth:: validat
e_current_spfs

ExternalAuthenticat
ion

ExternalAuthentic
ation:: add_auth_li
nk

ExternalAuthentic
ation:: configured_
modules

ExternalAuthentic
ation:: get_authn_lin
ks

ExternalAuthentic
ation:: has_external
_auth_modules_co
nfigured

ExternalAuthentic
ation:: remove_auth
n_link

Features

Features:: has_fea
ture

Features:: list_feat
ures

Fileman

Fileman:: autocom
pletedir

Fileman:: empty_tr
ash

Fileman:: get_file_
content

Fileman:: get_file_i
nformation

Fileman:: list_files

Fileman:: save_file
_content

Fileman:: transcod
e

Fileman:: upload_fi
les

Ftp

Ftp:: add_ftp

Ftp:: allows_anonymous_ftp

Ftp:: allows_anonymous_incoming

Ftp:: delete_ftp

Ftp:: ftp_exists

Ftp:: get_ftp_daemon_info

Ftp:: get_port

Ftp:: get_quota

Ftp:: get_welcome_message

Ftp:: kill_session

Ftp:: list_ftp

Ftp:: list_ftp_with_disk

Ftp:: list_sessions

Ftp:: passwd

Ftp:: server_name

Ftp:: set_anonymous_ftp

Ftp:: set_anonymous_ftp_incoming

Ftp:: set_homedir

Ftp:: set_quota

Ftp:: set_welcome_message

▼ Integration

Integration:: fetch_url

▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

▼ LangPHP

LangPHP:: php_get_domain_handler

LangPHP:: php_get_impacted_domains

LangPHP:: php_get_installed_versions

LangPHP:: php_get

t_system_default_
version

LangPHP:: php_ge
t_vhost_versions

LangPHP:: php_ini
_get_user_basic_d
irectives

LangPHP:: php_ini
_get_user_content

LangPHP:: php_ini
_get_user_paths

LangPHP:: php_ini
_set_user_basic_d
irectives

LangPHP:: php_ini
_set_user_content

LangPHP:: php_se
t_vhost_versions

▼ LastLogin

LastLogin:: get_las
t_or_current_logge
d_in_ip

▼ Locale

Locale:: get_attri
butes

▼ Mailboxes

Mailboxes:: expun
ge_mailbox_mess
ages

Mailboxes:: expun
ge_messages_for
_mailbox_guid

Mailboxes:: get_m
ailbox_status

Mailboxes:: has_ut
f8_mailbox_names

Mailboxes:: set_utf
8_mailbox_names

▼ Market

Market:: cancel_pe
nding_ssl_certifica
te

Market:: create_sh
opping_cart

Market:: get_all_pr
oducts

Market:: get_certifi
cate_status_detail
s

Market:: get_login
_url

Market:: get_pendi
ng_ssl_certificates

Market:: get_provi

der_specific_dcv_
constraints

Market:: get_provi
ders_list

Market:: get_ssl_c
ertificate_if_availa
ble

Market:: process_s
sl_pending_queue

Market:: request_s
sl_certificates

Market:: set_status
_of_pending_queu
e_items

Market:: set_url_af
ter_checkout

Market:: validate_l
ogin_token

▼ Mime

Mime:: add_handl
er

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redire
ct

Mime:: delete_han
dler

Mime:: delete_hotli
nk

Mime:: delete_mim
e

Mime:: delete_redi
rect

Mime:: list_handler
s

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirect
s

Mime:: redirect_inf
o

▼ ModSecurity

ModSecurity:: disa
ble_all_domains

ModSecurity:: disa
ble_domains

ModSecurity:: ena
ble_all_domains

ModSecurity:: ena
ble_domains

ModSecurity:: has
_modsecurity_inst

alled

ModSecurity:: list_domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_note

Mysql:: check_database

Mysql:: create_database

Mysql:: create_user

Mysql:: delete_database

Mysql:: delete_host

Mysql:: delete_user

Mysql:: get_host_notes

Mysql:: get_privileges_on_database

Mysql:: get_restrictions

Mysql:: get_server_information

Mysql:: locate_server

Mysql:: rename_database

Mysql:: rename_user

Mysql:: repair_database

Mysql:: revoke_access_to_database

Mysql:: set_password

Mysql:: set_privileges_on_database

▼ Notifications

Notifications:: get_notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_relative_uri

▼ PassengerApps

PassengerApps:: d
isable_application

PassengerApps:: e
dit_application

PassengerApps:: e
nable_application

PassengerApps:: li
st_applications

PassengerApps:: r
egister_application

PassengerApps:: u
nregister_applicati
on

▼ PasswdStrength

PasswdStrength::
get_required_stren
gth

▼ Personalization

Personalization::se
t

Personalization::ge
t

▼ Postgresql

Postgresql:: create
_database

Postgresql:: create
_user

Postgresql:: delete
_database

Postgresql:: get_re
strictions

Postgresql:: grant_
all_privileges

Postgresql:: renam
e_database

Postgresql:: renam
e_user

Postgresql:: renam
e_user_no_passw
ord

Postgresql:: revok
e_all_privileges

Postgresql:: set_p
assword

▼ Pushbullet

Pushbullet:: send_
test_message

▼ Quota

Quota:: get_quota
_info

▼ Resellers

Resellers:: list_acc
ounts

- ▼ ResourceUsage
 - ResourceUsage:: get_usages
- ▼ Restore
 - Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- ▼ Session
 - Session:: create_temp_user
- ▼ SiteTemplates
 - SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- ▼ SpamAssassin
 - SpamAssassin:: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl_excluded_domains
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key
 - SSL:: delete_ssl
 - SSL:: disable_mail_sni
 - SSL:: enable_mail_sni
 - SSL:: fetch_best_for_domain

SSL:: fetch_cert_in
fo

SSL:: fetch_certific
ates_for_fqdns

SSL:: fetch_key_a
nd_cabundle_for_
certificate

SSL:: find_certifica
tes_for_key

SSL:: find_csrs_for
_key

SSL:: generate_ce
rt

SSL:: generate_cs
r

SSL:: generate_ke
y

SSL:: get_autoss_
excluded_domains

SSL:: get_autoss_
pending_queue

SSL:: get_autoss_
problems

SSL:: get_cabundl
e

SSL:: get_cn_nam
e

SSL:: install_ssl

SSL:: installed_ho
st

SSL:: installed_ho
sts

SSL:: is_autoss_
check_in_progress

SSL:: is_mail_sni_
supported

SSL:: is_sni_supp
orted

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_item
s

SSL:: mail_sni_sta
tus

SSL:: rebuild_mail
_sni_config

SSL:: rebuildssldb

SSL:: remove_aut
oss_excluded_do
mains

SSL:: set_autossl_excluded_domains

SSL:: set_cert_friendly_name

SSL:: set_csr_friendly_name

SSL:: set_key_friendly_name

SSL:: set_primary_ssl

SSL:: set_ssl_share

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_check

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stats

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: addsubdomain

▼ Themes

Themes:: get_theme_base

Themes:: list

Themes:: update

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflict

ts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete_user

WebDisk:: set_home_dir

WebDisk:: set_password

WebDisk:: set_permissions

▼ WebmailApps

WebmailApps:: list
webmailapps

▼ WebVhosts

WebVhost:: list_domains

WebVhost:: list_ssl_capable_domains

▼ WordPressInstance
Manager

WordPressInstanceManager:: cancel_scan

WordPressInstanceManager:: cleanup_scan

WordPressInstanceManager:: change_admin_password

WordPressInstanceManager:: configure_autoupdate

WordPressInstanceManager:: get_api_version

WordPressInstanceManager:: get_instance_by_id

WordPressInstanceManager:: get_instances

WordPressInstanceManager:: get_latest_wordpress_version_from_wordpress_org

WordPressInstanceManager:: get_scan_results

WordPressInstanceManager:: is_installer_addon_available

WordPressInstanceManager:: start_scan