

# The cpanel.config File

Overview  
Cached values  
Configuration setting validation  
    Absent cpanel.config file  
    Absent values  
    Invalid values  
Keys and default settings  
Additional documentation

## Overview

The `/var/cpanel/cpanel.config` file stores all of the settings that exist in WHM's [Tweak Settings](#) interface (*WHM >> Home >> Server Configuration >> Tweak Settings*). For more information about the requirements for each value, read the [Keys and default settings](#) section below.

You can preconfigure your server's settings before you install cPanel & WHM. For instructions for how to preconfigure your server's settings before installation, read our [Customize Your Installation](#) documentation.

## Cached values

To improve overall performance, the system caches the `/var/cpanel/cpanel.config` file's settings in the `cpanel.config.cache` file. This file updates each time that the `/var/cpanel/cpanel.config` file updates, to ensure that the cached settings are up-to-date.

## Configuration setting validation

The settings in the `/var/cpanel/cpanel.config` file use the key=value format. The system validates each key=value pair whenever you edit this file or change settings in WHM's [Tweak Settings](#) interface (*WHM >> Home >> Server Configuration >> Tweak Settings*).

If the system encounters problems during validation, it takes the following actions:

### Absent cpanel.config file

If the entire `/var/cpanel/cpanel.config` file does not exist, your server performs the following steps:

1. The server copies the contents of the `/etc/cpanel.config` default file and saves it as the `/var/cpanel/cpanel.config` file.
2. The server copies the contents of the `cpanel.config.cache` file, if it is present.
  - If the system cannot find the `cpanel.config.cache` file, you will receive an email notification.
  - You can change your email notification settings in WHM's [Contact Manager](#) interface (*WHM >> Home >> Server Contacts >> Contact Manager*).
3. For any dynamic values that are not set, the server attempts to guess the correct value.
  - For example, to set the `mailserver` value, the server checks whether your system uses the `dovecot` RPM.
4. The server logs the changes to the `/usr/local/cpanel/logs/error_log` file.

### Absent values

If one or more keys do not exist in the `/var/cpanel/cpanel.config` file, the server attempts to generate them from the following sources in the following order:

1. The server copies the key=value pair from the `cpanel.config.cache` file, if it exists.
2. If the key's value is static, and it does not exist in the `cpanel.config.cache` file, the system copies the key=value pair from the default value in the `/usr/local/cpanel/etc/cpanel.config` file.
3. If the key's value is dynamic, and it does not exist in the `cpanel.config.cache` file, the server calculates an appropriate value.
4. The server logs the changes to the `/usr/local/cpanel/logs/error_log` file.

### Invalid values

If one or more of the following values are invalid in the `/var/cpanel/cpanel.config` file, the server attempts to replace them with a valid value:

- mysql-version
- local\_nameserver\_type
- mailserver
- ftpserver

These variables are deprecated and we will remove them in later versions of cPanel & WHM. If you use them in custom code, update your code to use the `rpm.versions` system as soon as possible to avoid problems. For more information, read our [How to Override the `rpm.versions` System documentation](#).

## Keys and default settings

The following table lists the keys that the `/var/cpanel/cpanel.config` file stores, their *Tweak Settings* labels, default values, and validation requirements.

**Notes:**

- You can find the current cPanel-supplied default values for these keys in the `/usr/local/cpanel/etc/cpanel.config` file.
- You must edit keys that do not have an associated *Tweak Settings* tab and label in the `/var/cpanel/cpanel.config` file.

Key	<i>Tweak Settings</i> equivalent	Default and validation requirements
access_log	No <i>Tweak Settings</i> equivalent.  This setting specifies the location of cPanel's <b>Raw Access</b> logs, which contains general information about cPanel access requests.	<b>Default:</b> <code>/usr/local/cpanel/logs/access_log</code>
account_login_access	<b>System</b>  <i>Accounts that can access a cPanel user account:</i>	<b>Default:</b> <code>owner_root</code>  <div style="border: 1px solid red; padding: 5px;"><b>Warning:</b> <b>Only</b> set this key to one of the following values: <code>owner</code>, <code>owner_root</code>, or <code>user</code>.</div>
adminuser	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> <code>cpanel</code>
allow_DEPRECATED_accesshash	<b>Security</b>  <i>Allow deprecated WHM accesshash authentication.</i>	<b>Default:</b> 0  <div style="border: 1px solid red; padding: 5px;"><b>Warning:</b> We deprecated WHM's <i>Remote Access Key</i> feature in cPanel &amp; WHM version 64. We <b>strongly</b> recommend that you use API tokens instead.</div>
allow_login_autocomplete	<b>System</b>  <i>Allow autocomplete in login screens.</i>	<b>Default:</b> 1
allow_server_info_status_from	<b>System</b>  <i>Allow server-info and server-status</i>	<b>Default:</b> <code>undef</code>
allow_weak_checksums	<b>Security</b>  <i>Allow weak checksum schemes.</i>	<b>Default:</b> 0
allowcpsslinstall	<b>System</b>  <i>Allow cPanel users to install SSL Hosts</i>	<b>Default:</b> 1

allowparkhostnamedomainsubdomains	<b>Domains</b>  <i>Allow users to park subdomains of the server's hostname.</i>	<b>Default:</b> 0
allowparkonothers	<b>Domains</b>  <i>Allow cPanel users to create subdomains across accounts</i>	<b>Default:</b> 0
allowremotedomains	<b>Domains</b>  <i>Allow Remote Domains</i>	<b>Default:</b> 0
allowresellershostnamedomainsubdomains	<b>Domains</b>  <i>Allow resellers to create accounts with subdomains of the server's hostname.</i>	<b>Default:</b> 0
allowunregistereddomains	<b>Domains</b>  <i>Allow unregistered domains</i>	<b>Default:</b> 0
allowwhmparkonothers	<b>Domains</b>  <i>Allow WHM users to create subdomains across accounts</i>	<b>Default:</b> 0
alwaysredirecttossl	<b>Redirection</b>  <i>Choose the closest matched domain for which that the system has a valid certificate when redirecting from non-SSL to SSL URLs. Formerly known as "Always redirect to SSL/TLS"</i>	<b>Default:</b> 1
apache_port	<b>System</b>  <i>Apache non-SSL IP/port</i>	<b>Default:</b> 0.0.0.0:80
apache_ssl_port	<b>System</b>  <i>Apache SSL port</i>	<b>Default:</b> 0.0.0.0:443
api_shell	<b>System</b>  <i>cPanel &amp; WHM API shell (for developers)</i>	<b>Default:</b> 0
autocreateaentries	<b>Domains</b>  <i>Automatically add A entries for registered nameservers when creating a new zone</i>	<b>Default:</b> 1
autodiscover_host	<b>Domains</b>  <i>Host to publish in the SRV records for Outlook autodiscover support.</i>	<b>Default:</b> cpanelemaildiscovery.cpanel.net
autodiscover_mail_service	<b>Domains</b>  <i>Preferred mail service to configure to use for Thunderbird and Outlook autodiscover and autoconfig support</i>	<b>Default:</b> imap
autodiscover_proxy_subdomains	<b>Domains</b>  <i>Thunderbird and Outlook autodiscover and autoconfig support (enables proxy subdomain and SRV record creation)</i>	<b>Default:</b> 0

**Warning:**

This value is dynamic, and you must perform additional steps if you wish to update the value manually. We recommend that you modify this value through the cPanel & WHM interface.

autoupdate_certificate_on_hostname_mismatch	<b>Domains</b> <i>Replace SSL certificates that do not match the local hostname</i>	<b>Default:</b> 1
awstatsbrowserupdate	<b>Stats and Logs</b> <i>Allow users to update Awstats from cPanel</i>	<b>Default:</b> 0
awstatsreversedns	<b>Stats Programs</b> <i>Awstats reverse DNS resolution</i>	<b>Default:</b> 0
basename	No Tweak Settings equivalent.	<b>Default:</b> cpanel
bind_deferred_restart_time	<b>System</b> <i>DNS server reload deferral time</i>	<b>Default:</b> 0
blockcommanddomains	<b>Domains</b> <i>Prevent cPanel users from creating specific domains</i>	<b>Default:</b> 1
bwcycle	No Tweak Settings equivalent. This value specifies the bandwidth cycle.  <b>Note:</b> You can change this value in WHM's <a href="#">Statistics Software Configuration</a> interface (WHM >> Home >> Server Configuration >> Statistics Software Configuration).	<b>Default:</b> 2  <b>Note:</b> When your server validates the <code>cpanel.config</code> file, it rounds the value to the nearest quarter hour.
cgihidepass	<b>Security</b> <i>Hide login password from cgi scripts</i>	<b>Default:</b> 0
check_zone_owner	<b>Domains</b> <i>Check zone owner</i>	<b>Default:</b> 1
check_zone_syntax	<b>Domains</b> <i>Check zone syntax</i>	<b>Default:</b> 1
chkservd_check_interval	<b>System</b> <i>The number of seconds between ChkServd service checks.</i>	<b>Default:</b> 300
chkservd_hang_allowed_intervals	<b>System</b> <i>The number of times ChkServd allows a previous check to complete before termination.</i>	<b>Default:</b> 2

chkservd_plaintext_notify	<p><b>System</b></p> <p><i>The option to enable or disable ChkServd HTML notifications.</i></p>	<b>Default:</b> 0
cluster_autodisable_threshold	<p>No <i>Tweak Settings</i> equivalent.</p> <div style="border: 1px solid #f0e68c; padding: 10px;"> <p><b>Note:</b> To change this value, use the <i>Failure threshold for cluster members</i> setting in WHM's <i>DNS Cluster</i> interface (WHM &gt;&gt; Home &gt;&gt; Clusters &gt;&gt; DNS Cluster).</p> </div>	<b>Default:</b> 10
cluster_failure_notifications	<p>No <i>Tweak Settings</i> equivalent.</p> <div style="border: 1px solid #f0e68c; padding: 10px;"> <p><b>Note:</b> To change this value, select or deselect the <i>Receive a notification when WHM disables an unresponsive cluster member</i> checkbox in WHM's <i>DNS Cluster</i> interface (WHM &gt;&gt; Home &gt;&gt; Clusters &gt;&gt; DNS Cluster).</p> </div>	<b>Default:</b> 1
conserve_memory	<p><b>System</b></p> <p><i>Conserve memory</i></p>	<b>Default:</b> 0 <div style="border: 2px solid #c00; padding: 10px; margin-top: 10px;"> <p><b>Warning:</b> This value is dynamic, and you must perform additional steps if you wish to update the value manually. We recommend that you modify this value through the cPanel &amp; WHM interface.</p> </div>
cookieipvalidation	<p><b>Security</b></p> <p><i>Cookie IP validation</i></p>	<b>Default:</b> strict <div style="border: 1px solid #f0e68c; padding: 10px; margin-top: 10px;"> <p><b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will convert this value to <code>disabled</code> if it is currently 0. Otherwise, it converts this value to the default setting.</p> </div>
coredump	<p><b>Security</b></p> <p><i>Generate core dumps</i></p>	<b>Default:</b> 0
cpaddons_adminemail	<p><b>cPAddons Site Software</b></p> <p><i>cPAddons Site Software admin email</i></p>	<b>Default:</b> "" (an empty string)
cpaddons_autoupdate	<p><b>cPAddons Site Software</b></p> <p><i>cPAddons Site Software source automatic updates</i></p>	<b>Default:</b> 1
cpaddons_max_moderation_req_all_mod	<p><b>cPAddons Site Software</b></p> <p><i>Max cPAddons Site Software installation requests</i></p>	<b>Default:</b> 99

cpaddons_max_moderation_req_per_mod	cPAddons Site Software  <i>Max cPAddons Site Software installation requests per addon</i>	<b>Default:</b> 99
cpaddons_moderation_request	cPAddons Site Software  <i>cPAddons Site Software moderation notification</i>	<b>Default:</b> 0
cpaddons_no_3rd_party	cPAddons Site Software  <i>Allow cPAddons Site Software installations from non-cPanel sources</i>	<b>Default:</b> 0
cpaddons_no_modified_cpanel	cPAddons Site Software  <i>Allow cPAddons Site Software installations from modified sources</i>	<b>Default:</b> 1
cpaddons_notify_owner	cPAddons Site Software  <i>Notify reseller of cPAddons Site Software installations</i>	<b>Default:</b> 1
cpaddons_notify_root	cPAddons Site Software  <i>Notify root of cPAddons Site Software installations</i>	<b>Default:</b> 1
cpaddons_notify_users	cPAddons Site Software  <i>Notify cPanel users when they need to update their cPAddons Site Software installations</i>	<b>Default:</b> Allow users to choose
cpanel_locale	No Tweak Settings equivalent.	<b>Default:</b> undef
cpredirect	Redirection  <i>Non-SSL redirect destination</i>	<b>Default:</b> Origin Domain Name
cpredirectssl	Redirection  <i>SSL redirect destination</i>	<b>Default:</b> SSL Certificate Name
cpsrvd-domainlookup	System  <i>cpsrvd username domain lookup</i>	<b>Default:</b> 0
create_account_dkim	Domains  <i>Enable DKIM on domains for newly created accounts</i>	<b>Default:</b> 1

create_account_spf	<p><b>Domains</b></p> <p><i>Enable SPF on domains for newly created accounts</i></p> <div data-bbox="584 304 1013 608" style="border: 1px solid #ccc; padding: 10px;"> <p><b>Note:</b> The <code>/scripts/enable_spf_dkim_globally</code> script allows you to enable SPF and DKIM for accounts that exist on the server, and to create the appropriate DNS records for their domains. For more information, read our <a href="#">The SPF and DKIM Global Settings Script documentation</a>.</p> </div>	<p><b>Default:</b> 1</p> <div data-bbox="1029 234 1475 931" style="border: 1px solid #ccc; padding: 10px;"> <p><b>Note:</b> On servers that run CentOS 7, you may see a named warning about the absence of SPF resource records on DNS.</p> <ul style="list-style-type: none"> <li>• This warning is <b>not</b> relevant on CentOS 7 servers, because <a href="#">RFC 7208 deprecated SPF records</a>. CentOS 7 servers use TXT records instead of SPF records.</li> <li>• Red Hat 7.1 and CentOS 7.1 both contain <code>bind-9.9.4-23.el7</code>, which is an updated version of BIND that complies with RFC 7208. To resolve this issue, update your operating system to a version that contains the updated version of BIND. For more information, read the <a href="#">Red Hat Bugzilla case about SPF record errors</a>.</li> </ul> </div>
cycle_hours	<p>No <i>Tweak Settings</i> equivalent. This setting adjusts the frequency with which your server processes logs.</p> <div data-bbox="584 1064 1013 1296" style="border: 1px solid #ccc; padding: 10px;"> <p><b>Note:</b> You can change this value in WHM's <i>Statistics Schedule Configuration</i> interface (<i>WHM &gt;&gt; Home &gt;&gt; Server Configuration &gt;&gt; Statistics Software Configuration</i>).</p> </div>	<p><b>Default:</b> 24</p> <div data-bbox="1029 1015 1475 1199" style="border: 1px solid #ccc; padding: 10px;"> <p><b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will round this value to the nearest quarter hour.</p> </div>
database_prefix	<p><b>SQL</b></p> <p><i>Require a username prefix on names of new databases and database users</i></p>	<p><b>Default:</b> 1</p>

debughooks	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> 0
	<p><b>Warning:</b>  This setting acts as a fallback setting for the values in the <code>/var/cpanel/debughooks</code> file.</p> <ul style="list-style-type: none"> <li>The <i>Standardized Hooks - Debug Mode</i> option in the <i>Development</i> section of WHM's <i>Tweak Settings</i> interface (<code>WHM &gt;&gt; Home &gt;&gt; Server Configuration &gt;&gt; Tweak Settings</code>) controls this file.</li> <li>For more information about the <code>debughooks</code> key, read our <a href="#">Guide to Standardized Hooks - Debug Mode documentation</a>.</li> </ul>	
default_archive-logs	<b>Stats and Logs</b>  <i>Archive logs in the user's home directory at the end of each stats run unless configured by the user.</i>	<b>Default:</b> 1
default_login_theme	<b>Display</b>  <i>Default login theme</i>	<b>Default:</b> cpanel
default_remove-old-archived-logs	<b>Stats and Logs</b>  <i>Remove the previous month's archived logs from the user's home directory at the end of each month unless configured by the user.</i>	<b>Default:</b> 1
defaultmailaction	<b>Mail</b>  <i>Initial default/catch-all forwarder destination</i>	<b>Default:</b> localuser
default_pkg_bwlimit	<b>Packages</b>  <i>Default bandwidth limit for new packages</i>	<b>Default:</b> 1048576 MB
default_pkg_max_emailacct_quota	<b>Packages</b>  <i>Default maximum email quota for new packages</i>	<b>Default:</b> 1024 MB
	<p><b>Important:</b>  This setting applies to each email account, <b>not</b> each cPanel account.</p>	
default_pkg_quota	<b>Packages</b>  <i>Default disk usage quota for new packages</i>	<b>Default:</b> 10240 MB
disable-php-as-reseller-security	<b>Security</b>  <i>Allow PHP to be run when logged in as a reseller to WHM</i>	<b>Default:</b> 0
disablequotocache	<b>System</b>  <i>Cache disk quota information</i>	<b>Default:</b> 0
disk_usage_include_mailman	<b>Mail</b>  <i>Include mailman in disk usage calculations</i>	<b>Default:</b> 1

disk_usage_include_sqldbs	<b>SQL</b> <i>Include databases in disk usage calculations</i>	<b>Default:</b> 1
display_cpanel_doclinks	<b>Support</b> <i>Display documentation links in cPanel interface.</i>	<b>Default:</b> 0
dnsadmin_log	<b>Logging</b> <i>Log dnsadmin requests</i>	<b>Default:</b> 0
dnsadmin_verbose_sync	<b>Logging</b> <i>Enable verbose logging of DNS zone syncing</i>	<b>Default:</b> 0
dnsadminapp	<b>Domains</b> <i>DNS request management application</i>	<b>Default:</b> undef  <b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will convert this value to <code>undef</code> if this value is an empty string.
dnslookuponconnect	<b>System</b> <i>Reverse DNS lookup upon connect</i>	<b>Default:</b> 0
docroot	No <i>Tweak Settings</i> equivalent.  This setting specifies the document root for WHM.	<b>Default:</b> /usr/local/cpanel/base
domainowner_mail_pass	<b>Mail</b> <i>Mail authentication via domain owner password</i>	<b>Default:</b> 0  <b>Warning:</b> This value is dynamic, and additional steps are required if you wish to update the value manually. We recommend that you modify this value through the cPanel & WHM interface.
dormant_services	<b>Software</b> <i>Dormant services</i>	<b>Default:</b> cpdavd, cphulkd, cpsrvd, dnsadmin, spamd  <b>Warning:</b> This value is dynamic, and additional steps are required if you wish to update the value manually. We recommend that you modify this value through the cPanel & WHM interface.
dumplogs	<b>Stats and Logs</b> <i>Delete each domain's access logs after statistics are gathered</i>	<b>Default:</b> 1
email_account_quota_default_selected	<b>Mail</b> <i>Default quota option for new email accounts</i>	<b>Default:</b> userdefined

email_account_quota_userdefined_default_value	<b>Mail</b>  <i>Default user-defined quota value for new email accounts</i>	<b>Default:</b> 250
email_outbound_spam_detect_enable	<b>Mail</b>  <i>Monitor the number of unique recipients per hour to detect potential spammers.</i>	<b>Default:</b> 1
email_outbound_spam_detect_threshold	<b>Mail</b>  <i>Number of unique recipients per hour to trigger potential spammer notification.</i>	<b>Default:</b> 500
email_send_limits_count_mailman	<b>Mail</b>  <i>Count mailman deliveries towards a domain's Max hourly emails.</i>	<b>Default:</b> 0
email_send_limits_defer_cutoff	<b>Mail</b>  <i>The percentage of email messages (above the account's hourly maximum) to queue and retry for delivery.</i>	<b>Default:</b> 125
email_send_limits_max_defer_fail_percentage	<b>Mail</b>  <i>Maximum percentage of failed or deferred messages a domain may send per hour</i>	<b>Default:</b> undef
email_send_limits_min_defer_fail_to_trigger_protection	<b>Mail</b>  <i>Number of failed or deferred messages a domain may send before protections can be triggered</i>	<b>Default:</b> 5
emailarchive	<b>Mail</b>  <i>Enable Email Archiving support</i>	<b>Default:</b> 0
emailpasswords	<b>Security</b>  <i>Send passwords when creating a new account</i>	<b>Default:</b> 0
emailsperdaynotify	<b>Mail</b>  <i>Number of emails a domain may send per day before the system sends a notification</i>	<b>Default:</b> (none)
emailusers_diskusage_critical_contact_admin	<b>Notifications</b>  <i>Notify admin or reseller when disk quota reaches "critical" state</i>	<b>Default:</b> 1
emailusers_diskusage_critical_percent	<b>Notifications</b>  <i>Account disk quota "critical" percentage</i>	<b>Default:</b> 90  <div style="border: 1px solid #f0e68c; padding: 5px;"><b>Note:</b> When your server validates the <code>cp anel.config</code> file, it will convert this value to <code>undef</code> if this value is set to 0.</div>
emailusers_diskusage_full_contact_admin	<b>Notifications</b>  <i>Notify admin or reseller when disk quota reaches "full" state</i>	<b>Default:</b> 1

emailusers_diskusage_full_percent	<p><b>Notifications</b></p> <p><i>Account disk quota "full" percentage</i></p>	<p><b>Default:</b> 98</p> <div style="border: 1px solid #f0c080; padding: 5px;"> <p><b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will convert this value to <code>undef</code> if this value is set to 0.</p> </div>
emailusers_diskusage_warn_contact_admin	<p><b>Notifications</b></p> <p><i>Notify admin or reseller when disk quota reaches "warn" state</i></p>	<p><b>Default:</b> 0</p>
emailusers_diskusage_warn_percent	<p><b>Notifications</b></p> <p><i>Account disk quota "warn" percentage</i></p>	<p><b>Default:</b> 80</p> <div style="border: 1px solid #f0c080; padding: 5px;"> <p><b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will convert this value to <code>undef</code> if this value is set to 0.</p> </div>
emailusers_mailbox_critical_percent	<p><b>Notifications</b></p> <p><i>Account disk quota "critical" percentage</i></p>	<p><b>Default:</b> 90</p> <div style="border: 1px solid #f0c080; padding: 5px;"> <p><b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will convert this value to <code>undef</code> if this value is set to 0.</p> </div>
emailusers_mailbox_full_percent	<p><b>Notifications</b></p> <p><i>Mailbox disk quota "full" percentage</i></p>	<p><b>Default:</b> 98</p> <div style="border: 1px solid #f0c080; padding: 5px;"> <p><b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will convert this value to <code>undef</code> if this value is set to 0.</p> </div>
emailusers_mailbox_warn_percent	<p><b>Notifications</b></p> <p><i>Mailbox disk quota "warn" percentage</i></p>	<p><b>Default:</b> 80</p> <div style="border: 1px solid #f0c080; padding: 5px;"> <p><b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will convert this value to <code>undef</code> if this value is set to 0.</p> </div>
emailusersbandwidthexceed	<p><b>Notifications</b></p> <p><i>Send bandwidth limit notification emails</i></p>	<p><b>Default:</b> 0</p>
emailusersbandwidthexceed70	<p><b>Notifications</b></p> <p><i>Bandwidth usage warning: 70%</i></p>	<p><b>Default:</b> 0</p>
emailusersbandwidthexceed75	<p><b>Notifications</b></p> <p><i>Bandwidth usage warning: 75%</i></p>	<p><b>Default:</b> 0</p>
emailusersbandwidthexceed80	<p><b>Notifications</b></p> <p><i>Bandwidth usage warning: 80%</i></p>	<p><b>Default:</b> 1</p>

emailusersbandwidthexceed85	<b>Notifications</b> <i>Bandwidth usage warning: 85%</i>	<b>Default:</b> 0
emailusersbandwidthexceed90	<b>Notifications</b> <i>Bandwidth usage warning: 90%</i>	<b>Default:</b> 0
emailusersbandwidthexceed95	<b>Notifications</b> <i>Bandwidth usage warning: 95%</i>	<b>Default:</b> 0
emailusersbandwidthexceed97	<b>Notifications</b> <i>Bandwidth usage warning: 97%</i>	<b>Default:</b> 0
emailusersbandwidthexceed98	<b>Notifications</b> <i>Bandwidth usage warning: 98%</i>	<b>Default:</b> 0
emailusersbandwidthexceed99	<b>Notifications</b> <i>Bandwidth usage warning: 99%</i>	<b>Default:</b> 0
empty_trash_days	<b>System</b> <i>Age of content to purge from users' File Manager Trash</i>	<b>Default:</b> disabled
enablecompileroptimizations	<b>System</b> <i>Enable optimizations for the C compiler</i>	<b>Default:</b> 0
enable_piped_logs	No <i>Tweak Settings</i> equivalent.  <b>Note:</b> To change this value, select or deselect the <i>Enable Piped Apache Logs</i> checkbox in the <i>Piped Log Configuration</i> section of WHM's <a href="#">Apache Configuration</a> interface ( <a href="#">WHM &gt;&gt; Home &gt;&gt; Service Configuration &gt;&gt; Apache Configuration</a> ).	<b>Default:</b> 0
enablefileprotect	<b>Security</b> <i>Enable File Protect</i>	<b>Default:</b> 1
engine	No <i>Tweak Settings</i> equivalent.  This setting specifies the name of the cPanel binary.	<b>Default:</b> cpanel
enginepl	No <i>Tweak Settings</i> equivalent.  This setting specifies the name of the cPanel .pl file.	<b>Default:</b> cpanel.pl
engineroot	No <i>Tweak Settings</i> equivalent.  This setting specifies the location of the cPanel binary.	<b>Default:</b> /usr/local/cpanel
exim_retention_days	<b>Stats and Logs</b> <i>The interval, in days, to retain Exim stats in the database</i>	<b>Default:</b> 30
exim-retrytime	<b>Mail</b> <i>Email delivery retry time</i>	<b>Default:</b> 60

eximmailtrap	<p><b>Mail</b></p> <p><i>Track email origin via X-Source email headers</i></p>	<p><b>Default:</b> 1</p> <div style="border: 2px solid red; padding: 5px;"> <p><b>Warning:</b> This value is dynamic, and additional steps are required if you wish to update the value manually. We recommend that you modify this value through the cPanel &amp; WHM interface.</p> </div>
extracpus	<p><b>Stats and Logs</b></p> <p><i>Extra CPUs for server load</i></p>	<p><b>Default:</b> 0</p>
file_upload_max_bytes	<p><b>System</b></p> <p><i>Max HTTP submission size</i></p>	<p><b>Default:</b> <code>undef</code></p> <div style="border: 1px solid orange; padding: 5px;"> <p><b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will convert this value to <code>undef</code> if this value contains <code>unlimited</code>.</p> </div>
file_upload_must_leave_bytes	<p><b>System</b></p> <p><i>File upload required free space</i></p>	<p><b>Default:</b> 5</p>
file_usage	<p><b>Display</b></p> <p><i>Display File Usage information in the cPanel stats bar (inode count)</i></p>	<p><b>Default:</b> 0</p>
ftppasslogs	<p><b>Stats and Logs</b></p> <p><i>Include password in the raw log download link in cPanel (via FTP).</i></p>	<p><b>Default:</b> 0</p>
ftpquotacheck_expire_time	<p><b>System</b></p> <p><i>Interval, in days, between rebuilds of the FTP quota and disk usage data (applies to Pure-FTPd only)</i></p>	<p><b>Default:</b> 30</p>
ftpserver	<p>No Tweak Settings equivalent.</p> <div style="border: 1px solid orange; padding: 5px;"> <p><b>Note:</b> You can select an FTP server in WHM's <a href="#">FTP Server Selection</a> interface (<code>WHM &gt;&gt; Home &gt;&gt; Service Configuration &gt;&gt; FTP Server Selection</code>).</p> </div>	<p><b>Default:</b> <code>pure-ftpd</code></p> <div style="border: 2px solid red; padding: 5px;"> <p><b>Warning:</b></p> <ul style="list-style-type: none"> <li>This value is dynamic, and additional steps are required if you wish to update the value manually. We recommend that you modify this value through the cPanel &amp; WHM interface.</li> <li>This variable is deprecated, and we will remove it in a later version of cPanel &amp; WHM. If you use this variable in <code>customcode</code>, update that code to use the <code>rpm.versions</code> system as soon as possible to avoid problems. For more information, read our <a href="#">How to Override the rpm.versions System</a> documentation.</li> </ul> </div>

global_dcv_rewrite_exclude	<p><b>Domains</b></p> <p><i>Use a Global DCV rewrite exclude instead of .htaccess modification (requires Apache 2.4+, EA4)</i></p> <div style="border: 1px solid #f0e68c; padding: 5px; margin-top: 10px;"> <p><b>Note:</b> This setting <b>only</b> applies to systems that run EasyApache 4 and Apache 2.4 or newer.</p> </div>	<b>Default:</b> 0
gzip_compression_level	<p><b>Compression</b></p> <p><i>gzip compression level</i></p>	<b>Default:</b> 6
gzip_pigz_block_size	<p><b>Compression</b></p> <p><i>Number of kilobyte chunks per compression work unit</i></p>	<b>Default:</b> 4096
gzip_pigz_processes	<p><b>Compression</b></p> <p><i>Number of pigz processes</i></p>	<p><b>Default:</b> 1</p> <div style="border: 2px solid #c00; padding: 10px; margin-top: 10px;"> <p><b>Warning:</b> This value is dynamic, and additional steps are required if you wish to update the value manually. We recommend that you modify this value through the cPanel &amp; WHM interface.</p> </div>
htaccess_check_recurse	<p><b>System</b></p> <p><i>Depth to recurse for .htaccess checks</i></p>	<b>Default:</b> 2
httpd_deferred_restart_time	<p><b>System</b></p> <p><i>HTTPD deferred restart time</i></p>	<b>Default:</b> 0
ignoredeprecated	<p><b>System</b></p> <p><i>Enable legacy warnings</i></p>	<b>Default:</b> 0
invite_sub	<p><b>System</b></p> <p><i>Account Invites for Subaccounts</i></p>	<b>Default:</b> On
ionice_bandwidth_processing	<p><b>System</b></p> <p><i>I/O priority level at which bandwidth usage is processed</i></p>	<b>Default:</b> 4
ionice_cpbackup	<p><b>System</b></p> <p><i>I/O priority level at which nightly backups are run</i></p>	<b>Default:</b> 3
ionice_dovecot_maintenance	<p><b>System</b></p> <p><i>I/O priority level at which dovecot_maintenance is run</i></p>	<b>Default:</b> 7
ionice_email_archive_maintenance	<p><b>System</b></p> <p><i>I/O priority level at which email_archive_maintenance is run</i></p>	<b>Default:</b> 6

ionice_ftpquotacheck	System <i>I/O priority level at which FTP quota checks are run (when Pure-FTPd is enabled)</i>	<b>Default:</b> 6
ionice_log_processing	System <i>I/O priority level at which stats logs are processed</i>	<b>Default:</b> 4
ionice_quotacheck	System <i>I/O priority level at which quota checks are run</i>	<b>Default:</b> 6
ionice_userbackup	System <i>I/O priority level at which cPanel-generated backups are run</i>	<b>Default:</b> 5
ionice_userproc	System <i>I/O priority level for user-initiated processes</i>	<b>Default:</b> 5
ipv6_control	No Tweak Settings equivalent.	<b>Default:</b> 0
ipv6_listen	System <i>Listen on IPv6 Addresses</i>	<b>Default:</b> 0
jailapache	Security <i>EXPERIMENTAL: Jail Apache Virtual Hosts using mod_ruid2 and cPanel® jailshell.</i>	<b>Default:</b> 0
jaildefaultshell	System <i>Use cPanel® jailshell by default</i>	<b>Default:</b> 0
jailmountbinsuid	System <i>Jailed /bin mounted uid</i>	<b>Default:</b> 0
<p><b>Note:</b> This setting has no effect on servers that run CentOS, CloudLinux™, or Red Hat® Enterprise Linux 7.</p>		
jailmountusrbinsuid	System <i>Jailed /usr/bin mounted uid</i>	<b>Default:</b> 0
jailprocmode	System <i>Jailed /proc mount method</i>	<b>Default:</b> mount_proc_jailedFallback_full
keepftplogs	Stats and Logs <i>Keep master FTP log file</i>	<b>Default:</b> 0
keeplogs	Stats and Logs <i>Keep log files at the end of the month</i>	<b>Default:</b> 0
keepstatslog	Stats and Logs <i>Keep stats logs</i>	<b>Default:</b> 0

loadthreshold	Status  <i>Critical load threshold</i>	<b>Default:</b> undef  <b>Warning:</b> This value is dynamic, and additional steps are required if you wish to update the value manually. We recommend that you modify this value through the cPanel & WHM interface.
local_nameserver_type	No <i>Tweak Settings</i> equivalent. This setting specifies yournameserver's type.  <div style="border: 1px solid #f0e68c; padding: 10px;"> <p><b>Note:</b> You can change this value in WHM's <a href="#">Nameserver Selection</a> interface (<i>WHM &gt;&gt; Home &gt;&gt; Service Configuration &gt;&gt; Nameserver Selection</i>).</p> </div>	<b>Default:</b> bind  <b>Warning:</b> <ul style="list-style-type: none"> <li>This value is dynamic, and additional steps are required if you wish to update the value manually. We recommend that you modify this value through the cPanel &amp; WHM interface.</li> <li>This variable is deprecated, and we will remove it in a later version of cPanel &amp; WHM. If you use this variable in customcode, update that code to use the rpm.versions system as soon as possible to avoid problems. For more information, read our <a href="#">How to Override the rpm.versions System</a> documentation.</li> </ul>
logchmod	Stats and Logs  <i>Apache log file chmod value</i>	<b>Default:</b> 640
log_successful_logins	Logging  <i>Log successful logins</i>	<b>Default:</b> 0
logout_redirect_url	Redirection  <i>Logout redirection URL</i>	<b>Default:</b> "" (an empty string)
mailbox_storage_format	Mail  <i>The storage format for new accounts</i>	<b>Default:</b> maildir

mailserver	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> dovecot
		<p><b>Warning:</b></p> <ul style="list-style-type: none"> <li>• This value is dynamic, and additional steps are required if you wish to update the value manually. We recommend that you modify this value through the cPanel &amp; WHM interface.</li> <li>• This variable is deprecated, and we will remove it in a later version of cPanel &amp; WHM. If you use this variable in customcode, update that code to use the rpm.versions system as soon as possible to avoid problems. For more information, read our <a href="#">How to Override the rpm.versions System documentation</a>.</li> </ul>
maintenance_rpm_version_check	Software <i>Maintenance cPanel RPM Check</i>	<b>Default:</b> 1
maintenance_rpm_version_digest_check	Software <i>Maintenance cPanel RPM Digest Check</i>	<b>Default:</b> 1
maxcpsrvdconnections	System <i>Max cPanel/WHM/Webmail service handlers</i>	<b>Default:</b> 200 <p><b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will convert this value to the default value if you set to less than 200.</p>
maxmailsperhour	Mail <i>Max hourly emails per domain</i>	<b>Default:</b> <code>undef</code> <p><b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will convert this value to <code>undef</code> if this value evaluates to zero.</p>
maxmem	System <i>Max cPanel process memory</i>	<b>Default:</b> 512 <p><b>Note:</b> This value is dynamic.</p>
min_time_between_apache_graceful_restarts	System <i>Minimum time between Apache graceful restarts.</i>	<b>Default:</b> 10

minpwstrength	No Tweak Settings equivalent.	<b>Default:</b> 0
	<p><b>Note:</b>            You can specify the minimum strength for cPanel users' passwords in WHM's <a href="#">Password Strength Configuration</a> interface (<a href="#">WHM &gt;&gt; Home &gt;&gt; Security Center &gt;&gt; Password Strength Configuration</a>).</p>	<p><b>Note:</b>            When your server validates the <code>cpanel.config</code> file, it will round this value to the nearest multiple of five.</p>
modsec_keep_hits	Stats and Logs  <i>The number of days to keep records of ModSecurity™ rule hits. (Use zero to keep forever).</i>	<b>Default:</b> 7
mycnf_auto_adjust_maxallowedpacket	SQL  <i>Allow cPanel &amp; WHM to determine the best value for your MySQL max_allowed_packet configuration?</i>	<b>Default:</b> 1
mycnf_auto_adjust_openfiles_limit	SQL  <i>Allow cPanel &amp; WHM to determine the best value for your MySQL open_files_limit configuration</i>	<b>Default:</b> 1
mycnf_auto_adjust_innodb_buffer_pool_size	SQL  <i>Allow cPanel &amp; WHM to determine the best value for your MySQL innodb_buffer_pool_size configuration</i>	<b>Default:</b> 1
myname	No Tweak Settings equivalent.	<b>Default:</b> cpaneld
mysql-version	No Tweak Settings equivalent.	<p><b>Default:</b> 5.7</p> <p><b>Note:</b>            You can upgrade to a new MySQL version in WHM's <a href="#">MySQL or MariaDB Upgrade</a> interface (<a href="#">WHM &gt;&gt; Home &gt;&gt; Software &gt;&gt; MariaDB/MySQL Upgrade</a> ).</p> <p><b>Warning:</b></p> <ul style="list-style-type: none"> <li>This value is dynamic, and additional steps are required if you wish to update the value manually. We recommend that you modify this value through the cPanel &amp; WHM interface.</li> <li>This variable is deprecated, and we will remove it in a later version of cPanel &amp; WHM. If you use this variable in customcode, update that code to use the <code>rpm.versions</code> system as soon as possible to avoid problems. For more information, read our <a href="#">How to Override the rpm.versions System</a> documentation.</li> </ul>

mysql-host	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> localhost  <b>Note:</b> You can specify a remote MySQL host in WHM's <a href="#">Remote MySQL interface</a> ( <i>WHM &gt;&gt; Home &gt;&gt; Databases &gt;&gt; Remote MySQL</i> ).	<b>Warning:</b> This value is dynamic, and additional steps are required if you wish to update the value manually. We recommend that you modify this value through the cPanel & WHM interface.
mysqldebug	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> 0	
nobodyspam	<b>Mail</b>  <i>Prevent "nobody" from sending mail</i>	<b>Default:</b> 0	
nocpbackuplogs	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> 0  <b>Note:</b> You can modify this setting in WHM's <a href="#">Statistics Software Configuration</a> interface ( <i>WHM &gt;&gt; Home &gt;&gt; Server Configuration &gt;&gt; Statistics Software Configuration</i> ).	
notify_expiring_certificates	<b>Notifications</b>  <i>Send notifications when certificates approach expiry</i>	<b>Default:</b> 1	
numacctlist	<b>Display</b>  <i>Number of accounts per page to display in "List Accounts".</i>	<b>Default:</b> 30  <b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will convert this value to <code>undef</code> if this value contains <code>all</code> (case insensitive).	
overwritecustomproxysubdomains	<b>Domains</b>  <i>Overwrite custom A records used for proxy subdomains</i>	<b>Default:</b> 0  <b>Warning:</b> If you enable this setting, do <b>not</b> enable the <code>proxysubdomainsoverride</code> setting. Improper configuration will create unintended consequences.	
overwritecustomsrvrecords	<b>Domains</b>  <i>Overwrite custom SRV records used by Outlook AutoDiscover support</i>	<b>Default:</b> 0	
permit_appconfig_entries_without_acls	<b>Security</b>  <i>This setting allows WHM applications and addons to execute even if an ACL list has not been defined.</i>	<b>Default:</b> 0	
permit_appconfig_entries_without_features	<b>Security</b>  <i>This setting allows cPanel and Webmail applications and addons to execute even if a feature list has not been defined.</i>	<b>Default:</b> 0	

permit_unregistered_apps_as_reseller	<b>Security</b>  Allow apps that have not registered with AppConfig to be run when logged in as a reseller to WHM.	<b>Default:</b> 0
permit_unregistered_apps_as_root	<b>Security</b>  Allow apps that have not registered with AppConfig to be run when logged in as root or a reseller with the "all" ACL in WHM.	<b>Default:</b> 0
php_max_execution_time	<b>PHP</b>  <i>cPanel PHP max execution time</i>	<b>Default:</b> 90
php_post_max_size	<b>PHP</b>  <i>cPanel PHP max POST size</i>	<b>Default:</b> 55
php_system_default_version	No Tweak Settings equivalent.  <div style="border: 1px solid #f0e68c; padding: 5px;"><b>Notes:</b><ul style="list-style-type: none"><li>This setting <b>only</b> applies to systems that run EasyApache 4.</li><li>You can set your system's default version of PHP in WHM's <a href="#">MultiPHP Manager</a> interface (<i>WHM &gt;&gt; Home &gt;&gt; Software &gt;&gt; MultiPHP Manager</i>).</li></ul></div>	<b>Default:</b> ea-php56
php_upload_max_filesize	<b>PHP</b>  <i>cPanel PHP max upload size</i>	<b>Default:</b> 50
phploader	<b>PHP</b>  <i>cPanel PHP loader</i>	<b>Default:</b> "" (an empty string)
phpopenbasedirhome	No Tweak Settings equivalent.  <div style="border: 1px solid #f0e68c; padding: 5px;"><b>Note:</b> You can enable or disable this setting in WHM's <a href="#">PHP open_basedir Tweak</a> interface (<i>WHM &gt;&gt; Home &gt;&gt; Security Center &gt;&gt; PHP open_basedir Tweak</i>).</div>	<b>Default:</b> 0
pma_disableis	<b>Software</b>  Enable phpMyAdmin information schema searches	<b>Default:</b> 0
popbeforesmtp	<b>Mail</b>  Allow users to relay mail if they use an IP address through which someone has validated an IMAP or POP3 login within the last hour (Pop-before-SMTP)	<b>Default:</b> 0
popbeforesmtppersenders	<b>Mail</b>  Add X-PopBeforeSMTP header for mail sent via POP-before-SMTP	<b>Default:</b> 0
postgresdebug	No Tweak Settings equivalent.	<b>Default:</b> 0
product	No Tweak Settings equivalent.	<b>Default:</b> cPanel

proxysubdomains	Domains <i>Proxy subdomains</i>	<b>Default:</b> 1  <div style="border: 1px solid red; padding: 5px;"><b>Warning:</b> This value is dynamic, and you must perform additional steps if you wish to update the value manually. We recommend that you modify this value through the cPanel &amp; WHM interface.</div>
proxysubdomainsfornewaccounts	Domains <i>Proxy subdomain creation</i>	<b>Default:</b> 1
proxysubdomainsoverride	Domains <i>Proxy subdomain override</i>	<b>Default:</b> 1  <div style="border: 1px solid red; padding: 5px;"><b>Warning:</b> If you enable this setting, do <b>not</b> enable the <code>overwritecustomproxysubdomains</code> setting. Improper configuration will create unintended consequences.</div>
publichtmlsubsonly	Domains <i>Restrict document roots to public_html</i>	<b>Default:</b> 0
query_apache_for_nobody_senders	No <i>Tweak Settings</i> equivalent.  <div style="border: 1px solid orange; padding: 10px;"><b>Note:</b> This setting indicates whether you enabled the <i>Query Apache server status to determine the sender of email sent from processes running as nobody</i> option in WHM's <a href="#">Exim Configuration Manager</a> interface (<a href="#">WHM &gt;&gt; Home &gt;&gt; Service Configuration &gt;&gt; Exim Configuration Manager</a>).</div>	
referrerblanksafety	Security <i>Blank referrer safety check</i>	<b>Default:</b> 0
referrersafety	Security <i>Referrer safety check</i>	<b>Default:</b> 0
remotewhmtimeout	System <i>Remote WHM timeout</i>	<b>Default:</b> 35
repquota_timeout	System <i>Disk usage/quota bailout time</i>	<b>Default:</b> 60
requiressl	Security <i>Require SSL</i>	<b>Default:</b> 1
resetpass	System <i>Reset Password for cPanel accounts</i>	<b>Default:</b> 0
resetpass_sub	System <i>Reset Password for cPanel Subaccounts</i>	<b>Default:</b> On

root	No <i>Tweak Settings</i> equivalent.  This setting specifies the location of the cPanel root installation.	<b>Default:</b> /usr/local/cpanel
rotatelogs_size_threshold_in_megabytes	<b>Stats and Logs</b>  <i>Log rotation size threshold</i>	<b>Default:</b> 300
roundcube_db	No <i>Tweak Settings</i> equivalent.  This setting specifies which type of database the Roundcube webmail application uses.	<b>Default:</b> mysql
rpmupdate_allow_kernel	<b>System</b>  <i>Enable Linux kernel update during nightly maintenance</i>	<b>Default:</b> off
RS	No <i>Tweak Settings</i> equivalent.  The cPanel interface theme.	<b>Default:</b> paper_lantern
SecurityPolicy::PasswordAge	No <i>Tweak Settings</i> equivalent.  <b>Note:</b> This setting indicates whether you enabled the <i>Password Age</i> option in WHM's <a href="#">Configure Security Policies</a> interface (WHM >> Home >> Security Center >> Configure Security Policies) and may not appear in this file until you enable it.	<b>Default:</b> 0
SecurityPolicy::PasswordStrength	No <i>Tweak Settings</i> equivalent.  <b>Note:</b> This setting indicates whether you enabled the <i>Password Strength</i> option in WHM's <a href="#">Configure Security Policies</a> interface (WHM >> Home >> Security Center >> Configure Security Policies) and may not appear in this file until you enable it.	<b>Default:</b> 0
SecurityPolicy::SourceIPCheck	No <i>Tweak Settings</i> equivalent.  <b>Note:</b> This setting indicates whether you enabled the <i>Limit logins to verified IP addresses</i> option in WHM's <a href="#">Configure Security Policies</a> interface (WHM >> Home >> Security Center >> Configure Security Policies) and may not appear in this file until you enable it.	<b>Default:</b> 0

SecurityPolicy::TwoFactorAuth	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> 0
	<p><b>Note:</b>            This setting indicates whether you enabled the <i>Two-Factor Authentication</i> option in WHM's <a href="#">Configure Security Policies</a> interface (<i>WHM &gt;&gt; Home &gt;&gt; Security Center &gt;&gt; Configure Security Policies</i>) and may not appear in this file until you enable it.</p>	
SecurityPolicy::dnsclustering	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> 0
	<p><b>Note:</b>            This setting indicates whether you enabled the <i>DNS Cluster Requests</i> option in WHM's <a href="#">Configure Security Policies</a> interface (<i>WHM &gt;&gt; Home &gt;&gt; Security Center &gt;&gt; Configure Security Policies</i>) and may not appear in this file until you enable it.</p>	
SecurityPolicy::xml-api	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> 0
	<p><b>Notes:</b></p> <ul style="list-style-type: none"> <li>This setting indicates whether you enabled the <i>API requests</i> option in WHM's <a href="#">Configure Security Policies</a> interface (<i>WHM &gt;&gt; Home &gt;&gt; Security Center &gt;&gt; Configure Security Policies</i>) and may not appear in this file until you enable it.</li> <li>cPanel &amp; WHM version 66 <b>deprecated</b> XML output.</li> </ul>	
selfsigned_generation_for_bestavailable_ssl_install	<b>Security</b>  <i>Generate a self signed SSL certificate if a CA signed certificate is not available when setting up new domains.</i>	<b>Default:</b> 1
send_error_reports	<b>Support</b>  <i>Send error reports to cPanel for analysis</i>	<b>Default:</b> 1
send_server_configuration	<b>Support</b>  <i>Send information about server configuration to cPanel for analysis</i>	<b>Default:</b> 1
send_server_usage	<b>Support</b>  <i>Send information about server usage to cPanel for analysis</i>	<b>Default:</b> 0
server_locale	<b>System</b>  <i>Server Locale</i>	<b>Default:</b> en

showwhmbwusageinmegs	<b>Stats and Logs</b> <i>Show bandwidth usage in megabytes by default in WHM</i>	<b>Default:</b> 0
signature_validation	<b>Security</b> <i>Signature validation on assets downloaded from cPanel &amp; WHM mirrors.</i>	<b>Default:</b> off
skip_chkservd_recovery_notify	<b>System</b> <i>The option to enable or disable ChkServd recovery notifications.</i>	<b>Default:</b> 0
skipanalog	<b>Stats Programs</b> <i>Enable Analog stats</i>	<b>Default:</b> 0
skipapacheclientsoptimizer	<b>No Tweak Settings equivalent.</b>	<b>Default:</b> 0
skipawstats	<b>Stats Programs</b> <i>Enable Awstats stats</i>	<b>Default:</b> 0
skipboxcheck	<b>Notifications</b> <i>Enable mailbox usage warnings</i>	<b>Default:</b> 1
skipboxtrapper	<b>Mail</b> <i>Enable BoxTrapper spam trap</i>	<b>Default:</b> 0
skipbwlimitcheck	<b>Notifications</b> <i>Bandwidth limit check</i>	<b>Default:</b> 0
skipchkservd	<b>No Tweak Settings equivalent.</b>  <b>Note:</b> This setting indicates whether you enabled the ChkServd option in WHM's <i>Service Manager</i> interface ( <i>WHM &gt;&gt; Home &gt;&gt; Service Configuration &gt;&gt; Service Manager</i> ).	<b>Default:</b> 0
skipcpbandwd	<b>No Tweak Settings equivalent.</b>	<b>Default:</b> 0
skipdiskcheck	<b>Notifications</b> <i>Disk quota usage warnings</i>	<b>Default:</b> 0
skipdiskusage	<b>Notifications</b> <i>System disk space usage warnings</i>	<b>Default:</b> 0
skipeximstats	<b>No Tweak Settings equivalent.</b>  <b>Note:</b> This setting indicates whether you enabled the Eximstats option in WHM's <i>Service Manager</i> interface ( <i>WHM &gt;&gt; Home &gt;&gt; Service Configuration &gt;&gt; Service Manager</i> ).	<b>Default:</b> 0

skiphorde	<p><b>Mail</b></p> <p><i>Enable Horde Webmail</i></p> <div style="border: 1px solid #f0c080; padding: 5px;"> <p><b>Note:</b> This setting does <b>not</b> uninstall Horde.</p> </div>	<b>Default:</b> 0
skiphttpauth	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> 0
skipjailmanager	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> 0
	<div style="border: 1px solid #f0c080; padding: 5px;"> <p><b>Note:</b> This setting indicates whether you enabled the <i>JailManager</i> option in WHM's <i>Service Manager</i> interface (<i>WHM &gt;&gt; Home &gt;&gt; Service Configuration &gt;&gt; Service Manager</i> ).</p> </div>	
skipmailauthoptimizer	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> 0
	<div style="border: 1px solid #f0c080; padding: 5px;"> <p><b>Note:</b> This setting indicates whether you enabled the <i>MailAuthOptimizer</i> option in WHM's <i>Service Manager</i> interface (<i>WHM &gt;&gt; Home &gt;&gt; Service Configuration &gt;&gt; Service Manager</i> ).</p> </div>	
skipmailman	<p><b>Mail</b></p> <p><i>Enable Mailman mailing lists</i></p>	<b>Default:</b> 0
skipmodseclog	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> 0
	<div style="border: 1px solid #f0c080; padding: 5px;"> <p><b>Note:</b> This setting indicates whether you enabled the <i>RecentAuthenticatedMailIpTracker</i> option in WHM's <i>Service Manager</i> interface (<i>WHM &gt;&gt; Home &gt;&gt; Service Configuration &gt;&gt; Service Manager</i> ).</p> </div>	
skipoomcheck	<p><b>Notifications</b></p> <p><i>Out of memory warnings.</i></p>	<b>Default:</b> On
skipnotifyacctbackupfailure	<p><b>System</b></p> <p><i>Send a notification when a user's backup has errors</i></p>	<b>Default:</b> 0
skipparentcheck	<p><b>System</b></p> <p><i>Allow other applications to run the cPanel and admin binaries</i></p>	<b>Default:</b> 0

skiprecentauthedmailiptracker	No Tweak Settings equivalent.  <div style="border: 1px solid #f0c080; padding: 5px;"> <p><b>Note:</b>            This setting indicates whether you enabled the <i>ModSecLog</i> option in WHM's <i>Service Manager</i> interface (<i>WHM &gt;&gt; Home &gt;&gt; Service Configuration &gt;&gt; Service Manager</i> ).</p> </div>	<b>Default:</b> 0
skiproundcube	Mail  <i>Enable Roundcube webmail</i>	<b>Default:</b> 0
skipspamassassin	Mail  <i>Enable Apache SpamAssassin™ spam filter</i>	<b>Default:</b> 0
skipspambox	Mail  <i>Enable Apache SpamAssassin™ Spam Box delivery for messages marked as spam (user configurable).</i>	<b>Default:</b> 1
skipsqmail	Mail  <i>Enable SquirrelMail webmail</i>	<b>Default:</b> 0
skiptailwatchd	No Tweak Settings equivalent.  <div style="border: 1px solid #f0c080; padding: 5px;"> <p><b>Note:</b>            This setting indicates whether you enabled the <i>tailwatchd</i> option in WHM's <i>Service Manager</i> interface (<i>WHM &gt;&gt; Home &gt;&gt; Service Configuration &gt;&gt; Service Manager</i> ).</p> </div>	<b>Default:</b> 0
skipwebalizer	Stats Programs  <i>Enable Webalizer stats</i>	<b>Default:</b> 0
smtpmailgidonly	Mail  <i>Restrict outgoing SMTP to root, exim, and mailman (FKA SMTP Tweak)</i>	<b>Default:</b> 0
ssh_host_key_checking	Security  <i>Enable strict SSH host key checking</i>	<b>Default:</b> disabled
statsloglevel	Stats and Logs  <i>Stats log level</i>	<b>Default:</b> 1
stats_log	No Tweak Settings equivalent.  This setting specifies the location of the <i>stats_log</i> file.	<b>Default:</b> /usr/local/cpanel/logs/stats_log

statthreshold	No <i>Tweak Settings</i> equivalent.	<b>Default:</b> 256  <b>Note:</b> If an account's available disk space is less than the amount that this value specifies, the system does not process statistics for the account.
system_diskusage_critical_percent	Notifications  <i>Account system disk usage "critical" percentage</i>	<b>Default:</b> 92.55
system_diskusage_warn_percent	Notifications  <i>Account system disk usage "warn" percentage</i>	<b>Default:</b> 82.55
tcp_check_failure_threshold	System  <i>ChkServd TCP check failure threshold</i>	<b>Default:</b> 3  <b>Note:</b> When your server validates the <code>cpanel.config</code> file, it will convert this value to <code>undef</code> if this value is set to 0.
transfers_timeout	System  <i>Number of seconds an SSH connection related to an account transfer may be inactive before timing out</i>	<b>Default:</b> 300
tweak_unset_vars	No <i>Tweak Settings</i> equivalent.  <b>Note:</b> This setting determines which items appear with a warning icon in the <i>Tweak Settings</i> interface. <ul style="list-style-type: none"> <li>• The warning icon indicates that you have not set the value since the last time cPanel &amp; WHM automatically configured it.</li> <li>• For example, this icon appears if the system configured a setting to the default value due to an absent value.</li> </ul>	<i>No default value.</i>  <b>Note:</b> The system <b>only</b> uses this value internally.
upcp_log_retention_days	Stats and Logs  <i>Number of days to retain upcp logs before purging them</i>	<b>Default:</b> 45
update_log_analysis_retention_length	Support  <i>Update analysis retention interval</i>	<b>Default:</b> 90
use_apache_md5_for_htaccess	Security  <i>Use MD5 passwords with Apache</i>	<b>Default:</b> 1

use_information_schema	<b>SQL</b> <i>Use INFORMATION_SCHEMA to acquire MySQL disk usage (MySQL 5+ required)</i>	<b>Default:</b> 1
useauthnameservers	<b>Domains</b> <i>Always use authoritative (registered) nameservers when creating a new DNS zone.</i>	<b>Default:</b> 0
usemailformailmanurl	<b>Mail</b> <i>Prefix "mail." onto Mailman URLs</i>	<b>Default:</b> 0
usemysqloldpass	<b>SQL</b> <i>Use pre-4.1-style MySQL® passwords</i>	<b>Default:</b> 0
userdirprotect	No Tweak Settings equivalent.  <b>Note:</b> You can enable or disable this setting in WHM's <a href="#">Apache mod_userdir Tweak</a> interface (WH M >> Home >> Security Center >> Apache mod_userdir Tweak).	<b>Default:</b> 0
verify_3rdparty_cpaddons	<b>Security</b> <i>Verify signatures of 3rdparty cPaddons.</i>	<b>Default:</b> 0
version	No Tweak Settings equivalent.	<b>Default:</b> 3.4
VFILTERDIR	The Exim email filter storage directory.	<b>Default:</b> /etc/vfilters
xframecpsrvd	<b>Security</b> <i>Use X-Frame-Options and X-Content-Type-Options headers with cpsrvd</i>	<b>Default:</b> 0

## Additional documentation

[Suggested documentation for cPanel users](#)[For WHM users](#)[For developers](#)

[Tweak Settings](#) — This interface allows you to configure many cPanel & WHM settings.

- [Server Information for cPanel](#)
- [How to Install WHMCS](#)
- [General System Administration](#)
- [How to Install KernelCare](#)
- [How to Authenticate your Server for cPanel Technical Support](#)
- [Recommended Security Settings](#)
- [WHM API 1 Functions - system\\_needs\\_reboot](#)
- [WHM API 1 Functions - start\\_profile\\_activation](#)
- [WHM API 1 Functions - expunge\\_mailbox\\_messages](#)
- [WHM API 1 Functions - get\\_all\\_contact\\_importances](#)

- WHM API 1 Functions - [set\\_tweaksetting](#)