

WHM API 1 Functions - editpkg

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

- Account Restoration
- restore_modules_summary
- restore_queue_activate
- restore_queue_add_task
- restore_queue_clear_all_completed_tasks
- restore_queue_clear_all_failed_tasks
- restore_queue_clear_all_pending_tasks
- restore_queue_clear_all_tasks
- restore_queue_clear_completed_task
- restore_queue_clear_pending_task
- restore_queue_is_active
- restore_queue_list_active
- restore_queue_list_completed
- restore_queue

Description

This function edits a hosting plan (package).

Note:
This function **cannot** modify package names.

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/editpkg?api.version=1&name=package1&featurelist=default&quota=unlimited
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/editpkg?api.version=1&name=package1&featurelist=default&quota=unlimited
```

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Sc
- ro
- us
- Yc
- mi
- us
- 20
- or
- 20
-)tc

ue_list_pending
restore_queue_state
restoreaccount
verify_new_username_or_restore

Accounts

accountsummary
applist
createacct
domainuserdata
editquota
forcepasswordchange
get_domain_info
getdomainowner
has_digest_auth
has_mycnf_for_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
removeacct
set_digest_auth
showbw
suspendacct
unsuspendacct
untrack_acct_id
verify_new_username

Addon Domains

Command Line

```
whmapil editpkg  
name=package1  
featurelist=default  
quota=unlimited
```

Notes:

- You **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local  
/cpanel/bin/whmapil
```

Output (JSON)

```
{  
  "data": {  
    "changepackage": [  
      ],  
      "pkg":  
      "newpackage1"  
    },  
    "metadata": {  
      "version": 1,  
      "reason": "OK",  
      "result": 1,  
      "command":  
      "editpkg"  
    }  
  }  
}
```

Find a function

- WHM API 1 Functions - killpkg — This function deletes a hosting plan (package).
- WHM API 1 Functions - _getpkge xtensioninfo rm — This function retrieves a hosting plan's package extension templates.

convert_add
on_fetch_co
nversion_de
tails

convert_add
on_fetch_do
main_details

convert_add
on_get_con
version_stat
us

convert_add
on_initiate_c
onversion

convert_add
on_list_add
on_domains

convert_add
on_list_conv
ersions

▼ Authentication

api_token_c
reate

api_token_li
st

api_token_r
evoke

api_token_u
pdate

disable_aut
hentication_
provider

disable_fail
ing_authenti
cation_provi
ders

enable_auth
entication_p
rovider

get_availabl
e_authentic
ation_provid
ers

get_login_ur
l

get_provider
_client_confi
gurations

get_provider
_configurati
on_fields

get_provider
_display_co
nfigurations

get_users_a
uthn_linked
_accounts

▼ Output (XML)

```
<result>
  <data>

  <pkg>newpackage1</pkg>
  >

  </data>
  <metadata>

  <version>1</version>

  <reason>OK</reason>

  <result>1</result>

  <command>editpkg</com  
mand>
  </metadata>
</result>
```

Note:
Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

Note:
The Access Control List (ACL) restricts some of the following parameters, which limit the features that WHM users can access. For more information, read our [Access Control Lists](#) documentation.

Parameter	Type	Description	Possible values	Example
name	string	Required The hosting plan's name.	An existing hosting plan name on the server.	package1
featurelist	string	The hosting plan's feature list. If you do not use this parameter, the function assigns the default feature list to the hosting plan's accounts.	A valid feature list name on the server.	feature_list

- WHM API 1 Sections - Packages - Package functions allow you to manage hosting plans for resellers and cPanel users.
- WHM API 1 Functions - addpkgext - This function adds a package extension to a hosting plan (package).

link_user_authn_provider	quota	string	The hosting plan's disk space quota.	<ul style="list-style-type: none"> A positive integer between one and 999,999 that represents the maximum disk space that the account may use, in Megabytes (MB). 0, unlimited, or null — The hosting plan's disk space is unlimited. 	10240
set_provider_client_configurations					
set_provider_display_configurations					
twofactorauth_disable_policy					
twofactorauth_enable_policy					
twofactorauth_generate_tfa_config					
twofactorauth_get_issuer					
twofactorauth_get_user_configs					
twofactorauth_policy_status					
twofactorauth_remove_user_config					
twofactorauth_set_issuer					
twofactorauth_set_tfa_config					
unlink_user_authn_provider					
validate_login_token					
<div style="background-color: #f0f0f0; padding: 2px;"> Backups </div> backup_config_get					
backup_config_set					
backup_date_list					
backup_destination_add					
backup_destination_delete					
backup_destination_get					
backup_destination_list					

Note: In cPanel & WHM version 70 and earlier, this parameter defaults to unlimited.

This parameter defaults to 10240.

Note: The values 0, unlimited, or null are only available to users.

backup_dest
ination_set

backup_dest
ination_valid
ate

backup_get
_transport_s
tatus

backup_list_
transported

backup_set_
list

backup_skip
_users_all

backup_skip
_users_all_s
tatus

backup_use
r_list

convert_and
_migrate_fro
m_legacy_c
onfig

get_users_w
ith_backup_
metadata

list_cparchiv
e_files

start_backgr
ound_pkgac
t

toggle_user
_backup_sta
te

▼ cPHulk

cphulk_statu
s

create_cphu
lk_record

delete_cphu
lk_record

disable_cph
ulk

enable_cph
ulk

flush_cphulk
_login_histo
ry

flush_cphulk
_login_histo
ry_for_ips

get_countrie
s_with_kno
wn_ip_rang
es

s
t
h
a
t
p
o
s
s
e
s
s
t
h
e
c
o
r
r
e
s
p
o
n
d
i
n
g
u
n
l
i
m
i
t
e
d
A
C
L
p
e
r
m
i
s
s
i
o

get_cphulk_brutes
 get_cphulk_excessive_brutes
 get_cphulk_failed_logins
 get_cphulk_user_brutes
 load_cphulk_config
 read_cphulk_records
 save_cphulk_config
 set_cphulk_config_key

▼ Databases

background_mysql_upgrade_status
 current_mysql_version
 installable_mysql_versions
 latest_available_mysql_version
 list_database_users
 list_databases
 list_mysql_databases_and_users
 remote_mysql_create_profile
 remote_mysql_create_profile_via_ssh
 remote_mysql_delete_profile
 remote_mysql_initiate_profile_activation
 remote_mysql_monitor_profile_activation
 remote_mysql_read_prof

				n
ip	string	Whether the account has a dedicated IP address. This parameter defaults to n.	<ul style="list-style-type: none"> y — The account possesses a dedicated IP address. n — The account does not possess a dedicated IP address. 	n
cgi	Boolean	Whether CGI access is enabled for the account. This parameter defaults to 1.	<ul style="list-style-type: none"> 1 — Enabled. 0 — Disabled. 	1
frontpage	Boolean	Whether Microsoft® FrontPage Extensions are enabled for the account. Note : cPanel & WHM will ignore all FrontPage settings and parameters if either of the following statements is true:	<ul style="list-style-type: none"> 1 — Enabled. 0 — Disabled. 	0

ile
remote_mysql_read_profiles
remote_mysql_update_profile
remote_mysql_validate_profile
rename_mysql_database
rename_mysql_user
rename_postgresql_database
rename_postgresql_user
set_local_mysql_root_password
set_mysql_password
set_postgresql_password
start_background_mysql_upgrade

▼ DNS

addns
addzonerecord
addzonerecord (Reverse DNS)
dumpzone
editzonerecord
get_nameserver_config
getzonerecord
has_local_authority
killdns
listmxs
listzones
lookupnsip
lookupnsips

• These server run scripts Panel & WHM versions 11.44 and Front Page Extensions 4.2.0 are not installed.

removezone
record

resetzone

resolvedom
ainname

savemxs

setresolvers

update_nam
eservers_co
nfig

▼ EasyApache

ea4_get_cur
rently_install
ed_packages

ea4_get_ea
_pkgs_state

ea4_list_pro
files

ea4_migrati
on

ea4_pre_mi
grate_check

ea4_recom
mendations

ea4_save_p
rofile

ea4_tomcat
85_add

ea4_tomcat
85_list

ea4_tomcat
85_rem

▼ Greylisting

cpgreylist_is
_server_net
block_truste
d

cpgreylist_li
st_entries_f
or_common
_mail_provid
er

cpgreylist_lo
ad_common
_mail_provid
ers_config

cpgreylist_s
ave_commo
n_mail_provi
ders_config

cpgreylist_st
atus

cpgreylist_tr
ust_entries_

• These server runscpanel & WHM versions 1.11.46 or later.

cpmod	string	The hosting plan's cPanel theme. This parameter defaults to the server's default cPanel theme.	<ul style="list-style-type: none"> paper_lantern A valid theme on the server. 	paper_lantern
language	string	The hosting plan's default locale. This parameter defaults to the server's default locale.	A two-letter ISO-3166 code.	en
max_emailaccount_quota	string	The hosting plan's maximum email account quota size. Note s:	<ul style="list-style-type: none"> A positive integer between one and 4,294,967,296 that represents the maximum email quota size, in MB. 	1024

for_common_mail_provider

cpgreylist_untrusted_entries_for_common_mail_provider

create_cpgreylist_trusted_host

delete_cpgreylist_trusted_host

disable_cpgreylist

enable_cpgreylist

load_cpgreylist_config

read_cpgreylist_deferred_entries

read_cpgreylist_trusted_host

save_cpgreylist_config

Integration

batch

cpanel

create_integration_group

create_integration_link

get_integration_link_user_config

list_integration_groups

list_integration_links

remove_integration_group

remove_integration_link

update_integration_link_token

IP Addresses

addips

delip

get_public_ip

This parameter does not affect any existing configurations.

unlimited — The account possesses an unlimited quota.

Note: The 0, unlimited, or unlimited values are only available to users that possess the c

p
get_shared_
ip
ipv6_disable_
_account
ipv6_enable_
_account
ipv6_range_
add
ipv6_range_
edit
ipv6_range_
list
ipv6_range_
remove
ipv6_range_
usage
listips
nat_checkip
nat_set_pub
lic_ip
setsiteip
▼ Mail
disable_dki
m
disable_mail
_sni
emailtrack_s
earch
emailtrack_s
tats
emailtrack_u
ser_stats
enable_dkim
enable_mail
_sni
ensure_dki
m_keys_exi
st
exim_config
uration_che
ck
expunge_m
ailbox_mess
ages
expunge_m
essages_for
_mailbox_gu
id
fetch_dkim_
private_keys
fetch_mail_

• We
e
i
n
t
r
o
d
u
c
e
d
t
h
i
s
p
a
r
a
m
e
t
e
r
i
n
c
P
a
n
e
l
&
W
H
M
v
e
r
s
i
o
n
7
0
.

o
r
r
e
s
p
o
n
d
i
n
g
u
n
l
i
m
i
t
e
d
A
C
L
p
e
r
m
i
s
s
i
o

This parameter
defaults to 1024

queue

generate_mobileconfig

get_mailbox_status

get_mailbox_status_list

get_user_email_forward_destination

hold_outgoing_email

install_dkim_private_keys

install_spf_records

is_sni_supported

list_pops_for_mail_sni_status

rebuild_mail_sni_config

release_outgoing_email

save_spamd_config

set_user_email_forward_destination

suspend_outgoing_email

unsuspend_outgoing_email

validate_current_installed_exim_config

validate_current_dkims

validate_current_ptrs

validate_current_spfs

validate_exim_configuration_syntax

			<div style="border: 1px solid black; padding: 2px; display: inline-block;">n</div>	
maxftp	string	<p>The hosting plan's maximum number of FTP accounts.</p> <p>This parameter defaults to unlimited.</p>	<ul style="list-style-type: none"> A positive integer between one and 999,999. 0, unlimited, or null — The account possesses unlimited FTP accounts. 	unlimited
maxsql	string	<p>The hosting plan's maximum number of each available type of SQL database.</p> <p>For example, if you set this value to 5 and the system administrator allows MySQL® and PostgreSQL® databases, users can create up to five MySQL databases and up to five PostgreSQL databases.</p> <p>This parameter defaults to unlimited.</p>	<ul style="list-style-type: none"> A positive integer between one and 999,999. 0, unlimited, or null — The account possesses unlimited databases. 	unlimited
maxpop	string	<p>The hosting plan's maximum number of email accounts.</p> <p>This parameter defaults to unlimited.</p>	<ul style="list-style-type: none"> A positive integer between one and 999,999. 0, unlimited, or null — The account possesses unlimited email accounts. 	unlimited
maxlists	string	<p>The hosting plan's maximum number of mailing lists.</p> <p>This parameter defaults to unlimited.</p>	<ul style="list-style-type: none"> A positive integer between one and 999,999. 0, unlimited, or null — The account possesses unlimited mailing lists. 	unlimited

▼ Market

disable_market_provider

<p>enable_market_provider</p> <p>get_adjusted_market_providers_products</p> <p>get_market_providers_commission_config</p> <p>get_market_providers_list</p> <p>get_market_providers_product_metadata</p> <p>get_market_providers_products</p> <p>set_market_product_attribute</p> <p>set_market_provider_commission_id</p> <p>▼ ModSecurity™</p> <p>modsec_add_rule</p> <p>modsec_add_vendor</p> <p>modsec_assemble_config_text</p> <p>modsec_batch_settings</p> <p>modsec_checkout_rule</p> <p>modsec_clone_rule</p> <p>modsec_deploy_all_rule_changes</p> <p>modsec_deploy_rule_changes</p> <p>modsec_deploy_settings_changes</p> <p>modsec_disable_rule</p> <p>modsec_disable_vendor</p> <p>modsec_disable_vendor_configs</p>	<p>maxsub</p> <p>maxpark</p> <p>maxaddon</p> <p>hasshell</p> <p>bwlimit</p>	<p><i>string</i></p> <p><i>string</i></p> <p><i>string</i></p> <p><i>Boolean</i></p> <p><i>string</i></p>	<p>The hosting plan's maximum number of subdomains.</p> <p>This parameter defaults to unlimited.</p> <p>The hosting plan's maximum number of parked domains (aliases).</p> <p>This parameter defaults to 0.</p> <p>The hosting plan's maximum number of addon domains.</p> <p>This parameter defaults to 0.</p> <p>Whether the account has shell access.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — The account possesses unlimited subdomains. <ul style="list-style-type: none"> • An integer between zero and 999,999. • unlimited or null — The account possesses unlimited parked domains. <ul style="list-style-type: none"> • An integer between zero and 999,999. • unlimited or null — The account possess unlimited addon domains. <ul style="list-style-type: none"> • 1 — The account has shell access. • 0 — No shell access. <ul style="list-style-type: none"> • A positive integer between one and 999,999 that represents the maximum bandwidth use, in Megabytes (MB). • 0, unlimited, or null — The account possesses unlimited bandwidth. <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>N o t : T h e 0 ,</p> </div>	<p>unlimited</p> <p>unlimited</p> <p>unlimited</p> <p>1</p> <p>1048576</p>
---	---	---	---	--	--

modsec_disable_vendor_updates
modsec_discard_all_rule_changes
modsec_discard_rule_changes
modsec_edit_rule
modsec_enable_vendor
modsec_enable_vendor_configs
modsec_enable_vendor_updates
modsec_get_config_text
modsec_get_configs
modsec_get_configs_with_changes_pending
modsec_get_log
modsec_get_rules
modsec_get_settings
modsec_get_vendors
modsec_is_installed
modsec_make_config_active
modsec_make_config_inactive
modsec_preview_vendor
modsec_remove_rule
modsec_remove_setting
modsec_remove_vendor
modsec_report_rule

The hosting plan's maximum bandwidth use.

Note

: In cPanel & WHM version 70 and earlier, this parameter defaults to unlimited.

This parameter defaults to 1048576.

unlimited, or unlimitedly available to users that possess the correct response and unlimited

modsec_set
_config_text

modsec_set
_setting

modsec_un
disable_rule

modsec_up
date_vendor

▼ Packages

_getpkgexte
nsionform

add_overrid
e_features_f
or_user

addpkg

addpkgext

changepack
age

create_featu
relist

delete_featu
relist

delpkgext

editpkg

get_availabl
e_applicatio
ns

get_availabl
e_featurelist
s

get_feature_
metadata

get_feature_
names

get_featureli
st_data

get_featureli
sts

get_users_f
eatures_sett
ings

getfeaturelis
t

getpkginfo

killpkg

listpkgs

manage_fea
tures

matchpkgs

read_feature
list

e
d
A
C
L
P
e
r
m
i
s
s
i
o

remove_override_features_for_user					
update_featurelist					
verify_user_has_feature	max_email_per_hour	string	<p>The maximum number of emails that the account can send in one hour.</p> <p>This parameter defaults to unlimited.</p> <div style="border: 1px solid black; padding: 5px;"> <p>Note : This parameter is only available in cPanel & WHM version 11.32 or later.</p> </div>	<ul style="list-style-type: none"> A positive integer. 0 or unlimited — The account can send an unlimited number of emails. 	unlimited
PHP convert_all_domains_to_fpm get_fpm_count_and_utilization is_conversion_in_progress php_get_default_accounts_to_fpm php_get_handlers php_get_impacted_domains php_get_installed_versions php_get_old_fpm_flag php_get_system_default_version php_get_versions_by_version php_get_versions php_ini_get_content php_ini_get_directives php_ini_set_content php_ini_set_directives php_set_default_accounts_to_fpm php_set_handler php_set_old_fpm_flag php_set_session_save_p	max_defer_failed_percentage	string	<p>The percentage of failed or deferred email messages that the account can send per hour before outgoing mail is rate-limited.</p> <div style="border: 1px solid black; padding: 5px;"> <p>Note : This parameter is only available in cPanel & WHM version 11.32 or later.</p> </div>	<ul style="list-style-type: none"> A positive integer. 0 or unlimited — The account can send an unlimited number of failed or deferred messages. 	unlimited

<p>ath</p> <p>php_set_system_default_version</p> <p>php_set_vhost_versions</p> <p>▼ Resellers</p> <p>acccounts</p> <p>get_public_contact</p> <p>getresellers</p> <p>listacts</p> <p>listresellers</p> <p>resellerstats</p> <p>saveaclist</p> <p>set_public_contact</p> <p>setacts</p>	<p>digestauth</p>	<p><i>Boolean</i></p>	<p>Whether to enable Digest Authentication for accounts on the hosting plan.</p> <div data-bbox="734 296 873 772" style="border: 1px solid #f0e68c; padding: 5px;"> <p>Note : This parameter is only available in cPanel & WHM version 11.34 or later.</p> </div> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • 1 — Enable. • 0 — Disable. 	<p>1</p>
<p>setresellers</p> <p>setresellerlimits</p> <p>setresellermainip</p> <p>setresellernameservers</p> <p>setresellerpackage_limit</p> <p>setupreseller</p> <p>suspendreseller</p> <p>terminatereseller</p> <p>unsetupreseller</p> <p>unsuspendreseller</p> <p>▼ RPM</p> <p>delete_rpm_version</p> <p>edit_rpm_version</p> <p>get_rpm_version_data</p> <p>install_rpm_plugin</p> <p>list_rpms</p> <p>package_m</p>	<p><i>_PACKAGE_EXTENSIONS</i></p> <p><i>string</i></p>	<p>The hosting plan's package extensions.</p> <p>If you do not provide a value, the hosting plan will not include package extensions.</p> <div data-bbox="734 1104 873 1965" style="border: 1px solid #f0e68c; padding: 5px;"> <p>Notes:</p> </div>	<p>A space-delimited list of one or more package extensions on the server.</p> <div data-bbox="896 1020 1036 1965" style="border: 1px solid #f0e68c; padding: 5px;"> <p>Notes:</p> <ul style="list-style-type: none"> • You can allow so include the extension's variable </div>	<p>extension1 extension2 extension3</p>	<p>extension1 extension2 extension3</p>

- anager_fixc
- ache
- package_m
- anager_get_
- build_log
- package_m
- anager_get_
- package_inf
- o
- package_m
- anager_is_p
- erforming_a
- ctions
- package_m
- anager_list_
- packages
- package_m
- anager_reso
- lve_actions
- package_m
- anager_sub
- mit_actions
- package_m
- anager_upgr
- ade
- uninstall_rp
- m_plugin
- ▼ Script Hooks
- delete_hook
- edit_hook
- list_hooks
- reorder_hoo
- ks
- ▼ Security
- accesshash
- authorizessh
- key
- check_remo
- te_ssh_conn
- ection
- convertopen
- sshtoputty
- deletesshke
- y
- generatessh
- keypair
- importsshke
- y
- listsshkeys
- ▼ Server
- Administration
- add_configcl
- usterserver
- configureba

- This parameter is only available in the ncPanel & WHM version 11.40 and later.
- In the ncPanel & WHM 6.8 and la

esinyourfunction call; in key = value for format. Consult the external session's documentations for details

ckgroundpro
cesskiller

configureser
vice

cors_proxy_
get

create_user
_session

delete_confi
gclusterserv
er

enable_mon
itor_all_ena
bled_service
s

get_all_cont
act_importa
nces

get_appconf
ig_applicatio
n_list

get_applicati
on_contact_
event_import
tance

get_applicati
on_contact_
importance

get_availabl
e_profiles

get_current_
profile

get_passwor
d_strength

get_remote_
access_has
h

get_service_
config

get_service_
config_key

get_tweakse
tting

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

t
e
r
,
w
e
s
t
r
o
n
g
l
y
r
e
c
o
m
m
e
n
d
t
h
a
t
y
o
u
m
a
n
a
g
e
p
a
c
k
a
g
e
e
x
t
e
n
s
i
o
n
s
t
h
r
o
u
g
h
W
H
M
A
P
I
1
,
s
a
d
d
p
k
g
e
x
t
a

t
o
f
p
o
s
s
i
b
l
e
v
a
r
i
a
b
l
e

loadavg
nvget
nvset
personalization_get
personalization_set
purchase_a_license
reboot
remove_in_progress_exim_config_edit
restartservice
restore_config_from_file
restore_config_from_upload
run_cpkeyctl
send_test_posturl
send_test_pushbullet_note
servicestatus
set_application_contact_event_importance
set_application_contact_importance
set_primary_servername
set_service_config_key
set_tweaksetting
sethostname
setminimumpasswordstrengths
start_profile_activation
system_needs_reboot
systemloada

nd
de
l
p
k
g
e
x
t
f
u
n
c
t
i
o
n

s
.
E
x
t
e
n
s
i
o
n
n
a
m
e
s
a
n
d
v
a
r
i
a
b
l
e
s
a
r
e
c
a
s
e
-
s
e
n
s
i
t
i
v
e
.

vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

fetchcrtinfo

fetchsslinfo

generatessl

get_autossl
_check_sch
edule

get_autossl
_log

get_autossl
_logs_catalo
g

get_autossl
_metadata

get_autossl
_pending_q
ueue

get_autossl
_pending_q
ueue_for_do
main

get_autossl
_pending_q
ueue_for_us
er

		s		
--	--	---	--	--

Returns

Return	Type	Description	Possible values	Example
pkg	<i>string</i>	The hosting plan's name.	The name input parameter's value.	package1

get_autossl
_problems_f
or_domain

get_autossl
_problems_f
or_user

get_autossl
_providers

get_best_ssl
domain_for_
service

install_servi
ce_ssl_certif
icate

installssl

listcrts

rebuildinstall
edssldb

rebuildusers
sldb

reset_autos
ssl_provider

reset_servic
e_ssl_certifi
cate

set_autossl_
metadata

set_autossl_
metadata_k
ey

set_autossl_
provider

start_autossl
_check_for_
all_users

start_autossl
_check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

abort_transf
er_session

analyze_tra
nsfer_sessio
n_remote

available_tr
ansfer_mod
ules

create_remo
te_root_tran
sfer_session

create_remo
te_user_tran
sfer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transf
er_session_l
og

get_transfer
_session_st
ate

pause_trans
fer_session

remote_basi
c_credential

_check

retrieve_transfer_session
_remote_analysis

start_transfer_session

transfer_module_schema

validate_system_user

▼ Updates

accept_eula

get_available_tiers

get_current_lts_expiration_status

get_lts_wexpire

getlongterm_support

installed_versions

set_cpanel_updates

set_tier

update_updateconf

version