

# UAPI Functions - Brand::read

## Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup:  
Backup::fullbacku  
p\_to\_ftp

Backup::fullbacku  
p\_to\_homedir

Backup::fullbacku  
p\_to\_scp\_with\_key

Backup::fullbacku  
p\_to\_scp\_with\_pa  
ssword

Backup::list\_back  
ups

### Bandwidth

Bandwidth::get\_e  
nabled\_protocols

Bandwidth::get\_re  
tention\_periods

Bandwidth::query

### Batch

Batch::strict

### Brand

Brand::read

### Branding

Branding::file

Branding::get\_app  
lications

Branding::get\_app  
lication\_informati  
on

Branding::get\_ava  
ilable\_applications

Branding::get\_info  
rmation\_for\_applic  
ations

## Description

This function retrieves the cPanel account's branding information. For more information, read our [Customization](#) documentation.

### Note:

cPanel accounts that do not use the Paper Lantern theme, or that use Paper Lantern without configured branding information, return blank values.

## Examples

### ▼ cPanel or Webmail Session URL

```
https://hostname.exam  
ple.com:2083/cpsess##  
#####/execute/Brand/  
read
```

### Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

### ▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// Get Paper Lantern  
branding settings.  
$pl_branding =  
$cpanel->uapi(  
    'Brand', 'read'  
);
```

### Note:

For more information, read our [Guide to the LiveAPI System](#).

## Function information

## About this module

The Brand module accesses branding data.

## About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster:: read
    - CacheBuster:: update
- Chkservd:: get\_exit\_ports
    - Chkservd:: get\_exit\_ports\_ssl
- Chrome:: get\_dom
- Contactus:: is\_enabled
- cPAddons:: get\_available\_addons
    - cPAddons:: get\_instance\_settings
    - cPAddons:: list\_addon\_instances
- cPGreyList:: disable\_all\_domains
    - cPGreyList:: disable\_domains
    - cPGreyList:: enable\_all\_domains
    - cPGreyList:: enable\_domains
    - cPGreyList:: has\_greylisting\_enabled
    - cPGreyList:: list\_domains
- DAV:: disable\_shared\_global\_addressbook
    - DAV:: enable\_shared\_global\_addressbook
    - DAV:: get\_calendar\_contacts\_config
    - DAV:: has\_shared\_global\_addressbook
    - DAV:: is\_dav\_service\_enabled

## LiveAPI Perl Module

```

my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Get Paper Lantern
branding settings.
my $pl_branding =
$cpliveapi->uapi(
    'Brand', 'read',
);

```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

**Notes:**

- The *Fe*
- The *Ur*
- The *mt*
- The *us*
- The *20*
- The *or*
- The *20*
- The *20*
- The *or*
- The *20*
- The *).*

## Find a function

- UAPI Functions - [Style s::list](#) - This function lists information about a reseller account's available styles.

DAV:: is\_horde\_enabled

#### ▼ DCV

DCV:: check\_domains\_via\_dns

DCV:: check\_domains\_via\_http

DCV:: ensure\_domains\_can\_pass\_dcv

#### ▼ DomainInfo

DomainInfo:: domains\_data

DomainInfo:: list\_domains

DomainInfo:: main\_domain\_builtin\_subdomain\_aliases

DomainInfo:: single\_domain\_data

#### ▼ DNS

DNS:: ensure\_domains\_reside\_only\_locally

DNS:: has\_local\_authority

#### ▼ DNSSEC

DNSSEC:: disable\_dnssec

DNSSEC:: enable\_dnssec

DNSSEC:: fetch\_dns\_records

DNSSEC:: set\_nsec3

DNSSEC:: unset\_nsec3

#### ▼ Email

Email:: account\_name

Email:: add\_auto\_responder

Email:: add\_domain\_forwarder

Email:: add\_forwarder

Email:: add\_list

Email:: add\_mailman\_delegates

Email:: add\_mx

Email:: add\_pop

Email:: add\_spam\_filter

### ▼ cPanel Template Toolkit

```
<!-- Get a hash of all the data, then display the company_name value. -->
[% data = execute('Brand', 'read'); %]
[% FOREACH q = data.company_name %]
    <p>
        [% q %]
    </p>
[% END %]

<!-- Get only the company name. -->
[% execute('Brand', 'read').data.company_name %]
```

#### **Note:**

For more information, read our [Guide to Template Toolkit](#) documentation.

- UAPI Functions - `Style::set_default` — This function sets a customer's default style.
- UAPI Functions - `Style::update` — This function applies a new style to the cPanel interface.
- UAPI Functions - `Themes::update` — This function applies a new style to the cPanel interface.

Email:: browse\_mailbox

Email:: change\_mx

Email:: check\_fastmail

Email:: check\_pipe\_forwarder

Email:: delete\_auto\_responder

Email:: delete\_dominion\_forwarder

Email:: delete\_filter

Email:: delete\_forwarder

Email:: delete\_help\_messages

Email:: delete\_list

Email:: delete\_mx

Email:: delete\_pop

Email:: disable\_filter

Email:: disable\_mailbox\_autocreate

Email:: disable\_spam\_assassin

Email:: disable\_spam\_autodelete

Email:: disable\_spam\_box

Email:: dispatch\_client\_settings

Email:: edit\_pop\_quota

Email:: enable\_filter

Email:: enable\_mailbox\_autocreate

Email:: enable\_spam\_assassin

Email:: enable\_spam\_box

Email:: fetch\_charmaps

Email:: fts\_rescan\_mailbox

Email:: generate\_mailman\_opt

Email:: get\_auto\_responder

Email:: get\_chase

## Command Line

```
uapi --user=username  
Brand read
```

### Notes:

- You **must** [URI-encode](#) values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local  
/cpanel/bin/uapi
```

ts

Email: get\_client\_settings

Email: get\_default\_email\_quota

Email: get\_default\_email\_quota\_mib

Email: get\_disk\_usage

Email: get\_filter

Email: get\_held\_message\_count

Email: get\_mailbox\_autocreate

Email: get\_mailman\_delegates

Email: get\_main\_account\_disk\_usage

Email: get\_main\_account\_disk\_usage\_bytes

Email: get\_max\_email\_quota

Email: get\_max\_email\_quota\_mib

Email: get\_pop\_quota

Email: get\_spam\_settings

Email: get\_webmail\_settings

Email: has\_delegated\_mailman\_lists

Email: has\_plaintext\_authentication

Email: hold\_outgoing

Email: is\_integer

Email: list\_autoresponders

Email: list\_default\_address

Email: list\_domain\_forwarders

Email: list\_filters

Email: list\_filters\_backups

Email: list\_forwarders

Email: list\_forward

## Output (JSON)

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "metadata": {

  },
  "data": {
    "company_name":
    "Hosting Company,
    Inc.",
    "display_company_name": 1,
    "webmail_display_company_name": 1,
    "documentation_url":
    "http://www.hostingcompany.com/docs",
    "help_url":
    "http://www.hostingcompany.com/support",
    "cpanel_logo":
    "logo.svg",
    "cpanel_logo_small":
    "logo_small.svg",
    "webmail_logo":
    "webmail.svg"
  }
}
```

### Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

## Parameters

This function does not accept parameters.

## Returns

ers\_backups

Email:: list\_lists

Email:: list\_mail\_domains

Email:: list\_mx

Email:: list\_pops

Email:: list\_pops\_with\_disk

Email:: list\_system\_filter\_info

Email:: passwd\_list

Email:: passwd\_pop

Email:: release\_outgoing

Email:: remove\_mailman\_delegates

Email:: reorder\_filters

Email:: set\_always\_accept

Email:: set\_default\_address

Email:: set\_list\_privacy\_options

Email:: stats\_db\_status

Email:: store\_filter

Email:: suspend\_incoming

Email:: suspend\_login

Email:: suspend\_outgoing

Email:: trace\_filter

Email:: unsuspend\_incoming

Email:: unsuspend\_login

Email:: unsuspend\_outgoing

Email:: verify\_password

▼ EmailAuth

EmailAuth:: disable\_dkim

EmailAuth:: enable\_dkim

EmailAuth:: ensure\_dkim\_keys\_exist

Return	Type	Description	Possible values	Example
company_name	string	The company name.  This name appears in the top left corner of the branded cPanel interface.	<ul style="list-style-type: none"><li>• A string value.</li><li>• An empty string.</li></ul>	Hosting Company, Inc.
display_company_name	Boolean	Whether the cPanel interface displays the company_name value or a logo in the branded cPanel interface.	<ul style="list-style-type: none"><li>• 1 — Display the company_name value.</li><li>• 0 — Display the company's logo.</li></ul>	1
webmail_display_company_name	Boolean	Whether the Webmail interface displays the company_name value or a logo in the branded Webmail interface.  <b>Note</b> : We added this return in cPanel & WHM version 60.	<ul style="list-style-type: none"><li>• 1 — Display the company_name value.</li><li>• 0 — Display the company's logo.</li></ul>	1
documentation_url	string	The company's documentation URL.  The <i>Documentation</i> link uses this URL in branded cPanel interfaces.	<ul style="list-style-type: none"><li>• A valid URL.</li><li>• An empty string.</li></ul>	<a href="http://www.hostingcompany.com/docs">http://www.hostingcompany.com/docs</a>

<p>EmailAuth:: fetch_dkim_private_keys</p> <p>EmailAuth:: install_dkim_private_keys</p> <p>EmailAuth:: install_spf_records</p> <p>EmailAuth:: validate_current_dkims</p> <p>EmailAuth:: validate_current_ptrs</p> <p>EmailAuth:: validate_current_spfs</p> <p>ExternalAuthentication</p> <p>ExternalAuthentication:: add_auth_link</p> <p>ExternalAuthentication:: configured_modules</p> <p>ExternalAuthentication:: get_auth_links</p> <p>ExternalAuthentication:: has_external_auth_modules_configured</p>	<p>help_url</p> <p>string</p>	<p>The company's support URL.</p> <p>In cPanel &amp; WHM version 11.48 and earlier, the <i>Help</i> link uses this URL in branded cPanel interfaces.</p> <div data-bbox="732 405 873 1020" style="border: 1px solid orange; padding: 5px;"> <p><b>Note</b> : In cPanel &amp; WHM version 11.50 and later, we removed the <i>Help</i> link from the cPanel interface.</p> </div>	<ul style="list-style-type: none"> <li>• A valid URL.</li> <li>• An empty string.</li> </ul>	<p>http://www.hostingcompany.com/support</p>
<p>ExternalAuthentication:: remove_authn_link</p> <p>Features</p> <p>Features:: has_feature</p> <p>Features:: list_features</p> <p>Fileman</p> <p>Fileman:: autocompletdir</p> <p>Fileman:: empty_trash</p> <p>Fileman:: get_file_content</p> <p>Fileman:: get_file_information</p> <p>Fileman:: list_files</p> <p>Fileman:: save_file_content</p> <p>Fileman:: transcode</p> <p>Fileman:: upload_files</p> <p>Ftp</p> <p>Ftp:: add_ftp</p>	<p>cpanel_logo</p> <p>string</p>	<p>The filename of the logo file that displays in the cPanel interface.</p> <div data-bbox="732 1192 873 1577" style="border: 1px solid orange; padding: 5px;"> <p><b>Note</b> : We added this return in cPanel &amp; WHM version 60.</p> </div>	<ul style="list-style-type: none"> <li>• logo.svg</li> <li>• logo.png</li> </ul>	<p>logo.svg</p>

Ftp:: allows\_anonymous\_ftp  
 Ftp:: allows\_anonymous\_ftp\_incoming  
 Ftp:: delete\_ftp  
 Ftp:: ftp\_exists  
 Ftp:: get\_ftp\_daemon\_info  
 Ftp:: get\_port  
 Ftp:: get\_quota  
 Ftp:: get\_welcome\_message  
 Ftp:: kill\_session  
 Ftp:: list\_ftp

cpanel_logo_small	string	<p>The filename of the small logo file that displays in the cPanel interface.</p> <div style="border: 1px solid orange; padding: 5px;"> <p><b>Note</b> : We added this return in cPanel &amp; WHM version 60.</p> </div>	<ul style="list-style-type: none"> <li>logo_small.svg</li> <li>logo_small.png</li> </ul>	logo_small.svg
-------------------	--------	--	--	----------------

Ftp:: list\_ftp\_with\_disk  
 Ftp:: list\_sessions  
 Ftp:: passwd  
 Ftp:: server\_name  
 Ftp:: set\_anonymous\_ftp  
 Ftp:: set\_anonymous\_ftp\_incoming  
 Ftp:: set\_homedir  
 Ftp:: set\_quota  
 Ftp:: set\_welcome\_message

webmail_logo	string	<p>The filename of the logo file that displays in the Webmail interface.</p> <div style="border: 1px solid orange; padding: 5px;"> <p><b>Note</b> : We added this return in cPanel &amp; WHM version 60.</p> </div>	<ul style="list-style-type: none"> <li>webmail.svg</li> <li>webmail.png</li> </ul>	webmail.svg
--------------	--------	---	--	-------------

▼ Integration

Integration:: fetch\_url

▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

▼ LangPHP

LangPHP:: php\_get\_domain\_handler

LangPHP:: php\_get\_impacted\_domains

LangPHP:: php\_get\_installed\_versions

LangPHP:: php\_get



t\_system\_default\_  
version

LangPHP:: php\_ge  
t\_vhost\_versions

LangPHP:: php\_ini  
\_get\_user\_basic\_d  
irectives

LangPHP:: php\_ini  
\_get\_user\_content

LangPHP:: php\_ini  
\_get\_user\_paths

LangPHP:: php\_ini  
\_set\_user\_basic\_d  
irectives

LangPHP:: php\_ini  
\_set\_user\_content

LangPHP:: php\_se  
t\_vhost\_versions

▼ LastLogin

LastLogin:: get\_las  
t\_or\_current\_logge  
d\_in\_ip

▼ Locale

Locale:: get\_attrib  
utes

▼ Mailboxes

Mailboxes:: expun  
ge\_mailbox\_mess  
ages

Mailboxes:: expun  
ge\_messages\_for  
\_mailbox\_guid

Mailboxes:: get\_m  
ailbox\_status

Mailboxes:: has\_ut  
f8\_mailbox\_names

Mailboxes:: set\_utf  
8\_mailbox\_names

▼ Market

Market:: cancel\_pe  
nding\_ssl\_certifica  
te

Market:: create\_sh  
opping\_cart

Market:: get\_all\_pr  
oducts

Market:: get\_certifi  
cate\_status\_detail  
s

Market:: get\_login  
\_url

Market:: get\_pendi  
ng\_ssl\_certificates

Market:: get\_provi

der\_specific\_dcv\_  
constraints

Market:: get\_provi  
ders\_list

Market:: get\_ssl\_c  
ertificate\_if\_availa  
ble

Market:: process\_s  
sl\_pending\_queue

Market:: request\_s  
sl\_certificates

Market:: set\_status  
\_of\_pending\_queu  
e\_items

Market:: set\_url\_af  
ter\_checkout

Market:: validate\_l  
ogin\_token

▼ Mime

Mime:: add\_handl  
er

Mime:: add\_hotlink

Mime:: add\_mime

Mime:: add\_redire  
ct

Mime:: delete\_han  
dler

Mime:: delete\_hotli  
nk

Mime:: delete\_mim  
e

Mime:: delete\_redi  
rect

Mime:: list\_handler  
s

Mime:: list\_hotlinks

Mime:: list\_mime

Mime:: list\_redirect  
s

Mime:: redirect\_inf  
o

▼ ModSecurity

ModSecurity:: disa  
ble\_all\_domains

ModSecurity:: disa  
ble\_domains

ModSecurity:: ena  
ble\_all\_domains

ModSecurity:: ena  
ble\_domains

ModSecurity:: has  
\_modsecurity\_inst

alled

ModSecurity:: list\_domains

▼ Mysql

Mysql:: add\_host

Mysql:: add\_host\_note

Mysql :: check\_database

Mysql:: create\_database

Mysql:: create\_user

Mysql:: delete\_database

Mysql:: delete\_host

Mysql:: delete\_user

Mysql:: get\_host\_notes

Mysql:: get\_privileges\_on\_database

Mysql:: get\_restrictions

Mysql:: get\_server\_information

Mysql:: locate\_server

Mysql:: rename\_database

Mysql:: rename\_user

Mysql:: repair\_database

Mysql:: revoke\_access\_to\_database

Mysql:: set\_password

Mysql:: set\_privileges\_on\_database

▼ Notifications

Notifications:: get\_notifications\_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile\_relative\_uri

▼ PassengerApps

PassengerApps:: d  
isable\_application

PassengerApps:: e  
dit\_application

PassengerApps:: e  
nable\_application

PassengerApps:: li  
st\_applications

PassengerApps:: r  
egister\_application

PassengerApps:: u  
nregister\_applicati  
on

▼ PasswdStrength

PasswdStrength::  
get\_required\_stren  
gth

▼ Personalization

Personalization::se  
t

Personalization ::g  
et

▼ Postgresql

Postgresql:: create  
\_database

Postgresql:: create  
\_user

Postgresql:: delete  
\_database

Postgresql:: get\_re  
strictions

Postgresql:: grant\_  
all\_privileges

Postgresql:: renam  
e\_database

Postgresql:: renam  
e\_user

Postgresql:: renam  
e\_user\_no\_passw  
ord

Postgresql:: revok  
e\_all\_privileges

Postgresql:: set\_p  
assword

▼ Pushbullet

Pushbullet:: send\_  
test\_message

▼ Quota

Quota:: get\_quota  
\_info

▼ Resellers

Resellers:: list\_acc  
ounts

- ▼ ResourceUsage
  - ResourceUsage:: get\_usages
- ▼ Restore
  - Restore:: directory\_listing
  - Restore:: get\_users
  - Restore:: query\_file\_info
  - Restore:: restore\_file
- ▼ Session
  - Session:: create\_temp\_user
- ▼ SiteTemplates
  - SiteTemplates:: list\_site\_templates
  - SiteTemplates:: list\_user\_settings
  - SiteTemplates:: publish
- ▼ SpamAssassin
  - SpamAssassin :: clear\_spam\_box
  - SpamAssassin:: get\_symbolic\_test\_names
  - SpamAssassin:: get\_user\_preferences
  - SpamAssassin:: update\_user\_preference
- ▼ SSH
  - SSH:: get\_port
- ▼ SSL
  - SSL:: add\_autossl\_excluded\_domains
  - SSL:: check\_shared\_cert
  - SSL:: delete\_cert
  - SSL:: delete\_csr
  - SSL:: delete\_key
  - SSL:: delete\_ssl
  - SSL :: disable\_mail\_sni
  - SSL:: enable\_mail\_sni
  - SSL:: fetch\_best\_for\_domain

SSL:: fetch\_cert\_in  
fo

SSL:: fetch\_certific  
ates\_for\_fqdns

SSL:: fetch\_key\_a  
nd\_cabundle\_for\_  
certificate

SSL:: find\_certifica  
tes\_for\_key

SSL:: find\_csrs\_for  
\_key

SSL:: generate\_ce  
rt

SSL:: generate\_cs  
r

SSL:: generate\_ke  
y

SSL:: get\_autoss\_  
excluded\_domains

SSL:: get\_autoss\_  
pending\_queue

SSL:: get\_autoss\_  
problems

SSL:: get\_cabundl  
e

SSL:: get\_cn\_nam  
e

SSL:: install\_ssl

SSL:: installed\_ho  
st

SSL:: installed\_ho  
sts

SSL:: is\_autoss\_  
check\_in\_progress

SSL:: is\_mail\_sni\_  
supported

SSL:: is\_sni\_supp  
orted

SSL:: list\_certs

SSL:: list\_csrs

SSL:: list\_keys

SSL:: list\_ssl\_item  
s

SSL:: mail\_sni\_sta  
tus

SSL:: rebuild\_mail  
\_sni\_config

SSL:: rebuildssldb

SSL:: remove\_aut  
oss\_excluded\_do  
mains

SSL:: set\_autossl\_excluded\_domains

SSL:: set\_cert\_friendly\_name

SSL:: set\_csr\_friendly\_name

SSL:: set\_key\_friendly\_name

SSL:: set\_primary\_ssl

SSL:: set\_ssl\_share

SSL:: show\_cert

SSL:: show\_csr

SSL:: show\_key

SSL:: start\_autossl\_check

SSL:: upload\_cert

SSL:: upload\_key

▼ StatsBar

StatsBar:: get\_stats

▼ Styles

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

▼ SubDomain

SubDomain:: addsubdomain

▼ Themes

Themes:: get\_theme\_base

Themes:: list

Themes:: update

▼ TwoFactorAuth

TwoFactorAuth:: generate\_user\_configuration

TwoFactorAuth:: get\_user\_configuration

TwoFactorAuth:: remove\_user\_configuration

TwoFactorAuth:: set\_user\_configuration

▼ UserManager

UserManager:: check\_account\_conflict

ts

UserManager:: create\_user

UserManager:: delete\_user

UserManager:: dismiss\_user

UserManager:: edit\_user

UserManager:: list\_users

UserManager:: lookup\_service\_account

UserManager:: lookup\_user

UserManager:: merge\_service\_account

UserManager:: unlink\_service\_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete\_user

WebDisk:: set\_home\_dir

WebDisk:: set\_password

WebDisk:: set\_permissions

▼ WebmailApps



WebmailApps:: list  
webmailapps

▼ WebVhosts

WebVhost:: list\_do  
mains

WebVhost:: list\_ssl  
\_capable\_domains

▼ WordPressBackup

WordPressBackup  
:: any\_running

WordPressBackup  
:: cancel

WordPressBackup  
:: cleanup

WordPressBackup  
:: get\_available\_ba  
ckups

WordPressBackup  
:: is\_running

WordPressBackup  
:: start

▼ WordPressInstance

Manager

WordPressInstanc  
eManager:: cancel  
\_scan

WordPressInstanc  
eManager:: cleanu  
p\_scan

WordPressInstanc  
eManager:: chang  
e\_admin\_passwor  
d

WordPressInstanc  
eManager:: config  
ure\_autoupdate

WordPressInstanc  
eManager:: get\_ap  
i\_version

WordPressInstanc  
eManager:: get\_in  
stance\_by\_id

WordPressInstanc  
eManager:: get\_in  
stances

WordPressInstanc  
eManager:: get\_lat  
est\_wordpress\_ver  
sion\_from\_wordpr  
ess\_org

WordPressInstanc  
eManager:: get\_sc  
an\_results

WordPressInstanc  
eManager:: is\_inst  
allable\_addon\_ava  
ilable

WordPressInstanceManager:: **start\_scan**

▼ **WordPressRestore**

WordPressRestore  
:: **any\_running**

WordPressRestore  
:: **cleanup**

WordPressRestore  
:: **start**