

cPanel API 2 Functions - MysqlFE::getalldbusersanddbs

Guide to cPanel API 2

Return Data

Filter and Sort Output

Paginate Output

Output Columns

Calls from the WHM API

cPanel Tags (deprecated)

AddonDomain:: adddondomain

omain

AddonDomain:: listaddondomain

AddonDomain:: listaddondomains

Backups

Backups:: listfullbackups

Bandwidth

Bandwidth:: addhttpbandwidth

Bandwidth:: getbwdata

Bandwidth:: gethourlyaveragebwoveryear

BoxTrapper

BoxTrapper:: accountmanagelist

Branding

Branding:: addbrandingobj

Branding:: applist

Branding:: brandingeditor

Branding:: createpkg

Branding:: cssmerge

Branding:: delbrandingobj

Branding:: delpkg

Description

This function lists the databases for which a user has authorization.

Warning:

We **strongly** recommend that you use [UAPI](#) instead of cPanel API 2. However, no equivalent UAPI function exists.

Examples

WHM API (JSON)

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?cpanel_jsonapi_user=user&cpanel_jsonapi_apiversion=2&cpanel_jsonapi_module=MysqlFE&cpanel_jsonapi_function=getalldbusersanddbs
```

Note:

For more information, read our [Calls from the WHM API](#) documentation.

Function information

About this module

The MysqlFE module manages MySQL databases, users, and services.

Branding:: gensprites

Branding:: getbrandingpkg

Branding:: getbrandingpkgstatus

Branding:: getdefaultbrandingpkg

Branding:: installbrandingpkgs

Branding:: installimages

Branding:: killimages

Branding:: listingtypes

Branding:: listobjecttypes

Branding:: preloadconf

Branding:: resetall

Branding:: resetscss

Branding:: resethtml

Branding:: resolve_file

Branding:: resolveocalcss

Branding:: saveocalcss

Branding:: setbrandingpkgstatus

Branding:: showpackages

Branding:: spritelist

▼ CSVImport

CSVImport:: columnchoices

CSVImport:: configimport

CSVImport:: data

CSVImport:: fetchimportdata

CSVImport:: isenabled

CSVImport:: loaddata

CSVImport:: processdata

CSVImport:: sendcontact

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// Retrieve all  
information about  
database users and  
databases that they  
are authorized to use  
$get_dbinfo =  
$cpanel->api2(  
    'MysqlFE',  
    'getalldbusersanddbs'  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
  
# Retrieve all  
information about  
database users and  
databases that they  
are authorized to use  
my $get_dbinfo =  
$cpliveapi->api2(  
    'MysqlFE',  
    'getalldbusersanddbs'  
,  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

About cPanel API 2

cPanel API 2 accesses and modifies data for cPanel accounts.

Notes:

- The
Fe

int
• Ur
mu
us
20
or
20
)'.
20
or
20
)

Find a function

- CSVImport:: uploadimport
- Contactus
 - Contactus:: isenabled
 - Contactus:: sendcontact
- Cron
 - Cron:: add_line
 - Cron:: edit_line
 - Cron:: fetchcron
 - Cron:: get_email
 - Cron:: listcron
 - Cron:: remove_line
 - Cron:: set_email
- CustInfo
 - CustInfo:: contactemails
 - CustInfo:: contactrefs
 - CustInfo:: displaycontactinfo
 - CustInfo:: savecontactinfo
- DBmap
 - DBmap:: status
 - DBmap:: version
- DKIMUI
 - DKIMUI:: available
 - DKIMUI:: getrecords
 - DKIMUI:: install
 - DKIMUI:: installed
 - DKIMUI:: uninstall
- DenyIp
 - DenyIp:: listdenyps
- DiskCounter
 - DiskCounter:: disk_counter
- DiskUsage
 - DiskUsage:: buildcache
 - DiskUsage:: clearcache
 - DiskUsage:: fetch_raw_disk_usage
 - DiskUsage:: fetchdiskusage

▼ cPanel Tag System (deprecated)

Warnings:

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Deprecated cPanel Tag Usage](#) documentation.

▼ Command Line

```
cpapi2
--user=username
MysqlFE
getalldbusersanddbs
```

Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- You **must** run the `--user=username` command.
- For more information and additional output options, read our [Guide to cPanel API 2](#) documentation or run the `cpapi2 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapi2` command:

```
/usr/local
/cpanel/bin/cpapi2
```

▼ Output (JSON)

- cPanel API 2 Modules - MysqlFE — The MysqlFE module manages MySQL® database, users, and services.
- cPanel API 2 Functions - MysqlFE:: authorize host — This function authorizes a host for remote access to the account's database.

- DiskUsage: fetchdiskusagewithextras
- DnsLookup: name2ip
 - DomainLookup: countbaseddomains
 - DomainLookup: getbaseddomains
 - DomainLookup: getdocroot
 - DomainLookup: getdocroots
 - DomainLookup: getmaindomain
- Email: accountname
 - Email: adddomainforward
 - Email: addforward
 - Email: addmx
 - Email: addpop
 - Email: browseboxes
 - Email: changemx
 - Email: checkmaindiscard
 - Email: clearpopcache
 - Email: deletefilter
 - Email: delforward
 - Email: delmx
 - Email: delpop
 - Email: disablefilter
 - Email: editquota
 - Email: enablefilter
 - Email: fetchautosponder
 - Email: fetchchamps
 - Email: filteractions
 - Email: filterlist
 - Email: filtername
 - Email: filterrules
 - Email: get_archiving_configuration

```

{
  "cpanelresult": {
    "apiversion": 2,
    "data": [
      {
        "dbuser":
"cpses_ex24NqG8AX",
        "dbs": [
          ]
        },
      {
        "dbuser":
"cpses_exb03uMNZD",
        "dbs": [
          ]
        },
      {
        "dbuser":
"example_bobby",
        "dbs": [
          ]
        },
      {
        "dbuser":
"example_fred",
        "dbs": [
          "example_fred"
        ]
        },
      {
        "dbuser":
"example_username",
        "dbs": [
          "example_test"
        ]
        },
      ],
      "func":
"getalldbusersanddbs"
    },
    "event": {
      "result": 1
    },
    "module":
"MysqlFE"
  }
}

```

- cPanel API 2 Functions - MySQLFE::changeuserpassword — This function changes a database user's password.
- cPanel API 2 Functions - MySQLFE::createedb — This function creates a database.

Email: [get_archiving_default_configuration](#)

Email: [get_archiving_types](#)

Email: [get_default_email_quota](#)

Email: [get_email_signing](#)

Email: [get_max_email_quota](#)

Email: [getabsbrowse_dir](#)

Email: [getalwaysaccept](#)

Email: [getdiskusage](#)

Email: [getmxcheck](#)

Email: [has_delegated_mailman_lists](#)

Email: [list_system_filter_info](#)

Email: [listaliasbackups](#)

Email: [listautoresponders](#)

Email: [listdefaultaddresses](#)

Email: [listdomainforwards](#)

Email: [listfilterbackups](#)

Email: [listfilters](#)

Email: [listforwards](#)

Email: [listlists](#)

Email: [listmaildomains](#)

Email: [listmx](#)

Email: [listmxs](#)

Email: [listpops](#)

Email: [listpopssingle](#)

Email: [listpopswithdisk](#)

Email: [listpopswithimage](#)

Email: [loadfilter](#)

Email: [passwdpop](#)

Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

This function does not accept parameters.

Returns

Return	Type	Description	Possible values	Example
	<i>array of hashes</i>	An array of hashes that contain information about a database user and the user's authorized databases.	Each hash contains the db user and db server.	
dbuser	<i>string</i>	The database user's name. The function returns this value in the unnamed hash.	A valid username.	example_user1
dbserver	<i>array</i>	A list of the user's authorized databases. The function returns this value in the unnamed hash.	A valid database name or names.	example_database
reason	<i>string</i>	A reason for failure. Note : This function only returns a reason value if it failed.	A string that describes the error.	This is an error message.

Email:: reorderfilters

Email:: set_archiving_configuration

Email:: set_archiving_default_configuration

Email:: set_email_signing

Email:: setalwaysaccept

Email:: setdefaultaddress

Email:: setmxcheck

Email:: storefilter

Email:: tracefilter

▼ EmailTrack

EmailTrack:: search

EmailTrack:: stats

EmailTrack:: trace

▼ Encoding

Encoding:: get_encodings

Encoding:: guess_file

Encoding:: guess_file_opts

▼ FSTest

FSTest:: dirisempty

▼ Fileman

Fileman:: autocompletedir

Fileman:: fileop

Fileman:: getabsdir

Fileman:: getdir

Fileman:: getdiractions

Fileman:: getdiskinfo

Fileman:: geteditty

Fileman:: getfileactions

Fileman:: getpath

Fileman:: listfiles

Fileman:: mkdir

Fileman:: mkfile

result	<i>Boolean</i>	Whether the function succeeded.	<ul style="list-style-type: none">• 1 — The function succeeded.• 0 — The function failed.	1
--------	----------------	---------------------------------	--	---

Fileman:: savefile

Fileman:: search

Fileman:: statfiles

Fileman:: uploadfiles

Fileman:: viewfile

▼ ForcePassword

ForcePassword:: get_force_password_flags

ForcePassword:: update_force_password_flags

▼ Frontpage

Frontpage:: fpenabled

Frontpage:: list

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: listftp

Ftp:: listftpsessions

Ftp:: listftpwithdisk

Ftp:: passwd

Ftp:: setquota

▼ Gpg

Gpg:: listgpgkeys

Gpg:: listsecretgpgkeys

Gpg:: number_of_private_keys

Gpg:: number_of_public_keys

▼ Htaccess

Htaccess:: listusers

Htaccess:: listusers

▼ HttpUtils

HttpUtils:: getdirindices

▼ ImageManager

ImageManager:: thumbnail

▼ LVEInfo

LVEInfo:: getUsage

▼ LangMods

LangMods:: getarchname

LangMods:: getkey

LangMods:: getpre
fix

LangMods:: install

LangMods:: langlis
t

LangMods:: list_av
ailable

LangMods:: list_in
stalled

LangMods:: magic
_status

LangMods:: pre_ru
n

LangMods:: search

LangMods:: setup

LangMods:: uninst
all

LangMods:: updat
e

▼ LeechProtect

LeechProtect:: set
up

▼ Locale

Locale:: get_encod
ing

Locale:: get_html_
dir_attr

Locale:: get_locale
_name

Locale:: get_user_
ocale

Locale:: get_user_
ocale_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse
r

Logaholic:: adduse
rprofile

Logaholic:: deleteu
ser

Logaholic:: deleteu
serprofile

Logaholic:: edituse
r

Logaholic:: fetchus
er

Logaholic:: listuser
profiles

Logaholic:: logahol

iclink

Logaholic:: proces
sstats

▼ Mime

Mime:: list_hotlinks

Mime:: listhandlers

Mime:: listmime

Mime:: listredirects

Mime:: redirectna
me

Mime:: redirecturln
ame

▼ MysqlFE

MysqlFE:: authoriz
ehost

MysqlFE:: change
dbuserpassword

MysqlFE:: created
b

MysqlFE:: created
buser

MysqlFE:: dbusere
xists

MysqlFE:: deautho
rizehost

MysqlFE:: deleted
b

MysqlFE:: deleted
buser

MysqlFE:: getalldb
sinfo

MysqlFE:: getalldb
usersanddbs

MysqlFE:: getdbus
erprivileges

MysqlFE:: getdbus
ers

MysqlFE:: gethosts

MysqlFE:: getmys
qlprivileges

MysqlFE:: getmys
qlserverprivileges

MysqlFE:: has_my
cnf_for_cpuser

MysqlFE:: listdbs

MysqlFE:: listdbsb
ackup

MysqlFE:: listhosts

MysqlFE:: listusers

MysqlFE:: listusers

indb

MysqlFE:: revoked
buserprivileges

MysqlFE:: setdbu
erprivileges

MysqlFE:: userdbp
rivs

▼ MysqlOptimizer

MysqlOptimizer:: f
etch_slow_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does_news
_exist

News:: does_news
_type_exist

News:: get_news

▼ PHPINI

PHPINI:: getallopti
ons

PHPINI:: getoption
s

▼ Park

Park:: listaddondo
mains

Park:: listparkeddo
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change_
password

Passwd:: set_dige
st_auth

▼ PasswdStrength

PasswdStrength::
appstrengths

PasswdStrength::
get_password_stre
ngth

PasswdStrength::
get_required_stren
gth

▼ Postgres

Postgres:: listdbs

Postgres:: listusers

Postgres:: listusers
indb

Postgres:: userexists

▼ Rand

Rand:: getranddata

▼ Resellers

Resellers:: get_sub_accounts

▼ RoR

RoR:: addapp

RoR:: changeapp

RoR:: importrails

RoR:: listapps

RoR:: listrewrites

RoR:: needsimport

RoR:: removeapp

RoR:: removerewrite

RoR:: restartapp

RoR:: setuprewrite

RoR:: softrestartapp

RoR:: startapp

RoR:: stopapp

▼ SetLang

SetLang:: setlocale

▼ SourceIPCheck

SourceIPCheck:: addip

SourceIPCheck:: delip

SourceIPCheck:: getaccount

SourceIPCheck:: listips

SourceIPCheck:: loadsecquestions

SourceIPCheck:: resetsecquestions

SourceIPCheck:: samplequestions

SourceIPCheck:: savequestions

▼ SPFUI

SPFUI:: available

SPFUI:: count_settings

SPFUI:: entries_complete

SPFUI:: get_raw_record

SPFUI:: getmainserverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list_settings

SPFUI:: load_current_values

SPFUI:: uninstall

▼ SSH

SSH:: authkey

SSH:: converttopk

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey_legacy

SSH:: importkey

SSH:: listkeys

▼ SSL

SSL:: fetchcertificate

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcnname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

▼ SSLInfo

SSLInfo:: fetchinfo

▼ StatCache

StatCache:: clearcache

▼ Stats

- Stats:: getmonthly bandwidth
- Stats:: getmonthly domainbandwidth
- Stats:: getthismont hsbwusage
- Stats:: lastapache hits
- Stats:: lastvisitors
- Stats:: listanalog
- Stats:: listawstats
- Stats:: listlastvisitors
- Stats:: listrawlogs
- Stats:: listurchin
- Stats:: listwebalizer

▼ StatsBar

- StatsBar:: getrowcounter
- StatsBar:: rowcounter
- StatsBar:: setrowcounter
- StatsBar:: stat

▼ SubDomain

- SubDomain:: adds ubdomain
- SubDomain:: changedocroot
- SubDomain:: delsubdomain
- SubDomain:: getservedsubdomains
- SubDomain:: listsubdomains
- SubDomain:: validregex

▼ Themes

- Themes:: apply_new_theme
- Themes:: does_cpanel_theme_exist
- Themes:: get_available_themes
- Themes:: get_themes_list
- Themes:: restore_saved_theme

▼ UI

- UI:: dynamicincludelist
- UI:: includelist
- UI:: listform
- UI:: paginate
- UI:: paginate_list

▼ UserHttpUtils

- UserHttpUtils:: getdirindices

▼ WebDisk

- WebDisk:: addwebdisk
- WebDisk:: delwebdisk
- WebDisk:: hasdigest
- WebDisk:: listwebdisks
- WebDisk:: passwdwebdisk
- WebDisk:: set_digest_auth
- WebDisk:: set_homedir
- WebDisk:: set_perms
- WebDisk:: setstatus

▼ WebmailApps

- WebmailApps:: listwebmailapps

▼ ZoneEdit

- ZoneEdit:: add_zone_record
- ZoneEdit:: edit_zone_record
- ZoneEdit:: fetch_cpanel_generated_domains
- ZoneEdit:: fetchzone
- ZoneEdit:: fetchzone_records
- ZoneEdit:: fetchzones
- ZoneEdit:: get_zone_record
- ZoneEdit:: remove_zone_record
- ZoneEdit:: resetzone

