

cPanel API 1 Functions - BoxTrapper::showqueuesearch

Guide to cPanel API 1

Return Data

cPanel Tags
(deprecated)

Bandwidth:
displayheader

Bandwidth:
displaybw

Bandwidth:
displayday

Bandwidth:
displaymainbwheder

BoxTrapper

BoxTrapper::chan
gestatus

BoxTrapper::clean
cfgfilelist

BoxTrapper::edit
msg

BoxTrapper::fetch
cfgfile

BoxTrapper::getb
oxconfdir

BoxTrapper::listm
sgs

BoxTrapper::logco
ntrols

BoxTrapper::mess
ageaction

BoxTrapper::multi
messageaction

BoxTrapper::reset
msg

BoxTrapper::save
cfgfile

BoxTrapper::save
conf

BoxTrapper::show
autowhitelist

BoxTrapper::show
emails

BoxTrapper::show
fromname

BoxTrapper::show
log

Description

This function searches the account's BoxTrapper queue.

Warning:

cPanel API 1 is **deprecated**. We **strongly** recommend that you **do not use** cPanel API 1. However, no equivalent function exists in our newer APIs.

Important:

In cPanel & WHM version 76 and later, when you disable the MailReceive role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
$search_boxtrapper_qu  
eue =  
$cpanel->apil('BoxTra  
pper',  
'showqueuesearch',  
array('sender',  
'John',  
'user@example.com',  
'queuesearch.html',  
'', '0'))); // Call  
the function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Function information

About this module

The Box Trapper module manages the BoxTrapper subsystem.

Note:

This module *BoxTrapper* feature.

BoxTrapper:: show message

BoxTrapper:: show queue

BoxTrapper:: show queuesearch

BoxTrapper:: show queuetime

BoxTrapper:: status

BoxTrapper:: statusbutton

Branding

Branding:: file

Branding:: image

Branding:: killing

Branding:: setbrandingpkg

Branding:: setmyacctspkg

Branding:: setupdirs

Branding:: tempsetbrandingpkg

Cgi

Cgi:: backuplink

Cgi:: displayurchin

Cgi:: phpmyadminlink

Chkservd

Chkservd:: getexport

Chkservd:: getexport_ssl

ClamScanner

ClamScanner:: bars

cPAddons

cPAddons:: mainpg

Cron

Cron:: crontab_perms

CustInfo

CustInfo:: getemail

Denylp

Denylp:: adddenyip

Denylp:: deldenyip

Denylp:: listdenyips

LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
my  
$search_boxtrapper_queue =  
$cpliveapi->api('Box  
Trapper',  
'showqueuesearch',  
['sender', 'John',  
'user@example.com',  
'queuesearch.html',  
'', '0']); # Call  
the function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

cPanel Tag System (deprecated)

Warning:

In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We provide this example to help developers move from the old cPanel tag system to our [LiveAPI](#) system. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs.

```
<cpanel  
Module="BoxTrapper::s  
howqueuesearch(  
$FORM('field','string  
, 'account', 'showfile  
, 'baction', 'skipcon  
trols') )">
```

About cPanel API 1

cPanel API 1 accesses information about cPanel accounts.

Warning: cPanel API 1 is deprecated. We **strongly** recommend you use cPanel API 2 or the [UAPI](#) instead.

Notes:

- The `int` return value is `200` or `201` or `202` or `203` or `204` or `205` or `206` or `207` or `208` or `209` or `210`.

Find a function

▼ DiskUsage

DiskUsage:: show manager

▼ Email

Email:: addautoresponder

Email:: addforward

Email:: addfilter

Email:: addlist

Email:: addmx

Email:: addpop

Email:: addspam

Email:: addspambox

Email:: addspamfilter

Email:: changemx

Email:: checkfastmail

Email:: checkpipewd

Email:: clearspambox

Email:: delautoresponder

Email:: delforward

Email:: delfilter

Email:: dellist

Email:: delmx

Email:: delpop

Email:: delspam

Email:: delspambox

Email:: disable_spam_autodelete

Email:: editquota

Email:: enable_spam_autodelete

Email:: getaging

Email:: getsbody

Email:: getscharset

Email:: getsfrom

Email:: getshtml

Email:: getsinterval

▼ Command Line

```
cpapil
--user=username
BoxTrapper
showqueuesearch
sender John
user@example.com
queuesearch.html ' ' 0
```

Notes:

- You **must** URI-encode these values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to cPanel API 1](#) documentation or run the `cpapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapil` command:

```
/usr/local
/cpanel/bin/cpapil
```

— This function enables Apache SpamAssassin™ for a cPanel account.

- cPanel API 1 Functions - Email::addspamfilter — This function modifies the minimum Apache SpamAssassin™ spam score.

Email: getarsstart
 Email: getarsstop
 Email: getarssubject
 Email: getmailserver
 Email: getmailserveruser
 Email: getpopquota
 Email: has_spam_as_acl
 Email: has_spam_autodelete
 Email: listmaildomains
 Email: listmaildomainsopt
 Email: listmaildomainsoptndef
 Email: mainacctdiskused
 Email: passwdlist
 Email: passwdpop
 Email: setmxaccept
 Email: spamboxstatus
 Email: spamstatus
 Email: tracefilter

Fileman

Fileman: changeperm
 Fileman: delfile
 Fileman: dofileop
 Fileman: emptytrash
 Fileman: extractfile
 Fileman: fileimg
 Fileman: fmmkdir
 Fileman: fmmkfile
 Fileman: fmpushfile
 Fileman: fmrename
 Fileman: fmsavefile
 Fileman: fmsaveht

Output (HTML)

```
<input type="hidden"
name="account"
value="test@example.com">
<input type="hidden"
name="bxaction"
value="multimsgaction">
<tr class="tdshade2">
<td width="5%"><input
type="checkbox"
name="msgid0"
value="qM3nKcgdNWKJQoJmzYxHtUfCHJYMMLki.msg"></td>
<td class="truncate"
truncate="25"
width="15%"><a
href="queuesearch.html?account=test@example.com&q=qM3nKcgdNWKJQoJmzYxHtUfCHJYMMLki.msg&bxaction=1">lee@cp
anel.net</a></td>
<td class="truncate"
truncate="75%"><a
href="queuesearch.html?account=test@example.com&q=qM3nKcgdNWKJQoJmzYxHtUfCHJYMMLki.m
sg&bxaction=1">Subject</a></td>
<td width="15%"><a
href="queuesearch.html?account=test@example.com&q=qM3nKcgdNWKJQoJmzYxHtUfCHJYMMLki.m
sg&bxaction=1">02/19
20:40:05</a></td>
</tr>
```

Parameters

Parameter	Type	Description	Possible values	Example
-----------	------	-------------	-----------------	---------

- cPanel API 1 Functions - Email::delspam — This function disables Apache SpamAssassin™ for a cPanel account.
- cPanel API 1 Functions - Email::spamboxstatus — This function checks whether Apache SpamAssassin™ Spam Box is enabled.

mfile

Fileman::fullbackup

Fileman::getfile

Fileman::htmleditor

Fileman::killdir

Fileman::listfiles

Fileman::listfullbackups

Fileman::listtemplates

Fileman::restoreaf

Fileman::restoredb

Fileman::restorefile

Fileman::restorefiles

Fileman::savehtmlfile

Fileman::showperm

Fileman::uploadfiles

Fileman::viewfile

Frontpage

FrontPage::addfp

FrontPage::delfp

FrontPage::fpstatus

Ftp

Ftp::addftp

Ftp::delftp

Ftp::ftpquota

Ftp::ftpservname

Ftp::ftpstatslogin

Ftp::get_anonftp

Ftp::get_anonftpin

Ftp::get_welcomemsg

Ftp::getftpquota

Ftp::kill_ftp_session

Ftp::listftpstatsurl

Ftp::passwdftp

field	string	Required The field to search.	<ul style="list-style-type: none"> sender subject body 	sender
string	string	Required The string for which to search.	Any string.	John
account	string	Required The account's email address.	A valid email address on the server.	user@example.com
showfile	string	Required The file to process requests to search emails.	queuesearch.html <div style="border: 1px solid red; padding: 5px; width: fit-content;"> <p>Warning: If you specify another file, the HTML output may contain broken links.</p> </div>	queuesearch.html
bxaction	string	Required The system does not use this parameter, and will ignore the value.	A placeholder value.	' '
skipcontrols	Boolean	Required Whether the function suppresses additional options. If you disable this option, the user receives additional options after the search (for example, the <code>multimessageaction</code> options).	<ul style="list-style-type: none"> 0 — Generate additional options. 1 — Do not generate additional options. 	0

Returns

This function returns HTML to generate a table that lists the search results.

- The table sorts messages by date.
- The table contains a checkbox, the message's sender, the message subject, and the date for each message.

- cPanel API 1 Functions - Email::spamstatus — This function checks whether Apache SpamAssassin™ is enabled.

Ftp:: set_anonftp

Ftp:: set_anonftpin

Ftp:: set_welcome
msg

▼ Gpg

Gpg:: deletekey

Gpg:: exportkey

Gpg:: exportsecret
key

Gpg:: genkey

Gpg:: importkeys

▼ Htaccess

Htaccess:: checkpr
otected

Htaccess:: del_use
r

Htaccess:: getinde
x

Htaccess:: htdirls

Htaccess:: number
_of_users

Htaccess:: phpsele
ctable

Htaccess:: resnam
e

Htaccess:: set_pas
s

Htaccess:: set_pro
tect

Htaccess:: setinde
x

Htaccess:: setphpr
eference

Htaccess:: showus
ers

▼ ImageManager

ImageManager:: c
onvert

ImageManager:: di
mensions

ImageManager:: h
dimension

ImageManager:: s
cale

ImageManager:: th
umbnail

ImageManager:: w
dimension

▼ LastLogin

LastLogin:: lastlogi
n

▼ LeechProtect

LeechProtect:: disable

LeechProtect:: enable

LeechProtect:: setup

LeechProtect:: showpasswdfile

LeechProtect:: status

▼ LogManager

LogManager:: listdownloads

LogManager:: save settings

LogManager:: show settings

▼ MagicRevision

MagicRevision:: uri

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: del_handler

Mime:: del_hotlink

Mime:: del_mime

Mime:: del_redirect

Mime:: linkallownull

Mime:: linkenable

Mime:: linkexts

Mime:: linkrurl

Mime:: linkurls

▼ Mysql

Mysql:: adddb

Mysql:: addhost

Mysql:: adduser

Mysql:: adduserdb

Mysql:: checkdb

Mysql:: deldb

Mysql:: delhost

Mysql:: deluser

Mysql:: deluserdb

Mysql:: gethost
Mysql:: initcache
Mysql:: listdbs
Mysql:: listdbsopt
Mysql:: listusers
Mysql:: listusersopt
Mysql:: number_of
_dbs
Mysql:: number_of
_users
Mysql:: repairdb
Mysql:: routines
Mysql:: updatepriv
s

▼ Net

Net:: dnslookup
Net:: dnszone
Net:: sethastracero
ute

▼ News

News:: displaynew
s

▼ NVData

NVData:: set

▼ OptimizeWS

OptimizeWS:: load
optimizesettings
OptimizeWS:: load
optimizesettings (b
ytes)
OptimizeWS:: opti
mizews

▼ Park

Park:: disabledir
ect
Park:: getredirectu
rl
Park:: park
Park:: setredirectur
l
Park:: unpark

▼ Postgres

Postgres:: adddb
Postgres:: adduser
Postgres:: adduser
db
Postgres:: deldb
Postgres:: deluser

Postgres:: deluser
db

Postgres:: initcach
e

Postgres:: listdbso
pt

Postgres:: listusers
opt

Postgres:: number
_of_dbs

Postgres:: number
_of_users

▼ ProxyUtils

ProxyUtils:: proxya
ddress

▼ Resellers

Resellers:: accoun
tlistopt

Resellers:: themeli
stopt

▼ Serverinfo

Serverinfo:: servic
estatus

▼ SetLang

SetLang:: listlangs
opt

SetLang:: setlang

▼ SpamAssassin

SpamAssassin:: co
nfig

SpamAssassin:: sa
veconfig

▼ SSH

SSH:: getport

▼ SSL

SSL:: delete

SSL:: deletectr

SSL:: deletecsr

SSL:: deletekey

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcabundle

SSL:: getcname

SSL:: install

SSL:: installedhost

SSL:: listkeysopt

SSL:: showcrt

SSL:: showcsr

SSL:: showkey

SSL:: sslsharedsta
tus

SSL:: uploadcrt

SSL:: uploadkey

▼ StatManager

StatManager:: doF
orm

StatManager:: upd
ateUserConfig

▼ Stats

Stats:: analoglist

Stats:: awstats

Stats:: bwbar

Stats:: errlog

Stats:: lastvisitors

Stats:: showbandw
idth

Stats:: webalizer

Stats:: webalizerftp

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: cplist
subdomains

SubDomain:: disab
lesubrd

SubDomain:: listsu
bdomainsop

SubDomain:: setsu
burl

▼ UI

UI:: confirm

UI:: redirect

UI:: showresult