

# UAPI Functions - Email::list\_system\_filter\_info

## Guide to UAPI

Return Data  
Filter Output  
Sort Output  
Paginate Output  
Output Columns  
Calls from the WHM API  
Custom UAPI Modules

Backup  
Backup::fullbackup

p\_to\_ftp

Backup::fullbackup  
p\_to\_homedir

Backup::fullbackup  
p\_to\_scp\_with\_key

Backup::fullbackup  
p\_to\_scp\_with\_password

Backup::list\_backups

### Bandwidth

Bandwidth::get\_enabled\_protocols

Bandwidth::get\_retention\_periods

Bandwidth::query

### Batch

Batch::strict

### Brand

Brand::read

### Branding

Branding::file

Branding::get\_applications

Branding::get\_application\_information

Branding::get\_available\_applications

Branding::get\_information\_for\_applications

## Description

This function retrieves a `.yaml.gz` file that contains system-level filter information.

### Important:

In cPanel & WHM version 76 and later, when you disable the `MailReceive` role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

## Examples

### ▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess###  
▼ #####/execute/Email/list_system_filter_info
```

### Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

### ▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// Get a .yaml.gz  
file of the account's  
system-level filters.  
$system_filters =  
$cpanel->uapi(  
    'Email',  
    'list_system_filter_info'  
);
```

### Note:

For more information, read our [Guide to the LiveAPI System](#).

## Function information

## About this module

The `Email` module modifies cPanel email account settings.

## About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster:: read
    - CacheBuster:: update
- Chkservd:: get\_exim\_ports
    - Chkservd:: get\_exim\_ports\_ssl
- Chrome:: get\_dom
- Contactus:: is\_enabled
- cPAddons:: get\_available\_addons
    - cPAddons:: get\_instance\_settings
    - cPAddons:: list\_addon\_instances
- cPGreyList:: disable\_all\_domains
      - cPGreyList:: disable\_domains
      - cPGreyList:: enable\_all\_domains
      - cPGreyList:: enable\_domains
      - cPGreyList:: has\_greylisting\_enabled
      - cPGreyList:: list\_domains
- DAV:: disable\_shared\_global\_addressbook
      - DAV:: enable\_shared\_global\_addressbook
      - DAV:: get\_calendar\_contacts\_config
      - DAV:: has\_shared\_global\_addressbook
      - DAV:: is\_dav\_service\_enabled

## LiveAPI Perl Module

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Get a .yaml.gz file
of the account's
system-level filters.
my $system_filters =
$cpliveapi->uapi(
'Email',
'list_system_filter_i
nfo',
);
```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

## cPanel Template Toolkit

```
<!-- Get a .yaml.gz
file of the account's
system-level filters.
-->
[% execute( 'Email',
'list_system_filter_i
nfo' ) %]
```

**Note:**  
For more information, read our [Guide to Template Toolkit documentation](#).

## Notes:

- The `Fe`
- The `int`
- The `Ur`
- The `mu`
- The `us`
- The `20`
- The `or`
- The `20`
- The `20`
- The `or`
- The `20`
- The `).`

## Find a function

globally unique identifier (GUID) by folder.

- [UAPI Modules - Mailboxes - The Mailboxes module manages email messages.](#)

- DAV:: is\_horde\_enabled
- DCV
    - DCV:: check\_domains\_via\_dns
    - DCV:: check\_domains\_via\_http
    - DCV:: ensure\_domains\_can\_pass\_dcv
  - DomainInfo
  - DomainInfo:: domains\_data
  - DomainInfo:: list\_domains
  - DomainInfo:: main\_domain\_builtin\_subdomain\_aliases
  - DomainInfo:: single\_domain\_data
- DNS
  - DNS:: ensure\_domains\_reside\_only\_locally
  - DNS:: has\_local\_authority
- DNSSEC
  - DNSSEC:: disable\_dnssec
  - DNSSEC:: enable\_dnssec
  - DNSSEC:: fetch\_dns\_records
  - DNSSEC:: set\_nsec3
  - DNSSEC:: unset\_nsec3
- Email
  - Email:: account\_name
  - Email:: add\_auto\_responder
  - Email:: add\_domain\_forwarder
  - Email:: add\_forwarder
  - Email:: add\_list
  - Email:: add\_mailman\_delegates
  - Email:: add\_mx
  - Email:: add\_pop
  - Email:: add\_spam\_filter

## Command Line

```
uapi --user=username
Email
list_system_filter_info
```

### Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

## Output (JSON)

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "data": {
    "filter_info":
    "filter_info.username
.yaml.gz"
  }
  "metadata": {
    "transformed": 1
  }
}
```

### Note:

Use cPanel's *API Shell* interface (`cPanel >> Home >> Advanced >> API Shell`) to directly test cPanel API calls.

- UAPI Functions - Email::edit\_pop\_quota — This function changes an email address's quota.
- UAPI Functions - SpamAssassin::get\_preferences — This function lists the Apache SpamAssassin™ settings for the account.

Email: browse\_mailbox

Email: change\_mx

Email: check\_fastmail

Email: check\_pipe\_forwarder

Email: delete\_auto\_responder

Email: delete\_domain\_forwarder

Email: delete\_filter

Email: delete\_forwarder

Email: delete\_held\_messages

Email: delete\_list

Email: delete\_mx

Email: delete\_pop

Email: disable\_filter

Email: disable\_mailbox\_autocreate

Email: disable\_spam\_assassin

Email: disable\_spam\_autodelete

Email: disable\_spam\_box

Email: dispatch\_client\_settings

Email: edit\_pop\_quota

Email: enable\_filter

Email: enable\_mailbox\_autocreate

Email: enable\_spam\_assassin

Email: enable\_spam\_box

Email: fetch\_charmaps

Email: fts\_rescan\_mailbox

Email: generate\_mailman\_opt

Email: get\_auto\_responder

Email: get\_chase

## Parameters

This function does not accept parameters.

## Returns

Return	Type	Description	Possible values	Example
filter_info	string	The file that contains the account's system-level filter information.	A .yaml.gz filename that contains the cPanel account username.	filter_info.username.yaml.gz

- UAPI Functions - SpamAssassin::clear\_spam\_box - This function clears the spam box of all its contents for all email accounts.

ts

Email:: get\_client\_  
settings

Email:: get\_default\_  
\_email\_quota

Email:: get\_default\_  
\_email\_quota\_mib

Email:: get\_disk\_u  
sage

Email:: get\_filter

Email:: get\_held\_  
message\_count

Email:: get\_mailbo  
x\_autocreate

Email:: get\_mailm  
an\_delegates

Email:: get\_main\_  
account\_disk\_usa  
ge

Email:: get\_main\_  
account\_disk\_usa  
ge\_bytes

Email:: get\_max\_e  
mail\_quota

Email:: get\_max\_e  
mail\_quota\_mib

Email:: get\_pop\_q  
uota

Email:: get\_spam\_  
settings

Email:: get\_webm  
ail\_settings

Email:: has\_deleg  
ated\_mailman\_list  
s

Email:: has\_plainte  
xt\_authentication

Email:: hold\_outgo  
ing

Email:: is\_integer

Email:: list\_auto\_r  
esponders

Email:: list\_default\_  
\_address

Email:: list\_domain\_  
\_forwarders

Email:: list\_filters

Email:: list\_filters\_  
backups

Email:: list\_forward  
ers

Email:: list\_forward

ers\_backups

Email:: list\_lists

Email:: list\_mail\_d  
omains

Email:: list\_mx

Email:: list\_pops

Email:: list\_pops\_  
with\_disk

Email:: list\_system  
\_filter\_info

Email:: passwd\_list

Email:: passwd\_po  
p

Email:: release\_ou  
tgoing

Email:: remove\_m  
ailman\_delegates

Email:: reorder\_filt  
ers

Email:: set\_always  
\_accept

Email:: set\_default  
\_address

Email:: set\_list\_pri  
vacy\_options

Email:: stats\_db\_st  
atus

Email:: store\_filter

Email:: suspend\_in  
coming

Email:: suspend\_lo  
gin

Email:: suspend\_o  
utgoing

Email:: trace\_filter

Email:: unsuspend  
\_incoming

Email:: unsuspend  
\_login

Email:: unsuspend  
\_outgoing

Email:: verify\_pass  
word

▼ EmailAuth

EmailAuth:: disabl  
e\_dkim

EmailAuth:: enable  
\_dkim

EmailAuth:: ensure  
\_dkim\_keys\_exist

EmailAuth:: fetch\_  
dkim\_private\_keys

EmailAuth:: install  
\_dkim\_private\_key  
s

EmailAuth:: install  
\_spf\_records

EmailAuth:: validat  
e\_current\_dkims

EmailAuth:: validat  
e\_current\_ptrs

EmailAuth:: validat  
e\_current\_spfs

ExternalAuthenticat  
ion

ExternalAuthentic  
ation:: add\_auth\_li  
nk

ExternalAuthentic  
ation:: configured\_  
modules

ExternalAuthentic  
ation:: get\_authn\_lin  
ks

ExternalAuthentic  
ation:: has\_external  
\_auth\_modules\_co  
nfigured

ExternalAuthentic  
ation:: remove\_auth  
n\_link

Features

Features:: has\_fea  
ture

Features:: list\_feat  
ures

Fileman

Fileman:: autocom  
pletedir

Fileman:: empty\_tr  
ash

Fileman:: get\_file\_  
content

Fileman:: get\_file\_i  
nformation

Fileman:: list\_files

Fileman:: save\_file  
\_content

Fileman:: transcod  
e

Fileman:: upload\_fi  
les

Ftp

Ftp:: add\_ftp

Ftp:: allows\_anonymous\_ftp

Ftp:: allows\_anonymous\_ftp\_incoming

Ftp:: delete\_ftp

Ftp:: ftp\_exists

Ftp:: get\_ftp\_daemon\_info

Ftp:: get\_port

Ftp:: get\_quota

Ftp:: get\_welcome\_message

Ftp:: kill\_session

Ftp:: list\_ftp

Ftp:: list\_ftp\_with\_disk

Ftp:: list\_sessions

Ftp:: passwd

Ftp:: server\_name

Ftp:: set\_anonymous\_ftp

Ftp:: set\_anonymous\_ftp\_incoming

Ftp:: set\_homedir

Ftp:: set\_quota

Ftp:: set\_welcome\_message

#### ▼ Integration

Integration:: fetch\_url

#### ▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

#### ▼ LangPHP

LangPHP:: php\_get\_domain\_handler

LangPHP:: php\_get\_impacted\_domains

LangPHP:: php\_get\_installed\_versions

LangPHP:: php\_get



t\_system\_default\_  
version

LangPHP:: php\_ge  
t\_vhost\_versions

LangPHP:: php\_ini  
\_get\_user\_basic\_d  
irectives

LangPHP:: php\_ini  
\_get\_user\_content

LangPHP:: php\_ini  
\_get\_user\_paths

LangPHP:: php\_ini  
\_set\_user\_basic\_d  
irectives

LangPHP:: php\_ini  
\_set\_user\_content

LangPHP:: php\_se  
t\_vhost\_versions

▼ LastLogin

LastLogin:: get\_las  
t\_or\_current\_logge  
d\_in\_ip

▼ Locale

Locale:: get\_attri  
butes

▼ Mailboxes

Mailboxes:: expun  
ge\_mailbox\_mess  
ages

Mailboxes:: expun  
ge\_messages\_for  
\_mailbox\_guid

Mailboxes:: get\_m  
ailbox\_status

Mailboxes:: has\_ut  
f8\_mailbox\_names

Mailboxes:: set\_utf  
8\_mailbox\_names

▼ Market

Market:: cancel\_pe  
nding\_ssl\_certifica  
te

Market:: create\_sh  
opping\_cart

Market:: get\_all\_pr  
oducts

Market:: get\_certifi  
cate\_status\_detail  
s

Market:: get\_login  
\_url

Market:: get\_pendi  
ng\_ssl\_certificates

Market:: get\_provi

der\_specific\_dcv\_  
constraints

Market:: get\_provi  
ders\_list

Market:: get\_ssl\_c  
ertificate\_if\_availa  
ble

Market:: process\_s  
sl\_pending\_queue

Market:: request\_s  
sl\_certificates

Market:: set\_status  
\_of\_pending\_queu  
e\_items

Market:: set\_url\_af  
ter\_checkout

Market:: validate\_l  
ogin\_token

▼ Mime

Mime:: add\_handl  
er

Mime:: add\_hotlink

Mime:: add\_mime

Mime:: add\_redire  
ct

Mime:: delete\_han  
dler

Mime:: delete\_hotli  
nk

Mime:: delete\_mim  
e

Mime:: delete\_redi  
rect

Mime:: list\_handler  
s

Mime:: list\_hotlinks

Mime:: list\_mime

Mime:: list\_redirect  
s

Mime:: redirect\_inf  
o

▼ ModSecurity

ModSecurity:: disa  
ble\_all\_domains

ModSecurity:: disa  
ble\_domains

ModSecurity:: ena  
ble\_all\_domains

ModSecurity:: ena  
ble\_domains

ModSecurity:: has  
\_modsecurity\_inst

alled

ModSecurity:: list\_ domains

▼ Mysql

Mysql:: add\_host

Mysql:: add\_host\_ note

Mysql :: check\_dat abase

Mysql:: create\_dat abase

Mysql:: create\_use r

Mysql:: delete\_dat abase

Mysql:: delete\_hos t

Mysql:: delete\_use r

Mysql:: get\_host\_n otes

Mysql:: get\_privile ges\_on\_database

Mysql:: get\_restrict ions

Mysql:: get\_server \_information

Mysql:: locate\_ser ver

Mysql:: rename\_d atabase

Mysql:: rename\_us er

Mysql:: repair\_dat abase

Mysql:: revoke\_ac cess\_to\_database

Mysql:: set\_passw ord

Mysql:: set\_privile ges\_on\_database

▼ Notifications

Notifications:: get\_ notifications\_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile\_rel ative\_uri

▼ PassengerApps

PassengerApps:: d  
isable\_application

PassengerApps:: e  
dit\_application

PassengerApps:: e  
nable\_application

PassengerApps:: li  
st\_applications

PassengerApps:: r  
egister\_application

PassengerApps:: u  
nregister\_applicati  
on

▼ PasswdStrength

PasswdStrength::  
get\_required\_stren  
gth

▼ Personalization

Personalization::se  
t

Personalization ::g  
et

▼ Postgresql

Postgresql:: create  
\_database

Postgresql:: create  
\_user

Postgresql:: delete  
\_database

Postgresql:: get\_re  
strictions

Postgresql:: grant\_  
all\_privileges

Postgresql:: renam  
e\_database

Postgresql:: renam  
e\_user

Postgresql:: renam  
e\_user\_no\_passw  
ord

Postgresql:: revok  
e\_all\_privileges

Postgresql:: set\_p  
assword

▼ Pushbullet

Pushbullet:: send\_  
test\_message

▼ Quota

Quota:: get\_quota  
\_info

▼ Resellers

Resellers:: list\_acc  
ounts

- ▼ ResourceUsage
  - ResourceUsage::  
get\_usages
- ▼ Restore
  - Restore:: directory  
\_listing
  - Restore:: get\_user  
s
  - Restore:: query\_fil  
e\_info
  - Restore:: restore\_f  
ile
- ▼ Session
  - Session:: create\_t  
emp\_user
- ▼ SiteTemplates
  - SiteTemplates:: list  
\_site\_templates
  - SiteTemplates:: list  
\_user\_settings
  - SiteTemplates:: pu  
blish
- ▼ SpamAssassin
  - SpamAssassin :: cl  
ear\_spam\_box
  - SpamAssassin:: g  
et\_symbolic\_test\_  
names
  - SpamAssassin:: g  
et\_user\_preferenc  
es
  - SpamAssassin:: u  
pdate\_user\_prefer  
ence
- ▼ SSH
  - SSH:: get\_port
- ▼ SSL
  - SSL:: add\_autossl  
\_excluded\_domain  
s
  - SSL:: check\_share  
d\_cert
  - SSL:: delete\_cert
  - SSL:: delete\_csr
  - SSL:: delete\_key
  - SSL:: delete\_ssl
  - SSL :: disable\_mai  
l\_sni
  - SSL:: enable\_mail  
\_sni
  - SSL:: fetch\_best\_f  
or\_domain

SSL:: fetch\_cert\_in  
fo

SSL:: fetch\_certific  
ates\_for\_fqdns

SSL:: fetch\_key\_a  
nd\_cabundle\_for\_  
certificate

SSL:: find\_certifica  
tes\_for\_key

SSL:: find\_csrs\_for  
\_key

SSL:: generate\_ce  
rt

SSL:: generate\_cs  
r

SSL:: generate\_ke  
y

SSL:: get\_autoss\_  
excluded\_domains

SSL:: get\_autoss\_  
pending\_queue

SSL:: get\_autoss\_  
problems

SSL:: get\_cabundl  
e

SSL:: get\_cn\_nam  
e

SSL:: install\_ssl

SSL:: installed\_ho  
st

SSL:: installed\_ho  
sts

SSL:: is\_autoss\_  
check\_in\_progress

SSL:: is\_mail\_sni\_  
supported

SSL:: is\_sni\_supp  
orted

SSL:: list\_certs

SSL:: list\_csrs

SSL:: list\_keys

SSL:: list\_ssl\_item  
s

SSL:: mail\_sni\_sta  
tus

SSL:: rebuild\_mail  
\_sni\_config

SSL:: rebuildssldb

SSL:: remove\_aut  
oss\_excluded\_do  
mains

SSL:: set\_autossl\_excluded\_domains

SSL:: set\_cert\_friendly\_name

SSL:: set\_csr\_friendly\_name

SSL:: set\_key\_friendly\_name

SSL:: set\_primary\_ssl

SSL:: set\_ssl\_share

SSL:: show\_cert

SSL:: show\_csr

SSL:: show\_key

SSL:: start\_autossl\_check

SSL:: upload\_cert

SSL:: upload\_key

▼ StatsBar

StatsBar:: get\_stats

▼ Styles

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

▼ SubDomain

SubDomain:: addsubdomain

▼ Themes

Themes:: get\_theme\_base

Themes:: list

Themes:: update

▼ TwoFactorAuth

TwoFactorAuth:: generate\_user\_configuration

TwoFactorAuth:: get\_user\_configuration

TwoFactorAuth:: remove\_user\_configuration

TwoFactorAuth:: set\_user\_configuration

▼ UserManager

UserManager:: check\_account\_conflict

ts

UserManager:: create\_user

UserManager:: delete\_user

UserManager:: dismiss\_user

UserManager:: edit\_user

UserManager:: list\_users

UserManager:: lookup\_service\_account

UserManager:: lookup\_user

UserManager:: merge\_service\_account

UserManager:: unlink\_service\_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete\_user

WebDisk:: set\_home\_dir

WebDisk:: set\_password

WebDisk:: set\_permissions

▼ WebmailApps



WebmailApps:: list  
webmailapps

▼ WebVhosts

WebVhost:: list\_do  
mains

WebVhost:: list\_ssl  
\_capable\_domains

▼ WordPressBackup

WordPressBackup  
:: any\_running

WordPressBackup  
:: cancel

WordPressBackup  
:: cleanup

WordPressBackup  
:: get\_available\_ba  
ckups

WordPressBackup  
:: is\_running

WordPressBackup  
:: start

▼ WordPressInstance

Manager

WordPressInstanc  
eManager:: cancel  
\_scan

WordPressInstanc  
eManager:: cleanu  
p\_scan

WordPressInstanc  
eManager:: chang  
e\_admin\_passwor  
d

WordPressInstanc  
eManager:: config  
ure\_autoupdate

WordPressInstanc  
eManager:: get\_ap  
i\_version

WordPressInstanc  
eManager:: get\_in  
stance\_by\_id

WordPressInstanc  
eManager:: get\_in  
stances

WordPressInstanc  
eManager:: get\_lat  
est\_wordpress\_ver  
sion\_from\_wordpr  
ess\_org

WordPressInstanc  
eManager:: get\_sc  
an\_results

WordPressInstanc  
eManager:: is\_inst  
allable\_addon\_ava  
ilable

WordPressInstanceManager:: **start\_scan**

▼ **WordPressRestore**

WordPressRestore  
:: **any\_running**

WordPressRestore  
:: **cleanup**

WordPressRestore  
:: **start**