

# cPanel API 1 Functions - Email::addpop

## Guide to cPanel API 1

Return Data

cPanel Tags  
(deprecated)

Bandwidth:  
display  
header

er

Bandwidth:  
display  
bw

Bandwidth:  
display  
day

Bandwidth:  
display  
mainbwhheader

### ▼ BoxTrapper

BoxTrapper::chan  
gestatus

BoxTrapper::clean  
cfgfilelist

BoxTrapper::edit  
msg

BoxTrapper::fetch  
cfgfile

BoxTrapper::getb  
oxconfdir

BoxTrapper::listm  
sgs

BoxTrapper::logco  
ntrols

BoxTrapper::mess  
ageaction

BoxTrapper::multi  
messageaction

BoxTrapper::reset  
msg

BoxTrapper::save  
cfgfile

BoxTrapper::save  
conf

BoxTrapper::show  
autowhitelist

BoxTrapper::show  
emails

BoxTrapper::show  
fromname

BoxTrapper::show  
log

## Description

This function adds an email account.

### Warning:

cPanel API 1 is **deprecated**. Do not use this function. Instead, we **strongly** recommend that you use the following newer functions:

- **UAPI (recommended)** — `Email::add_pop` — This function creates an email address.
- **cPanel API 2** — `Email::addpop` — This function adds an email account.

### Important:

In cPanel & WHM version 76 and later, when you disable the `MailReceive` role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

## Examples

### ▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
$new_email_account =  
$cpanel->apil('Email'  
, 'addpop',  
array('user',  
'12345luggage',  
'500', 'example.com')  
); // Call the  
function.
```

### Note:

For more information, read our [Guide to the LiveAPI System](#).

## Func tion infor mati on

## About this mod ule

The `Email` module modifies cPanel email account settings.

## About cPan el API 1

cPanel API 1 accesses information about cPanel accounts.

BoxTrapper:: show message  
BoxTrapper:: show queue  
BoxTrapper:: show queuesearch  
BoxTrapper:: show queuetime  
BoxTrapper:: status  
BoxTrapper:: statusbutton

#### Branding

Branding:: file  
Branding:: image  
Branding:: killing  
Branding:: setbrandingpkg  
Branding:: setmyacctspkg  
Branding:: setupdirs  
Branding:: tempsetbrandingpkg

#### Cgi

Cgi:: backuplink  
Cgi:: displayurchin  
Cgi:: phpmyadminlink

#### Chkservd

Chkservd:: getximport  
Chkservd:: getximport\_ssl

#### ClamScanner

ClamScanner:: bars

#### cPAddons

cPAddons:: mainpg

#### Cron

Cron:: crontab\_perms

#### CustInfo

CustInfo:: getemail

#### Denylp

Denylp:: adddenyip  
Denylp:: deldenyip  
Denylp:: listdenyips

### LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
my $new_email_account  
=  
$cpliveapi->apil('Email', 'addpop',  
['user',  
'12345luggage',  
'500', 'example.com']  
); # Call the  
function.
```

#### Note:

For more information, read our [Guide to the LiveAPI System](#).

### cPanel Tag System (deprecated)

#### Warning:

In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We provide this example to help developers move from the old cPanel tag system to our [LiveAPI](#) system. We **strongly** recommend that you **only** use the LiveAPI system to call the cPanel APIs.

```
<cpanel  
Module="Email::addpop  
(  
$FORM('email','password',  
'quota','domain')  
)">
```

**Warning:**  
cPanel API deprecated. We **strongly** recommend cPanel API or UAPI instead.

#### Notes:

- The
- Ur
- m
- us
- 20
- or
- 20
- ).'
- 20
- or
- 20
- ).

Find  
a  
function



Email: [getarsstart](#)  
 Email: [getarsstop](#)  
 Email: [getarssubject](#)  
 Email: [getmailserver](#)  
 Email: [getmailserveruser](#)  
 Email: [getpopquota](#)  
 Email: [has\\_spam\\_as\\_acl](#)  
 Email: [has\\_spam\\_autodelete](#)  
 Email: [listmaildomains](#)  
 Email: [listmaildomainsopt](#)  
 Email: [listmaildomainsoptndef](#)  
 Email: [mainacctdiskused](#)  
 Email: [passwdlist](#)  
 Email: [passwdpop](#)  
 Email: [setmxaccept](#)  
 Email: [spamboxstatus](#)  
 Email: [spamstatus](#)  
 Email: [tracefilter](#)

▼ [Fileman](#)

Fileman: [changeperm](#)  
 Fileman: [delfile](#)  
 Fileman: [dofileop](#)  
 Fileman: [emptytrash](#)  
 Fileman: [extractfile](#)  
 Fileman: [fileimg](#)  
 Fileman: [fmmkdir](#)  
 Fileman: [fmmkfile](#)  
 Fileman: [fmpushfile](#)  
 Fileman: [fmrename](#)  
 Fileman: [fmsavefile](#)  
 Fileman: [fmsaveht](#)

quota	integer	<b>Required</b>  The maximum amount of disk space that the new email account may use.	A positive integer.  <b>Note</b> : To grant the account unlimited disk space, specify 0 for this parameter.	500
domain	string	<b>Required</b>  The email account's domain.	The domain that corresponds to the email account.  For example, example if the email address is user@example.com.	example.com

## Returns

This function returns the new email address, in `email@domain.tld` format.

- [cPanel API 1 Functions - Email::addspamfilter](#) — This function enables Apache SpamAssassin™ for a cPanel account.
- [cPanel API 1 Functions - Email::addspamfilter](#) — This function modifies the minimum Apache SpamAssassin™ spam score.

mfile

Fileman:: fullbacku  
p

Fileman:: getfile

Fileman:: htmleedito  
r

Fileman:: killdir

Fileman:: listfiles

Fileman:: listfullba  
ckups

Fileman:: listtempl  
ates

Fileman:: restoreaf

Fileman:: restored  
b

Fileman:: restorefil  
e

Fileman:: restorefil  
es

Fileman:: savehtml  
file

Fileman:: showper  
m

Fileman:: uploadfil  
es

Fileman:: viewfile

▼ Frontpage

FrontPage:: addfp

FrontPage:: delfp

FrontPage:: fpstat  
us

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: ftpquota

Ftp:: ftpservernam  
e

Ftp:: ftpstatslogin

Ftp:: get\_anonftp

Ftp:: get\_anonftpin

Ftp:: get\_welcome  
msg

Ftp:: getftpquota

Ftp:: kill\_ftp\_sessi  
on

Ftp:: listftpstatsurl

Ftp:: passwdftp

Ftp:: set\_anonftp

Ftp:: set\_anonftpin

Ftp:: set\_welcome  
msg

▼ Gpg

Gpg:: deletekey

Gpg:: exportkey

Gpg:: exportsecret  
key

Gpg:: genkey

Gpg:: importkeys

▼ Htaccess

Htaccess:: checkpr  
otected

Htaccess:: del\_use  
r

Htaccess:: getinde  
x

Htaccess:: htdirls

Htaccess:: number  
\_of\_users

Htaccess:: phpsele  
ctable

Htaccess:: resnam  
e

Htaccess:: set\_pas  
s

Htaccess:: set\_pro  
tect

Htaccess:: setinde  
x

Htaccess:: setphpr  
eference

Htaccess:: showus  
ers

▼ ImageManager

ImageManager:: c  
onvert

ImageManager:: di  
mensions

ImageManager:: h  
dimension

ImageManager:: s  
cale

ImageManager:: th  
umbnail

ImageManager:: w  
dimension

▼ LastLogin

LastLogin:: lastlogi  
n

▼ LeechProtect

LeechProtect:: disable

LeechProtect:: enable

LeechProtect:: setup

LeechProtect:: showpasswdfile

LeechProtect:: status

▼ LogManager

LogManager:: listdownloads

LogManager:: save settings

LogManager:: show settings

▼ MagicRevision

MagicRevision:: uri

▼ Mime

Mime:: add\_handler

Mime:: add\_hotlink

Mime:: add\_mime

Mime:: add\_redirect

Mime:: del\_handler

Mime:: del\_hotlink

Mime:: del\_mime

Mime:: del\_redirect

Mime:: linkallownull

Mime:: linkenable

Mime:: linkexts

Mime:: linkrurl

Mime:: linkurls

▼ Mysql

Mysql:: adddb

Mysql:: addhost

Mysql:: adduser

Mysql:: adduserdb

Mysql:: checkdb

Mysql:: deldb

Mysql:: delhost

Mysql:: deluser

Mysql:: deluserdb

Mysql:: gethost  
Mysql:: initcache  
Mysql:: listdbs  
Mysql:: listdbsopt  
Mysql:: listusers  
Mysql:: listusersopt  
Mysql:: number\_of  
\_dbs  
Mysql:: number\_of  
\_users  
Mysql:: repairdb  
Mysql:: routines  
Mysql:: updatepriv  
s

▼ Net

Net:: dnslookup  
Net:: dnszone  
Net:: sethastracero  
ute

▼ News

News:: displaynew  
s

▼ NVData

NVData:: set

▼ OptimizeWS

OptimizeWS:: load  
optimizesettings  
OptimizeWS:: load  
optimizesettings (b  
ytes)  
OptimizeWS:: opti  
mizews

▼ Park

Park:: disabledir  
ect  
Park:: getredirectu  
rl  
Park:: park  
Park:: setredirectur  
l  
Park:: unpark

▼ Postgres

Postgres:: adddb  
Postgres:: adduser  
Postgres:: adduser  
db  
Postgres:: deldb  
Postgres:: deluser



Postgres:: deluser  
db

Postgres:: initcach  
e

Postgres:: listdbso  
pt

Postgres:: listusers  
opt

Postgres:: number  
\_of\_dbs

Postgres:: number  
\_of\_users

#### ▼ ProxyUtils

ProxyUtils:: proxya  
ddress

#### ▼ Resellers

Resellers:: accoun  
tlistopt

Resellers:: themeli  
stopt

#### ▼ Serverinfo

Serverinfo:: servic  
estatus

#### ▼ SetLang

SetLang:: listlangs  
opt

SetLang:: setlang

#### ▼ SpamAssassin

SpamAssassin:: co  
nfig

SpamAssassin:: sa  
veconfig

#### ▼ SSH

SSH:: getport

#### ▼ SSL

SSL:: delete

SSL:: deletectr

SSL:: deletecsr

SSL:: deletekey

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcabundle

SSL:: getcname

SSL:: install

SSL:: installedhost

SSL:: listkeysopt

SSL:: showcrt

SSL:: showcsr

SSL:: showkey

SSL:: sslsharedsta  
tus

SSL:: uploadcrt

SSL:: uploadkey

▼ StatManager

StatManager:: doF  
orm

StatManager:: upd  
ateUserConfig

▼ Stats

Stats:: analoglist

Stats:: awstats

Stats:: bwbar

Stats:: errlog

Stats:: lastvisitors

Stats:: showbandw  
idth

Stats:: webalizer

Stats:: webalizerftp

▼ SubDomain

SubDomain:: adds  
ubdomain

SubDomain:: cplist  
subdomains

SubDomain:: disab  
lesubrd

SubDomain:: listsu  
bdomainsop

SubDomain:: setsu  
burl

▼ UI

UI:: confirm

UI:: redirect

UI:: showresult