

cPanel API 1 Functions - ProxyUtils::proxyaddress

Guide to cPanel API 1

Return Data

cPanel Tags
(deprecated)

Bandwidth:
displaybandwidth

er

Bandwidth:
displaybandwidth

Bandwidth:
displaybandwidth

Bandwidth:
displaybandwidth

BoxTrapper

BoxTrapper:
change_status

BoxTrapper:
cleanupfilelist

BoxTrapper:
editmessage

BoxTrapper:
fetchconfigfile

BoxTrapper:
getboxconfdir

BoxTrapper:
listmessages

BoxTrapper:
logcontrols

BoxTrapper:
messageaction

BoxTrapper:
multimessageaction

BoxTrapper:
resetmessage

BoxTrapper:
saveconfigfile

BoxTrapper:
saveconfig

BoxTrapper:
showautowhitelist

BoxTrapper:
showemails

BoxTrapper:
showfromname

BoxTrapper:
show

Description

This function displays the proxy address for a specific application.

Warning:

cPanel API 1 is **deprecated**. We **strongly** recommend that you **do not use** cPanel API 1. However, no equivalent function exists in our newer APIs.

Examples

LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
$get_proxyaddress =  
$cpanel->apil('ProxyU  
tils', 'proxyaddress',  
array('cpanel')) );  
// Call the function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
my $get_proxyaddress  
=  
$cpliveapi->apil('Pro  
xyUtils', 'proxyadres  
s', ['cpanel']); #  
Call the function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Function information

About this module

The ProxyUtils module retrieves proxy addresses for applications.

About cPanel API 1

cPanel API 1 accesses information about cPanel accounts.

- log
- BoxTrapper:: show message
- BoxTrapper:: show queue
- BoxTrapper:: show queuesearch
- BoxTrapper:: show queuetime
- BoxTrapper:: status
- BoxTrapper:: statusbutton
- Branding
 - Branding:: file
 - Branding:: image
 - Branding:: killing
 - Branding:: setbrandingpkg
 - Branding:: setmyacctspkg
 - Branding:: setupdirs
 - Branding:: tempsetbrandingpkg
- Cgi
 - Cgi:: backuplink
 - Cgi:: displayurchin
 - Cgi:: phpmyadminlink
- Chkserverd
 - Chkserverd:: getximport
 - Chkserverd:: getximport_ssl
- ClamScanner
 - ClamScanner:: bars
- cPAddons
 - cPAddons:: mainpg
- Cron
 - Cron:: crontab_perms
- CustInfo
 - CustInfo:: getemail
- Denylp
 - Denylp:: adddenyip
 - Denylp:: deldenyip

▼ cPanel Tag System (deprecated)

Warning:
 In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We provide this example to help developers move from the old cPanel tag system to our [LiveAPI](#) system. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs.

```
<cpanel
Module="ProxyUtils::proxyaddress($FORM('newapp'))">
```

▼ Command Line

```
cpapil
--user=username
ProxyUtils
proxyaddress cpanel
```

Notes:

- You **must** [URI-encode](#) these values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to cPanel API 1](#) documentation or run the `cpapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapil` command:

```
/usr/local
/cpanel/bin/cpapil
```

▼ Output (plaintext)

```
appname.host.com
```

Warning:
 cPanel API deprecated. We **strongly** recommend [cPanel API](#) or [UAPI](#) instead.

Notes:

- Th
- Fe
- int
- Ur
- mi
- us
- 20
- or
- 20
-).
- 20
- or
- 20
-).

Find
 a
 funct
 ion

Parameters

- DenyIp:: listdenyips
- DiskUsage
 - DiskUsage:: showmanager
 - Email
 - Email:: addautoresponder
 - Email:: addforward
 - Email:: addfilter
 - Email:: addlist
 - Email:: addmx
 - Email:: addpop
 - Email:: addspam
 - Email:: addspambox
 - Email:: addspamfilter
 - Email:: changemx
 - Email:: checkfastmail
 - Email:: checkpipewd
 - Email:: clearspambox
 - Email:: delautoresponder
 - Email:: deldforward
 - Email:: delfilter
 - Email:: dellist
 - Email:: delmx
 - Email:: delpop
 - Email:: delspam
 - Email:: delspambox
 - Email:: disable_spam_autodelete
 - Email:: editquota
 - Email:: enable_spam_autodelete
 - Email:: getaging
 - Email:: getarsbody
 - Email:: getarscharset
 - Email:: getarsfrom
 - Email:: getarshtml

Parameter	Type	Description	Possible values	Example
newapp	string	Required The application's name.	<ul style="list-style-type: none"> • cpanel • webmail • whm • webdisk 	cpanel

Returns

This function returns the proxy address for the application.

- [cPanel API 1 Modules - ProxyUtils](#) — The ProxyUtils module retrieves proxy addresses for applications.
- [cPanel API 1 Modules - Serverinfo](#) — The Serverinfo module displays the status of services on your server.

Email:: getarsinter
val

Email:: getarsstart

Email:: getarsstop

Email:: getarssubj
ect

Email:: getmailserv
er

Email:: getmailserv
eruser

Email:: getpopquot
a

Email:: has_spam
_as_acl

Email:: has_spam
_autodelete

Email:: listmaildom
ains

Email:: listmaildom
ainsopt

Email:: listmaildom
ainsoptndef

Email:: mainacctdi
skused

Email:: passwdlist

Email:: passwdpop

Email:: setmxacce
pt

Email:: spamboxst
atus

Email:: spamstatus

Email:: tracefilter

▼ Fileman

Fileman:: changep
erm

Fileman:: delfile

Fileman:: dofileop

Fileman:: emptytra
sh

Fileman:: extractfil
e

Fileman:: fileimg

Fileman:: fmmkdir

Fileman:: fmmkfile

Fileman:: fmpushfil
e

Fileman:: fmrenam
e

Fileman:: fmsavefil

- cPanel API 1 Functions - Serverinfo::servicestatus — This function displays the status of services that the cPanel rvd daemon monitors.

e

Fileman:: fmsaveht
mlfile

Fileman:: fullbacku
p

Fileman:: getfile

Fileman:: htmledito
r

Fileman:: killdir

Fileman:: listfiles

Fileman:: listfullba
ckups

Fileman:: listtempl
ates

Fileman:: restoreaf

Fileman:: restored
b

Fileman:: restorefil
e

Fileman:: restorefil
es

Fileman:: savehtml
file

Fileman:: showper
m

Fileman:: uploadfil
es

Fileman:: viewfile

▼ Frontpage

FrontPage:: addfp

FrontPage:: delfp

FrontPage:: fpstat
us

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: ftpquota

Ftp:: ftpservernam
e

Ftp:: ftpstatslogin

Ftp:: get_anonftp

Ftp:: get_anonftpin

Ftp:: get_welcome
msg

Ftp:: getftpquota

Ftp:: kill_ftp_sessi
on

Ftp:: listftpstatsurl

Ftp:: passwdftp

Ftp:: set_anonftp

Ftp:: set_anonftpin

Ftp:: set_welcome
msg

▼ Gpg

Gpg:: deletekey

Gpg:: exportkey

Gpg:: exportsecret
key

Gpg:: genkey

Gpg:: importkeys

▼ Htaccess

Htaccess:: checkpr
otected

Htaccess:: del_use
r

Htaccess:: getinde
x

Htaccess:: htdirls

Htaccess:: number
_of_users

Htaccess:: phpsele
ctable

Htaccess:: resnam
e

Htaccess:: set_pas
s

Htaccess:: set_pro
tect

Htaccess:: setinde
x

Htaccess:: setphpr
eference

Htaccess:: showus
ers

▼ ImageManager

ImageManager:: c
onvert

ImageManager:: di
mensions

ImageManager:: h
dimension

ImageManager:: s
cale

ImageManager:: th
umbnail

ImageManager:: w
dimension

▼ LastLogin

LastLogin:: lastlogi
n

▼ LeechProtect

LeechProtect:: dis
able

LeechProtect:: ena
ble

LeechProtect:: set
up

LeechProtect:: sho
wpasswdfile

LeechProtect:: stat
us

▼ LogManager

LogManager:: listd
ownloads

LogManager:: sav
esettings

LogManager:: sho
wsettings

▼ MagicRevision

MagicRevision:: uri

▼ Mime

Mime:: add_handl
er

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redire
ct

Mime:: del_handler

Mime:: del_hotlink

Mime:: del_mime

Mime:: del_redirect

Mime:: linkallownul
l

Mime:: linkenable

Mime:: linkexts

Mime:: linkrurl

Mime:: linkurIs

▼ Mysql

Mysql:: adddb

Mysql:: addhost

Mysql:: adduser

Mysql:: adduserdb

Mysql:: checkdb

Mysql:: deldb

Mysql:: delhost

Mysql:: deluser

Mysql:: deluserdb

Mysql:: gethost

Mysql:: initcache

Mysql:: listdbs

Mysql:: listdbsopt

Mysql:: listusers

Mysql:: listusersopt

Mysql:: number_of
_dbs

Mysql:: number_of
_users

Mysql:: repairdb

Mysql:: routines

Mysql:: updatepriv
s

▼ Net

Net:: dnslookup

Net:: dnszone

Net:: sethastracero
ute

▼ News

News:: displaynew
s

▼ NVData

NVData:: set

▼ OptimizeWS

OptimizeWS:: load
optimizesettings

OptimizeWS:: load
optimizesettings (b
ytes)

OptimizeWS:: opti
mizews

▼ Park

Park:: disabledir
ect

Park:: getredirectu
rl

Park:: park

Park:: setredirectur
l

Park:: unpark

▼ Postgres

Postgres:: adddb

Postgres:: adduser

Postgres:: adduser
db

Postgres:: deldb

Postgres:: deluser

Postgres:: deluser
db

Postgres:: initcach
e

Postgres:: listdbso
pt

Postgres:: listusers
opt

Postgres:: number
_of_dbs

Postgres:: number
_of_users

▼ ProxyUtils

ProxyUtils:: proxya
ddress

▼ Resellers

Resellers:: accoun
tlistopt

Resellers:: themeli
stopt

▼ Serverinfo

Serverinfo:: servic
estatus

▼ SetLang

SetLang:: listlangs
opt

SetLang:: setlang

▼ SpamAssassin

SpamAssassin:: co
nfig

SpamAssassin:: sa
veconfig

▼ SSH

SSH:: getport

▼ SSL

SSL:: delete

SSL:: deletecrt

SSL:: deletecsr

SSL:: deletekey

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcabundle

SSL:: getcnname

SSL:: install

SSL:: installedhost

SSL:: listkeysopt

SSL:: showcrt

SSL:: showcsr

SSL:: showkey

SSL:: sslsharedsta
tus

SSL:: uploadcrt

SSL:: uploadkey

▼ StatManager

StatManager:: doF
orm

StatManager:: upd
ateUserConfig

▼ Stats

Stats:: analoglist

Stats:: awstats

Stats:: bwbar

Stats:: errlog

Stats:: lastvisitors

Stats:: showbandw
idth

Stats:: webalizer

Stats:: webalizerftp

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: cplist
subdomains

SubDomain:: disab
lesubrd

SubDomain:: listsu
bdomainsop

SubDomain:: setsu
burl

▼ UI

UI:: confirm

UI:: redirect

UI:: showresult