

# UAPI Functions - Bandwidth::get\_enabled\_protocols

## Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

- Backup
  - Backup::fullbackup\_to\_ftp
  - Backup::fullbackup\_to\_homedir
  - Backup::fullbackup\_to\_scp\_with\_key

- Backup::fullbackup\_to\_scp\_with\_password

- Backup::list\_backups

- Bandwidth
  - Bandwidth::get\_enabled\_protocols
  - Bandwidth::get\_retention\_periods
  - Bandwidth::query

- Batch
  - Batch::strict

- Brand
  - Brand::read

- Branding
  - Branding::file
  - Branding::get\_applications
  - Branding::get\_application\_information
  - Branding::get\_available\_applications
  - Branding::get\_information\_for\_applications

## Description

This function returns a list of the server's enabled protocols.

## Examples

### ▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/Bandwidth/get_enabled_protocols
```

**Note:**  
This example calls the UAPI function via a cPanel session. For more information, read our Guide to UAPI documentation.

### ▼ LiveAPI PHP Class

```
$cpanel = new CPANEL(); // Connect to cPanel - only do this once.  
  
//Retrieves the server's enabled protocols.  
$get_protocols = $cpanel->uapi('Bandwidth', 'get_enabled_protocols');
```

**Note:**  
For more information, read our Guide to the LiveAPI System.

## Function information

## About this module

The Bandwidth module reports bandwidth information for the account.

## About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster
  - CacheBuster:: read
  - CacheBuster:: update
- Chkserverd
  - Chkserverd:: get\_external\_ports
  - Chkserverd:: get\_external\_ports\_ssl
- Chrome
  - Chrome:: get\_domain
- Contactus
  - Contactus:: is\_enabled
- cPAddons
  - cPAddons:: get\_available\_addons
  - cPAddons:: get\_instance\_settings
  - cPAddons:: list\_addon\_instances
- cPGreyList
  - cPGreyList:: disable\_all\_domains
  - cPGreyList:: disable\_domains
  - cPGreyList:: enable\_all\_domains
  - cPGreyList:: enable\_domains
  - cPGreyList:: has\_greylisting\_enabled
  - cPGreyList:: list\_domains
- DAV
  - DAV:: disable\_shared\_global\_addressbook
  - DAV:: enable\_shared\_global\_addressbook
  - DAV:: get\_calendar\_contacts\_config
  - DAV:: has\_shared\_global\_addressbook
  - DAV:: is\_dav\_service\_enabled

### LiveAPI Perl Module

```

my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Retrieves the
server's enabled
protocols.
my $get_protocols =
$cpliveapi->uapi(
    'Bandwidth',
    'get_enabled_protocols'
);

```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

### cPanel Template Toolkit

```

<!-- Retrieves the
server's enabled
protocols. -->
[%
execute('Bandwidth',
'get_enabled_protocols')
%]

```

**Note:**  
For more information, read our [Guide to Template Toolkit documentation](#).

**Notes:**

- The *Fe*
- *Ur*
- *mu*
- *us*
- *20*
- *or*
- *20*
- *20*
- *or*
- *20*
- *).*

### Find a function

- UAPI Modules - Bandwidth - The Bandwidth module reports bandwidth information for the account.

- DAV:: is\_horde\_enabled
- DCV
    - DCV:: check\_domains\_via\_dns
    - DCV:: check\_domains\_via\_http
    - DCV:: ensure\_domains\_can\_pass\_dcv
  - DomainInfo
  - DomainInfo:: domains\_data
  - DomainInfo:: list\_domains
  - DomainInfo:: main\_domain\_builtin\_subdomain\_aliases
  - DomainInfo:: single\_domain\_data
- DNS
  - DNS:: ensure\_domains\_reside\_only\_locally
  - DNS:: has\_local\_authority
- DNSSEC
  - DNSSEC:: disable\_dnssec
  - DNSSEC:: enable\_dnssec
  - DNSSEC:: fetch\_dns\_records
  - DNSSEC:: set\_nsec3
  - DNSSEC:: unset\_nsec3
- Email
  - Email:: account\_name
  - Email:: add\_auto\_responder
  - Email:: add\_domain\_forwarder
  - Email:: add\_forwarder
  - Email:: add\_list
  - Email:: add\_mailman\_delegates
  - Email:: add\_mx
  - Email:: add\_pop
  - Email:: add\_spam\_filter

## Command Line

```
uapi --user=username
Bandwidth
get_enabled_protocols
```

### Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

## Output (JSON)

```
{
  "result": {
    "messages": null,
    "warnings": null,
    "status": 1,
    "data": [
      "imap",
      "pop3",
      "smtp"
    ],
    "metadata": {
      "transformed": 1
    },
    "errors": null
  }
}
```

### Note:

Use cPanel's *API Shell* interface (`cPanel >> Home >> Advanced >> API Shell`) to directly test cPanel API calls.

- UAPI Functions - Bandwidth::query — This function queries an account's bandwidth data and returns a report.

Email:: browse\_mailbox

Email:: change\_mx

Email:: check\_fastmail

Email:: check\_pipe\_forwarder

Email:: delete\_auto\_responder

Email:: delete\_domain\_forwarder

Email:: delete\_filter

Email:: delete\_forwarder

Email:: delete\_held\_messages

Email:: delete\_list

Email:: delete\_mx

Email:: delete\_pop

Email:: disable\_filter

Email:: disable\_mailbox\_autocreate

Email:: disable\_spam\_assassin

Email:: disable\_spam\_autodelete

Email:: disable\_spam\_box

Email:: dispatch\_client\_settings

Email:: edit\_pop\_quota

Email:: enable\_filter

Email:: enable\_mailbox\_autocreate

Email:: enable\_spam\_assassin

Email:: enable\_spam\_box

Email:: fetch\_charmaps

Email:: fts\_rescan\_mailbox

Email:: generate\_mailman\_opt

Email:: get\_auto\_responder

Email:: get\_chase

## Parameters

This function does not accept parameters.

## Returns

Return	Type	Description	Possible values	Example
--------	------	-------------	-----------------	---------

ts

Email: get\_client\_settings

Email: get\_default\_email\_quota

Email: get\_default\_email\_quota\_mib

Email: get\_disk\_usage

Email: get\_filter

Email: get\_held\_message\_count

Email: get\_mailbox\_autocreate

Email: get\_mailman\_delegates

Email: get\_main\_account\_disk\_usage

Email: get\_main\_account\_disk\_usage\_bytes

Email: get\_max\_email\_quota

Email: get\_max\_email\_quota\_mib

Email: get\_pop\_quota

Email: get\_spam\_settings

Email: get\_webmail\_settings

Email: has\_delegated\_mailman\_lists

Email: has\_plaintext\_authentication

Email: hold\_outgoing

Email: is\_integer

Email: list\_autoresponders

Email: list\_default\_address

Email: list\_domain\_forwarders

Email: list\_filters

Email: list\_filters\_backups

Email: list\_forwarders

Email: list\_forward

data	<i>array of strings</i>	The bandwidth protocols that the server records.	<ul style="list-style-type: none"> <li>• ftp</li> <li>• http</li> </ul> <div data-bbox="935 201 1031 1514" style="border: 1px solid orange; padding: 5px; text-align: center;"> <p><b>N o t e : T h i s v a l u e i n c l u d e s a l l w e b t r a f f i c f o r t h e 8 0 a n d 4 4 3 p o r t s .</b></p> </div> <ul style="list-style-type: none"> <li>• imap</li> <li>• pop3</li> <li>• smtp</li> </ul>	imap
------	-------------------------	--	---	------

ers\_backups

Email:: list\_lists

Email:: list\_mail\_d  
omains

Email:: list\_mx

Email:: list\_pops

Email:: list\_pops\_  
with\_disk

Email:: list\_system  
\_filter\_info

Email:: passwd\_list

Email:: passwd\_po  
p

Email:: release\_ou  
tgoing

Email:: remove\_m  
ailman\_delegates

Email:: reorder\_filt  
ers

Email:: set\_always  
\_accept

Email:: set\_default  
\_address

Email:: set\_list\_pri  
vacy\_options

Email:: stats\_db\_st  
atus

Email:: store\_filter

Email:: suspend\_in  
coming

Email:: suspend\_lo  
gin

Email:: suspend\_o  
utgoing

Email:: trace\_filter

Email:: unsuspend  
\_incoming

Email:: unsuspend  
\_login

Email:: unsuspend  
\_outgoing

Email:: verify\_pass  
word

▼ EmailAuth

EmailAuth:: disabl  
e\_dkim

EmailAuth:: enable  
\_dkim

EmailAuth:: ensure  
\_dkim\_keys\_exist

EmailAuth:: fetch\_  
dkim\_private\_keys

EmailAuth:: install  
\_dkim\_private\_key  
s

EmailAuth:: install  
\_spf\_records

EmailAuth:: validat  
e\_current\_dkims

EmailAuth:: validat  
e\_current\_ptrs

EmailAuth:: validat  
e\_current\_spfs

ExternalAuthenticat  
ion

ExternalAuthentic  
ation:: add\_auth\_li  
nk

ExternalAuthentic  
ation:: configured\_  
modules

ExternalAuthentic  
ation:: get\_authn\_lin  
ks

ExternalAuthentic  
ation:: has\_external  
\_auth\_modules\_co  
nfigured

ExternalAuthentic  
ation:: remove\_auth  
n\_link

Features

Features:: has\_fea  
ture

Features:: list\_feat  
ures

Fileman

Fileman:: autocom  
pletedir

Fileman:: empty\_tr  
ash

Fileman:: get\_file\_  
content

Fileman:: get\_file\_i  
nformation

Fileman:: list\_files

Fileman:: save\_file  
\_content

Fileman:: transcod  
e

Fileman:: upload\_fi  
les

Ftp

Ftp:: add\_ftp

Ftp:: allows\_anonymous\_ftp

Ftp:: allows\_anonymous\_incoming

Ftp:: delete\_ftp

Ftp:: ftp\_exists

Ftp:: get\_ftp\_daemon\_info

Ftp:: get\_port

Ftp:: get\_quota

Ftp:: get\_welcome\_message

Ftp:: kill\_session

Ftp:: list\_ftp

Ftp:: list\_ftp\_with\_disk

Ftp:: list\_sessions

Ftp:: passwd

Ftp:: server\_name

Ftp:: set\_anonymous\_ftp

Ftp:: set\_anonymous\_ftp\_incoming

Ftp:: set\_homedir

Ftp:: set\_quota

Ftp:: set\_welcome\_message

#### ▼ Integration

Integration:: fetch\_url

#### ▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

#### ▼ LangPHP

LangPHP:: php\_get\_domain\_handler

LangPHP:: php\_get\_impacted\_domains

LangPHP:: php\_get\_installed\_versions

LangPHP:: php\_get



t\_system\_default\_  
version

LangPHP:: php\_ge  
t\_vhost\_versions

LangPHP:: php\_ini  
\_get\_user\_basic\_d  
irectives

LangPHP:: php\_ini  
\_get\_user\_content

LangPHP:: php\_ini  
\_get\_user\_paths

LangPHP:: php\_ini  
\_set\_user\_basic\_d  
irectives

LangPHP:: php\_ini  
\_set\_user\_content

LangPHP:: php\_se  
t\_vhost\_versions

▼ LastLogin

LastLogin:: get\_las  
t\_or\_current\_logge  
d\_in\_ip

▼ Locale

Locale:: get\_attri  
butes

▼ Mailboxes

Mailboxes:: expun  
ge\_mailbox\_mess  
ages

Mailboxes:: expun  
ge\_messages\_for  
\_mailbox\_guid

Mailboxes:: get\_m  
ailbox\_status

Mailboxes:: has\_ut  
f8\_mailbox\_names

Mailboxes:: set\_utf  
8\_mailbox\_names

▼ Market

Market:: cancel\_pe  
nding\_ssl\_certifica  
te

Market:: create\_sh  
opping\_cart

Market:: get\_all\_pr  
oducts

Market:: get\_certifi  
cate\_status\_detail  
s

Market:: get\_login  
\_url

Market:: get\_pendi  
ng\_ssl\_certificates

Market:: get\_provi

der\_specific\_dcv\_  
constraints

Market:: get\_provi  
ders\_list

Market:: get\_ssl\_c  
ertificate\_if\_availa  
ble

Market:: process\_s  
sl\_pending\_queue

Market:: request\_s  
sl\_certificates

Market:: set\_status  
\_of\_pending\_queu  
e\_items

Market:: set\_url\_af  
ter\_checkout

Market:: validate\_l  
ogin\_token

▼ Mime

Mime:: add\_handl  
er

Mime:: add\_hotlink

Mime:: add\_mime

Mime:: add\_redire  
ct

Mime:: delete\_han  
dler

Mime:: delete\_hotli  
nk

Mime:: delete\_mim  
e

Mime:: delete\_redi  
rect

Mime:: list\_handler  
s

Mime:: list\_hotlinks

Mime:: list\_mime

Mime:: list\_redirect  
s

Mime:: redirect\_inf  
o

▼ ModSecurity

ModSecurity:: disa  
ble\_all\_domains

ModSecurity:: disa  
ble\_domains

ModSecurity:: ena  
ble\_all\_domains

ModSecurity:: ena  
ble\_domains

ModSecurity:: has  
\_modsecurity\_inst

alled

ModSecurity:: list\_ domains

▼ Mysql

Mysql:: add\_host

Mysql:: add\_host\_ note

Mysql :: check\_dat abase

Mysql:: create\_dat abase

Mysql:: create\_use r

Mysql:: delete\_dat abase

Mysql:: delete\_hos t

Mysql:: delete\_use r

Mysql:: get\_host\_n otes

Mysql:: get\_privile ges\_on\_database

Mysql:: get\_restrict ions

Mysql:: get\_server \_information

Mysql:: locate\_ser ver

Mysql:: rename\_d atabase

Mysql:: rename\_us er

Mysql:: repair\_dat abase

Mysql:: revoke\_ac cess\_to\_database

Mysql:: set\_passw ord

Mysql:: set\_privile ges\_on\_database

▼ Notifications

Notifications:: get\_ notifications\_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile\_rel ative\_uri

▼ PassengerApps

PassengerApps:: d  
isable\_application

PassengerApps:: e  
dit\_application

PassengerApps:: e  
nable\_application

PassengerApps:: li  
st\_applications

PassengerApps:: r  
egister\_application

PassengerApps:: u  
nregister\_applicati  
on

▼ PasswdStrength

PasswdStrength::  
get\_required\_stren  
gth

▼ Personalization

Personalization::se  
t

Personalization ::g  
et

▼ Postgresql

Postgresql:: create  
\_database

Postgresql:: create  
\_user

Postgresql:: delete  
\_database

Postgresql:: get\_re  
strictions

Postgresql:: grant\_  
all\_privileges

Postgresql:: renam  
e\_database

Postgresql:: renam  
e\_user

Postgresql:: renam  
e\_user\_no\_passw  
ord

Postgresql:: revok  
e\_all\_privileges

Postgresql:: set\_p  
assword

▼ Pushbullet

Pushbullet:: send\_  
test\_message

▼ Quota

Quota:: get\_quota  
\_info

▼ Resellers

Resellers:: list\_acc  
ounts

- ▼ ResourceUsage
  - ResourceUsage:: get\_usages
- ▼ Restore
  - Restore:: directory\_listing
  - Restore:: get\_users
  - Restore:: query\_file\_info
  - Restore:: restore\_file
- ▼ Session
  - Session:: create\_temp\_user
- ▼ SiteTemplates
  - SiteTemplates:: list\_site\_templates
  - SiteTemplates:: list\_user\_settings
  - SiteTemplates:: publish
- ▼ SpamAssassin
  - SpamAssassin :: clear\_spam\_box
  - SpamAssassin:: get\_symbolic\_test\_names
  - SpamAssassin:: get\_user\_preferences
  - SpamAssassin:: update\_user\_preference
- ▼ SSH
  - SSH:: get\_port
- ▼ SSL
  - SSL:: add\_autossl\_excluded\_domains
  - SSL:: check\_shared\_cert
  - SSL:: delete\_cert
  - SSL:: delete\_csr
  - SSL:: delete\_key
  - SSL:: delete\_ssl
  - SSL :: disable\_mail\_sni
  - SSL:: enable\_mail\_sni
  - SSL:: fetch\_best\_for\_domain

SSL:: fetch\_cert\_in  
fo

SSL:: fetch\_certific  
ates\_for\_fqdns

SSL:: fetch\_key\_a  
nd\_cabundle\_for\_  
certificate

SSL:: find\_certifica  
tes\_for\_key

SSL:: find\_csrs\_for  
\_key

SSL:: generate\_ce  
rt

SSL:: generate\_cs  
r

SSL:: generate\_ke  
y

SSL:: get\_autoss\_  
excluded\_domains

SSL:: get\_autoss\_  
pending\_queue

SSL:: get\_autoss\_  
problems

SSL:: get\_cabundl  
e

SSL:: get\_cn\_nam  
e

SSL:: install\_ssl

SSL:: installed\_ho  
st

SSL:: installed\_ho  
sts

SSL:: is\_autoss\_  
check\_in\_progress

SSL:: is\_mail\_sni\_  
supported

SSL:: is\_sni\_supp  
orted

SSL:: list\_certs

SSL:: list\_csrs

SSL:: list\_keys

SSL:: list\_ssl\_item  
s

SSL:: mail\_sni\_sta  
tus

SSL:: rebuild\_mail  
\_sni\_config

SSL:: rebuildssldb

SSL:: remove\_aut  
oss\_excluded\_do  
mains

SSL:: set\_autossl\_excluded\_domains

SSL:: set\_cert\_friendly\_name

SSL:: set\_csr\_friendly\_name

SSL:: set\_key\_friendly\_name

SSL:: set\_primary\_ssl

SSL:: set\_ssl\_share

SSL:: show\_cert

SSL:: show\_csr

SSL:: show\_key

SSL:: start\_autossl\_check

SSL:: upload\_cert

SSL:: upload\_key

▼ StatsBar

StatsBar:: get\_stats

▼ Styles

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

▼ SubDomain

SubDomain:: addsubdomain

▼ Themes

Themes:: get\_theme\_base

Themes:: list

Themes:: update

▼ TwoFactorAuth

TwoFactorAuth:: generate\_user\_configuration

TwoFactorAuth:: get\_user\_configuration

TwoFactorAuth:: remove\_user\_configuration

TwoFactorAuth:: set\_user\_configuration

▼ UserManager

UserManager:: check\_account\_conflict

ts

UserManager:: create\_user

UserManager:: delete\_user

UserManager:: dismiss\_user

UserManager:: edit\_user

UserManager:: list\_users

UserManager:: lookup\_service\_account

UserManager:: lookup\_user

UserManager:: merge\_service\_account

UserManager:: unlink\_service\_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete\_user

WebDisk:: set\_home\_dir

WebDisk:: set\_password

WebDisk:: set\_permissions

▼ WebmailApps



WebmailApps:: list  
webmailapps

▼ WebVhosts

WebVhost:: list\_do  
mains

WebVhost:: list\_ssl  
\_capable\_domains

▼ WordPressBackup

WordPressBackup  
:: any\_running

WordPressBackup  
:: cancel

WordPressBackup  
:: cleanup

WordPressBackup  
:: get\_available\_ba  
ckups

WordPressBackup  
:: is\_running

WordPressBackup  
:: start

▼ WordPressInstance

Manager

WordPressInstanc  
eManager:: cancel  
\_scan

WordPressInstanc  
eManager:: cleanu  
p\_scan

WordPressInstanc  
eManager:: chang  
e\_admin\_passwor  
d

WordPressInstanc  
eManager:: config  
ure\_autoupdate

WordPressInstanc  
eManager:: get\_ap  
i\_version

WordPressInstanc  
eManager:: get\_in  
stance\_by\_id

WordPressInstanc  
eManager:: get\_in  
stances

WordPressInstanc  
eManager:: get\_lat  
est\_wordpress\_ver  
sion\_from\_wordpr  
ess\_org

WordPressInstanc  
eManager:: get\_sc  
an\_results

WordPressInstanc  
eManager:: is\_inst  
allable\_addon\_ava  
ilable

WordPressInstanceManager:: **start\_scan**

▼ **WordPressRestore**

WordPressRestore  
:: **any\_running**

WordPressRestore  
:: **cleanup**

WordPressRestore  
:: **start**