

cPanel API 2 Functions - Email::listpopswithimage

Guide to cPanel API 2

Return Data

Filter and Sort Output

Paginate Output

Output Columns

Calls from the WHM API

cPanel Tags (deprecated)

Description

This function lists the cPanel account's email addresses with `mainacct.jpg` image links.

Warning:

We **strongly** recommend that you use [UAPI](#) instead of cPanel API 2. However, no equivalent UAPI function exists.

Important:

In cPanel & WHM version 76 and later, when you disable the `MailReceive` role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples [AddOnDomain](#)

WHM API (JSON)

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?cpanel_jsonapi_user=user&cpanel_jsonapi_api_version=2&cpanel_jsonapi_module=Email&cpanel_jsonapi_func=listpopswithimage&regex="user"
```

Note:

For more information, read our [Calls from the WHM API](#) documentation.

Function information

About this module

The Email module modifies cPanel email account settings.

About cPanel API 2

AddOnDomain:: adddondomain

main:: adddondomain

AddOnDomain:: deladdondomain

AddOnDomain:: listaddondomains

Backups

Backups:: listfullbackups

Bandwidth

Bandwidth:: addhttpbandwidth

Bandwidth:: getbwdata

Bandwidth:: gethourlyaveragebwoveryear

BoxTrapper

BoxTrapper:: accountmanagelist

Branding

Branding:: addbrandingobj

Branding:: applist

Branding:: brandingeditor

Branding:: createpkg

Branding:: cssmerge

Branding:: delbrandingobj

Branding:: delpkg

Branding:: gensprites

Branding:: getbrandingpkg

Branding:: getbrandingpkgstatus

Branding:: getdefaultbrandingpkg

Branding:: installbrandingpkgs

Branding:: installimages

Branding:: killimages

Branding:: listingtypes

Branding:: listobjecttypes

Branding:: preloadconf

Branding:: resetall

Branding:: resetscss

Branding:: resethtml

Branding:: resolvefile

Branding:: resolveocalcss

Branding:: saveocalcss

Branding:: setbrandingpkgstatus

Branding:: showpkgs

Branding:: spritelist

▼ CSVImport

CSVImport:: columnchoices

CSVImport:: configimport

CSVImport:: data

CSVImport:: fetchimportdata

CSVImport:: isenabled

CSVImport:: loaddata

CSVImport:: processdata

CSVImport:: sendcontact

CSVImport:: uploadimport

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// List email  
addresses that  
contain "user", with  
mainacct.jpg links.  
$list_email_addresses  
= $cpanel->api2(  
    'Email',  
    'listpopswithimage',  
    array(  
        'regex'  
=> 'user',  
    )  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

cPanel API 2 accesses and modifies data for cPanel accounts.

Notes:

- The `Fe`
- The `Ur`
- The `mt`
- The `us`
- The `20`
- The `or`
- The `20`
- The `).`
- The `20`
- The `or`
- The `20`
- The `).`

Find a function

- cPanel API 2 Functions - Email::editQuota — This function modifies an email account's disk quota.

- Contactus:: isenab led
 - Contactus:: sendcontact
 - Cron:: add_line
 - Cron:: edit_line
 - Cron:: fetchcron
 - Cron:: get_email
 - Cron:: listcron
 - Cron:: remove_line
 - Cron:: set_email
 - CustInfo:: contactemails
 - CustInfo:: contactrefs
 - CustInfo:: displaycontactinfo
 - CustInfo:: savecontactinfo
 - DBmap:: status
 - DBmap:: version
 - DKIMUI:: available
 - DKIMUI:: getrecords
 - DKIMUI:: install
 - DKIMUI:: installed
 - DKIMUI:: uninstall
 - DenyIp:: listdenypis
 - DiskCounter:: disk_counter
 - DiskUsage:: buildcache
 - DiskUsage:: clearcache
 - DiskUsage:: fetch_raw_disk_usage
 - DiskUsage:: fetchdiskusage
 - DiskUsage:: fetchdiskusagewithextras

LiveAPI Perl Module

```

my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# List email
addresses that
contain "user", with
mainacct.jpg links.
my
$list_email_addresses
= $cpliveapi->api2(
'Email',
'listpopswithimage',
{
'regex'
=> 'user',
}
);

```

Note:

For more information, read our [Guide to the LiveAPI System](#).

cPanel Tag System (deprecated)

Warnings:

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Deprecated cPanel Tag Usage](#) documentation.

- cPanel API 2 Functions - Email::password - This function modifies an email account's password.
- cPanel API 2 Functions - Email::listdefaultaddresses - This function retrieves the domain's default address and its rules.

▼ DnsLookup

DnsLookup:: name
2ip

▼ DomainLookup

DomainLookup:: c
ountbaseddomains

DomainLookup:: g
etbaseddomains

DomainLookup:: g
etdocroot

DomainLookup:: g
etdocroots

DomainLookup:: g
etmaindomain

▼ Email

Email:: accountna
me

Email:: adddomain
forward

Email:: addforward

Email:: addmx

Email:: addpop

Email:: browsebox
es

Email:: changemx

Email:: checkmain
discard

Email:: clearpopca
che

Email:: deletefilter

Email:: delforward

Email:: delmx

Email:: delpop

Email:: disablefilter

Email:: editquota

Email:: enablefilter

Email:: fetchautore
sponder

Email:: fetchcharm
aps

Email:: filteractions

Email:: filterlist

Email:: filtername

Email:: filterrules

Email:: get_archivi
ng_configuration

Email:: get_archivi
ng_default_configu

▼ Command Line

```
cpapi2  
--user=username Email  
listpopswithimage  
regex=user
```

Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- You **must** run the `--user=username` command.
- For more information and additional output options, read our [Guide to cPanel API 2](#) documentation or run the `cpapi2 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapi2` command:

```
/usr/local  
/cpanel/bi  
n/cpapi2
```

▼ Output (JSON)

```
{  
  "cpanelresult": {  
    "apiversion": 2,  
    "func":  
    "listpopswithimage",  
    "data": [  
      {  
        "email":  
        "user@example.com",  
        "login":  
        "user@example.com",  
        "login":  
        "<img  
src=\"/frontend/cpanel  
-skin/images/mainacct  
.jpg\">",  
        "suspended_incoming":  
        0,  
        "suspended_login": 0  
      },  
      {
```

- cPanel API 2 Functions - Email::listaliasbackups - This function retrieves a list of the account's domains that use aliases and custom default addresses.

ration
Email: get_archiving_types
Email: get_default_email_quota
Email: get_email_signing
Email: get_max_email_quota
Email: getabsbrowserwsedir
Email: getalwaysaccept
Email: getdiskusage
Email: getmxcheck
Email: has_delegated_mailman_lists
Email: list_system_filter_info
Email: listaliasbackups
Email: listautoresponders
Email: listdefaultaddresses
Email: listdomainforwards
Email: listfilterbackups
Email: listfilters
Email: listforwards
Email: listlists
Email: listmaildomains
Email: listmx
Email: listmxs
Email: listpops
Email: listpopssingle
Email: listpopswithdisk
Email: listpopswithimage
Email: loadfilter
Email: passwdpop
Email: reorderfilters

```
        "email":  
"data@userexample.com"  
    ,  
        "login":  
"data@userexample.com"  
    ,  
        "login":  
"src="/frontend/cpanel  
-skin/images/mainacct  
.jpg">"  
    ,  
    "suspended_incoming":  
0,  
    "suspended_login":0  
    },  
    {  
        "email":  
"manyusers@example.co  
m"  
    ,  
        "login":  
"manyusers@example.co  
m"  
    ,  
        "login":  
"src="/frontend/cpanel  
-skin/images/mainacct  
.jpg">"  
    ,  
    "suspended_incoming":  
0,  
    "suspended_login":0  
    },  
    {  
        "email":  
"cpaneluser"  
    ,  
        "login":  
"Main Account"  
    ,  
        "login":  
"src="/frontend/cpanel  
-skin/images/mainacct  
.jpg">"  
    ,  
    "suspended_incoming":  
0,  
    "suspended_login":0  
    }  
    ],  
    "event": {
```

Email:: set_archiving_configuration

Email:: set_archiving_default_configuration

Email:: set_email_signing

Email:: setalwaysaccept

Email:: setdefaultaddress

Email:: setmxcheck

Email:: storefilter

Email:: tracefilter

▼ EmailTrack

EmailTrack:: search

EmailTrack:: stats

EmailTrack:: trace

▼ Encoding

Encoding:: get_encodings

Encoding:: guess_file

Encoding:: guess_file_opts

▼ FSTest

FSTest:: dirisempty

▼ Fileman

Fileman:: autocompletedir

Fileman:: fileop

Fileman:: getabsdir

Fileman:: getdir

Fileman:: getdiractions

Fileman:: getdiskinfo

Fileman:: getedittype

Fileman:: getfileactions

Fileman:: getpath

Fileman:: listfiles


Fileman:: mkdir

Fileman:: mkfile

Fileman:: savefile

```
"result": 1  
},
```

- Fileman:: search
- Fileman:: statfiles
- Fileman:: uploadfiles
- Fileman:: viewfile
- ForcePassword
 - ForcePassword:: get_force_password_flags
 - ForcePassword:: update_force_password_flags
- Frontpage
 - Frontpage:: fpenabled
 - Frontpage:: list
- Ftp
 - Ftp:: addftp
 - Ftp:: delftp
 - Ftp:: listftp
 - Ftp:: listftpsessions
 - Ftp:: listftpwithdisk
 - Ftp:: passwd
 - Ftp:: setquota
- Gpg
 - Gpg:: listgpgkeys
 - Gpg:: listsecretgpgkeys
 - Gpg:: number_of_private_keys
 - Gpg:: number_of_public_keys
- Htaccess
 - Htaccess:: listusers
 - Htaccess:: listusers
- HttpUtils
 - HttpUtils:: getdirindices
- ImageManager
 - ImageManager:: thumbnail
- LVEInfo
 - LVEInfo:: getUsage
- LangMods
 - LangMods:: getarchname
 - LangMods:: getkey



Parameters

Parameter	Type	Description	Possible values	Example
regex	string	A Perl Compatible Regular Expression (PCRE) that filters the results. The system matches the PCRE to both the email address's username and domain. If you do not use this parameter, the function returns image links for all of the cPanel account's email addresses.	A valid PCRE.	user

Returns

Return	Type	Description	Possible values	Example
email	string	The email address, or the main account username.	A valid email address, or the username for the main account.	user@example.com

LangMods:: getpre
fix

LangMods:: install

LangMods:: langlis
t

LangMods:: list_av
ailable

LangMods:: list_in
stalled

LangMods:: magic
_status

LangMods:: pre_ru
n

LangMods:: search

LangMods:: setup

LangMods:: uninst
all

LangMods:: updat
e

▼ LeechProtect

LeechProtect:: set
up

▼ Locale

Locale:: get_encod
ing

Locale:: get_html_
dir_attr

Locale:: get_locale
_name

Locale:: get_user_
ocale

Locale:: get_user_
ocale_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse
r

Logaholic:: adduse
rprofile

Logaholic:: deleteu
ser

Logaholic:: deleteu
serprofile

Logaholic:: edituse
r

Logaholic:: fetchus
er

Logaholic:: listuser
profiles

Logaholic:: logahol
iclink

login	<i>string</i>	The email address or the Main Account string, and an HTML link to the mainacct.jpg image.	<ul style="list-style-type: none"> • A valid email address, or the string Main Account. • HTML code to display the account's mainacct.jpg image. The cPanel theme that the account uses determines this image's location. 	
suspended_incoming	<i>Boolean</i>	Whether the email account's incoming email is suspended.	<ul style="list-style-type: none"> • 1 — Incoming email is suspended. • 0 — Incoming email is not suspended. <p>Note : We introduced this return in cPanel & WHM version 54.</p>	0
suspended_login	<i>Boolean</i>	Whether the user's ability to log in to, send mail from, and read their email account is suspended.	<ul style="list-style-type: none"> • 1 — Logins are suspended. • 0 — Logins are not suspended. <p>Note : We introduced this return in cPanel & WHM version 54.</p>	0

- Logaholic:: proces
sstats
- ▼ Mime
 - Mime:: list_hotlinks
 - Mime:: listhandlers
 - Mime:: listmime
 - Mime:: listredirects
 - Mime:: redirectname
 - Mime:: redirecturlname
- ▼ MySQLFE
 - MySQLFE:: authorizehost
 - MySQLFE:: changedbuserpassword
 - MySQLFE:: createdb
 - MySQLFE:: createdbuser
 - MySQLFE:: dbuserexists
 - MySQLFE:: deauthorizehost
 - MySQLFE:: deletedb
 - MySQLFE:: deletedbuser
 - MySQLFE:: getalldbinfo
 - MySQLFE:: getalldbusersanddbs
 - MySQLFE:: getdbserverprivileges
 - MySQLFE:: getdbusers
 - MySQLFE:: gethosts
 - MySQLFE:: getmysqlprivileges
 - MySQLFE:: getmysqlserverprivileges
 - MySQLFE:: has_my.cnf_for_cpuser
 - MySQLFE:: listdbs
 - MySQLFE:: listdbsbackup
 - MySQLFE:: listhosts
 - MySQLFE:: listusers
 - MySQLFE:: listusersindb

reason	string	A reason for failure. <div style="border: 1px solid orange; padding: 5px; text-align: center;"> Note : This function only returns a reason value if there is an error. </div>	A string that describes the error.	This is an error message.
result	Boolean	Whether the function succeeded.	<ul style="list-style-type: none"> • 1 — The function succeeded. • 0 — The function failed. 	1

MysqlFE:: revoked
buserprivileges

MysqlFE:: setdbu
erprivileges

MysqlFE:: userdbp
rivs

▼ MysqlOptimizer

MysqlOptimizer:: f
etch_slow_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does_news
_exist

News:: does_news
_type_exist

News:: get_news

▼ PHPINI

PHPINI:: getallopti
ons

PHPINI:: getoption
s

▼ Park

Park:: listaddondo
mains

Park:: listparkeddo
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change_
password

Passwd:: set_dige
st_auth

▼ PasswdStrength

PasswdStrength::
appstrengths

PasswdStrength::
get_password_stre
ngth

PasswdStrength::
get_required_stren
gth

▼ Postgres

Postgres:: listdbs

Postgres:: listusers

Postgres:: listusers
indb

Postgres:: userexi
sts

▼ Rand

Rand:: getranddat
a

▼ Resellers

Resellers:: get_su
b_accounts

▼ RoR

RoR:: addapp

RoR:: changeapp

RoR:: importrails

RoR:: listapps

RoR:: listrewrites

RoR:: needsimport

RoR:: removeapp

RoR:: removerewri
te

RoR:: restartapp

RoR:: setuprewrite

RoR:: softrestartap
p

RoR:: startapp

RoR:: stopapp

▼ SetLang

SetLang:: setlocale

▼ SourceIPCheck

SourceIPCheck:: a
ddip

SourceIPCheck:: d
elip

SourceIPCheck:: g
etaccount

SourceIPCheck:: li
stips

SourceIPCheck:: l
oadsecquestions

SourceIPCheck:: r
esetsecquestions

SourceIPCheck:: s
amplequestions

SourceIPCheck:: s
avesecquestions

▼ SPFUJ

SPFUJ:: available

SPFUJ:: count_sett
ings

SPFUI:: entries_co
mplete

SPFUI:: get_raw_r
ecord

SPFUI:: getmainse
rverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list_settin
gs

SPFUI:: load_curr
ent_values

SPFUI:: uninstall

▼ SSH

SSH:: authkey

SSH:: converttopp
k

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey_leg
acy

SSH:: importkey

SSH:: listkeys

▼ SSL

SSL:: fetchcabundl
e

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcnname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

▼ SSLInfo

SSLInfo:: fetchinfo

▼ StatCache

StatCache:: clearc
ache

▼ Stats

Stats:: getmonthly

bandwidth

Stats:: getmonthly
domainbandwidth

Stats:: getthismont
hsbwusage

Stats:: lastapache
hits

Stats:: lastvisitors

Stats:: listanalog

Stats:: listawstats

Stats:: listlastvisito
rs

Stats:: listrawlogs

Stats:: listurchin

Stats:: listwebalize
r

▼ StatsBar

StatsBar:: getrowc
ounter

StatsBar:: rowcoun
ter

StatsBar:: setrowc
ounter

StatsBar:: stat

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: chan
gedocroot

SubDomain:: delsu
bdomain

SubDomain:: getre
servedsubdomains

SubDomain:: listsu
bdomains

SubDomain:: validr
egex

▼ Themes

Themes:: apply_n
ew_theme

Themes:: does_cp
anel_theme_exist

Themes:: get_avail
able_themes

Themes:: get_the
mes_list

Themes:: restore_
saved_theme

▼ UI

UI:: dynamicinclud
elist

UI:: includelist

UI:: listform

UI:: paginate

UI:: paginate_list

▼ UserHttpUtils

UserHttpUtils:: get
dirindices

▼ WebDisk

WebDisk:: addweb
disk

WebDisk:: delweb
disk

WebDisk:: hasdige
st

WebDisk:: listwebd
isks

WebDisk:: passwd
webdisk

WebDisk:: set_dig
est_auth

WebDisk:: set_ho
medir

WebDisk:: set_per
ms

WebDisk:: setstatu
s

▼ WebmailApps

WebmailApps:: list
webmailapps

▼ ZoneEdit

ZoneEdit:: add_zo
ne_record

ZoneEdit:: edit_zo
ne_record

ZoneEdit:: fetch_c
panel_generated_
domains

ZoneEdit:: fetchzo
ne

ZoneEdit:: fetchzo
ne_records

ZoneEdit:: fetchzo
nes

ZoneEdit:: get_zon
e_record

ZoneEdit:: remove
_zone_record

ZoneEdit:: resetzo
ne

