

cPanel API 1 Functions - BoxTrapper::showqueue

Guide to cPanel API 1

Return Data

cPanel Tags
(deprecated)

Bandwidth:
displayheader

Bandwidth:
displaybw

Bandwidth:
displayday

Bandwidth:
displaymainbwheder

▼ BoxTrapper

BoxTrapper::chan
gestatus

BoxTrapper::clean
cfgfilelist

BoxTrapper::edit
msg

BoxTrapper::fetch
cfgfile

BoxTrapper::getb
oxconfdir

BoxTrapper::listm
sgs

BoxTrapper::logco
ntrols

BoxTrapper::mess
ageaction

BoxTrapper::multi
messageaction

BoxTrapper::reset
msg

BoxTrapper::save
cfgfile

BoxTrapper::save
conf

BoxTrapper::show
autowhitelist

BoxTrapper::show
emails

BoxTrapper::show
fromname

BoxTrapper::show
log

Description

This function generates a list of messages in the BoxTrapper queue.

Warning:

cPanel API 1 is **deprecated**. We **strongly** recommend that you **do not use** cPanel API 1. However, no equivalent function exists in our newer APIs.

Important:

In cPanel & WHM version 76 and later, when you disable the MailReceiver role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
$list_boxtrapper_queu  
e =  
$cpanel->apil('BoxTra  
pper', 'showqueue',  
array('1410277881',  
'user@example.com',  
'showmsg.html', '',  
'0') ); // Call the  
function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Func tion infor mati on

About this mod ule

The Box
Trapper
module
manages
the
BoxTrapp
er
subsystem.

Note:

This modul
BoxTrappe
feature.

```
BoxTrapper:: show
message

BoxTrapper:: show
queue

BoxTrapper:: show
queuesearch

BoxTrapper:: show
queuetime

BoxTrapper:: statu
s

BoxTrapper:: statu
sbutton
```

Branding

```
Branding:: file

Branding:: image

Branding:: killing

Branding:: setbran
dingpkg

Branding:: setmya
cctspkg

Branding:: setupdir
s

Branding:: tempset
brandingpkg
```

Cgi

```
Cgi:: backuplink

Cgi:: displayurchin

Cgi:: phpmyadminl
ink
```

Chkserverd

```
Chkserverd:: getexi
mport

Chkserverd:: getexi
mport_ssl
```

ClamScanner

```
ClamScanner:: bar
s
```

cPAddons

```
cPAddons:: mainp
g
```

Cron

```
Cron:: crontab_per
ms
```

CustInfo

```
CustInfo:: getemail
```

Denylp

```
Denylp:: adddenyi
p

Denylp:: deldenyip

Denylp:: listdenyi
ps
```

LiveAPI Perl Module

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.
my
$list_boxtrapper_queu
e =
$cpliveapi->apil('Box
Trapper',
'showqueue',
['1410277881',
'user@example.com',
'showmsg.html', '',
'0'] ); # Call the
function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

cPanel Tag System (deprecated)

Warning:

In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We provide this example to help developers move from the old cPanel tag system to our [LiveAPI](#) system. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs.

```
<cpanel
Module="BoxTrapper::s
howqueue(
$FORM('logdate','acco
unt','showfile','bxac
tion','skipcontrols')
)">
```

About cPanel API 1

cPanel API 1 accesses information about cPanel accounts.

Warning: cPanel API 1 is deprecated. We **strongly** recommend you use cPanel API 2 or the LiveAPI instead.

Notes:

- The `int` return value is `200` or `201` or `202` or `203`.

Find a function

▼ DiskUsage

DiskUsage:: show manager

▼ Email

Email:: addautoresponder

Email:: addforward

Email:: addfilter

Email:: addlist

Email:: addmx

Email:: addpop

Email:: addspam

Email:: addspambox

Email:: addspamfilter

Email:: changemx

Email:: checkfastmail

Email:: checkpipewd

Email:: clearspambox

Email:: delautoresponder

Email:: delforward

Email:: delfilter

Email:: dellist

Email:: delmx

Email:: delpop

Email:: delspam

Email:: delspambox

Email:: disable_spam_autodelete

Email:: editquota

Email:: enable_spam_autodelete

Email:: getaging

Email:: getarsbody

Email:: getarscharset

Email:: getarsfrom

Email:: getarshtml

Email:: getarsinterval

▼ Command Line

```
cpapil
--user=username
BoxTrapper showqueue
1410277881
user@example.com
showmsg.html ' ' 0
```

Notes:

- You **must** URI-encode these values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to cPanel API 1 documentation](#) or run the `cpapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapil` command:

```
/usr/local
/cpanel/bin/cpapil
```

▼ Output (HTML)

```
<input type="hidden"
name="account"
value="test@example.com">
<input type="hidden"
name="baction"
value="multimsgaction">
<tr class="tdshadel">
<td width="5%"><input
type="checkbox"
name="msgid0"
value="qM3nKcgdNWKJQoJmzYxHtUfCHJYMMLki.msg"></td>
<td class="truncate"
truncate="25"
width="15%"><a
href="showmsg.html?account=test@example.com&q=qM3nKcgdNWKJQoJmzYxHtUfCHJYMMLki.msg&b
```

— This function enables Apache SpamAssassin™ for a cPanel account.

- [cPanel API 1 Functions - Email::addspamfilter](#) — This function modifies the minimum Apache SpamAssassin™ spam score.

Email: getarsstart
 Email: getarsstop
 Email: getarssubject
 Email: getmailserver
 Email: getmailserveruser
 Email: getpopquota
 Email: has_spam_as_acl
 Email: has_spam_autodelete
 Email: listmaildomains
 Email: listmaildomainsopt
 Email: listmaildomainsoptndef
 Email: mainacctdiskused
 Email: passwdlist
 Email: passwdpop
 Email: setmxaccept
 Email: spamboxstatus
 Email: spamstatus
 Email: tracefilter

▼ Fileman

Fileman: changeperm
 Fileman: delfile
 Fileman: dofileop
 Fileman: emptytrash
 Fileman: extractfile
 Fileman: fileimg
 Fileman: fmmkdir
 Fileman: fmmkfile
 Fileman: fmpushfile
 Fileman: fmrename
 Fileman: fmsavefile
 Fileman: fmsaveht

```
xaction=">test@cpanel
.net</a></td>
<td class="truncate"
truncate="75"><a
href="showmsg.html?ac
count=test@example.co
m&q=qM3nKcgdNWKJQoJmz
YxHtUfCHJYMMLki.msg&b
xaction=">Subject</a>
</td>
<td width="15%"><a
href="showmsg.html?ac
count=test@example.co
m&q=qM3nKcgdNWKJQoJmz
YxHtUfCHJYMMLki.msg&b
xaction=">02/19
20:40:05</a></td>
</tr>
<tr class="tdshade2">
<td width="5%"><input
type="checkbox"
name="msgid1"
value="TnOFsIHUb3EX19
Wcqlc1DwAEqwSxaIUL.ms
g"></td>
<td class="truncate"
truncate="25"
width="15%"><a
href="showmsg.html?ac
count=test@example.co
m&q=TnOFsIHUb3EX19Wcq
lc1DwAEqwSxaIUL.msg&b
xaction=">test@cpanel
.net</a></td>
<td class="truncate"
truncate="75"><a
href="showmsg.html?ac
count=test@example.co
m&q=TnOFsIHUb3EX19Wcq
lc1DwAEqwSxaIUL.msg&b
xaction=">Subject</a>
</td>
<td width="15%"><a
href="showmsg.html?ac
count=test@example.co
m&q=TnOFsIHUb3EX19Wcq
lc1DwAEqwSxaIUL.msg&b
```

- cPanel API 1 Functions - Email: delspam — This function disables Apache SpamAssassin™ for a cPanel account.
- cPanel API 1 Functions - Email: spamboxstatus — This function checks whether Apache SpamAssassin™ Spam Box is enabled.

- myfile
- Fileman:: fullbacku
p
- Fileman:: getfile
- Fileman:: htmledito
r
- Fileman:: killdir
- Fileman:: listfiles
- Fileman:: listfullba
ckups
- Fileman:: listtempl
ates
- Fileman:: restoreaf
- Fileman:: restored
b
- Fileman:: restorefil
e
- Fileman:: restorefil
es
- Fileman:: savehtml
file
- Fileman:: showper
m
- Fileman:: uploadfil
es
- Fileman:: viewfile
- ▼ Frontpage
 - FrontPage:: addfp
 - FrontPage:: delfp
 - FrontPage:: fpstat
us
- ▼ Ftp
 - Ftp:: addftp
 - Ftp:: delftp
 - Ftp:: ftpquota
 - Ftp:: ftpservernam
e
 - Ftp:: ftpstatslogin
 - Ftp:: get_anonftp
 - Ftp:: get_anonftp
pin
 - Ftp:: get_welcome
msg
 - Ftp:: getftpquota
 - Ftp:: kill_ftp_sessi
on
 - Ftp:: listftpstatsurl
 - Ftp:: passwdfp

```

xaction=">02/19
20:40:14</a></td>
</tr>
```

Parameters

Parameter	Type	Description	Possible values	Example
logdate	string	The date to view. This parameter defaults to the current time.	Any valid time, in Unix time format.	1410277881
account	string	Required The account's email address.	A valid email address on the server.	user@example.com
showfile	string	Required The file to process requests to view emails.	showmsg.html <div style="border: 1px solid red; padding: 5px; width: fit-content; margin: 5px auto;"> Warning : If you specify another file, the HTML output may contain broken links. </div>	showmsg.html
bxaction	string	Required The system does not use this parameter, and will ignore the value.	A placeholder value.	' '
skipcontrols	Boolean	Required Whether the function skips multi-message functions when it prints.	<ul style="list-style-type: none"> 0 — Print multi-message functions. 1 — Skip multi-message functions. 	0

- cPanel API 1 Functions - Email::spamstatus — This function checks whether Apache SpamAssassin™ is enabled.

Ftp:: set_anonftp

Ftp:: set_anonftpin

Ftp:: set_welcome
msg

▼ Gpg

Gpg:: deletekey

Gpg:: exportkey

Gpg:: exportsecret
key

Gpg:: genkey

Gpg:: importkeys

▼ Htaccess

Htaccess:: checkpr
otected

Htaccess:: del_use
r

Htaccess:: getinde
x

Htaccess:: htdirls

Htaccess:: number
_of_users

Htaccess:: phpsele
ctable

Htaccess:: resnam
e

Htaccess:: set_pas
s

Htaccess:: set_pro
tect

Htaccess:: setinde
x

Htaccess:: setphpr
eference

Htaccess:: showus
ers

▼ ImageManager

ImageManager:: c
onvert

ImageManager:: di
mensions

ImageManager:: h
dimension

ImageManager:: s
cale

ImageManager:: th
umbnail

ImageManager:: w
dimension

▼ LastLogin

LastLogin:: lastlogi
n

Returns

This function returns HTML to generate a table that lists the account's queued messages.

- The table sorts messages by date.
- The table contains a checkbox, the message's sender, the message subject, and the date for each message.

▼ LeechProtect

LeechProtect:: disable

LeechProtect:: enable

LeechProtect:: setup

LeechProtect:: showpasswdfile

LeechProtect:: status

▼ LogManager

LogManager:: listdownloads

LogManager:: save settings

LogManager:: show settings

▼ MagicRevision

MagicRevision:: uri

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: del_handler

Mime:: del_hotlink

Mime:: del_mime

Mime:: del_redirect

Mime:: linkallownull

Mime:: linkenable

Mime:: linkexts

Mime:: linkrurl

Mime:: linkurls

▼ Mysql

Mysql:: adddb

Mysql:: addhost

Mysql:: adduser

Mysql:: adduserdb

Mysql:: checkdb

Mysql:: deldb

Mysql:: delhost

Mysql:: deluser

Mysql:: deluserdb

Mysql:: gethost
Mysql:: initcache
Mysql:: listdbs
Mysql:: listdbsopt
Mysql:: listusers
Mysql:: listusersopt
Mysql:: number_of
_dbs
Mysql:: number_of
_users
Mysql:: repairdb
Mysql:: routines
Mysql:: updatepriv
s

▼ Net

Net:: dnslookup
Net:: dnszone
Net:: sethastracero
ute

▼ News

News:: displaynew
s

▼ NVData

NVData:: set

▼ OptimizeWS

OptimizeWS:: load
optimizesettings
OptimizeWS:: load
optimizesettings (b
ytes)
OptimizeWS:: opti
mizews

▼ Park

Park:: disabledir
ect
Park:: getredirectu
rl
Park:: park
Park:: setredirectur
l
Park:: unpark

▼ Postgres

Postgres:: adddb
Postgres:: adduser
Postgres:: adduser
db
Postgres:: deldb
Postgres:: deluser

Postgres:: deluser
db

Postgres:: initcach
e

Postgres:: listdbso
pt

Postgres:: listusers
opt

Postgres:: number
_of_dbs

Postgres:: number
_of_users

▼ ProxyUtils

ProxyUtils:: proxya
ddress

▼ Resellers

Resellers:: accoun
tlistopt

Resellers:: themeli
stopt

▼ Serverinfo

Serverinfo:: servic
estatus

▼ SetLang

SetLang:: listlangs
opt

SetLang:: setlang

▼ SpamAssassin

SpamAssassin:: co
nfig

SpamAssassin:: sa
veconfig

▼ SSH

SSH:: getport

▼ SSL

SSL:: delete

SSL:: deletectr

SSL:: deletecsr

SSL:: deletekey

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcabundle

SSL:: getcname

SSL:: install

SSL:: installedhost

SSL:: listkeysopt

SSL:: showcrt

SSL:: showcsr

SSL:: showkey

SSL:: sslsharedsta
tus

SSL:: uploadcrt

SSL:: uploadkey

▼ StatManager

StatManager:: doF
orm

StatManager:: upd
ateUserConfig

▼ Stats

Stats:: analoglist

Stats:: awstats

Stats:: bwbar

Stats:: errlog

Stats:: lastvisitors

Stats:: showbandw
idth

Stats:: webalizer

Stats:: webalizerftp

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: cplist
subdomains

SubDomain:: disab
lesubrd

SubDomain:: listsu
bdomainsop

SubDomain:: setsu
burl

▼ UI

UI:: confirm

UI:: redirect

UI:: showresult