

UAPI Functions - Fileman::save_file_content

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup:: fullbacku
p_to_ftp

Backup:: fullbacku
p_to_homedir

Backup:: fullbacku
p_to_scp_with_key

Backup:: fullbacku
p_to_scp_with_password

Backup:: list_backups

Bandwidth

Bandwidth:: get_enabled_protocols

Bandwidth:: get_retention_periods

Bandwidth:: query

Batch

Batch:: strict

Brand

Brand:: read

Branding

Branding:: file

Branding:: get_applications

Branding:: get_application_information

Branding:: get_available_applications

Branding:: get_information_for_applications

Description

This function saves a file in a directory and encodes it in a character set.

Important:

In cPanel & WHM version 76 and later, when you disable the FileStorage role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess##  
▼ #####/execute/Fileman/save_file_content?  
&dir=/home/username/public_html&file=example.html&from_charset=utf-8&to_charset=utf-8&content="hi"&fallback=0
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

Function information

About this module

The Fileman module provides access to file functions.

About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster
 - CacheBuster:: read
 - CacheBuster:: update
- Chkserverd
 - Chkserverd:: get_exim_ports
 - Chkserverd:: get_exim_ports_ssl
- Chrome
 - Chrome:: get_dom
- Contactus
 - Contactus:: is_enabled
- cPAddons
 - cPAddons:: get_available_addons
 - cPAddons:: get_instance_settings
 - cPAddons:: list_addon_instances
- cPGreyList
 - cPGreyList:: disable_all_domains
 - cPGreyList:: disable_domains
 - cPGreyList:: enable_all_domains
 - cPGreyList:: enable_domains
 - cPGreyList:: has_greylisting_enabled
 - cPGreyList:: list_domains
- DAV
 - DAV:: disable_shared_global_addressbook
 - DAV:: enable_shared_global_addressbook
 - DAV:: get_calendar_contacts_config
 - DAV:: has_shared_global_addressbook
 - DAV:: is_dav_service_enabled

LiveAPI PHP Class

```

$cpanel = new
CPANEL(); // Connect
to cPanel - only do
this once.

// Save
example.html's
content.
$save_file_content =
$cpanel->uapi(
    'Fileman',
    'save_file_content',
    array(
        'dir' =>
'public_html',
        'file' =>
'example.html',
        'from_charset' =>
'UTF-8',
        'to_charset' =>
'ASCII',
        'content' =>
'"hi"',
        'fallback' => '0',
    )
);

```

Note:
For more information, read our [Guide to the LiveAPI System](#).

Notes:

- The
- Ur
- m
- us
- 20
- or
- 20
-).`
- 20
- or
- 20
-).

Find a function

reports the first file's URI, relative to the cPanel base directory.

- DAV:: is_horde_enabled
- DCV
 - DCV:: check_domains_via_dns
 - DCV:: check_domains_via_http
 - DCV:: ensure_domains_can_pass_dcv
 - DomainInfo
 - DomainInfo:: domains_data
 - DomainInfo:: list_domains
 - DomainInfo:: main_domain_builtin_subdomain_aliases
 - DomainInfo:: single_domain_data
- DNS
 - DNS:: ensure_domains_reside_only_locally
 - DNS:: has_local_authority
- DNSSEC
 - DNSSEC:: disable_dnssec
 - DNSSEC:: enable_dnssec
 - DNSSEC:: fetch_dns_records
 - DNSSEC:: set_nsec3
 - DNSSEC:: unset_nsec3
- Email
 - Email:: account_name
 - Email:: add_auto_responder
 - Email:: add_domain_forwarder
 - Email:: add_forwarder
 - Email:: add_list
 - Email:: add_mailman_delegates
 - Email:: add_mx
 - Email:: add_pop
 - Email:: add_spam_filter

LiveAPI Perl Module

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Save example.html's
content.
my $
save_file_content =
$cpliveapi->uapi(
'Fileman',
'save_file_content',
{
'dir' =>
'public_html',
'file' =>
'example.html',
'from_charset' =>
'UTF-8',
'to_charset' =>
'ASCII',
'content' =>
"hi",
'fallback' => '0',
}
);
```

Note:
For more information, read our [Guide to the LiveAPI System](#).

- UAPI Modules - Parser — The Parser module returns parsed URI information.
 - UAPI Modules - Fileman — The Fileman module provides access to file functions.
 - UAPI Functions - Fileman: auto complete dir — This function returns any files and directories that begin with a specified string.

Email: browse_mailbox
Email: change_mx
Email: check_fastmail
Email: check_pipe_forwarder
Email: delete_auto_responder
Email: delete_domin_forwarder
Email: delete_filter
Email: delete_forwarder
Email: delete_hidden_messages
Email: delete_list
Email: delete_mx
Email: delete_pop
Email: disable_filter
Email: disable_mailbox_autocreate
Email: disable_spam_assassin
Email: disable_spam_autodelete
Email: disable_spam_box
Email: dispatch_client_settings
Email: edit_pop_quota
Email: enable_filter
Email: enable_mailbox_autocreate
Email: enable_spam_assassin
Email: enable_spam_box
Email: fetch_charmaps
Email: fts_rescan_mailbox
Email: generate_mailman_opt
Email: get_auto_responder
Email: get_chase

▼ cPanel Template Toolkit

```
<!-- Get a hash of all the data, then display the path value. -->
[% data = execute(
  'Fileman',
  'upload_files' {dir
=> 'public_html',
'file' =>
'example.html',
'from_charset' =>
'UTF-8', 'to_charset'
=> 'ASCII', 'content'
=> "hi",} ); %]
[% FOREACH q =
data.path %]
  <p>
    [% q %]
  </p>
[% END %]

<!-- Get only a hash of the data. -->
[% execute('Fileman',
'upload_files' {dir
=> 'public_html',
'file' =>
'example.html',
'from_charset' =>
'UTF-8', 'to_charset'
=> 'ASCII', 'content'
=> "hi",}
).data.path %]
```

Note:

For more information, read our [Guide to Template Toolkit](#) documentation.

- UAPI Functions - Fileman:empty_trash - This function purges content from the .trash folder in the user's home directory.

ts

Email: get_client_settings

Email: get_default_email_quota

Email: get_default_email_quota_mib

Email: get_disk_usage

Email: get_filter

Email: get_held_message_count

Email: get_mailbox_autocreate

Email: get_mailman_delegates

Email: get_main_account_disk_usage

Email: get_main_account_disk_usage_bytes

Email: get_max_email_quota

Email: get_max_email_quota_mib

Email: get_pop_quota

Email: get_spam_settings

Email: get_webmail_settings

Email: has_delegated_mailman_lists

Email: has_plaintext_authentication

Email: hold_outgoing

Email: is_integer

Email: list_autoresponders

Email: list_default_address

Email: list_domain_forwarders

Email: list_filters

Email: list_filters_backups

Email: list_forwarders

Email: list_forward

Command Line

```
uapi --user=username
Fileman
save_file_content
dir=/home/username/public_html
file=example.html
from_charset=utf-8
to_charset=utf-8
content="hi"
fallback=0
```

Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

Output (JSON)

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "metadata": {
  },
  "data": {
    "from_charset":
"utf-8",
    "to_charset":
"utf-8",
    "path":
"/home/username/public_html/example.html"
  }
}
```

ers_backups

Email:: list_lists

Email:: list_mail_domains

Email:: list_mx

Email:: list_pops

Email:: list_pops_with_disk

Email:: list_system_filter_info

Email:: passwd_list

Email:: passwd_pop

Email:: release_outgoing

Email:: remove_mailman_delegates

Email:: reorder_filters

Email:: set_always_accept

Email:: set_default_address

Email:: set_list_privacy_options

Email:: stats_db_status

Email:: store_filter

Email:: suspend_incoming

Email:: suspend_login

Email:: suspend_outgoing

Email:: trace_filter

Email:: unsuspend_incoming

Email:: unsuspend_login

Email:: unsuspend_outgoing

Email:: verify_password

▼ EmailAuth

EmailAuth:: disable_dkim

EmailAuth:: enable_dkim

EmailAuth:: ensure_dkim_keys_exist

Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

Parameters	Type	Description	Possible values	Example
dir	string	The directory that contains the selected file. This parameter defaults to the user's /home directory.	A valid directory name.	public_html
file	string	Required The files to retrieve.	A valid filename.	example.html
from_charset	string	The character set encoding of the content parameter's value. This parameter defaults to UTF-8.	Any cPanel-supported character encoding .	UTF-8
to_charset	string	The character set encoding in which to encode the file. This parameter defaults to UTF-8.	Any cPanel-supported character encoding .	ASCII
content	string	The new file's contents. If you do not use this parameter, the function creates a blank file.	A string value.	hi
fallback	Boolean	Whether the function will return an error or save in the default character set if it cannot save in the specified character set. This parameter defaults to 1.	<ul style="list-style-type: none">0 — Return an error.1 — Save in the default character set.	0

Returns

EmailAuth:: fetch_
dkim_private_keys

EmailAuth:: install_
dkim_private_key
s

EmailAuth:: install_
spf_records

EmailAuth:: validat
e_current_dkims

EmailAuth:: validat
e_current_ptrs

EmailAuth:: validat
e_current_spfs

Return	Type	Description	Possible values	Example
path	string	The path to the file.	A valid absolute file path.	/home/user/pub lic_html/ex ample.html
from_charset	string	The file's character set.	Any cPanel-supporte d character set encoding.	UTF-8
to_charset	string	The file's new character set.	Any cPanel-supporte d character set encoding.	ASCII

ExternalAuthenticat
ion

ExternalAuthentic
ation:: add_authn_li
nk

ExternalAuthentic
ation:: configured_
modules

ExternalAuthentic
ation:: get_authn_lin
ks

ExternalAuthentic
ation:: has_external_
auth_modules_co
nfigured

ExternalAuthentic
ation:: remove_auth
n_link

Features

Features:: has_fea
ture

Features:: list_feat
ures

Fileman

Fileman:: autocom
pletedir

Fileman:: empty_tr
ash

Fileman:: get_file_
content

Fileman:: get_file_i
nformation

Fileman:: list_files

Fileman:: save_file_
content

Fileman:: transcod
e

Fileman:: upload_fi
les

Ftp

Ftp:: add_ftp

Ftp:: allows_anonymous_ftp

Ftp:: allows_anonymous_ftp_incoming

Ftp:: delete_ftp

Ftp:: ftp_exists

Ftp:: get_ftp_daemon_info

Ftp:: get_port

Ftp:: get_quota

Ftp:: get_welcome_message

Ftp:: kill_session

Ftp:: list_ftp

Ftp:: list_ftp_with_disk

Ftp:: list_sessions

Ftp:: passwd

Ftp:: server_name

Ftp:: set_anonymous_ftp

Ftp:: set_anonymous_ftp_incoming

Ftp:: set_homedir

Ftp:: set_quota

Ftp:: set_welcome_message

▼ Integration

Integration:: fetch_url

▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

▼ LangPHP

LangPHP:: php_get_domain_handler

LangPHP:: php_get_impacted_domains

LangPHP:: php_get_installed_versions

LangPHP:: php_get

t_system_default_
version

LangPHP:: php_ge
t_vhost_versions

LangPHP:: php_ini
_get_user_basic_d
irectives

LangPHP:: php_ini
_get_user_content

LangPHP:: php_ini
_get_user_paths

LangPHP:: php_ini
_set_user_basic_d
irectives

LangPHP:: php_ini
_set_user_content

LangPHP:: php_se
t_vhost_versions

▼ LastLogin

LastLogin:: get_las
t_or_current_logge
d_in_ip

▼ Locale

Locale:: get_attri
butes

▼ Mailboxes

Mailboxes:: expun
ge_mailbox_mess
ages

Mailboxes:: expun
ge_messages_for
_mailbox_guid

Mailboxes:: get_m
ailbox_status

Mailboxes:: has_ut
f8_mailbox_names

Mailboxes:: set_utf
8_mailbox_names

▼ Market

Market:: cancel_pe
nding_ssl_certifica
te

Market:: create_sh
opping_cart

Market:: get_all_pr
oducts

Market:: get_certifi
cate_status_detail
s

Market:: get_login
_url

Market:: get_pendi
ng_ssl_certificates

Market:: get_provi

der_specific_dcv_
constraints

Market:: get_provi
ders_list

Market:: get_ssl_c
ertificate_if_availa
ble

Market:: process_s
sl_pending_queue

Market:: request_s
sl_certificates

Market:: set_status
_of_pending_queu
e_items

Market:: set_url_af
ter_checkout

Market:: validate_l
ogin_token

▼ Mime

Mime:: add_handl
er

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redire
ct

Mime:: delete_han
dler

Mime:: delete_hotli
nk

Mime:: delete_mim
e

Mime:: delete_redi
rect

Mime:: list_handler
s

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirect
s

Mime:: redirect_inf
o

▼ ModSecurity

ModSecurity:: disa
ble_all_domains

ModSecurity:: disa
ble_domains

ModSecurity:: ena
ble_all_domains

ModSecurity:: ena
ble_domains

ModSecurity:: has
_modsecurity_inst

alled

ModSecurity:: list_domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_note

Mysql :: check_database

Mysql:: create_database

Mysql:: create_user

Mysql:: delete_database

Mysql:: delete_host

Mysql:: delete_user

Mysql:: get_host_notes

Mysql:: get_privileges_on_database

Mysql:: get_restrictions

Mysql:: get_server_information

Mysql:: locate_server

Mysql:: rename_database

Mysql:: rename_user

Mysql:: repair_database

Mysql:: revoke_access_to_database

Mysql:: set_password

Mysql:: set_privileges_on_database

▼ Notifications

Notifications:: get_notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_relative_uri

▼ PassengerApps

PassengerApps:: d
isable_application

PassengerApps:: e
dit_application

PassengerApps:: e
nable_application

PassengerApps:: li
st_applications

PassengerApps:: r
egister_application

PassengerApps:: u
nregister_applicati
on

▼ PasswdStrength

PasswdStrength::
get_required_stren
gth

▼ Personalization

Personalization::se
t

Personalization ::g
et

▼ Postgresql

Postgresql:: create
_database

Postgresql:: create
_user

Postgresql:: delete
_database

Postgresql:: get_re
strictions

Postgresql:: grant_
all_privileges

Postgresql:: renam
e_database

Postgresql:: renam
e_user

Postgresql:: renam
e_user_no_passw
ord

Postgresql:: revok
e_all_privileges

Postgresql:: set_p
assword

▼ Pushbullet

Pushbullet:: send_
test_message

▼ Quota

Quota:: get_quota
_info

▼ Resellers

Resellers:: list_acc
ounts

- ▼ ResourceUsage
 - ResourceUsage::
get_usages
- ▼ Restore
 - Restore:: directory
_listing
 - Restore:: get_user
s
 - Restore:: query_fil
e_info
 - Restore:: restore_f
ile
- ▼ Session
 - Session:: create_t
emp_user
- ▼ SiteTemplates
 - SiteTemplates:: list
_site_templates
 - SiteTemplates:: list
_user_settings
 - SiteTemplates:: pu
blish
- ▼ SpamAssassin
 - SpamAssassin :: cl
ear_spam_box
 - SpamAssassin:: g
et_symbolic_test_
names
 - SpamAssassin:: g
et_user_preferenc
es
 - SpamAssassin:: u
pdate_user_prefer
ence
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl
_excluded_domain
s
 - SSL:: check_share
d_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key
 - SSL:: delete_ssl
 - SSL :: disable_mai
l_sni
 - SSL:: enable_mail
_sni
 - SSL:: fetch_best_f
or_domain

SSL:: fetch_cert_in
fo

SSL:: fetch_certific
ates_for_fqdns

SSL:: fetch_key_a
nd_cabundle_for_
certificate

SSL:: find_certifica
tes_for_key

SSL:: find_csrs_for
_key

SSL:: generate_ce
rt

SSL:: generate_cs
r

SSL:: generate_ke
y

SSL:: get_autoss_
excluded_domains

SSL:: get_autoss_
pending_queue

SSL:: get_autoss_
problems

SSL:: get_cabundl
e

SSL:: get_cn_nam
e

SSL:: install_ssl

SSL:: installed_ho
st

SSL:: installed_ho
sts

SSL:: is_autoss_
check_in_progress

SSL:: is_mail_sni_
supported

SSL:: is_sni_supp
orted

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_item
s

SSL:: mail_sni_sta
tus

SSL:: rebuild_mail
_sni_config

SSL:: rebuildssldb

SSL:: remove_aut
oss_excluded_do
mains

SSL:: set_autossl_excluded_domains

SSL:: set_cert_friendly_name

SSL:: set_csr_friendly_name

SSL:: set_key_friendly_name

SSL:: set_primary_ssl

SSL:: set_ssl_share

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_check

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stats

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: addsubdomain

▼ Themes

Themes:: get_theme_base

Themes:: list

Themes:: update

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflict

ts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete_user

WebDisk:: set_home_dir

WebDisk:: set_password

WebDisk:: set_permissions

▼ WebmailApps

WebmailApps:: list
webmailapps

▼ WebVhosts

WebVhost:: list_do
mains

WebVhost:: list_ssl
_capable_domains

▼ WordPressBackup

WordPressBackup
:: any_running

WordPressBackup
:: cancel

WordPressBackup
:: cleanup

WordPressBackup
:: get_available_ba
ckups

WordPressBackup
:: is_running

WordPressBackup
:: start

▼ WordPressInstance

Manager

WordPressInstanc
eManager:: cancel
_scan

WordPressInstanc
eManager:: cleanu
p_scan

WordPressInstanc
eManager:: chang
e_admin_passwor
d

WordPressInstanc
eManager:: config
ure_autoupdate

WordPressInstanc
eManager:: get_ap
i_version

WordPressInstanc
eManager:: get_in
stance_by_id

WordPressInstanc
eManager:: get_in
stances

WordPressInstanc
eManager:: get_lat
est_wordpress_ver
sion_from_wordpr
ess_org

WordPressInstanc
eManager:: get_sc
an_results

WordPressInstanc
eManager:: is_inst
allable_addon_ava
ilable

WordPressInstanceManager:: **start_scan**

▼ **WordPressRestore**

WordPressRestore
:: **any_running**

WordPressRestore
:: **cleanup**

WordPressRestore
:: **start**