

UAPI Functions - Ftp::set_welcome_message

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup::
fullbacku

p_to_ftp

Backup:: fullbacku
p_to_homedir

Backup:: fullbacku
p_to_scp_with_key

Backup:: fullbacku
p_to_scp_with_password

Backup:: list_backups

Bandwidth

Bandwidth:: get_enabled_protocols

Bandwidth:: get_retention_periods

Bandwidth:: query

Batch

Batch:: strict

Brand

Brand:: read

Branding

Branding:: file

Branding:: get_applications

Branding:: get_application_information

Branding:: get_available_applications

Branding:: get_information_for_applications

Description

This function sets the FTP welcome message.

Important:

In cPanel & WHM version 76 and later, when you disable the `FTP` role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess##  
▼ #####/execute/Ftp/  
set_welcome_message?message=Greetings%2C%20Professor%20Falken.
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

Function information

About this module

The `Ftp` module manages FTP users, connections, and services.

About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster
 - CacheBuster:: read
 - CacheBuster:: update
- Chkserverd
 - Chkserverd:: get_external_ports
 - Chkserverd:: get_external_ports_ssl
- Chrome
 - Chrome:: get_domain
- Contactus
 - Contactus:: is_enabled
- cPAddons
 - cPAddons:: get_available_addons
 - cPAddons:: get_instance_settings
 - cPAddons:: list_addon_instances
- cPGreyList
 - cPGreyList:: disable_all_domains
 - cPGreyList:: disable_domains
 - cPGreyList:: enable_all_domains
 - cPGreyList:: enable_domains
 - cPGreyList:: has_greylisting_enabled
 - cPGreyList:: list_domains
- DAV
 - DAV:: disable_shared_global_addressbook
 - DAV:: enable_shared_global_addressbook
 - DAV:: get_calendar_contacts_config
 - DAV:: has_shared_global_addressbook
 - DAV:: is_dav_service_enabled

LiveAPI PHP Class

```

$cpnl = new
CPANEL(); // Connect
to cPanel - only do
this once.

// Set the FTP
welcome message.
$welcome =
$cpnl->uapi(
    'Ftp',
    'set_welcome_message'
,
    array(
        'message'
=> 'Greetings,
Professor Falken.',
    )
);

```

Note:
For more information, read our [Guide to the LiveAPI System](#).

Notes:

- The
- Ur
- int
- us
- 20
- or
- 20
-).'
- 20
- or
- 20
-).

Find a function

- UAPI Functions - Ftp:: get_ftp_daemon_info — This function retrieves the extended information about the server's FTP daemon.

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

Email:: add_spam_filter

▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# Set the FTP welcome  
message.  
my $welcome =  
$cpliveapi->uapi(  
  'Ftp',  
  'set_welcome_message'  
,  
  {  
    'message'  
=> 'Greetings,  
Professor Falken.',  
  }  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

▼ cPanel Template Toolkit

```
<!-- Set the FTP  
welcome message. -->  
[% execute( 'Ftp',  
'set_welcome_message'  
, { message =>  
'Greetings, Professor  
Falken.' } ); %]
```

Note:

For more information, read our [Guide to Template Toolkit documentation](#).

- UAPI Modules - Ftp — The Ftp module manages FTP users, connections, and services.
- UAPI Functions - Ftp::add_ftp — This function creates an FTP account.
- UAPI Functions - Ftp::allow_anonymous_ftp — This function checks whether the account allows anonymous FTP connections.

Email:: browse_mailbox
Email:: change_mx
Email:: check_fast_mail
Email:: check_pipe_forwarder
Email:: delete_auto_responder
Email:: delete_domain_forwarder
Email:: delete_filter
Email:: delete_forwarder
Email:: delete_hidden_messages
Email:: delete_list
Email:: delete_mx
Email:: delete_pop
Email:: disable_filter
Email:: disable_mailbox_autocreate
Email:: disable_spam_assassin
Email:: disable_spam_autodelete
Email:: disable_spam_box
Email:: dispatch_client_settings
Email:: edit_pop_quota
Email:: enable_filter
Email:: enable_mailbox_autocreate
Email:: enable_spam_assassin
Email:: enable_spam_box
Email:: fetch_charmaps
Email:: fts_rescan_mailbox
Email:: generate_mailman_opt
Email:: get_auto_responder
Email:: get_chase

Command Line

```
uapi --user=username  
Ftp  
set_welcome_message  
message='Greetings,  
Professor Falken.'
```

Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local  
/cpanel/bin/  
uapi
```

Output (JSON)

```
{  
  "messages":null,  
  "errors":null,  
  "status":1,  
  "metadata":{  
  
  },  
  "data":null  
}
```

Note:

Use cPanel's *API Shell* interface (`cPanel >> Home >> Advanced >> API Shell`) to directly test cPanel API calls.

Parameters

ts

Email:: get_client_settings

Email:: get_default_email_quota

Email:: get_default_email_quota_mib

Email:: get_disk_usage

Email:: get_filter

Email:: get_held_message_count

Email:: get_mailbox_autocreate

Email:: get_mailman_delegates

Email:: get_main_account_disk_usage

Email:: get_main_account_disk_usage_bytes

Email:: get_max_email_quota

Email:: get_max_email_quota_mib

Email:: get_pop_quota

Email:: get_spam_settings

Email:: get_webmail_settings

Email:: has_delegated_mailman_lists

Email:: has_plaintext_authentication

Email:: hold_outgoing

Email:: is_integer

Email:: list_autoresponders

Email:: list_default_address

Email:: list_domain_forwarders

Email:: list_filters

Email:: list_filters_backups

Email:: list_forwarders

Email:: list_forward

Parameter	Type	Description	Possible values	Example
message	string	Required The cPanel account's new FTP welcome message.	A string.	Greetings, Professor Falken.

Returns

This function returns only metadata.

ers_backups

Email:: list_lists

Email:: list_mail_d
omains

Email:: list_mx

Email:: list_pops

Email:: list_pops_
with_disk

Email:: list_system
_filter_info

Email:: passwd_list

Email:: passwd_po
p

Email:: release_ou
tgoing

Email:: remove_m
ailman_delegates

Email:: reorder_filt
ers

Email:: set_always
_accept

Email:: set_default
_address

Email:: set_list_pri
vacy_options

Email:: stats_db_st
atus

Email:: store_filter

Email:: suspend_in
coming

Email:: suspend_lo
gin

Email:: suspend_o
utgoing

Email:: trace_filter

Email:: unsuspend
_incoming

Email:: unsuspend
_login

Email:: unsuspend
_outgoing

Email:: verify_pass
word

▼ EmailAuth

EmailAuth:: disabl
e_dkim

EmailAuth:: enable
_dkim

EmailAuth:: ensure
_dkim_keys_exist

EmailAuth:: fetch_
dkim_private_keys

EmailAuth:: install
_dkim_private_key
s

EmailAuth:: install
_spf_records

EmailAuth:: validat
e_current_dkims

EmailAuth:: validat
e_current_ptrs

EmailAuth:: validat
e_current_spfs

ExternalAuthenticat
ion

ExternalAuthentic
ation:: add_auth_li
nk

ExternalAuthentic
ation:: configured_
modules

ExternalAuthentic
ation:: get_authn_lin
ks

ExternalAuthentic
ation:: has_external
_auth_modules_co
nfigured

ExternalAuthentic
ation:: remove_auth
n_link

Features

Features:: has_fea
ture

Features:: list_feat
ures

Fileman

Fileman:: autocom
pletedir

Fileman:: empty_tr
ash

Fileman:: get_file_
content

Fileman:: get_file_i
nformation

Fileman:: list_files

Fileman:: save_file
_content

Fileman:: transcod
e

Fileman:: upload_fi
les

Ftp

Ftp:: add_ftp

Ftp:: allows_anonymous_ftp

Ftp:: allows_anonymous_incoming

Ftp:: delete_ftp

Ftp:: ftp_exists

Ftp:: get_ftp_daemon_info

Ftp:: get_port

Ftp:: get_quota

Ftp:: get_welcome_message

Ftp:: kill_session

Ftp:: list_ftp

Ftp:: list_ftp_with_disk

Ftp:: list_sessions

Ftp:: passwd

Ftp:: server_name

Ftp:: set_anonymous_ftp

Ftp:: set_anonymous_ftp_incoming

Ftp:: set_homedir

Ftp:: set_quota

Ftp:: set_welcome_message

▼ Integration

Integration:: fetch_url

▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

▼ LangPHP

LangPHP:: php_get_domain_handler

LangPHP:: php_get_impacted_domains

LangPHP:: php_get_installed_versions

LangPHP:: php_get

t_system_default_
version

LangPHP:: php_ge
t_vhost_versions

LangPHP:: php_ini
_get_user_basic_d
irectives

LangPHP:: php_ini
_get_user_content

LangPHP:: php_ini
_get_user_paths

LangPHP:: php_ini
_set_user_basic_d
irectives

LangPHP:: php_ini
_set_user_content

LangPHP:: php_se
t_vhost_versions

▼ LastLogin

LastLogin:: get_las
t_or_current_logge
d_in_ip

▼ Locale

Locale:: get_attri
butes

▼ Mailboxes

Mailboxes:: expun
ge_mailbox_mess
ages

Mailboxes:: expun
ge_messages_for
_mailbox_guid

Mailboxes:: get_m
ailbox_status

Mailboxes:: has_ut
f8_mailbox_names

Mailboxes:: set_utf
8_mailbox_names

▼ Market

Market:: cancel_pe
nding_ssl_certifica
te

Market:: create_sh
opping_cart

Market:: get_all_pr
oducts

Market:: get_certifi
cate_status_detail
s

Market:: get_login
_url

Market:: get_pendi
ng_ssl_certificates

Market:: get_provi

der_specific_dcv_
constraints

Market:: get_provi
ders_list

Market:: get_ssl_c
ertificate_if_availa
ble

Market:: process_s
sl_pending_queue

Market:: request_s
sl_certificates

Market:: set_status
_of_pending_queu
e_items

Market:: set_url_af
ter_checkout

Market:: validate_l
ogin_token

▼ Mime

Mime:: add_handl
er

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redire
ct

Mime:: delete_han
dler

Mime:: delete_hotli
nk

Mime:: delete_mim
e

Mime:: delete_redi
rect

Mime:: list_handler
s

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirect
s

Mime:: redirect_inf
o

▼ ModSecurity

ModSecurity:: disa
ble_all_domains

ModSecurity:: disa
ble_domains

ModSecurity:: ena
ble_all_domains

ModSecurity:: ena
ble_domains

ModSecurity:: has
_modsecurity_inst

alled

ModSecurity:: list_ domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_ note

Mysql :: check_dat abase

Mysql:: create_dat abase

Mysql:: create_use r

Mysql:: delete_dat abase

Mysql:: delete_hos t

Mysql:: delete_use r

Mysql:: get_host_n otes

Mysql:: get_privile ges_on_database

Mysql:: get_restrict ions

Mysql:: get_server _information

Mysql:: locate_ser ver

Mysql:: rename_d atabase

Mysql:: rename_us er

Mysql:: repair_dat abase

Mysql:: revoke_ac cess_to_database

Mysql:: set_passw ord

Mysql:: set_privile ges_on_database

▼ Notifications

Notifications:: get_ notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_rel ative_uri

▼ PassengerApps

PassengerApps:: d
isable_application

PassengerApps:: e
dit_application

PassengerApps:: e
nable_application

PassengerApps:: li
st_applications

PassengerApps:: r
egister_application

PassengerApps:: u
nregister_applicati
on

▼ PasswdStrength

PasswdStrength::
get_required_stren
gth

▼ Personalization

Personalization::se
t

Personalization ::g
et

▼ Postgresql

Postgresql:: create
_database

Postgresql:: create
_user

Postgresql:: delete
_database

Postgresql:: get_re
strictions

Postgresql:: grant_
all_privileges

Postgresql:: renam
e_database

Postgresql:: renam
e_user

Postgresql:: renam
e_user_no_passw
ord

Postgresql:: revok
e_all_privileges

Postgresql:: set_p
assword

▼ Pushbullet

Pushbullet:: send_
test_message

▼ Quota

Quota:: get_quota
_info

▼ Resellers

Resellers:: list_acc
ounts

- ▼ ResourceUsage
 - ResourceUsage::
get_usages
- ▼ Restore
 - Restore:: directory
_listing
 - Restore:: get_user
s
 - Restore:: query_fil
e_info
 - Restore:: restore_f
ile
- ▼ Session
 - Session:: create_t
emp_user
- ▼ SiteTemplates
 - SiteTemplates:: list
_site_templates
 - SiteTemplates:: list
_user_settings
 - SiteTemplates:: pu
blish
- ▼ SpamAssassin
 - SpamAssassin :: cl
ear_spam_box
 - SpamAssassin:: g
et_symbolic_test_
names
 - SpamAssassin:: g
et_user_preferenc
es
 - SpamAssassin:: u
pdate_user_prefer
ence
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl
_excluded_domain
s
 - SSL:: check_share
d_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key
 - SSL:: delete_ssl
 - SSL :: disable_mai
l_sni
 - SSL:: enable_mail
_sni
 - SSL:: fetch_best_f
or_domain

SSL:: fetch_cert_in
fo

SSL:: fetch_certific
ates_for_fqdns

SSL:: fetch_key_a
nd_cabundle_for_
certificate

SSL:: find_certifica
tes_for_key

SSL:: find_csrs_for
_key

SSL:: generate_ce
rt

SSL:: generate_cs
r

SSL:: generate_ke
y

SSL:: get_autoss_
excluded_domains

SSL:: get_autoss_
pending_queue

SSL:: get_autoss_
problems

SSL:: get_cabundl
e

SSL:: get_cn_nam
e

SSL:: install_ssl

SSL:: installed_ho
st

SSL:: installed_ho
sts

SSL:: is_autoss_
check_in_progress

SSL:: is_mail_sni_
supported

SSL:: is_sni_supp
orted

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_item
s

SSL:: mail_sni_sta
tus

SSL:: rebuild_mail
_sni_config

SSL:: rebuildssldb

SSL:: remove_aut
oss_excluded_do
mains

SSL:: set_autossl_excluded_domains

SSL:: set_cert_friendly_name

SSL:: set_csr_friendly_name

SSL:: set_key_friendly_name

SSL:: set_primary_ssl

SSL:: set_ssl_share

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_check

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stats

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: addsubdomain

▼ Themes

Themes:: get_theme_base

Themes:: list

Themes:: update

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflict

ts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete_user

WebDisk:: set_home_dir

WebDisk:: set_password

WebDisk:: set_permissions

▼ WebmailApps

WebmailApps:: list
webmailapps

▼ WebVhosts

WebVhost:: list_do
mains

WebVhost:: list_ssl
_capable_domains

▼ WordPressBackup

WordPressBackup
:: any_running

WordPressBackup
:: cancel

WordPressBackup
:: cleanup

WordPressBackup
:: get_available_ba
ckups

WordPressBackup
:: is_running

WordPressBackup
:: start

▼ WordPressInstance

Manager

WordPressInstanc
eManager:: cancel
_scan

WordPressInstanc
eManager:: cleanu
p_scan

WordPressInstanc
eManager:: chang
e_admin_passwor
d

WordPressInstanc
eManager:: config
ure_autoupdate

WordPressInstanc
eManager:: get_ap
i_version

WordPressInstanc
eManager:: get_in
stance_by_id

WordPressInstanc
eManager:: get_in
stances

WordPressInstanc
eManager:: get_lat
est_wordpress_ver
sion_from_wordpr
ess_org

WordPressInstanc
eManager:: get_sc
an_results

WordPressInstanc
eManager:: is_inst
allable_addon_ava
ilable

WordPressInstanceManager:: **start_scan**

▼ **WordPressRestore**

WordPressRestore
:: **any_running**

WordPressRestore
:: **cleanup**

WordPressRestore
:: **start**