

cPanel API 2 Functions - Email::addpop

Guide to cPanel API 2

Return Data

Filter and Sort Output

Paginate Output

Output Columns

Calls from the WHM API

cPanel Tags (deprecated)

AddonDomain:: adddondomain

omain

AddonDomain:: deladdondomain

AddonDomain:: listaddondomains

Backups

Backups:: listfullbackups

Bandwidth

Bandwidth:: addhttpbandwidth

Bandwidth:: getbwdata

Bandwidth:: gethourlyaveragebwoveryear

BoxTrapper

BoxTrapper:: accountmanagerlist

Branding

Branding:: addbrandingobj

Branding:: applist

Branding:: brandingeditor

Branding:: createpkg

Branding:: cssmerge

Branding:: delbrandingobj

Branding:: delpkg

Branding:: gensprites

Description

This function adds an email account.

Warning:

We **strongly** recommend that you use the following [UAPI](#) function instead of this function:

- `Email::addpop` — This function creates an email address.

Important:

In cPanel & WHM version 76 and later, when you disable the `MailReceive` role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples [AddonDomain](#)

WHM API (JSON)

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?cpanel_jsonapi_user=user&cpanel_jsonapi_api_version=2&cpanel_jsonapi_module=Email&cpanel_jsonapi_func=addpop&domain="example.com"&email="user"&password="12345luggage"&quota="500"
```

Note:

For more information, read our [Calls from the WHM API](#) documentation.

Function information

About this module

The `Email` module modifies cPanel email account settings.

Branding:: getbrandingpkg

Branding:: getbrandingpkgstatus

Branding:: getdefaultbrandingpkg

Branding:: installbrandingpkgs

Branding:: installimages

Branding:: killimages

Branding:: listingtypes

Branding:: listobjecttypes

Branding:: preloadconf

Branding:: resetall

Branding:: resetscss

Branding:: resethtml

Branding:: resolvefile

Branding:: resolveocalcss

Branding:: saveocalcss

Branding:: setbrandingpkgstatus

Branding:: showpkgs

Branding:: spritelist

▼ CSVImport

CSVImport:: columnchoices

CSVImport:: configimport

CSVImport:: data

CSVImport:: fetchimportdata

CSVImport:: isenabled

CSVImport:: loaddata

CSVImport:: processdata

CSVImport:: sendcontact

CSVImport:: uploadimport

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.
```

```
// Create the  
user@example.com  
email address.  
$add_email_address =  
$cpanel->api2(  
    'Email',  
    'addpop',  
    array(  
        'domain'  
=> 'example.com',  
        'email'  
=> 'user',  
        'password'  
=> '12345luggage',  
        'quota'  
=> '500',  
    )  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

About cPanel API 2

cPanel API 2 accesses and modifies data for cPanel accounts.

Notes:

- The *Fe* int
- Ur **mi** us 20 or 20).` 20 or 20).

Find a function

- Contactus:: isenab led
 - Contactus:: sendcontact
 - Cron:: add_line
 - Cron:: edit_line
 - Cron:: fetchcron
 - Cron:: get_email
 - Cron:: listcron
 - Cron:: remove_line
 - Cron:: set_email
 - CustInfo:: contactemails
 - CustInfo:: contactprefs
 - CustInfo:: displaycontactinfo
 - CustInfo:: savecontactinfo
 - DBmap:: status
 - DBmap:: version
 - DKIMUI:: available
 - DKIMUI:: getrecords
 - DKIMUI:: install
 - DKIMUI:: installed
 - DKIMUI:: uninstall
 - DenyIp:: listdenyps
 - DiskCounter:: disk_counter
 - DiskUsage:: buildcache
 - DiskUsage:: clearcache
 - DiskUsage:: fetch_raw_disk_usage
 - DiskUsage:: fetchdiskusage
 - DiskUsage:: fetchdiskusagewithextras

LiveAPI Perl Module

```

my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Create the
user@example.com
email address.
my $add_email_address
= $cpliveapi->api2(
    'Email',
    'addpop',
    {
        'domain'
=> 'example.com',
        'email'
=> 'user',
        'password'
=> '12345luggage',
        'quota'
=> '500',
    }
);

```

Note:

For more information, read our [Guide to the LiveAPI System](#).

cPanel Tag System (deprecated)

Warnings:

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Deprecated cPanel Tag Usage](#) documentation.

- cPanel API 2 Functions - Email::editquota — This function modifies an email account's disk quota.
- cPanel API 2 Functions - Email::passwdpop — This function modifies an email account's password.

- DnsLookup:: name2ip
 - DomainLookup:: countbaseddomains
 - DomainLookup:: getbaseddomains
 - DomainLookup:: getdocroot
 - DomainLookup:: getdocroots
 - DomainLookup:: getmaindomain
- Email:: accountname
 - Email:: adddomainforward
 - Email:: addforward
 - Email:: addmx
 - Email:: addpop
 - Email:: browseboxes
 - Email:: changemx
 - Email:: checkmaindiscard
 - Email:: clearpopcache
 - Email:: deletefilter
 - Email:: delforward
 - Email:: delmx
 - Email:: delpop
 - Email:: disablefilter
 - Email:: editquota
 - Email:: enablefilter
 - Email:: fetchautoreponder
 - Email:: fetchcharmaps
 - Email:: filteractions
 - Email:: filterlist
 - Email:: filtername
 - Email:: filterrules
 - Email:: get_archiving_configuration
 - Email:: get_archiving_default_configu

Command Line

```
cpapi2
--user=username Email
addpop
domain=example.com email=user
password=12345luggage
quota=500
```

Note:
For more information and additional output options, read our [Guide to cPanel API 2 documentation](#) or run the `cpapi2 --help` command.

Output (JSON)

```
{
  "cpanelresult": {
    "apiversion": 2,
    "func": "addpop",
    "data": [
      {
        "reason": "",
        "result": 1
      }
    ],
    "event": {
      "result": 1
    },
    "module": "Email"
  }
}
```

Note:
Use cPanel's *API Shell* interface (`cPanel >> Home >> Advanced >> API Shell`) to directly test cPanel API calls.

Parameters

Parameter	Type	Description	Possible values	Example
-----------	------	-------------	-----------------	---------

- cPanel API 2 Functions - Email::listdefaultaddresses
 - This function retrieves the domain's default address and its rules.
 - cPanel API 2 Functions - Email::listaliasbackups
 - This function retrieves a list of the account's domains that use aliases and custom default addresses.

ration

Email: `get_archiving_types`

Email: `get_default_email_quota`

Email: `get_email_signing`

Email: `get_max_email_quota`

Email: `getabsbrowse_dir`

Email: `getalwaysaccept`

Email: `getdiskusage`

Email: `getmxcheck`

Email: `has_delegated_mailman_lists`

Email: `list_system_filter_info`

Email: `listaliasesbackups`

Email: `listautoresponders`

Email: `listdefaultaddresses`

Email: `listdomainforwards`

Email: `listfilterbackups`

Email: `listfilters`

Email: `listforwards`

Email: `listlists`

Email: `listmaildomains`

Email: `listmx`

Email: `listmxs`

Email: `listpops`

Email: `listpopssingle`

Email: `listpopswithdisk`

Email: `listpopswithimage`

Email: `loadfilter`

Email: `passwdpop`

Email: `reorderfilters`

domain	<i>string</i>	Required The email account's domain.	A valid domain on the cPanel account. For example, <code>example.com</code> to create <code>user@example.com</code> .	<code>example.com</code>
email	<i>string</i>	Required The email account's username.	A valid email account username. Note : In cPanel & WHM version 78 and later, you can not enter <code>cpanel</code> as an account name when you create an email account. For example, <code>user</code> to create <code>user@example.com</code> .	<code>user</code>
password	<i>string</i>	Required The email account's password.	A secure password.	<code>12345luggage</code>

Email:: [set_archiving_configuration](#)

Email:: [set_archiving_default_configuration](#)

Email:: [set_email_signing](#)

Email:: [setalwaysaccept](#)

Email:: [setdefaultaddress](#)

Email:: [setmxcheck](#)

Email:: [storefilter](#)

Email:: [tracefilter](#)

▼ [EmailTrack](#)

EmailTrack:: [search](#)

EmailTrack:: [stats](#)

EmailTrack:: [trace](#)

▼ [Encoding](#)

Encoding:: [get_encodings](#)

Encoding:: [guess_file](#)

Encoding:: [guess_file_opts](#)

▼ [FSTest](#)

FSTest:: [dirisempty](#)

▼ [Fileman](#)

Fileman:: [autocompletedir](#)

Fileman:: [fileop](#)

Fileman:: [getabsdir](#)

Fileman:: [getdir](#)

Fileman:: [getdiractions](#)

Fileman:: [getdiskinfo](#)

Fileman:: [getedittype](#)

Fileman:: [getfileactions](#)

Fileman:: [getpath](#)

Fileman:: [listfiles](#)

Fileman:: [mkdir](#)

Fileman:: [mkfile](#)

Fileman:: [savefile](#)

quota	integer	The maximum amount of disk space that the new email account may use. This parameter defaults to 250.	A positive integer that represents the maximum amount of disk space, in Megabytes (MB). Note : To grant unlimited disk space, specify 0.	500
send_welcome_email	Boolean	Whether to send client configuration instructions to the account. Note : We introduced this parameter in cPanel & WHM version 62. This parameter defaults to 0.	<ul style="list-style-type: none"> 1 — Send the instructions. 0 — Do not send the instructions. 	0

Returns

Return	Type	Description	Possible values	Example
reason	string	A reason for failure. Note : This function only returns a reason value if it failed.	A string that describes the error.	This is an error message.

Fileman:: search
 Fileman:: statfiles
 Fileman:: uploadfiles
 Fileman:: viewfile

result	<i>Boolean</i>	Whether the function succeeded.	<ul style="list-style-type: none"> • 1 — The function succeeded. • 0 — The function failed. 	1
--------	----------------	---------------------------------	---	---

▼ ForcePassword

ForcePassword:: get_force_password_flags
 ForcePassword:: update_force_password_flags

▼ Frontpage

Frontpage:: fpenabled
 Frontpage:: list

▼ Ftp

Ftp:: addftp
 Ftp:: delftp
 Ftp:: listftp
 Ftp:: listftpsessions
 Ftp:: listftpwithdisk
 Ftp:: passwd
 Ftp:: setquota

▼ Gpg

Gpg:: listgpgkeys
 Gpg:: listsecretgpgkeys
 Gpg:: number_of_private_keys
 Gpg:: number_of_public_keys

▼ Htaccess

Htaccess:: listuser
 Htaccess:: listusers

▼ HttpUtils

HttpUtils:: getdirindices

▼ ImageManager

ImageManager:: thumbnail

▼ LVEInfo

LVEInfo:: getUsage

▼ LangMods

LangMods:: getarcname
 LangMods:: getkey

LangMods:: getpre
fix

LangMods:: install

LangMods:: langlis
t

LangMods:: list_av
ailable

LangMods:: list_in
stalled

LangMods:: magic
_status

LangMods:: pre_ru
n

LangMods:: search

LangMods:: setup

LangMods:: uninst
all

LangMods:: updat
e

▼ LeechProtect

LeechProtect:: set
up

▼ Locale

Locale:: get_encod
ing

Locale:: get_html_
dir_attr

Locale:: get_locale
_name

Locale:: get_user_
locale

Locale:: get_user_
locale_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse
r

Logaholic:: adduse
rprofile

Logaholic:: deleteu
ser

Logaholic:: deleteu
serprofile

Logaholic:: edituse
r

Logaholic:: fetchu
ser

Logaholic:: listuser
profiles

Logaholic:: logahol
iclink

Logaholic:: proces
sstats

▼ Mime

Mime:: list_hotlinks

Mime:: listhandlers

Mime:: listmime

Mime:: listredirects

Mime:: redirectname

Mime:: redirecturlname

▼ MysqlFE

MysqlFE:: authorizehost

MysqlFE:: change
dbuserpassword

MysqlFE:: created
b

MysqlFE:: created
buser

MysqlFE:: dbuserexists

MysqlFE:: deauthorizehost

MysqlFE:: deleted
b

MysqlFE:: deleted
buser

MysqlFE:: getalldb
sinfo

MysqlFE:: getalldb
usersanddbs

MysqlFE:: getdatabasesprivileges

MysqlFE:: getdatabases

MysqlFE:: gethosts

MysqlFE:: getmysqlprivileges

MysqlFE:: getmysqlserverprivileges

MysqlFE:: has_my
cnf_for_cpuser

MysqlFE:: listdbs

MysqlFE:: listdatabases
ackup

MysqlFE:: listhosts

MysqlFE:: listusers

MysqlFE:: listusers
indb

MysqlFE:: revoked
buserprivileges

MysqlFE:: setdbu
erprivileges

MysqlFE:: userdbp
rivs

▼ MysqlOptimizer

MysqlOptimizer:: f
etch_slow_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does_news
_exist

News:: does_news
_type_exist

News:: get_news

▼ PHPINI

PHPINI:: getallopti
ons

PHPINI:: getoption
s

▼ Park

Park:: listaddondo
mains

Park:: listparkeddo
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change_
password

Passwd:: set_dige
st_auth

▼ PasswdStrength

PasswdStrength::
appstrengths

PasswdStrength::
get_password_stre
ngth

PasswdStrength::
get_required_stren
gth

▼ Postgres

Postgres:: listdbs

Postgres:: listusers

Postgres:: listusers
indb

Postgres:: userexi
sts

▼ Rand

Rand:: getranddat
a

▼ Resellers

Resellers:: get_su
b_accounts

▼ RoR

RoR:: addapp

RoR:: changeapp

RoR:: importrails

RoR:: listapps

RoR:: listrewrites

RoR:: needsimport

RoR:: removeapp

RoR:: removerewri
te

RoR:: restartapp

RoR:: setuprewrite

RoR:: softrestartap
p

RoR:: startapp

RoR:: stopapp

▼ SetLang

SetLang:: setlocale

▼ SourceIPCheck

SourceIPCheck:: a
ddip

SourceIPCheck:: d
elip

SourceIPCheck:: g
etaccount

SourceIPCheck:: li
stips

SourceIPCheck:: l
oadsecquestions

SourceIPCheck:: r
esetsecquestions

SourceIPCheck:: s
amplequestions

SourceIPCheck:: s
avesecquestions

▼ SPFUJ

SPFUJ:: available

SPFUJ:: count_sett
ings

SPFUI:: entries_co
mplete

SPFUI:: get_raw_r
ecord

SPFUI:: getmainse
rverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list_settin
gs

SPFUI:: load_curr
ent_values

SPFUI:: uninstall

▼ SSH

SSH:: authkey

SSH:: converttopp
k

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey_leg
acy

SSH:: importkey

SSH:: listkeys

▼ SSL

SSL:: fetchcabundl
e

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcnname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

▼ SSLInfo

SSLInfo:: fetchinfo

▼ StatCache

StatCache:: clearc
ache

▼ Stats

Stats:: getmonthly

bandwidth

Stats:: getmonthly
domainbandwidth

Stats:: getthismont
hsbwusage

Stats:: lastapache
hits

Stats:: lastvisitors

Stats:: listanalog

Stats:: listawstats

Stats:: listlastvisito
rs

Stats:: listrawlogs

Stats:: listurchin

Stats:: listwebalize
r

▼ StatsBar

StatsBar:: getrowc
ounter

StatsBar:: rowcoun
ter

StatsBar:: setrowc
ounter

StatsBar:: stat

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: chan
gedocroot

SubDomain:: delsu
bdomain

SubDomain:: getre
servedsubdomains

SubDomain:: listsu
bdomains

SubDomain:: validr
egex

▼ Themes

Themes:: apply_n
ew_theme

Themes:: does_cp
anel_theme_exist

Themes:: get_avail
able_themes

Themes:: get_the
mes_list

Themes:: restore_
saved_theme

▼ UI

UI:: dynamicinclud
elist

UI:: includelist

UI:: listform

UI:: paginate

UI:: paginate_list

▼ UserHttpUtils

UserHttpUtils:: get
dirindices

▼ WebDisk

WebDisk:: addweb
disk

WebDisk:: delweb
disk

WebDisk:: hasdige
st

WebDisk:: listwebd
isks

WebDisk:: passwd
webdisk

WebDisk:: set_dig
est_auth

WebDisk:: set_ho
mdir

WebDisk:: set_per
ms

WebDisk:: setstatu
s

▼ WebmailApps

WebmailApps:: list
webmailapps

▼ ZoneEdit

ZoneEdit:: add_zo
ne_record

ZoneEdit:: edit_zo
ne_record

ZoneEdit:: fetch_c
panel_generated_
domains

ZoneEdit:: fetchzo
ne

ZoneEdit:: fetchzo
ne_records

ZoneEdit:: fetchzo
nes

ZoneEdit:: get_zon
e_record

ZoneEdit:: remove
_zone_record

ZoneEdit:: resetzo
ne

