

cPanel API 1 Functions - Fileman::uploadfiles

Guide to cPanel API 1

Return Data

cPanel Tags
(deprecated)

Bandwidth:
display
bandwidth

er

Bandwidth:
display
bandwidth

Bandwidth:
display
bandwidth

Bandwidth:
display
bandwidth

▼ BoxTrapper

BoxTrapper::chan
gestatus

BoxTrapper::clean
cfgfilelist

BoxTrapper::edit
msg

BoxTrapper::fetch
cfgfile

BoxTrapper::getb
oxconfdir

BoxTrapper::listm
sgs

BoxTrapper::logco
ntrols

BoxTrapper::mess
ageaction

BoxTrapper::multi
messageaction

BoxTrapper::reset
msg

BoxTrapper::save
cfgfile

BoxTrapper::save
conf

BoxTrapper::show
autowhitelist

BoxTrapper::show
emails

BoxTrapper::show
fromname

BoxTrapper::show
log

Description

This function uploads files to the server.

Warning:

cPanel API 1 is **deprecated**. Do not use this function. Instead, we **strongly** recommend that you use the following newer functions:

- **UAPI (recommended)** — [Fileman::upload_files](#) — This function uploads files.
- **cPanel API 2** — [Fileman::uploadfiles](#) — This function uploads files.

Important:

In cPanel & WHM version 76 and later, when you disable the FileStorage role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
$upload_files =  
$cpanel->apil('Filema  
n', 'uploadfiles',  
array('public_html',  
'file1-myfile.txt',  
'file2-myotherfile.tx  
t')); // Call the  
function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Func tion infor mati on

About this mod ule

The Fileman module provides access to file functions.

Note:
This function is part of the File Management feature.

About cPan el API 1

BoxTrapper:: show message

BoxTrapper:: show queue

BoxTrapper:: show queuesearch

BoxTrapper:: show queuetime

BoxTrapper:: status

BoxTrapper:: statusbutton

▼ Branding

Branding:: file

Branding:: image

Branding:: killing

Branding:: setbrandingpkg

Branding:: setmyacctspkg

Branding:: setupdirs

Branding:: tempsetbrandingpkg

▼ Cgi

Cgi:: backuplink

Cgi:: displayurchin

Cgi:: phpmyadminlink

▼ Chkserverd

Chkserverd:: getexport

Chkserverd:: getexport_ssl

▼ ClamScanner

ClamScanner:: bars

▼ cPAddons

cPAddons:: mainpg

▼ Cron

Cron:: crontab_perms

▼ CustInfo

CustInfo:: getemail

▼ Denylp

Denylp:: adddenyip

Denylp:: deldenyip

Denylp:: listdenyips

▼ LiveAPI Perl Module

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.
my $upload_files =
$cpliveapi->apil('Fileman', 'uploadfiles'
['public_html',
'file1-myfile.txt',
'file2-myotherfile.txt']); # Call the
function.
```

Note:
For more information, read our [Guide to the LiveAPI System](#).

▼ cPanel Tag System (deprecated)

Warning:
In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We provide this example to help developers move from the old cPanel tag system to our [LiveAPI](#) system. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs.

```
<cpanel
Module="Fileman::uploadfiles (
$FORM('dir','file1','file2'))">
```

cPanel API 1 accesses information about cPanel accounts.

Warning:
cPanel API **deprecated**. We **strongly** recommend [cPanel API](#) or [UAPI](#) instead.

Notes:

- The `int`
- The `url`

Find a function

•

- ▼ DiskUsage
 - DiskUsage:: show manager
- ▼ Email
 - Email:: addautoresponder
 - Email:: addforward
 - Email:: addfilter
 - Email:: addlist
 - Email:: addmx
 - Email:: addpop
 - Email:: addspam
 - Email:: addspambox
 - Email:: addspamfilter
 - Email:: changemx
 - Email:: checkfastmail
 - Email:: checkpipeforward
 - Email:: clearspambox
 - Email:: delautoresponder
 - Email:: delforward
 - Email:: delfilter
 - Email:: dellist
 - Email:: delmx
 - Email:: delpop
 - Email:: delspam
 - Email:: delspambox
 - Email:: disable_spam_autodelete
 - Email:: editquota
 - Email:: enable_spam_autodelete
 - Email:: getaging
 - Email:: getarsbody
 - Email:: getarscharset
 - Email:: getarsfrom
 - Email:: getarshtml
 - Email:: getarsinterval

▼ Command Line

```
cpapil
--user=username
Fileman uploadfiles
public_html
file1-myfile.txt
file2-myotherfile.txt
```

Notes:

- You **must** URI-encode these values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to cPanel API 1](#) documentation or run the `cpapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapil` command:

```
/usr/local
/cpanel/bin/cpapil
```

▼ Output (plaintext)

```
test.html
(test.html): upload
succeeded, overwrote
old file.
```

- [cPanel API 1 Functions - Fileman:html editor](#) — This function opens a file in the HTML editor.
- [cPanel API 1 Functions - Fileman:killdir](#) — This function deletes a directory.

Parameters

Parameter	Type	Description	Possible values	Example
dir	string	Required The directory to which to upload the files.	Any valid directory name.	public_html
file*	string	Required The files to upload.	Any valid, incremented filename.	file1-myfile.txt

Important:

Email: getarsstart
Email: getarsstop
Email: getarssubject
Email: getmailserver
Email: getmailserveruser
Email: getpopquota
Email: has_spam_as_acl
Email: has_spam_autodelete
Email: listmaildomains
Email: listmaildomainsopt
Email: listmaildomainsoptndef
Email: mainacctdiskused
Email: passwdlist
Email: passwdpop
Email: setmxaccept
Email: spamboxstatus
Email: spamstatus
Email: tracefilter

▼ Fileman

Fileman: changeperm
Fileman: delfile
Fileman: dofileop
Fileman: emptytrash
Fileman: extractfile
Fileman: fileimg
Fileman: fmmkdir
Fileman: fmmkfile
Fileman: fmpushfile
Fileman: fmrename
Fileman: fmsavefile
Fileman: fmsaveht

• You must pass this parameter to reach file that you upload.
• You must increment each variable.

- cPanel API 1 Functions - Optimize WS:loadoptimizesettings - bytes — This function returns a cPanel account's free disk space quota.
- cPanel API 1 Modules - Fileman — The Fileman module provides access to file functions.

mfile

Fileman:: fullbacku
p

Fileman:: getfile

Fileman:: htmledito
r

Fileman:: killdir

Fileman:: listfiles

Fileman:: listfullba
ckups

Fileman:: listtempl
ates

Fileman:: restoreaf

Fileman:: restored
b

Fileman:: restorefil
e

Fileman:: restorefil
es

Fileman:: savehtml
file

Fileman:: showper
m

Fileman:: uploadfil
es

Fileman:: viewfile

▼ Frontpage

FrontPage:: addfp

FrontPage:: delfp

FrontPage:: fpstat
us

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: ftpquota

Ftp:: ftpservernam
e

Ftp:: ftpstatslogin

Ftp:: get_anonftp

Ftp:: get_anonftpin

Ftp:: get_welcome
msg

Ftp:: getftpquota

Ftp:: kill_ftp_sessi
on

Ftp:: listftpstatsurl

Ftp:: passwdftp

o
r
e
x
a
m
p
l
e
,
p
a
s
s
t
h
e
f
i
r
s
t
f
i
l
e
a
s
f
i
l
e
l
a
n
d
t
h
e
s
e
c
o
n
d
f
i
l
e
a
s
f
i
l
e

Ftp:: set_anonftp
Ftp:: set_anonftpin
Ftp:: set_welcome
msg

		2		
--	--	---	--	--

▼ Gpg

Gpg:: deletekey
Gpg:: exportkey
Gpg:: exportsecret
key
Gpg:: genkey
Gpg:: importkeys

Returns

This function returns a message of success or a reason for failure.

▼ Htaccess

Htaccess:: checkpr
otected
Htaccess:: del_use
r
Htaccess:: getinde
x
Htaccess:: htdirls
Htaccess:: number
_of_users
Htaccess:: phpsele
ctable
Htaccess:: resnam
e
Htaccess:: set_pas
s
Htaccess:: set_pro
tect
Htaccess:: setinde
x
Htaccess:: setphpr
eference
Htaccess:: showus
ers

▼ ImageManager

ImageManager:: c
onvert
ImageManager:: di
mensions
ImageManager:: h
dimension
ImageManager:: s
cale
ImageManager:: th
umbnail
ImageManager:: w
dimension

▼ LastLogin

LastLogin:: lastlogi
n

▼ LeechProtect

LeechProtect:: disable

LeechProtect:: enable

LeechProtect:: setup

LeechProtect:: showpasswdfile

LeechProtect:: status

▼ LogManager

LogManager:: listdownloads

LogManager:: save settings

LogManager:: show settings

▼ MagicRevision

MagicRevision:: uri

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: del_handler

Mime:: del_hotlink

Mime:: del_mime

Mime:: del_redirect

Mime:: linkallownull

Mime:: linkenable

Mime:: linkexts

Mime:: linkrurl

Mime:: linkurls

▼ Mysql

Mysql:: adddb

Mysql:: addhost

Mysql:: adduser

Mysql:: adduserdb

Mysql:: checkdb

Mysql:: deldb

Mysql:: delhost

Mysql:: deluser

Mysql:: deluserdb

Mysql:: gethost

Mysql:: initcache

Mysql:: listdbs

Mysql:: listdbsopt

Mysql:: listusers

Mysql:: listusersopt

Mysql:: number_of
_dbs

Mysql:: number_of
_users

Mysql:: repairdb

Mysql:: routines

Mysql:: updatepriv
s

▼ Net

Net:: dnslookup

Net:: dnszone

Net:: sethastracero
ute

▼ News

News:: displaynew
s

▼ NVData

NVData:: set

▼ OptimizeWS

OptimizeWS:: load
optimizesettings

OptimizeWS:: load
optimizesettings (b
ytes)

OptimizeWS:: opti
mizews

▼ Park

Park:: disabledir
ect

Park:: getredirectu
rl

Park:: park

Park:: setredirectur
l

Park:: unpark

▼ Postgres

Postgres:: adddb

Postgres:: adduser

Postgres:: adduser
db

Postgres:: deldb

Postgres:: deluser

Postgres:: deluser
db

Postgres:: initcach
e

Postgres:: listdbso
pt

Postgres:: listusers
opt

Postgres:: number
_of_dbs

Postgres:: number
_of_users

▼ ProxyUtils

ProxyUtils:: proxya
ddress

▼ Resellers

Resellers:: accoun
tlistopt

Resellers:: themeli
stopt

▼ Serverinfo

Serverinfo:: servic
estatus

▼ SetLang

SetLang:: listlangs
opt

SetLang:: setlang

▼ SpamAssassin

SpamAssassin:: co
nfig

SpamAssassin:: sa
veconfig

▼ SSH

SSH:: getport

▼ SSL

SSL:: delete

SSL:: deletectr

SSL:: deletecsr

SSL:: deletekey

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcabundle

SSL:: getcname

SSL:: install

SSL:: installedhost

SSL:: listkeysopt

SSL:: showcrt

SSL:: showcsr

SSL:: showkey

SSL:: sslsharedsta
tus

SSL:: uploadcrt

SSL:: uploadkey

▼ StatManager

StatManager:: doF
orm

StatManager:: upd
ateUserConfig

▼ Stats

Stats:: analoglist

Stats:: awstats

Stats:: bwbar

Stats:: errlog

Stats:: lastvisitors

Stats:: showbandw
idth

Stats:: webalizer

Stats:: webalizerftp

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: cplist
subdomains

SubDomain:: disab
lesubrd

SubDomain:: listsu
bdomainsop

SubDomain:: setsu
burl

▼ UI

UI:: confirm

UI:: redirect

UI:: showresult