

WHM API 1 Functions - list_mysql_databases_and_users

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

- Account Restoration
- restore_modules_summary
- restore_queue_activate
- restore_queue_add_task
- restore_queue_clear_all_completed_tasks
- restore_queue_clear_all_failed_tasks
- restore_queue_clear_all_pending_tasks
- restore_queue_clear_all_tasks
- restore_queue_clear_completed_task
- restore_queue_clear_pending_task
- restore_queue_is_active
- restore_queue_list_active
- restore_queue_list_completed
- restore_queue

Description

This function retrieves the MySQL® database and user data for the specified account.

Important:

In cPanel & WHM version 76 and later, when you disable the MySQL role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/list_mysql_databases_and_users?api.version=1&user=user1
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/list_mysql_databases_and_users?api.version=1&user=user1
```

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Scro
- Ycmt
- us
- 20
- or
- 20
-)tc

ue_list_pending

restore_queue_state

restoreaccount

verify_new_username_for_restore

Accounts

accountsummary

applist

createacct

domainuserdata

editquota

forcepasswordchange

get_domain_info

getdomainowner

has_digest_auth

has_my.cnf_for_cpuser

limitbw

list_users

listaccts

listlockedaccounts

listsuspended

modifyacct

myprivs

passwd

removeacct

set_digest_auth

showbw

suspendacct

unsuspendacct

untrack_acct_id

verify_new_username

Addon Domains

Command Line

```
whmapil  
list_mysql_databases_  
and_users user=user1
```

Notes:

- You **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local  
/cpanel/bin/  
whmapil
```

Find a function

convert_add
on_fetch_co
nversion_de
tails

convert_add
on_fetch_do
main_details

convert_add
on_get_con
version_stat
us

convert_add
on_initiate_c
onversion

convert_add
on_list_add
on_domains

convert_add
on_list_conv
ersions

Authentication

api_token_c
reate

api_token_li
st

api_token_r
evoke

api_token_u
pdate

disable_aut
hentication_
provider

disable_faili
ng_authenti
cation_provi
ders

enable_auth
entication_p
rovider

get_availabl
e_authentic
ation_provid
ers

get_login_ur
l

get_provider
_client_confi
gurations

get_provider
_configurati
on_fields

get_provider
_display_co
nfigurations

get_users_a
uthn_linked
_accounts

Output (JSON)

```
{
  "data": {
    "mysql_databases": {
      "user1_database1": [
        "user1_user5"
      ]
    },
    "mysql_config": {
      "use_db_prefix": "1",
      "prefix_length": 8,
      "mysql-version": "5.5"
    }
  },
  "metadata": {
    "reason": "OK",
    "version": 1,
    "command": "list_mysql_databases_and_users"
  },
  "result": 1
}
```

C
o
n
t
e
n
t
b
y
l
a
b
e
l

T
h
e
r
e
i
s
n
o
c
o
n
t
e
n
t
w
i
t
h
t
h
e
s
p
e
c
i
f
i
e
d
l
a
b
e
l
s

link_user_authn_provider
set_provider_client_configurations
set_provider_display_configurations
twofactorauth_disable_policy
twofactorauth_enable_policy
twofactorauth_generate_tfa_config
twofactorauth_get_issuer
twofactorauth_get_user_configs
twofactorauth_policy_status
twofactorauth_remove_user_config
twofactorauth_set_issuer
twofactorauth_set_tfa_config
unlink_user_authn_provider
validate_login_token

▼ Backups

backup_config_get
backup_config_set
backup_date_list
backup_destination_add
backup_destination_delete
backup_destination_get
backup_destination_list

▼ Output (XML)

```
<result>
  <metadata>
    <reason>OK</reason>
    <version>1</version>
  </metadata>
  <result>1</result>
  <command>list_mysql_databases_and_users</command>
  </metadata>
  <data>
    <mysql_config>
      <use_db_prefix>1</use_db_prefix>
      <mysql-version>5.5</mysql-version>
      <prefix_length>8</prefix_length>
    </mysql_config>
    <mysql_databases>
      <user1_database1>user1_user5</user1_database1>
    </mysql_databases>
  </data>
</result>
```

Note:
Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

[backup_destination_set](#)
[backup_destination_validate](#)
[backup_get_transport_status](#)
[backup_list_transported](#)
[backup_set_list](#)
[backup_skip_users_all](#)
[backup_skip_users_all_status](#)
[backup_user_list](#)
[convert_and_migrate_from_legacy_config](#)
[get_users_with_backup_metadata](#)
[list_cparchive_files](#)
[start_background_package](#)
[toggle_user_backup_state](#)
 ▼ [cPHulk](#)
[cphulk_statuses](#)
[create_cphulk_record](#)
[delete_cphulk_record](#)
[disable_cphulk](#)
[enable_cphulk](#)
[flush_cphulk_login_history](#)
[flush_cphulk_login_history_for_ips](#)
[get_countries_with_known_ip_ranges](#)

Parameter	Type	Description	Possible values	Example
user	string	Required The username for a specified account.	A valid string.	user1

Returns

Return	Type	Description	Possible values	Example
mysql_config	hash	A hash of the user's MySQL database configuration settings.	This hash includes the user_db_prefix, mysql-version, and prefix_length returns.	
use_db_prefix	Boolean	Whether database prefixing is enabled on the server. The function returns this value in the mysql_config hash.	<ul style="list-style-type: none"> 1 — Enabled. 0 — Disabled. 	1
mysql_version	integer	The MySQL version installed on the server. The function returns this value in the mysql_config hash.	A positive integer.	5.5
prefix_length	integer	The maximum number of characters allowed for the prefix on this server. The function returns this value in the mysql_config hash.	8 or 16, dependent upon the installed version of MySQL.	8
mysql_databases	hash	A hash of database names and users.	This hash includes the database_user return.	

[get_cphulk_brutes](#)
[get_cphulk_excessive_brutes](#)
[get_cphulk_failed_logins](#)
[get_cphulk_user_brutes](#)
[load_cphulk_config](#)
[read_cphulk_records](#)
[save_cphulk_config](#)
[set_cphulk_config_key](#)

▼ Databases

[background_mysql_upgrade_status](#)
[current_mysql_version](#)
[installable_mysql_versions](#)
[latest_available_mysql_version](#)
[list_database_users](#)
[list_databases](#)
[list_mysql_databases_and_users](#)
[remote_mysql_create_profile](#)
[remote_mysql_create_profile_via_ssh](#)
[remote_mysql_delete_profile](#)
[remote_mysql_initiate_profile_activation](#)
[remote_mysql_monitor_profile_activation](#)
[remote_mysql_read_prof](#)

<p>database_user</p>	<p>array</p>	<p>A list of database users.</p> <p>The function returns this value in the <code>mysql_databases</code> hash.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : The return's name is the MySQL database's name.</p> </div>	<p>A comma-separated list of database users.</p>	<p>user1_user5</p>
----------------------	--------------	---	--	--------------------

ile

remote_mysql_read_profiles

remote_mysql_update_profile

remote_mysql_validate_profile

rename_mysql_database

rename_mysql_user

rename_postgresql_database

rename_postgresql_user

set_local_mysql_root_password

set_mysql_password

set_postgresql_password

start_background_mysql_upgrade

▼ DNS

adddns

addzonerecord

addzonerecord
(Reverse DNS)

dumpzone

editzonerecord

get_nameserver_config

getzonerecord

has_local_authority

killdns

listmxs

listzones

lookupnsip

lookupnsips

removezone
record

resetzone

resolvedom
ainname

savemxs

setresolvers

update_nam
eservers_co
nfig

▼ EasyApache

ea4_get_cur
rently_install
ed_packages

ea4_get_ea
_pkgs_state

ea4_list_pro
files

ea4_migrati
on

ea4_pre_mi
grate_check

ea4_recom
mendations

ea4_save_p
rofile

ea4_tomcat
85_add

ea4_tomcat
85_list

ea4_tomcat
85_rem

▼ Greylisting

cpgreylist_is
_server_net
block_truste
d

cpgreylist_li
st_entries_f
or_common
_mail_provid
er

cpgreylist_lo
ad_common
_mail_provid
ers_config

cpgreylist_s
ave_commo
n_mail_provi
ders_config

cpgreylist_st
atus

cpgreylist_tr
ust_entries_

for_common_mail_provider

cpgreylist_untrusted_entries_for_common_mail_provider

create_cpgreylist_trusted_host

delete_cpgreylist_trusted_host

disable_cpgreylist

enable_cpgreylist

load_cpgreylist_config

read_cpgreylist_deferred_entries

read_cpgreylist_trusted_host

save_cpgreylist_config

Integration

batch

cpanel

create_integration_group

create_integration_link

get_integration_link_user_config

list_integration_groups

list_integration_links

remove_integration_group

remove_integration_link

update_integration_link_token

IP Addresses

addips

delip

get_public_i

p

get_shared_
ip

ipv6_disable_
_account

ipv6_enable_
_account

ipv6_range_
add

ipv6_range_
edit

ipv6_range_
list

ipv6_range_
remove

ipv6_range_
usage

listips

nat_checkip

nat_set_pub
lic_ip

setsiteip

▼ Mail

disable_dki
m

disable_mail_
_sni

emailtrack_s
earch

emailtrack_s
tats

emailtrack_u
ser_stats

enable_dkim

enable_mail_
_sni

ensure_dki
m_keys_exi
st

exim_config
uration_che
ck

expunge_m
ailbox_mess
ages

expunge_m
essages_for
_mailbox_gu
id

fetch_dkim_
private_keys

fetch_mail_

queue
generate_m
obileconfig
get_mailbox
_status
get_mailbox
_status_list
get_user_e
mail_forwar
d_destinatio
n
hold_outgoi
ng_email
install_dkim
_private_key
s
install_spf_r
ecords
is_sni_supp
orted
list_pops_for
mail_sni_sta
tus
rebuild_mail
_sni_config
release_out
going_email
save_spamd
_config
set_user_e
mail_forwar
d_destinatio
n
suspend_ou
tgoing_email
unsuspend_
outgoing_e
mail
validate_cur
rent_installe
d_exim_conf
ig
validate_cur
rent_dkims
validate_cur
rent_ptrs
validate_cur
rent_spfs
validate_exi
m_configura
tion_syntax

▼ Market

disable_mar
ket_provider

enable_market_provider

get_adjusted_market_providers_products

get_market_providers_commission_config

get_market_providers_list

get_market_providers_product_metadata

get_market_providers_products

set_market_product_attribute

set_market_provider_commission_id

▼ ModSecurity™

modsec_added_rule

modsec_added_vendor

modsec_assemble_config_text

modsec_batch_settings

modsec_check_rule

modsec_clone_rule

modsec_deploy_all_rule_changes

modsec_deploy_rule_changes

modsec_deploy_settings_changes

modsec_disable_rule

modsec_disable_vendor

modsec_disable_vendor_configs

modsec_disable_vendor_updates

modsec_disable_all_rule_changes

modsec_disable_rule_changes

modsec_edit_rule

modsec_enable_vendor

modsec_enable_vendor_configs

modsec_enable_vendor_updates

modsec_get_config_text

modsec_get_configs

modsec_get_configs_with_changes_pending

modsec_get_log

modsec_get_rules

modsec_get_settings

modsec_get_vendors

modsec_is_installed

modsec_make_config_active

modsec_make_config_inactive

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set
_config_text

modsec_set
_setting

modsec_un
disable_rule

modsec_up
date_vendor

▼ Packages

_getpkgexte
nsionform

add_overrid
e_features_f
or_user

addpkg

addpkgext

changepack
age

create_featu
relist

delete_featu
relist

delpkgext

editpkg

get_availabl
e_applicatio
ns

get_availabl
e_featurelist
s

get_feature_
metadata

get_feature_
names

get_featureli
st_data

get_featureli
sts

get_users_f
eatures_sett
ings

getfeaturelis
t

getpkginfo

killpkg

listpkgs

manage_fea
tures

matchpkgs

read_feature
list

remove_override_features_for_user

update_featurelist

verify_user_has_feature

▼ PHP

convert_all_domains_to_fpm

get_fpm_count_and_utilization

is_conversion_in_progress

php_get_default_accounts_to_fpm

php_get_handlers

php_get_impacted_domains

php_get_installed_versions

php_get_old_fpm_flag

php_get_system_default_version

php_get_versions_by_version

php_get_versions

php_ini_get_content

php_ini_get_directives

php_ini_set_content

php_ini_set_directives

php_set_default_accounts_to_fpm

php_set_handler

php_set_old_fpm_flag

php_set_session_save_p

ath

php_set_sys
tem_default
_version

php_set_vh
ost_versions

▼ Resellers

acctcounts

get_public_c
ontact

getresellerip
s

listacts

listresellers

resellerstats

saveacllist

set_public_c
ontact

setacts

setresellerip
s

setresellerli
mits

setresellerm
ainip

setresellern
ameservers

setresellerp
ackagelimit

setupreselle
r

suspendres
eller

terminateres
eller

unsetuprese
ller

unsuspendr
eseller

▼ RPM

delete_rpm_
version

edit_rpm_
rsion

get_rpm_
sion_data

install_rpm_
plugin

list_rpms

package_m

anager_fixc
ache

package_m
anager_get_
build_log

package_m
anager_get_
package_inf
o

package_m
anager_is_p
erforming_a
ctions

package_m
anager_list_
packages

package_m
anager_reso
lve_actions

package_m
anager_sub
mit_actions

package_m
anager_upgr
ade

uninstall_rp
m_plugin

▼ Script Hooks

delete_hook

edit_hook

list_hooks

reorder_hoo
ks

▼ Security

accesshash

authorizessh
key

check_remo
te_ssh_conn
ection

convertopen
shtoputty

deletesshke
y

generatessh
keypair

importsshke
y

listsshkeys

▼ Server

Administration

add_configcl
usterserver

configureba

ckgroundpro
cesskiller

configureser
vice

cors_proxy_
get

create_user
_session

delete_confi
gclusterserv
er

enable_mon
itor_all_ena
bled_service
s

get_all_cont
act_importa
nces

get_appconf
ig_applicatio
n_list

get_applicati
on_contact_
event_import
tance

get_applicati
on_contact_
importance

get_availabl
e_profiles

get_current_
profile

get_passwor
d_strength

get_remote_
access_has
h

get_service_
config

get_service_
config_key

get_tweakse
tting

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

loadavg
nvget
nvset
personalization_get
personalization_set
purchase_application_license
reboot
remove_in_progress_exim_configuration
restartservice
restore_configuration_from_file
restore_configuration_from_upload
run_cpkeyctl
send_test_posturl
send_test_pushbullet_notification
servicestatus
set_application_contact_event_importance
set_application_contact_importance
set_primary_servername
set_service_configuration_key
set_tweaking
sethostname
setminimumpasswordstrengths
start_profile_activation
systemneeds_reboot
systemloada

vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

fetchcrtinfo

fetchsslinfo

generatessl

get_autoss
l_check_sch
edule

get_autoss
l_log

get_autoss
l_logs_catalo
g

get_autoss
l_metadata

get_autoss
l_pending_q
ueue

get_autoss
l_pending_q
ueue_for_do
main

get_autoss
l_pending_q
ueue_for_us
er

get_autossl
_problems_f
or_domain

get_autossl
_problems_f
or_user

get_autossl
_providers

get_best_ssl
domain_for_
service

install_servi
ce_ssl_certif
icate

installssl

listcrts

rebuildinstall
edssldb

rebuildusers
sldb

reset_autos
ssl_provider

reset_servic
e_ssl_certifi
cate

set_autossl_
metadata

set_autossl_
metadata_k
ey

set_autossl_
provider

start_autossl
_check_for_
all_users

start_autossl
_check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_get_s
upport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

abort_transf
er_session

analyze_tra
nsfer_sessio
n_remote

available_tr
ansfer_mod
ules

create_remo
te_root_tran
sfer_session

create_remo
te_user_tran
sfer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transf
er_session_l
og

get_transfer
_session_st
ate

pause_trans
fer_session

remote_basi
c_credential
_check

retrieve_tran
sfer_session
_remote_an
alysis

start_transfe
r_session

transfer_mo
dule_schem
a

validate_sys
tem_user

▼ Updates

accept_eula

get_availabl
e_tiers

get_current_
lts_expiratio
n_status

get_lts_wex
pire

getlongterm
support

installed_ver
sions

set_cpanel_
updates

set_tier

update_upd
ateconf

version