

UAPI Modules - Restore

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup::fullbacku
p_to_ftp

Backup::fullbacku
p_to_homedir

Backup::fullbacku
p_to_scp_with_key

Backup::fullbacku
p_to_scp_with_password

Backup::list_backups

Bandwidth

Bandwidth::get_enabled_protocols

Bandwidth::get_retention_periods

Bandwidth::query

Batch

Batch::strict

Brand

Brand::read

Branding

Branding::file

Branding::get_applications

Branding::get_application_information

Branding::get_available_applications

Branding::get_info

Introduction

The `Restore` module provides functions to browse and restore a user's backup files and directories.

Available functions

- UAPI Functions - `Restore::directory_listing` — This function lists all of the backup files and directories in the user's home directory.
- UAPI Functions - `Restore::get_users` — This function lists a reseller's users with existing backup metadata.
- UAPI Functions - `Restore::query_file_info` — This function lists all of an item's backup locations. An item can be a file, a directory, or a symlink.
- UAPI Functions - `Restore::restore_file` — This function restores a file or directory from a backup to the file or directory's original location.

UAPI Basics

About UAPI

UAPI accesses and modifies data for cPanel accounts.

Notes:

- Th
Fe
- int
- Ur
mu
us
20
or
20
) .`
20
or
20
) .

information_for_applications

Branding:: image

Branding:: include

Branding:: spritelist

▼ CacheBuster

CacheBuster:: read

CacheBuster:: update

▼ Chkservd

Chkservd:: get_exit_ports

Chkservd:: get_exit_ports_ssl

▼ Chrome

Chrome:: get_domain

▼ Contactus

Contactus:: is_enabled

▼ cPAddons

cPAddons:: get_available_addons

cPAddons:: get_instance_settings

cPAddons:: list_addon_instances

▼ cPGreyList

cPGreyList:: disable_all_domains

cPGreyList:: disable_domains

cPGreyList:: enable_all_domains

cPGreyList:: enable_domains

cPGreyList:: has_greylisting_enabled

cPGreyList:: list_domains

▼ DAV

DAV:: disable_shared_global_addressbook

DAV:: enable_shared_global_addressbook

DAV:: get_calendar_contacts_config

DAV:: has_shared_global_addressbook

Related Documentation

- [Use WHM API to Call cPanel API and UAPI](#)
— You can call cPanel API and UAPI functions through the WHM API.
- [Guide to the Manage2 API](#)
— The Manage2 API automates cPanel license management procedures.

DAV:: is_dav_service_enabled

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

- [Guide to UAPI](#) — UAPI accesses the cPanel interface's features.
- [Guide to WHM API 0](#) — WHM API 0 accesses the WHM interface's features.
- [Guide to cPanel API 2](#) — cPanel API 2 accesses cPanel account information and modifies settings.

Email:: add_spam
_filter

Email:: browse_m
ailbox

Email:: change_mx

Email:: check_fast
mail

Email:: check_pipe
_forwarder

Email:: delete_aut
o_responder

Email:: delete_do
main_forwarder

Email:: delete_filter

Email:: delete_for
warder

Email:: delete_hel
d_messages

Email:: delete_list

Email:: delete_mx

Email:: delete_pop

Email:: disable_filt
er

Email:: disable_ma
ilbox_autocreate

Email:: disable_sp
am_assassin

Email:: disable_sp
am_autodelete

Email:: disable_sp
am_box

Email:: dispatch_cl
ient_settings

Email:: edit_pop_q
uota

Email:: enable_filte
r

Email:: enable_ma
ilbox_autocreate

Email:: enable_sp
am_assassin

Email:: enable_sp
am_box

Email:: fetch_char
maps

Email:: fts_rescan
_mailbox

Email:: generate_
mailman_otp

Email:: get_auto_r

esponder

Email:: get_charges

Email:: get_client_settings

Email:: get_default_email_quota

Email:: get_default_email_quota_mib

Email:: get_disk_usage

Email:: get_filter

Email:: get_held_message_count

Email:: get_mailbox_autocreate

Email:: get_mailman_delegates

Email:: get_main_account_disk_usage

Email:: get_main_account_disk_usage_bytes

Email:: get_max_email_quota

Email:: get_max_email_quota_mib

Email:: get_pop_quota

Email:: get_spam_settings

Email:: get_webmail_settings

Email:: has_delegated_mailman_lists

Email:: has_plaintext_authentication

Email:: hold_outgoing

Email:: is_integer

Email:: list_auto_responders

Email:: list_default_address

Email:: list_domain_forwarders

Email:: list_filters

Email:: list_filters_backups

Email:: list_forward

ers

Email:: list_forward
ers_backups

Email:: list_lists

Email:: list_mail_d
omains

Email:: list_mxs

Email:: list_pops

Email:: list_pops_
with_disk

Email:: list_system
_filter_info

Email:: passwd_list

Email:: passwd_po
p

Email:: release_ou
tgoing

Email:: remove_m
ailman_delegates

Email:: reorder_filt
ers

Email:: set_always
_accept

Email:: set_default
_address

Email:: set_list_pri
vacy_options

Email:: stats_db_st
atus

Email:: store_filter

Email:: suspend_in
coming

Email:: suspend_lo
gin

Email:: suspend_o
utgoing

Email:: trace_filter

Email:: unsuspend
_incoming

Email:: unsuspend
_login

Email:: unsuspend
_outgoing

Email:: verify_pass
word

▼ EmailAuth

EmailAuth:: disabl
e_dkim

EmailAuth:: enable
_dkim

EmailAuth:: ensure
_dkim_keys_exist

EmailAuth:: fetch_
dkim_private_keys

EmailAuth:: install
_dkim_private_key
s

EmailAuth:: install
_spf_records

EmailAuth:: validat
e_current_dkims

EmailAuth:: validat
e_current_ptrs

EmailAuth:: validat
e_current_spfs

ExternalAuthenticat ion

ExternalAuthentic
ation:: add_authn_li
nk

ExternalAuthentic
ation:: configured_
modules

ExternalAuthentic
ation:: get_authn_lin
ks

ExternalAuthentic
ation:: has_external
_auth_modules_co
nfigured

ExternalAuthentic
ation:: remove_auth
n_link

Features

Features:: has_fea
ture

Features:: list_feat
ures

Fileman

Fileman:: autocom
pletedir

Fileman:: empty_tr
ash

Fileman:: get_file_
content

Fileman:: get_file_i
nformation

Fileman:: list_files

Fileman:: save_file
_content

Fileman:: transcod
e

Fileman:: upload_fi
les

▼ Ftp

Ftp:: add_ftp

Ftp:: allows_anonymous_ftp

Ftp:: allows_anonymous_ftp_incoming

Ftp:: delete_ftp

Ftp:: ftp_exists

Ftp:: get_ftp_daemon_info

Ftp:: get_port

Ftp:: get_quota

Ftp:: get_welcome_message

Ftp:: kill_session

Ftp:: list_ftp

Ftp:: list_ftp_with_disk

Ftp:: list_sessions

Ftp:: passwd

Ftp:: server_name

Ftp:: set_anonymous_ftp

Ftp:: set_anonymous_ftp_incoming

Ftp:: set_homedir

Ftp:: set_quota

Ftp:: set_welcome_message

▼ Integration

Integration:: fetch_url

▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

▼ LangPHP

LangPHP:: php_get_domain_handler

LangPHP:: php_get_impacted_domains

LangPHP:: php_get_installed_version

s

LangPHP:: php_get_system_default_version

LangPHP:: php_get_vhost_versions

LangPHP:: php_ini_get_user_basic_directives

LangPHP:: php_ini_get_user_content

LangPHP:: php_ini_get_user_paths

LangPHP:: php_ini_set_user_basic_directives

LangPHP:: php_ini_set_user_content

LangPHP:: php_set_vhost_versions

▼ LastLogin

LastLogin:: get_last_or_current_logged_in_ip

▼ Locale

Locale:: get_attributes

▼ Mailboxes

Mailboxes:: expunge_mailbox_messages

Mailboxes:: expunge_messages_for_mailbox_guid

Mailboxes:: get_mailbox_status

Mailboxes:: has_utf8_mailbox_names

Mailboxes:: set_utf8_mailbox_names

▼ Market

Market:: cancel_pending_ssl_certificate

Market:: create_shopping_cart

Market:: get_all_products

Market:: get_certificate_status_details

Market:: get_login_url

Market:: get_pending_ssl_certificates

Market:: get_provi
der_specific_dcv_
constraints

Market:: get_provi
ders_list

Market:: get_ssl_c
ertificate_if_availa
ble

Market:: process_s
sl_pending_queue

Market:: request_s
sl_certificates

Market:: set_status
_of_pending_queu
e_items

Market:: set_url_af
ter_checkout

Market:: validate_l
ogin_token

▼ Mime

Mime:: add_handl
er

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redire
ct

Mime:: delete_han
dler

Mime:: delete_hotli
nk

Mime:: delete_mim
e

Mime:: delete_redi
rect

Mime:: list_handler
s

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirect
s

Mime:: redirect_inf
o

▼ ModSecurity

ModSecurity:: disa
ble_all_domains

ModSecurity:: disa
ble_domains

ModSecurity:: ena
ble_all_domains

ModSecurity:: ena
ble_domains

ModSecurity:: has
_modsecurity_inst
alled

ModSecurity:: list_
domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_
note

Mysql :: check_dat
abase

Mysql:: create_dat
abase

Mysql:: create_use
r

Mysql:: delete_dat
abase

Mysql:: delete_hos
t

Mysql:: delete_use
r

Mysql:: get_host_n
otes

Mysql:: get_privile
ges_on_database

Mysql:: get_restrict
ions

Mysql:: get_server
_information

Mysql:: locate_ser
ver

Mysql:: rename_d
atabase

Mysql:: rename_us
er

Mysql:: repair_dat
abase

Mysql:: revoke_ac
cess_to_database

Mysql:: set_passw
ord

Mysql:: set_privile
ges_on_database

▼ Notifications

Notifications:: get_
notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_rel
ative_uri

- ▼ PassengerApps
 - PassengerApps:: disable_application
 - PassengerApps:: edit_application
 - PassengerApps:: enable_application
 - PassengerApps:: list_applications
 - PassengerApps:: register_application
 - PassengerApps:: unregister_application
- ▼ PasswdStrength
 - PasswdStrength:: get_required_strength
- ▼ Personalization
 - Personalization::set
 - Personalization::get
- ▼ Postgresql
 - Postgresql:: create_database
 - Postgresql:: create_user
 - Postgresql:: delete_database
 - Postgresql:: get_restrictions
 - Postgresql:: grant_all_privileges
 - Postgresql:: rename_database
 - Postgresql:: rename_user
 - Postgresql:: rename_user_no_password
 - Postgresql:: revoke_all_privileges
 - Postgresql:: set_password
- ▼ Pushbullet
 - Pushbullet:: send_test_message
- ▼ Quota
 - Quota:: get_quota_info
- ▼ Resellers
 - Resellers:: list_acc

ounts

▼ ResourceUsage

ResourceUsage::
get_usages

▼ Restore

Restore:: directory
_listing

Restore:: get_user
s

Restore:: query_fil
e_info

Restore:: restore_f
ile

▼ Session

Session:: create_t
emp_user

▼ SiteTemplates

SiteTemplates:: list
_site_templates

SiteTemplates:: list
_user_settings

SiteTemplates:: pu
blish

▼ SpamAssassin

SpamAssassin :: cl
ear_spam_box

SpamAssassin:: g
et_symbolic_test_
names

SpamAssassin:: g
et_user_preferenc
es

SpamAssassin:: u
pdate_user_prefer
ence

▼ SSH

SSH:: get_port

▼ SSL

SSL:: add_autossl
_excluded_domain
s

SSL:: check_share
d_cert

SSL:: delete_cert

SSL:: delete_csr

SSL:: delete_key

SSL:: delete_ssl

SSL :: disable_mai
l_sni

SSL:: enable_mail
_sni

SSL:: fetch_best_f

or_domain

SSL:: fetch_cert_in
fo

SSL:: fetch_certific
ates_for_fqdns

SSL:: fetch_key_a
nd_cabundle_for_
certificate

SSL:: find_certifica
tes_for_key

SSL:: find_csrs_for
_key

SSL:: generate_ce
rt

SSL:: generate_cs
r

SSL:: generate_ke
y

SSL:: get_autoss_
excluded_domains

SSL:: get_autoss_
pending_queue

SSL:: get_autoss_
problems

SSL:: get_cabundl
e

SSL:: get_cn_nam
e

SSL:: install_ssl

SSL:: installed_ho
st

SSL:: installed_ho
sts

SSL:: is_autoss_
check_in_progress

SSL:: is_mail_sni_
supported

SSL:: is_sni_supp
orted

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_item
s

SSL:: mail_sni_sta
tus

SSL:: rebuild_mail
_sni_config

SSL:: rebuildssldb

SSL:: remove_aut
oss_excluded_do

mains

SSL:: set_autossl_excluded_domains

SSL:: set_cert_friendly_name

SSL:: set_csr_friendly_name

SSL:: set_key_friendly_name

SSL:: set_primary_ssl

SSL:: set_ssl_share

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_check

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stats

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: add_subdomain

▼ Themes

Themes:: get_theme_base

Themes:: list

Themes:: update

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete_user

WebDisk:: set_homedir

WebDisk:: set_password

WebDisk:: set_permissions

▼ WebmailApps

WebmailApps:: list
webmailapps

▼ WebVhosts

WebVhost:: list_domains

WebVhost:: list_ssl_capable_domains

▼ WordPressBackup

WordPressBackup
:: any_running

WordPressBackup
:: cancel

WordPressBackup
:: cleanup

WordPressBackup
:: get_available_backups

WordPressBackup
:: is_running

WordPressBackup
:: start

▼ WordPressInstance

Manager

WordPressInstanceManager:: cancel_scan

WordPressInstanceManager:: cleanup_scan

WordPressInstanceManager:: change_admin_password

WordPressInstanceManager:: configure_autoupdate

WordPressInstanceManager:: get_api_version

WordPressInstanceManager:: get_instance_by_id

WordPressInstanceManager:: get_instances

WordPressInstanceManager:: get_latest_wordpress_version_from_wordpress_org

WordPressInstanceManager:: get_scan_results

WordPressInstanceManager:: is_inst

allable_addon_ava
ilable

WordPressInstanc
eManager:: start_s
can

▼ WordPressRestore

WordPressRestore
:: any_running

WordPressRestore
:: cleanup

WordPressRestore
:: start