

cPanel API 1 Functions - CustInfo::getemail

Guide to cPanel API 1

Return Data

cPanel Tags
(deprecated)

Bandwidth:
display
header

er

Bandwidth:
display
bw

Bandwidth:
display
day

Bandwidth:
display
mainbwhheader

BoxTrapper

BoxTrapper::chan
gestatus

BoxTrapper::clean
cfgfilelist

BoxTrapper::edit
msg

BoxTrapper::fetch
cfgfile

BoxTrapper::getb
oxconfdir

BoxTrapper::listm
sgs

BoxTrapper::logco
ntrols

BoxTrapper::mess
ageaction

BoxTrapper::multi
messageaction

BoxTrapper::reset
msg

BoxTrapper::save
cfgfile

BoxTrapper::save
conf

BoxTrapper::show
autowhitelist

BoxTrapper::show
emails

BoxTrapper::show
fromname

BoxTrapper::show
log

Description

This function retrieves the account's contact email addresses.

Warning:

cPanel API 1 is **deprecated**. Do not use this function. Instead, we **strongly** recommend that you use the following newer functions:

- **UAPI (recommended)** — *None*.
- **cPanel API 2** — `CustInfo::contactemails` — This function retrieves the account's primary and secondary email addresses.

Examples

LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
$contact_email =  
$cpanel->apil('CustIn  
fo', 'getemail'); //  
Call the function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
my $contact_email =  
$cpliveapi->apil('Cus  
tInfo', 'getemail');  
# Call the function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Function information

About this module

The `CustInfo` module retrieves contact information for an account.

About cPanel API 1

cPanel API 1 accesses information about cPanel accounts.

- BoxTrapper:: show message
- BoxTrapper:: show queue
- BoxTrapper:: show queuesearch
- BoxTrapper:: show queuetime
- BoxTrapper:: status
- BoxTrapper:: statusbutton
- Branding:: file
 - Branding:: image
 - Branding:: killing
 - Branding:: setbrandingpkg
 - Branding:: setmyacctspkg
 - Branding:: setupdirs
 - Branding:: tempsetbrandingpkg
- Cgi:: backuplink
 - Cgi:: displayurchin
 - Cgi:: phpmyadminlink
- Chkserve:: getximport
 - Chkserve:: getximportssl
- ClamScanner:: bars
- cPAddons:: mainpg
- Cron:: crontabperms
- CustInfo:: getemail
- Deny:: adddenyip
 - Deny:: deldenyip
 - Deny:: listdenyips

Parameters

▼ cPanel Tag System (deprecated)

Warning:

In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We provide this example to help developers move from the old cPanel tag system to our [LiveAPI](#) system. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs.

```
<cpanel
Module="CustInfo::get
email() ">
```

▼ Command Line

```
cpapil
--user=username
CustInfo getemail
```

Notes:

- You **must** [URI-encode](#) these values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to cPanel API 1](#) documentation or run the `cpapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapil` command:

```
/usr/local
/cpanel/bin/cpapil
```

▼ Output (plaintext)

```
username@example.com
```

Warning:
cPanel API deprecated. We **strongly** recommend cPanel API or UAPI instead.

Notes:

- Th
Fe
- int
- Ur
mu
us
20
or
20
).`
20
or
20
).

Find
a
funct
ion

▼ [DiskUsage](#)

DiskUsage:: show manager

▼ [Email](#)

Email:: addautoresponder

Email:: addforward

Email:: addfilter

Email:: addlist

Email:: addmx

Email:: addpop

Email:: addspam

Email:: addspambox

Email:: addspamfilter

Email:: changemx

Email:: checkfastmail

Email:: checkpipewd

Email:: clearspambox

Email:: delautoresponder

Email:: delforward

Email:: delfilter

Email:: dellist

Email:: delmx

Email:: delpop

Email:: delspam

Email:: delspambox

Email:: disable_spam_autodelete

Email:: editquota

Email:: enable_spam_autodelete

Email:: getaging

Email:: getarsbody

Email:: getarscharset

Email:: getarsfrom

Email:: getarshtml

Email:: getarsinterval

This function does not accept parameters.

Returns

This function returns the email address or addresses that the `~/ .contactemail` file contains.

- [cPanel API 1 Functions - Cuserinfo:: getemail](#) — This function retrieves the account's contact email addresses.
- [cPanel API 1 Modules - Cuserinfo module retrieval](#) — The Cuserinfo module retrieves contact information for an account.

Email:: getarsstart

Email:: getarsstop

Email:: getarssubject

Email:: getmailserver

Email:: getmailserveruser

Email:: getpopquota

Email:: has_spam_as_acl

Email:: has_spam_autodelete

Email:: listmaildomains

Email:: listmaildomainsopt

Email:: listmaildomainsoptndef

Email:: mainacctdiskused

Email:: passwdlist

Email:: passwdpop

Email:: setmxaccept

Email:: spamboxstatus

Email:: spamstatus

Email:: tracefilter

▼ Fileman

Fileman:: changeperm

Fileman:: delfile

Fileman:: dofileop

Fileman:: emptytrash

Fileman:: extractfile

Fileman:: fileimg

Fileman:: fmmkdir

Fileman:: fmmkfile

Fileman:: fmpushfile

Fileman:: fmrename

Fileman:: fmsavefile

Fileman:: fmsaveht

mfile

Fileman:: fullbacku
p

Fileman:: getfile

Fileman:: htmledito
r

Fileman:: killdir

Fileman:: listfiles

Fileman:: listfullba
ckups

Fileman:: listtempl
ates

Fileman:: restoreaf

Fileman:: restored
b

Fileman:: restorefil
e

Fileman:: restorefil
es

Fileman:: savehtml
file

Fileman:: showper
m

Fileman:: uploadfil
es

Fileman:: viewfile

▼ Frontpage

FrontPage:: addfp

FrontPage:: delfp

FrontPage:: fpstat
us

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: ftpquota

Ftp:: ftpservernam
e

Ftp:: ftpstatslogin

Ftp:: get_anonftp

Ftp:: get_anonftpin

Ftp:: get_welcome
msg

Ftp:: getftpquota

Ftp:: kill_ftp_sessi
on

Ftp:: listftpstatsurl

Ftp:: passwdfp

Ftp:: set_anonftp

Ftp:: set_anonftpin

Ftp:: set_welcome
msg

▼ Gpg

Gpg:: deletekey

Gpg:: exportkey

Gpg:: exportsecret
key

Gpg:: genkey

Gpg:: importkeys

▼ Htaccess

Htaccess:: checkpr
otected

Htaccess:: del_use
r

Htaccess:: getinde
x

Htaccess:: htdirls

Htaccess:: number
_of_users

Htaccess:: phpsele
ctable

Htaccess:: resnam
e

Htaccess:: set_pas
s

Htaccess:: set_pro
tect

Htaccess:: setinde
x

Htaccess:: setphpr
eference

Htaccess:: showus
ers

▼ ImageManager

ImageManager:: c
onvert

ImageManager:: di
mensions

ImageManager:: h
dimension

ImageManager:: s
cale

ImageManager:: th
umbnail

ImageManager:: w
dimension

▼ LastLogin

LastLogin:: lastlogi
n

▼ LeechProtect

LeechProtect:: disable

LeechProtect:: enable

LeechProtect:: setup

LeechProtect:: showpasswdfile

LeechProtect:: status

▼ LogManager

LogManager:: listdownloads

LogManager:: save settings

LogManager:: show settings

▼ MagicRevision

MagicRevision:: uri

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: del_handler

Mime:: del_hotlink

Mime:: del_mime

Mime:: del_redirect

Mime:: linkallownull

Mime:: linkenable

Mime:: linkexts

Mime:: linkrurl

Mime:: linkurls

▼ Mysql

Mysql:: adddb

Mysql:: addhost

Mysql:: adduser

Mysql:: adduserdb

Mysql:: checkdb

Mysql:: deldb

Mysql:: delhost

Mysql:: deluser

Mysql:: deluserdb

Mysql:: gethost
Mysql:: initcache
Mysql:: listdbs
Mysql:: listdbsopt
Mysql:: listusers
Mysql:: listusersopt
Mysql:: number_of
_dbs
Mysql:: number_of
_users
Mysql:: repairdb
Mysql:: routines
Mysql:: updatepriv
s

▼ Net

Net:: dnslookup
Net:: dnszone
Net:: sethastracero
ute

▼ News

News:: displaynew
s

▼ NVData

NVData:: set

▼ OptimizeWS

OptimizeWS:: load
optimizesettings
OptimizeWS:: load
optimizesettings (b
ytes)
OptimizeWS:: opti
mizews

▼ Park

Park:: disabledir
ect
Park:: getredirectu
rl
Park:: park
Park:: setredirectur
l
Park:: unpark

▼ Postgres

Postgres:: adddb
Postgres:: adduser
Postgres:: adduser
db
Postgres:: deldb
Postgres:: deluser

Postgres:: deluser
db

Postgres:: initcach
e

Postgres:: listdbso
pt

Postgres:: listusers
opt

Postgres:: number
_of_dbs

Postgres:: number
_of_users

▼ ProxyUtils

ProxyUtils:: proxya
ddress

▼ Resellers

Resellers:: accoun
tlistopt

Resellers:: themeli
stopt

▼ Serverinfo

Serverinfo:: servic
estatus

▼ SetLang

SetLang:: listlangs
opt

SetLang:: setlang

▼ SpamAssassin

SpamAssassin:: co
nfig

SpamAssassin:: sa
veconfig

▼ SSH

SSH:: getport

▼ SSL

SSL:: delete

SSL:: deletectr

SSL:: deletecsr

SSL:: deletekey

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcabundle

SSL:: getcname

SSL:: install

SSL:: installedhost

SSL:: listkeysopt

SSL:: showcrt

SSL:: showcsr

SSL:: showkey

SSL:: sslsharedsta
tus

SSL:: uploadcrt

SSL:: uploadkey

▼ StatManager

StatManager:: doF
orm

StatManager:: upd
ateUserConfig

▼ Stats

Stats:: analoglist

Stats:: awstats

Stats:: bwbar

Stats:: errlog

Stats:: lastvisitors

Stats:: showbandw
idth

Stats:: webalizer

Stats:: webalizerftp

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: cplist
subdomains

SubDomain:: disab
lesubrd

SubDomain:: listsu
bdomainsop

SubDomain:: setsu
burl

▼ UI

UI:: confirm

UI:: redirect

UI:: showresult