

cPanel API 2 Functions - PHPINI::getalloptions

Guide to cPanel API 2

Return Data

Filter and Sort Output

Paginate Output

Output Columns

Calls from the WHM API

cPanel Tags (deprecated)

Description

This function retrieves a PHP configuration file's list of options.

Warning:

We **strongly** recommend that you use [UAPI](#) instead of cPanel API 2. However, no equivalent UAPI function exists.

Important:

In cPanel & WHM version 76 and later, when you disable the `WebServerRole`, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

[AddonDomain](#)

WHM API (JSON)

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?cpanel_jsonapi_user=user&cpanel_jsonapi_api_version=2&cpanel_jsonapi_module=PHPINI&cpanel_jsonapi_function=getalloptions&php_prefix="%2Fusr%2Flocal%2Fcppanel%2F3rdparty%2F"
```

Note:

For more information, read our [Calls from the WHM API](#) documentation.

Function information

About this module

The PHP INI module retrieves PHP configuration settings.

About cPanel API 2

- AddonDomain: `addondomain`
- AddonDomain: `deladdondomain`
- AddonDomain: `listaddondomains`
- Backups: `listfullbackups`
- Bandwidth: `addhttpbandwidth`
- Bandwidth: `getbwdata`
- Bandwidth: `gethourlyaveragebwoveryear`
- BoxTrapper: `accountmanagelist`
- Branding: `addbrandingobj`
- Branding: `applist`
- Branding: `brandingeditor`
- Branding: `createpkg`
- Branding: `cssmerge`
- Branding: `delbrandingobj`
- Branding: `delpkg`
- Branding: `gensprites`

Branding:: getbrandingpkg

Branding:: getbrandingpkgstatus

Branding:: getdefaultbrandingpkg

Branding:: installbrandingpkgs

Branding:: installimages

Branding:: killimages

Branding:: listingtypes

Branding:: listobjecttypes

Branding:: preloadconf

Branding:: resetall

Branding:: resetscss

Branding:: resethtml

Branding:: resolve_file

Branding:: resolveocalcss

Branding:: saveocalcss

Branding:: setbrandingpkgstatus

Branding:: showpackages

Branding:: spritelist

▼ CSVImport

CSVImport:: columnchoices

CSVImport:: configimport

CSVImport:: data

CSVImport:: fetchimportdata

CSVImport:: isenabled

CSVImport:: loaddata

CSVImport:: processdata

CSVImport:: sendcontact

CSVImport:: uploadimport

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// Get PHP  
configuration info.  
$get_php_config =  
$cpanel->api2(  
    'PHPINI',  
    'getalloptions',  
    array(  
        'php_prefix'  
    )  
=>  
    '/usr/local/cpanel/3r  
dparty/',  
    )  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

cPanel API 2 accesses and modifies data for cPanel accounts.

Notes:

- The *Fe*

int
• Ur
mt
us
20
or
20
)'.
20
or
20
)'.

Find
a
funct
ion

- Contactus:: isenab led
 - Contactus:: sendc ontact
 - Cron
 - Cron:: add_line
 - Cron:: edit_line
 - Cron:: fetchcron
 - Cron:: get_email
 - Cron:: listcron
 - Cron:: remove_line
 - Cron:: set_email
 - CustInfo
 - CustInfo:: contacte mails
 - CustInfo:: contactp refs
 - CustInfo:: displayc ontactinfo
 - CustInfo:: savecon tactinfo
 - DBmap
 - DBmap:: status
 - DBmap:: version
 - DKIMUI
 - DKIMUI:: available
 - DKIMUI:: getrecor ds
 - DKIMUI:: install
 - DKIMUI:: installed
 - DKIMUI:: uninstall
 - Denylp
 - Denylp:: listdenyip s
 - DiskCounter
 - DiskCounter:: disk _counter
 - DiskUsage
 - DiskUsage:: buildc ache
 - DiskUsage:: clearc ache
 - DiskUsage:: fetch_ raw_disk_usage
 - DiskUsage:: fetchd iskusage
 - DiskUsage:: fetchd iskusagewithextras

LiveAPI Perl Module

```

my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Get PHP
configuration info.
my $get_php_config =
$cpliveapi->api2(
  'PHPINI',
  'getaloptions',
  {
    'php_prefix'
  }
=>
  '/usr/local/cpanel/3r
dparty/',
  }
);

```

Note:
For more information, read our [Guide to the LiveAPI System](#).

cPanel Tag System (deprecated)

Warnings:

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecat ed**. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Dep recated cPanel Tag Usage](#) docume ntation.

- cPan el API 2 Func tions - PHPI NI::g etopt ions — This functi on retrie ves PHP direc tive confi gurati on infor mati on.
- cPan el API 2 Func tions - PHPI NI::g etallo ption s — This functi on retrie ves a PHP confi gurati on file's list of optio ns.

▼ DnsLookup

DnsLookup:: name
2ip

▼ DomainLookup

DomainLookup:: c
ountbaseddomains

DomainLookup:: g
etbaseddomains

DomainLookup:: g
etdocroot

DomainLookup:: g
etdocroots

DomainLookup:: g
etmaindomain

▼ Email

Email:: accountna
me

Email:: adddomain
forward

Email:: addforward

Email:: addmx

Email:: addpop

Email:: browsebox
es

Email:: changemx

Email:: checkmain
discard

Email:: clearpopca
che

Email:: deletefilter

Email:: delforward

Email:: delmx

Email:: delpop

Email:: disablefilter

Email:: editquota

Email:: enablefilter

Email:: fetchautore
sponder

Email:: fetchcharm
aps

Email:: filteractions

Email:: filterlist

Email:: filtername

Email:: filterrules

Email:: get_archivi
ng_configuration

Email:: get_archivi
ng_default_configu

▼ Command Line

```
cpapi2  
--user=username  
PHPINI getalloptions
```

Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- You **must** run the `--user=username` command.
- For more information and additional output options, read our [Guide to cPanel API 2](#) documentation or run the `cpapi2 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapi2` command:

```
/usr/local  
/cpanel/bi  
n/cpapi2
```

▼ Output (JSON)

```
{  
  "cpanelresult": {  
    "apiversion": 2,  
    "func":  
    "getalloptions",  
    "data": [  
      {  
        "dirlist": [  
          {  
            "info":  
            "User-function to be  
            called if an  
            assertion fails.",  
            "value":  
            "0",  
            "commented": 1,  
            "subsection": "main",  
            "directive":  
            "assert.callback",  
            "section":
```

ration
Email: get_archiving_types
Email: get_default_email_quota
Email: get_email_signing
Email: get_max_email_quota
Email: getabsbrowserwsedir
Email: getalwaysaccept
Email: getdiskusage
Email: getmxcheck
Email: has_delegated_mailman_lists
Email: list_system_filter_info
Email: listaliasesbackups
Email: listautoresponders
Email: listdefaultaddresses
Email: listdomainforwards
Email: listfilterbackups
Email: listfilters
Email: listforwards
Email: listlists
Email: listmaildomains
Email: listmx
Email: listmxs
Email: listpops
Email: listpopssingle
Email: listpopswithdisk
Email: listpopswithimage
Email: loadfilter
Email: passwdpop
Email: reorderfilters

```
"Assertion"  
    },  
    {  
        "info":  
        "Issue a PHP warning  
for each failed  
assertion.",  
        "value":  
        "On",  
  
        "commented": 1,  
  
        "subsection": "main",  
  
        "directive":  
        "assert.warning",  
  
        "section":  
        "Assertion"  
    },  
    {  
        "info":  
        "Eval the expression  
with current  
error_reporting().  
Set to true if you  
want\  
error_reporting(0)  
around the eval().",  
        "value":  
        "0",  
  
        "commented": 1,  
  
        "subsection": "main",  
  
        "directive":  
        "assert.quiet_eval",  
  
        "section":  
        "Assertion"  
    },  
    {  
        "info":  
        "Assert(expr); active  
by default.",  
        "value":  
        "On",  
  
        "commented": 1,  
  
        "subsection": "main",
```

Email:: set_archiving_configuration

Email:: set_archiving_default_configuration

Email:: set_email_signing

Email:: setalwaysaccept

Email:: setdefaultaddress

Email:: setmxcheck

Email:: storefilter

Email:: tracefilter

▼ EmailTrack

EmailTrack:: search

EmailTrack:: stats

EmailTrack:: trace

▼ Encoding

Encoding:: get_encodings

Encoding:: guess_file

Encoding:: guess_file_opts

▼ FSTest

FSTest:: dirisempty

▼ Fileman

Fileman:: autocompletedir

Fileman:: fileop

Fileman:: getabsdir

Fileman:: getdir

Fileman:: getdiractions

Fileman:: getdiskinfo

Fileman:: getedittype

Fileman:: getfileactions

Fileman:: getpath

Fileman:: listfiles

Fileman:: mkdir

Fileman:: mkfile

Fileman:: savefile

```

"directive":
"assert.active",

"section":
"Assertion"
    },
    {
        "info":
        "Don't bail out by
        default.",
        "value":
        "Off",

        "commented": 1,

        "subsection": "main",

        "directive":
        "assert.bail",

        "section":
        "Assertion"
            }
        ],
        "section":
        "Assertion"
            },
            {
                "dirlist": [
                    {
                        "info":
                        "Modify the setting
                        below to match the
                        directory location of
                        the cracklib\
                        dictionary files.
                        Include the base
                        filename, but not the
                        file extension.",
                        "value":
                        "c:\\php\\lib\\crackl
                        ib_dict",

                        "commented": 1,

                        "subsection": "main",

                        "directive":
                        "crack.default_diction
                        ary",

                        "section": "Crack"
                            }
                    }
                ]
            }
    }
}

```

Fileman:: search

Fileman:: staffiles

Fileman:: uploadfiles

Fileman:: viewfile

▼ ForcePassword

ForcePassword:: get_force_password_flags

ForcePassword:: update_force_password_flags

▼ Frontpage

Frontpage:: fpenabled

Frontpage:: list

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: listftp

Ftp:: listftpessions

Ftp:: listftpwithdisk

Ftp:: passwd

Ftp:: setquota

▼ Gpg

Gpg:: listgpgkeys

Gpg:: listsecretgpgkeys

Gpg:: number_of_private_keys

Gpg:: number_of_public_keys

▼ Htaccess

Htaccess:: listusers

Htaccess:: listusers

▼ HttpUtils

HttpUtils:: getdirindices

▼ ImageManager

ImageManager:: thumbnail

▼ LVEInfo

LVEInfo:: getUsage

▼ LangMods

LangMods:: getarchname

LangMods:: getkey

```

    ],
    "section":
"Crack"
    },
    {
        "dirlist": [
            {
                "info":
"",
                "value":
"128",
                "commented": 1,
                "subsection": "main",
                "directive":
"fbsql.max_results",
                "section":
"FrontBase"
            },
            {
                "info":
"",
                "value":
"",
                "commented": 1,
                "subsection": "main",
                "directive":
"fbsql.default_database_password",
                "section":
"FrontBase"
            },
            {
                "info":
"",
                "value":
"",
                "commented": 1,
                "subsection": "main",
                "directive":
"fbsql.default_database",

```

LangMods:: getpre
fix

LangMods:: install

LangMods:: langlis
t

LangMods:: list_av
ailable

LangMods:: list_in
stalled

LangMods:: magic
_status

LangMods:: pre_ru
n

LangMods:: search

LangMods:: setup

LangMods:: uninst
all

LangMods:: updat
e

▼ LeechProtect

LeechProtect:: set
up

▼ Locale

Locale:: get_encod
ing

Locale:: get_html_
dir_attr

Locale:: get_locale
_name

Locale:: get_user_
ocale

Locale:: get_user_
ocale_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse
r

Logaholic:: adduse
rprofile

Logaholic:: deleteu
ser

Logaholic:: deleteu
serprofile

Logaholic:: edituse
r

Logaholic:: fetchus
er

Logaholic:: listuser
profiles

Logaholic:: logahol
iclink

```
"section":  
"FrontBase"  
    },  
    {  
        "info":  
        "",  
        "value":  
        "On",  
        "commented": 1,  
        "subsection": "main",  
        "directive":  
        "fbsql.autocommit",  
        "section":  
        "FrontBase"  
        },  
        {  
            "info":  
            "",  
            "value":  
            "On",  
            "commented": 1,  
            "subsection": "main",  
            "directive":  
            "fbsql.allow_persiste  
nt",  
            "section":  
            "FrontBase"  
            },  
            {  
                "info":  
                "",  
                "value":  
                "128",  
                "commented": 1,  
                "subsection": "main",  
                "directive":  
                "fbsql.max_connection  
s",  
                "section":  
                "FrontBase"  
                },
```



```

Logaholic:: proces
sstats
  Mime
  Mime:: list_hotlinks
  Mime:: listhandlers
  Mime:: listmime
  Mime:: listredirects
  Mime:: redirectname
  Mime:: redirecturlname
  MysqlFE
  MysqlFE:: authorizehost
  MysqlFE:: change
dbuserpassword
  MysqlFE:: created
b
  MysqlFE:: created
buser
  MysqlFE:: dbuserexists
  MysqlFE:: deauthorizehost
  MysqlFE:: deleted
b
  MysqlFE:: deleted
buser
  MysqlFE:: getalldb
sinfo
  MysqlFE:: getalldb
usersanddbs
  MysqlFE:: getdbuserprivileges
  MysqlFE:: getdbusers
  MysqlFE:: gethosts
  MysqlFE:: getmysqlprivileges
  MysqlFE:: getmysqlserverprivileges
  MysqlFE:: has_my
cnf_for_cpuser
  MysqlFE:: listdbs
  MysqlFE:: listdbsbackup
  MysqlFE:: listhosts
  MysqlFE:: listusers
  MysqlFE:: listusers
indb

```

```

    {
      "info":
"",
      "value":
"1000",
      "commented": 1,
      "subsection": "main",
      "directive":
"fbsql.batchSize",
      "section":
"FrontBase"
    },
    {
      "info":
"",
      "value":
"_SYSTEM",
      "commented": 1,
      "subsection": "main",
      "directive":
"fbsql.default_user",
      "section":
"FrontBase"
    },
    {
      "info":
"",
      "value":
"128",
      "commented": 1,
      "subsection": "main",
      "directive":
"fbsql.max_links",
      "section":
"FrontBase"
    },
    {
      "info":
"",
      "value":
" ",

```

- MysqlFE:: revoked
buserprivileges
- MysqlFE:: setdbus
erprivileges
- MysqlFE:: userdbp
rivs
- ▼ MysqlOptimizer
 - MysqlOptimizer:: f
etch_slow_queries
- ▼ NVData
 - NVData:: get
 - NVData:: set
 - NVData:: setall
- ▼ Net
 - Net:: dnszone
 - Net:: traceroute
- ▼ News
 - News:: does_news
_exist
 - News:: does_news
_type_exist
 - News:: get_news
- ▼ PHPINI
 - PHPINI:: getallopti
ons
 - PHPINI:: getoption
s
- ▼ Park
 - Park:: listaddondo
mains
 - Park:: listparkeddo
mains
 - Park:: park
 - Park:: unpark
- ▼ Passwd
 - Passwd:: change_
password
 - Passwd:: set_dige
st_auth
- ▼ PasswdStrength
 - PasswdStrength::
appstrengths
 - PasswdStrength::
get_password_stre
ngth
 - PasswdStrength::
get_required_stren
gth
- ▼ Postgres
 - Postgres:: listdbs
 - Postgres:: listusers

```

"commented": 1,
"subsection": "main",
"directive":
"fbsql.default_passwo
rd",
"section":
"FrontBase"
      },
      {
        "info":
"",
        "value":
"-1",
"commented": 1,
"subsection": "main",
"directive":
"fbsql.max_persistent
",
"section":
"FrontBase"
      },
      {
        "info":
"",
        "value":
"Off",
"commented": 1,
"subsection": "main",
"directive":
"fbsql.generate_warni
ngs",
"section":
"FrontBase"
      },
      {
        "info":
"",
        "value":
"",
"commented": 1,

```

```

Postgres:: listusers
indb

Postgres:: userexi
sts

▼ Rand
  Rand:: getranddat
  a

▼ Resellers
  Resellers:: get_su
  b_accounts

▼ RoR
  RoR:: addapp

  RoR:: changeapp

  RoR:: importrails

  RoR:: listapps

  RoR:: listrewrites

  RoR:: needsimport

  RoR:: removeapp

  RoR:: removerewri
  te

  RoR:: restartapp

  RoR:: setuprewrite

  RoR:: softrestartap
  p

  RoR:: startapp

  RoR:: stopapp

▼ SetLang
  SetLang:: setlocale

▼ SourceIPCheck
  SourceIPCheck:: a
  ddip

  SourceIPCheck:: d
  elip

  SourceIPCheck:: g
  etaccount

  SourceIPCheck:: li
  stips

  SourceIPCheck:: l
  oadsecquestions

  SourceIPCheck:: r
  esetsecquestions

  SourceIPCheck:: s
  amplequestions

  SourceIPCheck:: s
  avesecquestions

▼ SPFU
  SPFU:: available

  SPFU:: count_sett
  ings

```

```

"subsection": "main",

"directive":
"fbsql.default_host",

"section":
"FrontBase"
  }
  ],
  "section":
"FrontBase"
  },
  {
    "dirlist": [
      {
        "info":
"Allow or prevent
persistent links.",
        "value":
"On",

"commented": 0,

"subsection": "main",

"directive":
"ifx.allow_persistent
",

"section": "Informix"
  },
  {
    "info":
"Trailing blanks are
stripped from
fixed-length char
columns. May help
the\n life of
Informix SE users.",
    "value":
"0",

"commented": 0,

"subsection": "main",

"directive":
"ifx.charasvarchar",

"section": "Informix"
  },
  {

```

```

SPFUI:: entries_co
mplete
SPFUI:: get_raw_r
ecord
SPFUI:: getmainse
rverip
SPFUI:: install
SPFUI:: installed
SPFUI:: list_settin
gs
SPFUI:: load_curr
ent_values
SPFUI:: uninstall

```

- SSH
 - SSH:: authkey
 - SSH:: converttopp
k
 - SSH:: delkey
 - SSH:: fetchkey
 - SSH:: genkey
 - SSH:: genkey_leg
acy
 - SSH:: importkey
 - SSH:: listkeys
- SSL
 - SSL:: fetchcabundl
e
 - SSL:: fetchinfo
 - SSL:: genctr
 - SSL:: genscr
 - SSL:: genkey
 - SSL:: getcname
 - SSL:: installssl
 - SSL:: listcrts
 - SSL:: listcsrs
 - SSL:: listkeys
 - SSL:: listsslitems
 - SSL:: uploadcrt
 - SSL:: uploadkey
- SSLInfo
 - SSLInfo:: fetchinfo
- StatCache
 - StatCache:: clearc
ache
- Stats
 - Stats:: getmonthly

```

        "info":
"Maximum number of
links (persistent +
non-persistent).  -1
means no limit.",
        "value":
"-1",
"commented": 0,
"subsection": "main",
"directive":
"ifx.max_links",
"section": "Informix"
        },
        {
        "info":
"Default host for
ifx_connect()
(doesn't apply in
safe mode).",
        "value":
"",
"commented": 0,
"subsection": "main",
"directive":
"ifx.default_host",
"section": "Informix"
        },
        {
        "info":
"Default user for
ifx_connect()
(doesn't apply in
safe mode).",
        "value":
"",
"commented": 0,
"subsection": "main",
"directive":
"ifx.default_user",
"section": "Informix"
        },

```

bandwidth

Stats:: getmonthly
domainbandwidth

Stats:: getthismont
hsbwusage

Stats:: lastapache
hits

Stats:: lastvisitors

Stats:: listanalog

Stats:: listawstats

Stats:: listlastvisito
rs

Stats:: listrawlogs

Stats:: listurchin

Stats:: listwealize
r

▼ StatsBar

StatsBar:: getrowc
ounter

StatsBar:: rowcoun
ter

StatsBar:: setrowc
ounter

StatsBar:: stat

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: chan
gedocroot

SubDomain:: delsu
bdomain

SubDomain:: getre
servedsubdomains

SubDomain:: listsu
bdomains

SubDomain:: validr
egex

▼ Themes

Themes:: apply_n
ew_theme

Themes:: does_cp
anel_theme_exist

Themes:: get_avail
able_themes

Themes:: get_the
mes_list

Themes:: restore_
saved_theme

▼ UI

UI:: dynamicinclud
elist

```

    {
      "info":
"NULL's are returned
as empty strings,
unless this is set to
1. In that case,\n
NULL's are returned
as string 'NULL'.",
      "value":
"0",
      "commented": 0,
      "subsection": "main",
      "directive":
"ifx.nullformat",
      "section": "Informix"
    },
    {
      "info":
"If on, select
statements return the
contents of a byte
blob instead of its
id.",
      "value":
"0",
      "commented": 0,
      "subsection": "main",
      "directive":
"ifx.byteasvarchar",
      "section": "Informix"
    },
    {
      "info":
"Maximum number of
persistent links. -1
means no limit.",
      "value":
"-1",
      "commented": 0,
      "subsection": "main",
      "directive":
"ifx.max_persistent",

```

- Ul:: includelist
- Ul:: listform
- Ul:: paginate
- Ul:: paginate_list
- ▼ UserHttpUtils
 - UserHttpUtils:: getdirindices
- ▼ WebDisk
 - WebDisk:: addwebdisk
 - WebDisk:: delwebdisk
 - WebDisk:: hasdigest
 - WebDisk:: listwebdisks
 - WebDisk:: passwordwebdisk
 - WebDisk:: set_digest_auth
 - WebDisk:: set_home_dir
 - WebDisk:: set_permissions
 - WebDisk:: setstatus
- ▼ WebmailApps
 - WebmailApps:: listwebmailapps
- ▼ ZoneEdit
 - ZoneEdit:: add_zone_record
 - ZoneEdit:: edit_zone_record
 - ZoneEdit:: fetch_panel_generated_domains
 - ZoneEdit:: fetchzone
 - ZoneEdit:: fetchzone_records
 - ZoneEdit:: fetchzones
 - ZoneEdit:: get_zone_record
 - ZoneEdit:: remove_zone_record
 - ZoneEdit:: resetzone

```

"section": "Informix"
      },
      {
        "info":
        "If on, the contents
        of text and byte
        blobs are dumped to a
        file instead of\n
        keeping them in
        memory.",
          "value":
          "0",
        "commented": 0,
        "subsection": "main",
        "directive":
        "ifx.blobinfile",
        "section": "Informix"
      },
      {
        "info":
        "Default password for
        ifx_connect()
        (doesn't apply in
        safe mode).",
          "value":
          "",
        "commented": 0,
        "subsection": "main",
        "directive":
        "ifx.default_password",
        "section": "Informix"
      },
      {
        "info":
        "If on, select
        statements return the
        contents of a text
        blob instead of its
        id.",
          "value":
          "0",
        "commented": 0,

```

```
"subsection": "main",

"directive":
"ifx.textasvarchar",

"section": "Informix"
    }
    ],
    "section":
    "Informix"
    },
    {
        "dirlist": [
            {
                "info":
                "Maximum number of
                links, including
                persistents. -1
                means no limit.",
                "value":
                "-1",

                "commented": 0,

                "subsection": "main",

                "directive":
                "ingres.max_links",

                "section": "Ingres
                II"
                },
                {
                    "info":
                    "Maximum number of
                    persistent links. -1
                    means no limit.",
                    "value":
                    "-1",

                    "commented": 0,

                    "subsection": "main",

                    "directive":
                    "ingres.max_persisten
                    t",

                    "section": "Ingres
                    II"
                    },
                    {
```

```
        "info":
"Default user.",
        "value":
"",
"commented": 0,
"subsection": "main",
"directive":
"ingres.default_user"
,
"section": "Ingres
II"
        },
        {
        "info":
"Allow or prevent
persistent links.",
        "value":
"On",
"commented": 0,
"subsection": "main",
"directive":
"ingres.allow_persist
ent",
"section": "Ingres
II"
        },
        {
        "info":
"Default password.",
        "value":
"",
"commented": 0,
"subsection": "main",
"directive":
"ingres.default_passw
ord",
"section": "Ingres
II"
        },
        {
        "info":
```



```
"Default database
(format:
[node_id::]dbname[\/s
rv_class]).",
    "value":
"",
    "commented": 0,
    "subsection": "main",
    "directive":
"ingres.default_datab
ase",
    "section": "Ingres
II"
        }
    ],
    "section":
"Ingres II"
        }
    ],
    "event": {
        "result": 1
    },
    "module":
```

```
"PHPINI"
}
}
```

Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

Parameter	Type	Description	Possible values	Example
php_prefix	string	The PHP installation to query. This parameter defaults to /usr/local/.	<ul style="list-style-type: none"> /usr/local/ /usr/local/php4/ /usr/local/cpanel/3rdparty/ <p>Note : In WHM API calls, replace each forward slash character with %2F.</p>	/usr/local/cpanel/3rdparty/

Returns

Return	Type	Description	Possible values	Example
info	string	Information from the php.ini file about the directive, if it exists.	A valid string.	Enable the PHP scripting language engine under Apache.
value	string	The directive's current option.	A valid string.	On

commented	<i>Boolean</i>	Whether the directive is disabled (commented out) in the <code>php.ini</code> file.	<ul style="list-style-type: none"> • 1 — Commented out. • 0 — Not commented out. 	0
subsection	<i>string</i>	The <code>php.ini</code> file subsection that contains the directive.	A valid string.	Language Options
directive	<i>string</i>	The PHP directive.	A PHP directive that you included in the <code>dirlist</code> input parameter.	engine
section	<i>string</i>	The <code>php.ini</code> file section.	A valid string.	PHP
reason	<i>string</i>	A reason for failure. <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;"> <p>Note : This function only returns a reason value if it failed.</p> </div>	A string that describes the error.	This is an error message.
result	<i>Boolean</i>	Whether the function succeeded.	<ul style="list-style-type: none"> • 1 — The function succeeded. • 0 — The function failed. 	1