

cPanel API 1 Functions - Email::getarshhtml

Guide to cPanel API 1

Return Data

cPanel Tags
(deprecated)

Bandwidth:
display
bandwidth

er

Bandwidth: display
bandwidth

Bandwidth: display
bandwidth

Bandwidth: display
bandwidth

BoxTrapper

BoxTrapper: change
status

BoxTrapper: clean
configfilelist

BoxTrapper: edit
message

BoxTrapper: fetch
configfile

BoxTrapper: get
boxconfdir

BoxTrapper: list
messages

BoxTrapper: log
controls

BoxTrapper: mess
ageaction

BoxTrapper: multi
messageaction

BoxTrapper: reset
message

BoxTrapper: save
configfile

BoxTrapper: save
config

BoxTrapper: show
autowhitelist

BoxTrapper: show
emails

BoxTrapper: show
fromname

BoxTrapper: show

Description

This function returns an autoresponder message's HTML body.

Warning:

cPanel API 1 is **deprecated**. Do not use this function. Instead, we **strongly** recommend that you use the following newer functions:

- **UAPI (recommended)** — `Email::get_auto_responder` — This function retrieves autoresponder information.
- **cPanel API 2** — `Email::fetchautoresponder` — This function retrieves an autoresponder's information.

Examples

LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
$get_autoresponder_ht  
ml =  
$cpanel->api('Email'  
, 'getarshhtml',  
array('user@example.c  
om') ); // Call the  
function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Function information

About this module

The Email module modifies cPanel email account settings.

About cPanel API 1

cPanel API 1 accesses information about cPanel accounts.

log

BoxTrapper:: show message

BoxTrapper:: show queue

BoxTrapper:: show queuesearch

BoxTrapper:: show queuetime

BoxTrapper:: status

BoxTrapper:: statusbutton

▼ Branding

Branding:: file

Branding:: image

Branding:: killing

Branding:: setbrandingpkg

Branding:: setmyacctspkg

Branding:: setupdirs

Branding:: tempsetbrandingpkg

▼ Cgi

Cgi:: backuplink

Cgi:: displayurchin

Cgi:: phpmyadminlink

▼ Chkserverd

Chkserverd:: getxmlport

Chkserverd:: getxmlport_ssl

▼ ClamScanner

ClamScanner:: bars

▼ cPAddons

cPAddons:: mainpage

▼ Cron

Cron:: crontab_perms

▼ CustInfo

CustInfo:: getemail

▼ Denylp

Denylp:: adddenyip

Denylp:: deldenyip

▼ LiveAPI Perl Module

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.
my
$get_autoresponder_html =
$cpliveapi->api('Email', 'getarshtml',
['user@example.com']
); # Call the
function.
```

Note:
For more information, read our [Guide to the LiveAPI System](#).

▼ cPanel Tag System (deprecated)

Warning:
In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We provide this example to help developers move from the old cPanel tag system to our [LiveAPI](#) system. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs.

```
<cpanel
Module="Email::getarshtml( $FORM('email')
)">
```

Warning:
cPanel API deprecated. We **strongly** recommend cPanel API or UAPI instead.

Notes:

- The Fe
- Ur
- m
- u
- 20
- or
- 20
-)
- `
- 20
- or
- 20
-)

Find a function

•

- Denylp:: listdenyips
- DiskUsage:: showmanager
- Email:: addautoresponder
 - Email:: addforward
 - Email:: addfilter
 - Email:: addlist
 - Email:: addmx
 - Email:: addpop
 - Email:: addspam
 - Email:: addspambox
 - Email:: addspamfilter
 - Email:: changemx
 - Email:: checkfastmail
 - Email:: checkpipewd
 - Email:: clearspambox
 - Email:: delautoresponder
 - Email:: delforward
 - Email:: delfilter
 - Email:: dellist
 - Email:: delmx
 - Email:: delpop
 - Email:: delspam
 - Email:: delspambox
 - Email:: disable_spam_autodelete
 - Email:: editquota
 - Email:: enable_spam_autodelete
 - Email:: getaging
 - Email:: getarsbody
 - Email:: getarscharset
 - Email:: getarsfrom
 - Email:: getarshtml

Command Line

```
cpapil
--user=username Email
getarshtml
user@example.com
```

Notes:

- You **must** URI-encode these values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to cPanel API 1](#) documentation or run the `cpapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapil` command:

```
/usr/local
/cpanel/bin/cpapil
```

Output (HTML)

```
This is an
autoresponder
message.<br />
<br />
```

Parameters

Parameter	Type	Description	Possible values	Example
email	string	Required The email address.	A valid email address on the server.	user@example.com

Returns

This function returns the contents of the autoresponder message's HTML body.

- [cPanel API 1 Functions - Email::addlist](#) — This function adds a Mailman mailing list.
- [cPanel API 1 Functions - Email::addspam](#) — This function enables Apache SpamAssassin™ for a cPanel account.

Email:: getarsinter
val

Email:: getarsstart

Email:: getarsstop

Email:: getarssubj
ect

Email:: getmailserv
er

Email:: getmailserv
eruser

Email:: getpopquot
a

Email:: has_spam
_as_acl

Email:: has_spam
_autodelete

Email:: listmaildom
ains

Email:: listmaildom
ainsopt

Email:: listmaildom
ainsoptndef

Email:: mainacctdi
skused

Email:: passwdlist

Email:: passwdpop

Email:: setmxacce
pt

Email:: spamboxst
atus

Email:: spamstatus

Email:: tracefilter

▼ Fileman

Fileman:: changep
erm

Fileman:: delfile

Fileman:: dofileop

Fileman:: emptytra
sh

Fileman:: extractfil
e

Fileman:: fileimg

Fileman:: fmmkdir

Fileman:: fmmkfile

Fileman:: fmpushfil
e

Fileman:: fmrenam
e

Fileman:: fmsavefil

- cPanel API 1 Functions - Email::adspamfilter — This function modifies the minimum Apache SpamAssassin™ spam score.
- cPanel API 1 Functions - Email::checkpipefwd — This function checks whether a pipe or a shebang should precede a script that receives forwarded mail.

e

Fileman:: fmsaveht
mlfile

Fileman:: fullbacku
p

Fileman:: getfile

Fileman:: htmledito
r

Fileman:: killdir

Fileman:: listfiles

Fileman:: listfullba
ckups

Fileman:: listtempl
ates

Fileman:: restoreaf

Fileman:: restored
b

Fileman:: restorefil
e

Fileman:: restorefil
es

Fileman:: savehtml
file

Fileman:: showper
m

Fileman:: uploadfil
es

Fileman:: viewfile

▼ Frontpage

FrontPage:: addfp

FrontPage:: delfp

FrontPage:: fpstat
us

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: ftpquota

Ftp:: ftpservernam
e

Ftp:: ftpstatslogin

Ftp:: get_anonftp

Ftp:: get_anonftpin

Ftp:: get_welcome
msg

Ftp:: getftpquota

Ftp:: kill_ftp_sessi
on

Ftp:: listftpstatsurl

Ftp:: passwdftp

Ftp:: set_anonftp

Ftp:: set_anonftpin

Ftp:: set_welcome
msg

▼ Gpg

Gpg:: deletekey

Gpg:: exportkey

Gpg:: exportsecret
key

Gpg:: genkey

Gpg:: importkeys

▼ Htaccess

Htaccess:: checkpr
otected

Htaccess:: del_use
r

Htaccess:: getinde
x

Htaccess:: htdirls

Htaccess:: number
_of_users

Htaccess:: phpsele
ctable

Htaccess:: resnam
e

Htaccess:: set_pas
s

Htaccess:: set_pro
tect

Htaccess:: setinde
x

Htaccess:: setphpr
eference

Htaccess:: showus
ers

▼ ImageManager

ImageManager:: c
onvert

ImageManager:: di
mensions

ImageManager:: h
dimension

ImageManager:: s
cale

ImageManager:: th
umbnail

ImageManager:: w
dimension

▼ LastLogin

LastLogin:: lastlogi
n

▼ LeechProtect

LeechProtect:: dis
able

LeechProtect:: ena
ble

LeechProtect:: set
up

LeechProtect:: sho
wpasswdfile

LeechProtect:: stat
us

▼ LogManager

LogManager:: listd
ownloads

LogManager:: sav
esettings

LogManager:: sho
wsettings

▼ MagicRevision

MagicRevision:: uri

▼ Mime

Mime:: add_handl
er

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redire
ct

Mime:: del_handler

Mime:: del_hotlink

Mime:: del_mime

Mime:: del_redirect

Mime:: linkallownul
l

Mime:: linkenable

Mime:: linkexts

Mime:: linkrurl

Mime:: linkurIs

▼ Mysql

Mysql:: adddb

Mysql:: addhost

Mysql:: adduser

Mysql:: adduserdb

Mysql:: checkdb

Mysql:: deldb

Mysql:: delhost

Mysql:: deluser

Mysql:: deluserdb

Mysql:: gethost

Mysql:: initcache

Mysql:: listdbs

Mysql:: listdbsopt

Mysql:: listusers

Mysql:: listusersopt

Mysql:: number_of
_dbs

Mysql:: number_of
_users

Mysql:: repairdb

Mysql:: routines

Mysql:: updatepriv
s

▼ Net

Net:: dnslookup

Net:: dnszone

Net:: sethastracero
ute

▼ News

News:: displaynew
s

▼ NVData

NVData:: set

▼ OptimizeWS

OptimizeWS:: load
optimizesettings

OptimizeWS:: load
optimizesettings (b
ytes)

OptimizeWS:: opti
mizews

▼ Park

Park:: disabledir
ect

Park:: getredirectu
rl

Park:: park

Park:: setredirectur
l

Park:: unpark

▼ Postgres

Postgres:: adddb

Postgres:: adduser

Postgres:: adduser
db

Postgres:: deldb

Postgres:: deluser

Postgres:: deluser
db

Postgres:: initcach
e

Postgres:: listdbso
pt

Postgres:: listusers
opt

Postgres:: number
_of_dbs

Postgres:: number
_of_users

▼ ProxyUtils

ProxyUtils:: proxya
ddress

▼ Resellers

Resellers:: accoun
tlistopt

Resellers:: themeli
stopt

▼ Serverinfo

Serverinfo:: servic
estatus

▼ SetLang

SetLang:: listlangs
opt

SetLang:: setlang

▼ SpamAssassin

SpamAssassin:: co
nfig

SpamAssassin:: sa
veconfig

▼ SSH

SSH:: getport

▼ SSL

SSL:: delete

SSL:: deletecrt

SSL:: deletecsr

SSL:: deletekey

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcabundle

SSL:: getcnname

SSL:: install

SSL:: installedhost

SSL:: listkeysopt

SSL:: showcrt

SSL:: showcsr

SSL:: showkey

SSL:: sslsharedsta
tus

SSL:: uploadcrt

SSL:: uploadkey

▼ StatManager

StatManager:: doF
orm

StatManager:: upd
ateUserConfig

▼ Stats

Stats:: analoglist

Stats:: awstats

Stats:: bwbar

Stats:: errlog

Stats:: lastvisitors

Stats:: showbandw
idth

Stats:: webalizer

Stats:: webalizerftp

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: cplist
subdomains

SubDomain:: disab
lesubrd

SubDomain:: listsu
bdomainsop

SubDomain:: setsu
burl

▼ UI

UI:: confirm

UI:: redirect

UI:: showresult