

cPanel API 1 Functions - BoxTrapper::showqueue

Guide to cPanel API 1

Return Data

cPanel Tags
(deprecated)

Bandwidth:
displayheader

Bandwidth:
displaybw

Bandwidth:
displayday

Bandwidth:
displaymainbwheder

▼ BoxTrapper

BoxTrapper::chan
gestatus

BoxTrapper::clean
cfgfilelist

BoxTrapper::edit
msg

BoxTrapper::fetch
cfgfile

BoxTrapper::getb
oxconfdir

BoxTrapper::listm
sgs

BoxTrapper::logco
ntrols

BoxTrapper::mess
ageaction

BoxTrapper::multi
messageaction

BoxTrapper::reset
msg

BoxTrapper::save
cfgfile

BoxTrapper::save
conf

BoxTrapper::show
autowhitelist

BoxTrapper::show
emails

BoxTrapper::show
fromname

BoxTrapper::show
log

Description

This function generates a list of messages in the BoxTrapper queue.

Warning:

cPanel API 1 is **deprecated**. We **strongly** recommend that you **do not use** cPanel API 1. However, no equivalent function exists in our newer APIs.

Important:

In cPanel & WHM version 76 and later, when you disable the MailReceiver role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
$list_boxtrapper_queu  
e =  
$cpanel->apil('BoxTra  
pper', 'showqueue',  
array('1410277881',  
'user@example.com',  
'showmsg.html', '',  
'0') ); // Call the  
function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Func tion infor mati on

About this mod ule

The Box
Trapper
module
manages
the
BoxTrapp
er
subsystem.

Note:

This modul
BoxTrappe
feature.

```
BoxTrapper:: show
message

BoxTrapper:: show
queue

BoxTrapper:: show
queuesearch

BoxTrapper:: show
queuetime

BoxTrapper:: statu
s

BoxTrapper:: statu
sbutton
```

Branding

```
Branding:: file

Branding:: image

Branding:: killing

Branding:: setbran
dingpkg

Branding:: setmya
cctspkg

Branding:: setupdir
s

Branding:: tempset
brandingpkg
```

Cgi

```
Cgi:: backuplink

Cgi:: displayurchin

Cgi:: phpmyadminl
ink
```

Chkserverd

```
Chkserverd:: getexi
mport

Chkserverd:: getexi
mport_ssl
```

ClamScanner

```
ClamScanner:: bar
s
```

cPAddons

```
cPAddons:: mainp
g
```

Cron

```
Cron:: crontab_per
ms
```

CustInfo

```
CustInfo:: getemail
```

Denylp

```
Denylp:: adddenyi
p

Denylp:: deldenyip

Denylp:: listdenyi
ps
```

LiveAPI Perl Module

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.
my
$list_boxtrapper_queu
e =
$cpliveapi->apil('Box
Trapper',
'showqueue',
['1410277881',
'user@example.com',
'showmsg.html', '',
'0'] ); # Call the
function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

cPanel Tag System (deprecated)

Warning:

In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We provide this example to help developers move from the old cPanel tag system to our [LiveAPI](#) system. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs.

```
<cpanel
Module="BoxTrapper::s
howqueue(
$FORM('logdate','acco
unt','showfile','bxac
tion','skipcontrols')
)">
```

About cPanel API 1

cPanel API 1 accesses information about cPanel accounts.

Warning: cPanel API 1 is deprecated. We **strongly** recommend you use cPanel API 2 or the LiveAPI instead.

Notes:

- The `int` return value is `200` or `201` or `202` or `203`.

Find a function

▼ DiskUsage

DiskUsage:: show manager

▼ Email

Email:: addautoresponder

Email:: addforward

Email:: addfilter

Email:: addlist

Email:: addmx

Email:: addpop

Email:: addspam

Email:: addspambox

Email:: addspamfilter

Email:: changemx

Email:: checkfastmail

Email:: checkpipewd

Email:: clearspambox

Email:: delautoresponder

Email:: delforward

Email:: delfilter

Email:: dellist

Email:: delmx

Email:: delpop

Email:: delspam

Email:: delspambox

Email:: disable_spam_autodelete

Email:: editquota

Email:: enable_spam_autodelete

Email:: getaging

Email:: getarsbody

Email:: getarscharset

Email:: getarsfrom

Email:: getarshtml

Email:: getarsinterval

▼ Command Line

```
cpapil
--user=username
BoxTrapper showqueue
1410277881
user@example.com
showmsg.html ' ' 0
```

Notes:

- You **must** URI-encode these values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to cPanel API 1 documentation](#) or run the `cpapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapil` command:

```
/usr/local
/cpanel/bin/cpapil
```

▼ Output (HTML)

```
<input type="hidden"
name="account"
value="test@example.com">
<input type="hidden"
name="baction"
value="multimsgaction">
<tr class="tdshadel">
<td width="5%"><input
type="checkbox"
name="msgid0"
value="qM3nKcgdNWKJQoJmzYxHtUfCHJYMMLki.msg"></td>
<td class="truncate"
truncate="25"
width="15%"><a
href="showmsg.html?account=test@example.com&q=qM3nKcgdNWKJQoJmzYxHtUfCHJYMMLki.msg&b
```

— This function enables Apache SpamAssassin™ for a cPanel account.

- [cPanel API 1 Functions - Email::addspamfilter](#) — This function modifies the minimum Apache SpamAssassin™ spam score.

Email: getarsstart
 Email: getarsstop
 Email: getarssubject
 Email: getmailserver
 Email: getmailserveruser
 Email: getpopquota
 Email: has_spam_as_acl
 Email: has_spam_autodelete
 Email: listmaildomains
 Email: listmaildomainsopt
 Email: listmaildomainsoptndef
 Email: mainacctdiskused
 Email: passwdlist
 Email: passwdpop
 Email: setmxaccept
 Email: spamboxstatus
 Email: spamstatus
 Email: tracefilter

▼ Fileman

Fileman: changeperm
 Fileman: delfile
 Fileman: dofileop
 Fileman: emptytrash
 Fileman: extractfile
 Fileman: fileimg
 Fileman: fmmkdir
 Fileman: fmmfile
 Fileman: fmpushfile
 Fileman: fmrename
 Fileman: fmsavefile
 Fileman: fmsaveht

```
xaction=">test@cpanel
.net</a></td>
<td class="truncate"
truncate="75"><a
href="showmsg.html?ac
count=test@example.co
m&q=qM3nKcgdNWKJQoJmz
YxHtUfCHJYMMLki.msg&b
xaction=">Subject</a>
</td>
<td width="15%"><a
href="showmsg.html?ac
count=test@example.co
m&q=qM3nKcgdNWKJQoJmz
YxHtUfCHJYMMLki.msg&b
xaction=">02/19
20:40:05</a></td>
</tr>
<tr class="tdshade2">
<td width="5%"><input
type="checkbox"
name="msgid1"
value="TnOFsIHUb3EX19
Wcqlc1DwAEqwSxaIUL.ms
g"></td>
<td class="truncate"
truncate="25"
width="15%"><a
href="showmsg.html?ac
count=test@example.co
m&q=TnOFsIHUb3EX19Wcq
lc1DwAEqwSxaIUL.msg&b
xaction=">test@cpanel
.net</a></td>
<td class="truncate"
truncate="75"><a
href="showmsg.html?ac
count=test@example.co
m&q=TnOFsIHUb3EX19Wcq
lc1DwAEqwSxaIUL.msg&b
xaction=">Subject</a>
</td>
<td width="15%"><a
href="showmsg.html?ac
count=test@example.co
m&q=TnOFsIHUb3EX19Wcq
lc1DwAEqwSxaIUL.msg&b
```

- cPanel API 1 Functions - Email::spamboxstatus — This function checks whether Apache SpamAssassin™ Spam Box is enabled.
- cPanel API 1 Functions - SpamAssassin::config — This function prints the cPanel account's Apache SpamAssassin's™ default value.

mfile
 Fileman:: fullbacku
 p
 Fileman:: getfile
 Fileman:: htmledito
 r
 Fileman:: killdir
 Fileman:: listfiles
 Fileman:: listfullba
 ckups
 Fileman:: listtempl
 ates
 Fileman:: restoreaf
 Fileman:: restored
 b
 Fileman:: restorefil
 e
 Fileman:: restorefil
 es
 Fileman:: savehtml
 file
 Fileman:: showper
 m
 Fileman:: uploadfil
 es
 Fileman:: viewfile
Frontpage
 FrontPage:: addfp
 FrontPage:: delfp
 FrontPage:: fpstat
 us
Ftp
 Ftp:: addftp
 Ftp:: delftp
 Ftp:: ftpquota
 Ftp:: ftpservernam
 e
 Ftp:: ftpstatslogin
 Ftp:: get_anonftp
 Ftp:: get_anonftp
 pin
 Ftp:: get_welcome
 msg
 Ftp:: getftpquota
 Ftp:: kill_ftp_sessi
 on
 Ftp:: listftpstatsurl
 Ftp:: passwdftp

```

xaction=">02/19
20:40:14</a></td>
</tr>
  
```

- cPanel API 1 Modules - SpamAssassin — The SpamAssassin module modifies Apache SpamAssassin™ settings.

Parameters

Parameter	Type	Description	Possible values	Example
logdate	string	<p>The date to view.</p> <p>This parameter defaults to the current time.</p>	Any valid time, in Unix time format.	1410277881
account	string	<p>Required</p> <p>The account's email address.</p>	A valid email address on the server.	user@example.com
showfile	string	<p>Required</p> <p>The file to process requests to view emails.</p>	showmsg.html <div style="border: 1px solid red; padding: 5px; margin-top: 10px;"> <p>Warning :</p> <p>If you specify another file, the HTML output may contain broken links.</p> </div>	showmsg.html
bxaction	string	<p>Required</p> <p>The system does not use this parameter, and will ignore the value.</p>	A placeholder value.	' '
skipcontrols	Boolean	<p>Required</p> <p>Whether the function skips multi-message functions when it prints.</p>	<ul style="list-style-type: none"> • 0 — Print multi-message functions. • 1 — Skip multi-message functions. 	0

Ftp:: set_anonftp

Ftp:: set_anonftpin

Ftp:: set_welcome
msg

▼ Gpg

Gpg:: deletekey

Gpg:: exportkey

Gpg:: exportsecret
key

Gpg:: genkey

Gpg:: importkeys

▼ Htaccess

Htaccess:: checkpr
otected

Htaccess:: del_use
r

Htaccess:: getinde
x

Htaccess:: htdirls

Htaccess:: number
_of_users

Htaccess:: phpsele
ctable

Htaccess:: resnam
e

Htaccess:: set_pas
s

Htaccess:: set_pro
tect

Htaccess:: setinde
x

Htaccess:: setphpr
eference

Htaccess:: showus
ers

▼ ImageManager

ImageManager:: c
onvert

ImageManager:: di
mensions

ImageManager:: h
dimension

ImageManager:: s
cale

ImageManager:: th
umbnail

ImageManager:: w
dimension

▼ LastLogin

LastLogin:: lastlogi
n

Returns

This function returns HTML to generate a table that lists the account's queued messages.

- The table sorts messages by date.
- The table contains a checkbox, the message's sender, the message subject, and the date for each message.

▼ LeechProtect

LeechProtect:: disable

LeechProtect:: enable

LeechProtect:: setup

LeechProtect:: showpasswdfile

LeechProtect:: status

▼ LogManager

LogManager:: listdownloads

LogManager:: save settings

LogManager:: show settings

▼ MagicRevision

MagicRevision:: uri

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: del_handler

Mime:: del_hotlink

Mime:: del_mime

Mime:: del_redirect

Mime:: linkallownull

Mime:: linkenable

Mime:: linkexts

Mime:: linkrurl

Mime:: linkurls

▼ Mysql

Mysql:: adddb

Mysql:: addhost

Mysql:: adduser

Mysql:: adduserdb

Mysql:: checkdb

Mysql:: deldb

Mysql:: delhost

Mysql:: deluser

Mysql:: deluserdb

Mysql:: gethost
Mysql:: initcache
Mysql:: listdbs
Mysql:: listdbsopt
Mysql:: listusers
Mysql:: listusersopt
Mysql:: number_of
_dbs
Mysql:: number_of
_users
Mysql:: repairdb
Mysql:: routines
Mysql:: updatepriv
s

▼ Net

Net:: dnslookup
Net:: dnszone
Net:: sethastracero
ute

▼ News

News:: displaynew
s

▼ NVData

NVData:: set

▼ OptimizeWS

OptimizeWS:: load
optimizesettings
OptimizeWS:: load
optimizesettings (b
ytes)
OptimizeWS:: opti
mizews

▼ Park

Park:: disabledir
ect
Park:: getredirectu
rl
Park:: park
Park:: setredirectur
l
Park:: unpark

▼ Postgres

Postgres:: adddb
Postgres:: adduser
Postgres:: adduser
db
Postgres:: deldb
Postgres:: deluser

Postgres:: deluser
db

Postgres:: initcach
e

Postgres:: listdbso
pt

Postgres:: listusers
opt

Postgres:: number
_of_dbs

Postgres:: number
_of_users

▼ ProxyUtils

ProxyUtils:: proxya
ddress

▼ Resellers

Resellers:: accoun
tlistopt

Resellers:: themeli
stopt

▼ Serverinfo

Serverinfo:: servic
estatus

▼ SetLang

SetLang:: listlangs
opt

SetLang:: setlang

▼ SpamAssassin

SpamAssassin:: co
nfig

SpamAssassin:: sa
veconfig

▼ SSH

SSH:: getport

▼ SSL

SSL:: delete

SSL:: deletectr

SSL:: deletecsr

SSL:: deletekey

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcabundle

SSL:: getcname

SSL:: install

SSL:: installedhost

SSL:: listkeysopt

SSL:: showcrt

SSL:: showcsr

SSL:: showkey

SSL:: sslsharedsta
tus

SSL:: uploadcrt

SSL:: uploadkey

▼ StatManager

StatManager:: doF
orm

StatManager:: upd
ateUserConfig

▼ Stats

Stats:: analoglist

Stats:: awstats

Stats:: bwbar

Stats:: errlog

Stats:: lastvisitors

Stats:: showbandw
idth

Stats:: webalizer

Stats:: webalizerftp

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: cplist
subdomains

SubDomain:: disab
lesubrd

SubDomain:: listsu
bdomainsop

SubDomain:: setsu
burl

▼ UI

UI:: confirm

UI:: redirect

UI:: showresult