

UAPI Functions - Email::set_always_accept

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Description

This function sets the Mail Exchanger (MX) type.

Note:

This function **only** affects the cPanel configuration. You **must** configure the mail exchanger's DNS entry separately.

Important:

In cPanel & WHM version 76 and later, when you disable the DNS role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/Email/set_always_accept?domain=example.com&mxcheck=auto&alwaysaccept=1
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

Function information

About this module

The Email module modifies cPanel email account settings.

About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Backup
 - Backup::fullbackup
 - p_to_ftp
 - Backup::fullbackup_to_homedir
 - Backup::fullbackup_to_scp_with_key
 - Backup::fullbackup_to_scp_with_password
 - Backup::list_backups
- ▼ Bandwidth
 - Bandwidth::get_enabled_protocols
 - Bandwidth::get_retention_periods
 - Bandwidth::query
- ▼ Batch
 - Batch::strict
- ▼ Brand
 - Brand::read
- ▼ Branding
 - Branding::file
 - Branding::get_applications
 - Branding::get_application_information
 - Branding::get_available_applications
 - Branding::get_information_for_applications

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster
 - CacheBuster:: read
 - CacheBuster:: update
- Chkserverd
 - Chkserverd:: get_exim_ports
 - Chkserverd:: get_exim_ports_ssl
- Chrome
 - Chrome:: get_domain
- Contactus
 - Contactus:: is_enabled
- cPAddons
 - cPAddons:: get_available_addons
 - cPAddons:: get_instance_settings
 - cPAddons:: list_addon_instances
- cPGreyList
 - cPGreyList:: disable_all_domains
 - cPGreyList:: disable_domains
 - cPGreyList:: enable_all_domains
 - cPGreyList:: enable_domains
 - cPGreyList:: has_greylisting_enabled
 - cPGreyList:: list_domains
- DAV
 - DAV:: disable_shared_global_addressbook
 - DAV:: enable_shared_global_addressbook
 - DAV:: get_calendar_contacts_config
 - DAV:: has_shared_global_addressbook
 - DAV:: is_dav_service_enabled

LiveAPI PHP Class

```

$cpanel = new
CPANEL(); // Connect
to cPanel - only do
this once.

// Set example.com's
mail exchanger type.
$set_mx_type =
$cpanel->uapi(
    'Email',
    'set_always_accept',
    array(
        'domain'
=> 'example.com',
        'mxcheck'
=> 'auto',

    'alwaysaccept' =>
    '1',
    )
);

```

Note:
For more information, read our [Guide to the LiveAPI System](#).

Notes:

- The *Fe*
- Ur
mu
us
20
or
20
)
'
20
or
20
)

Find a function

The Mail boxes module manages email messages.

- UAPI Functions - Email::edit_pop_quota — This function changes an email address's quota.

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

Email:: add_spam_filter

▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
  
# Set example.com's  
mail exchanger type.  
my $set_mx_type =  
$cpliveapi->uapi(  
  'Email',  
  'set_always_accept',  
  {  
    'domain'  
=> 'example.com',  
    'mxcheck'  
=> 'auto',  
  
    'alwaysaccept' =>  
    '1',  
  }  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

• UAPI Functions - SpamAssassin::get_user_preferences

This function lists the Apache SpamAssassin™ settings for the account.

• UAPI Functions - SpamAssassin::clear_spam_box

This function clears the spam box of all its contents for all email accounts.

Email: browse_mailbox
Email: change_mx
Email: check_fast_mail
Email: check_pipe_forwarder
Email: delete_auto_responder
Email: delete_domain_forwarder
Email: delete_filter
Email: delete_forwarder
Email: delete_held_messages
Email: delete_list
Email: delete_mx
Email: delete_pop
Email: disable_filter
Email: disable_mailbox_autocreate
Email: disable_spam_assassin
Email: disable_spam_autodelete
Email: disable_spam_box
Email: dispatch_client_settings
Email: edit_pop_quota
Email: enable_filter
Email: enable_mailbox_autocreate
Email: enable_spam_assassin
Email: enable_spam_box
Email: fetch_charmaps
Email: fts_rescan_mailbox
Email: generate_mailman_otp
Email: get_auto_responder
Email: get_chase

▼ cPanel Template Toolkit

```
<!-- Set example.com's mail exchanger type, then display the changed values. -->
[% data = execute(
  'Email',
  'set_always_accept',
  { 'domain' =>
    'example.com',
    'mxcheck' => 'auto',
    'alwaysaccept' => '1'
  } ); %]
[% FOREACH q =
  data.checkmx.changed
  %]
  <p>
    [% q %]
  </p>
[% END %]

<!-- Get only the changed values. -->
[% execute('Email',
  'set_always_accept',
  { 'domain' =>
    'example.com',
    'mxcheck' => 'auto',
    'alwaysaccept' => '1'
  }
).data.checkmx.changed
%]
```

Note:

For more information, read our [Guide to Template Toolkit](#) documentation.

- UAPI Functions - SpamAssassin::update_user_preference — This function sets the Apache SpamAssassin™ settings for the account.

ts

Email: get_client_settings

Email: get_default_email_quota

Email: get_default_email_quota_mib

Email: get_disk_usage

Email: get_filter

Email: get_held_message_count

Email: get_mailbox_autocreate

Email: get_mailman_delegates

Email: get_main_account_disk_usage

Email: get_main_account_disk_usage_bytes

Email: get_max_email_quota

Email: get_max_email_quota_mib

Email: get_pop_quota

Email: get_spam_settings

Email: get_webmail_settings

Email: has_delegated_mailman_lists

Email: has_plaint_authentication

Email: hold_outgoing

Email: is_integer

Email: list_autoresponders

Email: list_default_address

Email: list_domain_forwarders

Email: list_filters

Email: list_filters_backups

Email: list_forwarders

Email: list_forward

Command Line

```
uapi --user=username  
Email  
set_always_accept  
domain=example.com  
mxcheck=auto  
alwaysaccept=1
```

Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local  
/cpanel/bin/uapi
```

ers_backups

Email:: list_lists

Email:: list_mail_domains

Email:: list_mx

Email:: list_pops

Email:: list_pops_with_disk

Email:: list_system_filter_info

Email:: passwd_list

Email:: passwd_pop

Email:: release_outgoing

Email:: remove_mailman_delegates

Email:: reorder_filters

Email:: set_always_accept

Email:: set_default_address

Email:: set_list_privacy_options

Email:: stats_db_status

Email:: store_filter

Email:: suspend_incoming

Email:: suspend_login

Email:: suspend_outgoing

Email:: trace_filter

Email:: unsuspend_incoming

Email:: unsuspend_login

Email:: unsuspend_outgoing

Email:: verify_password

▼ EmailAuth

EmailAuth:: disable_dkim

EmailAuth:: enable_dkim

EmailAuth:: ensure_dkim_keys_exist

▼ Output (JSON)

```
{
  "messages":null,
  "errors":null,
  "status":1,
  "metadata":{
  },
  "data":{
    "statusmsg":"Set
Always Accept Status
to: auto",
    "checkmx":{
      "warnings":[
      ],
      "issecondary":0,
      "local":0,
      "remote":0,
      "detected":"local",
      "isprimary":1,
      "changed":0,
      "mxcheck":"auto",
      "secondary":0
    },
    "status":1,
    "local":0,
    "detected":"local",
    "remote":0,
    "mxcheck":"auto",
    "secondary":0,
    "results":"Set
Always Accept Status
to: auto"
  }
}
```

Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

EmailAuth:: fetch_ dkim_private_keys

EmailAuth:: install_ dkim_private_keys

EmailAuth:: install_ spf_records

EmailAuth:: validate_ current_dkims

EmailAuth:: validate_ current_ptrs

EmailAuth:: validate_ current_spfs

ExternalAuthentication

ExternalAuthentication:: add_authn_link

ExternalAuthentication:: configured_modules

ExternalAuthentication:: get_authn_links

ExternalAuthentication:: has_external_auth_modules_configured

ExternalAuthentication:: remove_authn_link

Features

Features:: get_feature_metadata

Features:: has_feature

Features:: list_features

Fileman

Fileman:: autocompletedir

Fileman:: empty_trash

Fileman:: get_file_content

Fileman:: get_file_information

Fileman:: list_files

Fileman:: save_file_content

Fileman:: transcoding

Fileman:: upload_files

Parameters

Parameter	Type	Description	Possible values	Example
domain	string	Required The mail exchanger's domain.	A valid domain on the cPanel account.	example.com
mxcheck	string	The mail exchanger type. This parameter defaults to auto.	<ul style="list-style-type: none">auto — Allow cPanel to determine the appropriate role.local — Always accept the domain's mail.secondary — Accept mail until a higher priority mail server is available.remote — Do not accept mail.	auto
alwaysaccept	Boolean	Whether the mail exchanger always accepts mail for the domain. This parameter defaults to 1.	<ul style="list-style-type: none">1 — Always accepts mail.0 — Does not always accept mail.	1

Returns

Return	Type	Description	Possible values	Example
statusmsg	string	A message of success or a reason for failure.	<ul style="list-style-type: none">A message of success that includes the new type.A string that describes an error.	Set Always Accept Status to: local
checkmx	hash	A hash of the mail exchanger's data.	This hash includes the warnings, issecondary, local, detected, remote, isprimary, changed, secondary, and mxcheck returns.	

- ▼ **Ftp**
 - Ftp:: [add_ftp](#)
 - Ftp:: [allows_anonymous_ftp](#)
 - Ftp:: [allows_anonymous_ftp_incoming](#)
 - Ftp:: [delete_ftp](#)
 - Ftp:: [ftp_exists](#)
 - Ftp:: [get_ftp_daemon_info](#)
 - Ftp:: [get_port](#)
 - Ftp:: [get_quota](#)
 - Ftp:: [get_welcome_message](#)
 - Ftp:: [kill_session](#)
 - Ftp:: [list_ftp](#)
 - Ftp:: [list_ftp_with_disk](#)
 - Ftp:: [list_sessions](#)
 - Ftp:: [passwd](#)
 - Ftp:: [server_name](#)
 - Ftp:: [set_anonymous_ftp](#)
 - Ftp:: [set_anonymous_ftp_incoming](#)
 - Ftp:: [set_homedir](#)
 - Ftp:: [set_quota](#)
 - Ftp:: [set_welcome_message](#)
- ▼ **Integration**
 - Integration:: [fetch_url](#)
- ▼ **KnownHosts**
 - KnownHosts:: [create](#)
 - KnownHosts:: [delete](#)
 - KnownHosts:: [update](#)
 - KnownHosts:: [verify](#)
- ▼ **LangPHP**
 - LangPHP:: [php_get_domain_handler](#)
 - LangPHP:: [php_get_impacted_domains](#)
 - LangPHP:: [php_get_installed_version](#)

warnings	<i>array</i>	<p>An array of warning messages, if any exist.</p> <p>The function returns this value in the checkmx hash.</p>	One or more warning messages.	<ul style="list-style-type: none"> ▼ Click to view... Auto Detect of MX configuration not possible due to non-resolving MX entries. Defaulting to last known setting: local.
issecondary	<i>Boolean</i>	<p>Whether the mail exchanger is a secondary exchanger.</p> <p>The function returns this value in the checkmx hash.</p>	<ul style="list-style-type: none"> • 1 — Secondary. • 0 — Not secondary. 	0
local	<i>Boolean</i>	<p>Whether the mail exchanger is a local exchanger.</p> <p>The function returns this value in the checkmx hash.</p>	<ul style="list-style-type: none"> • 1 — Local. • 0 — Not local. 	0
detected	<i>string</i>	<p>The mail exchanger type.</p> <p>The function returns this value in the checkmx hash.</p>	<ul style="list-style-type: none"> • auto • local • secondary • remote 	auto
remote	<i>Boolean</i>	<p>Whether the mail exchanger is a remote exchanger.</p> <p>The function returns this value in the checkmx hash.</p>	<ul style="list-style-type: none"> • 1 — Remote. • 0 — Not remote. 	0
isprimary	<i>Boolean</i>	<p>Whether the mail exchanger is the primary mail exchanger.</p> <p>The function returns this value in the checkmx hash.</p>	<ul style="list-style-type: none"> • 1 — Primary. • 0 — Not primary. 	0
changed	<i>Boolean</i>	<p>Whether a change occurred during the function.</p> <p>The function returns this value in the checkmx hash.</p>	<ul style="list-style-type: none"> • 1 — Change occurred. • 0 — No change. 	1

S

LangPHP:: [php_get_system_default_version](#)

LangPHP:: [php_get_vhost_versions](#)

LangPHP:: [php_ini_get_user_basic_directives](#)

LangPHP:: [php_ini_get_user_content](#)

LangPHP:: [php_ini_get_user_paths](#)

LangPHP:: [php_ini_set_user_basic_directives](#)

LangPHP:: [php_ini_set_user_content](#)

LangPHP:: [php_set_vhost_versions](#)

▼ [LastLogin](#)

LastLogin:: [get_last_or_current_logged_in_ip](#)

▼ [Locale](#)

Locale:: [get_attributes](#)

▼ [Mailboxes](#)

Mailboxes:: [expunge_mailbox_messages](#)

Mailboxes:: [expunge_messages_for_mailbox_guid](#)

Mailboxes:: [get_mailbox_status](#)

Mailboxes:: [has_utf8_mailbox_names](#)

Mailboxes:: [set_utf8_mailbox_names](#)

▼ [Market](#)

Market:: [cancel_pending_ssl_certificate](#)

Market:: [create_shopping_cart](#)

Market:: [get_all_products](#)

Market:: [get_certificate_status_details](#)

Market:: [get_login_url](#)

Market:: [get_pending_ssl_certificates](#)

secondary	<i>Boolean</i>	Whether the mail exchanger is a secondary exchanger. The function returns this value in the checkmx hash.	<ul style="list-style-type: none"> 1 — Secondary. 0 — Not secondary. 	0
mxcheck	<i>string</i>	The mail exchanger type. The function returns this value in the checkmx hash.	<ul style="list-style-type: none"> auto local secondary remote 	auto
status	<i>Boolean</i>	Whether the function succeeded.	<ul style="list-style-type: none"> 1 — Success. 0 — Failure. 	1
local	<i>Boolean</i>	Whether the mail exchanger is a local exchanger.	<ul style="list-style-type: none"> 1 — Local. 0 — Not local. 	0
remote	<i>Boolean</i>	Whether the mail exchanger is a remote exchanger.	<ul style="list-style-type: none"> 1 — Remote. 0 — Not remote. 	0
detected	<i>string</i>	The mail exchanger type.	<ul style="list-style-type: none"> auto local secondary remote 	auto
mxcheck	<i>string</i>	The mail exchanger type.	<ul style="list-style-type: none"> auto local secondary remote 	auto
secondary	<i>Boolean</i>	Whether the mail exchanger is a secondary exchanger.	<ul style="list-style-type: none"> 1 — Secondary. 0 — Not secondary. 	0
results	<i>string</i>	A message of success or a reason for failure.	<ul style="list-style-type: none"> A message of success that includes the new type. A string that describes an error. 	Set Always Accept Status to: local

Market:: get_provider_specific_dcv_constraints

Market:: get_providers_list

Market:: get_ssl_certificate_if_available

Market:: process_ssl_pending_queue

Market:: request_ssl_certificates

Market:: set_status_of_pending_queue_items

Market:: set_url_after_checkout

Market:: validate_login_token

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: delete_handler

Mime:: delete_hotlink

Mime:: delete_mime

Mime:: delete_redirect

Mime:: list_handlers

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirects

Mime:: redirect_info

▼ ModSecurity

ModSecurity:: disable_all_domains

ModSecurity:: disable_domains

ModSecurity:: enable_all_domains

ModSecurity:: enable_domains

ModSecurity:: has
_modsecurity_inst
alled

ModSecurity:: list_
domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_
note

Mysql :: check_dat
abase

Mysql:: create_dat
abase

Mysql:: create_use
r

Mysql:: delete_dat
abase

Mysql:: delete_hos
t

Mysql:: delete_use
r

Mysql:: get_host_n
otes

Mysql:: get_privile
ges_on_database

Mysql:: get_restrict
ions

Mysql:: get_server
_information

Mysql:: locate_ser
ver

Mysql:: rename_d
atabase

Mysql:: rename_us
er

Mysql:: repair_dat
abase

Mysql:: revoke_ac
cess_to_database

Mysql:: set_passw
ord

Mysql:: set_privile
ges_on_database

▼ Notifications

Notifications:: get_
notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_rel
ative_uri

- ▼ PassengerApps
 - PassengerApps:: disable_application
 - PassengerApps:: edit_application
 - PassengerApps:: enable_application
 - PassengerApps:: ensure_deps
 - PassengerApps:: list_applications
 - PassengerApps:: register_application
 - PassengerApps:: unregister_application
- ▼ PasswdStrength
 - PasswdStrength:: get_required_strength
- ▼ Personalization
 - Personalization::set
 - Personalization::get
- ▼ Postgresql
 - Postgresql:: create_database
 - Postgresql:: create_user
 - Postgresql:: delete_database
 - Postgresql:: get_restrictions
 - Postgresql:: grant_all_privileges
 - Postgresql:: rename_database
 - Postgresql:: rename_user
 - Postgresql:: rename_user_no_password
 - Postgresql:: revoke_all_privileges
 - Postgresql:: set_password
- ▼ Pushbullet
 - Pushbullet:: send_test_message
- ▼ Quota
 - Quota:: get_quota_info

- ▼ Resellers
 - Resellers:: list_accounts
- ▼ ResourceUsage
 - ResourceUsage:: get_usages
- ▼ Restore
 - Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- ▼ Session
 - Session:: create_temp_user
- ▼ SiteTemplates
 - SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- ▼ SpamAssassin
 - SpamAssassin :: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key
 - SSL:: delete_ssl
 - SSL :: disable_mail_sni

SSL:: enable_mail
_sni

SSL:: fetch_best_f
or_domain

SSL:: fetch_cert_in
fo

SSL:: fetch_certific
ates_for_fqdns

SSL:: fetch_key_a
nd_cabundle_for_
certificate

SSL:: find_certifica
tes_for_key

SSL:: find_csrs_for
_key

SSL:: generate_ce
rt

SSL:: generate_cs
r

SSL:: generate_ke
y

SSL:: get_autossl_
excluded_domains

SSL:: get_autossl_
pending_queue

SSL:: get_autossl_
problems

SSL:: get_cabundl
e

SSL:: get_cn_nam
e

SSL:: install_ssl

SSL:: installed_ho
st

SSL:: installed_ho
sts

SSL:: is_autossl_c
heck_in_progress

SSL:: is_mail_sni_
supported

SSL:: is_sni_supp
orted

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_item
s

SSL:: mail_sni_sta
tus

SSL:: rebuild_mail
_sni_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: **delete**

VersionControlDeployment:: **retrieve**

▼ **WebDisk**

WebDisk:: **delete_user**

WebDisk:: **set_homedir**

WebDisk:: **set_password**

WebDisk:: **set_permissions**

▼ **WebmailApps**

WebmailApps:: **list_webmailapps**

▼ **WebVhosts**

WebVhost:: **list_domains**

WebVhost:: **list_ssl_capable_domains**

▼ **WordPressBackup**

WordPressBackup:: **any_running**

WordPressBackup:: **cancel**

WordPressBackup:: **cleanup**

WordPressBackup:: **get_available_backups**

WordPressBackup:: **is_running**

WordPressBackup:: **start**

▼ **WordPressInstance**

Manager

WordPressInstanceManager:: **cancel_scan**

WordPressInstanceManager:: **cleanup_scan**

WordPressInstanceManager:: **change_admin_password**

WordPressInstanceManager:: **configure_autoupdate**

WordPressInstanceManager:: **get_api_version**

WordPressInstanceManager:: **get_in**

stance_by_id

WordPressInstanceManager::get_instances

WordPressInstanceManager::get_latest_wordpress_version_from_wordpress_org

WordPressInstanceManager::get_scan_results

WordPressInstanceManager::is_installable_addon_available

WordPressInstanceManager::start_scan

▼ WordPressRestore

WordPressRestore::any_running

WordPressRestore::cleanup

WordPressRestore::start