

WHM API 1 Functions - configureservice

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

Description

This function enables or disables a service and its monitoring.

Note:

In cPanel & WHM version 76, if a server profile **disables** a service, this function returns an error message.

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/configureservice?api.version=1&service=mysql&enabled=1&monitored=1
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/configureservice?api.version=1&service=mysql&enabled=1&monitored=1
```

- Account Restoration
- restore_modules_summary
- restore_queue_activate
- restore_queue_add_task
- restore_queue_clear_all_completed_tasks
- restore_queue_clear_all_failed_tasks
- restore_queue_clear_all_pending_tasks
- restore_queue_clear_all_tasks
- restore_queue_clear_completed_task
- restore_queue_clear_pending_task
- restore_queue_is_active
- restore_queue_list_active
- restore_queue_list_completed
- restore_queue

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Scro
- Yc
- mi
- us
- 20
- or
- 20
-)tc

ue_list_pending
restore_queue_state
restoreaccount
verify_new_username_or_restore

Accounts

accountsummary
applist
createacct
domainuserdata
editquota
forcepasswordchange
get_disk_usage
get_domain_info
getdomainowner
has_digest_auth
has_mycnf_for_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
quota_enabled
removeacct
set_digest_auth
showbw
suspendacct
unsuspendacct
untrack_acct

Command Line

```
whmapil  
configureservice  
service=mysql  
enabled=1 monitored=1
```

Notes:

- Unless otherwise noted, you **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local  
/cpanel/bin/whmapil
```

Output (JSON)

```
{  
  "metadata": {  
    "version": 1,  
    "reason":  
    "Enabled monitoring  
for mysql.",  
    "result": 1,  
    "command":  
    "configureservice"  
  }  
}
```

Find a function

- WHM API 1 Functions - fetch_service_ssl_components — This function lists the system's services and their associated certificates.

[nfigurations](#)
[get_users_authn_linked_accounts](#)
[link_user_authn_provider](#)
[set_provider_client_configurations](#)
[set_provider_display_configurations](#)
[twofactorauth_disable_policy](#)
[twofactorauth_enable_policy](#)
[twofactorauth_generate_tfa_config](#)
[twofactorauth_get_issuer](#)
[twofactorauth_get_user_configs](#)
[twofactorauth_policy_status](#)
[twofactorauth_remove_user_config](#)
[twofactorauth_set_issuer](#)
[twofactorauth_set_tfa_config](#)
[unlink_user_authn_provider](#)
[validate_login_token](#)

▼ Backups

[backup_config_get](#)
[backup_config_set](#)
[backup_date_list](#)
[backup_destination_add](#)
[backup_destination_delete](#)

| | | | | |
|----------------|---------------|---|--|--------------|
| <p>service</p> | <p>string</p> | <p>Required</p> <p>The service to configure.</p> | <ul style="list-style-type: none"> • apache_p hp_fpm • cpanel-dovecot-solr • cpanel_php_fpm • cpanellogd • cpdavd • cphulkd • cpsrzd • crond • dnsadmin • exim • exim-altport • ftpd • httpd • imap • ipaliases • lmtpl • mailman • mysql • named • nscd • p0f • pop • postgresql • queueprocd • rsyslogd • spamd • sshd <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note</p> <p>: For more information about each service, read our Service Manager documentation.</p> </div> | <p>mysql</p> |
|----------------|---------------|---|--|--------------|

- WHM API 1 Functions - enable_monitor_all_enabled_services - This function enables monitoring for all enabled services.

| | | | | | |
|---|------------------------|-----------------------|---|--|-----------|
| <p>backup_dest_inaction_get</p> <p>backup_dest_inaction_list</p> <p>backup_dest_inaction_set</p> <p>backup_dest_inaction_validate</p> <p>backup_get_transport_status</p> <p>backup_list_transported</p> <p>backup_set_list</p> <p>backup_set_list_combined</p> <p>backup_skip_users_all</p> <p>backup_skip_users_all_status</p> | <p>enabled</p> | <p><i>Boolean</i></p> | <p>Whether to enable the service.</p> <div data-bbox="732 226 873 661" style="border: 1px solid red; padding: 5px;"> <p>Warning: Do not use this function to disable the cpanel services.</p> </div> <p>If you do not use this parameter, the function will not change the enabled status of the service.</p> | <ul style="list-style-type: none"> • 1 — Enable the service. • 0 — Disable the service. | <p>1</p> |
| <p>backup_set_list_combined</p> <p>backup_skip_users_all</p> <p>backup_skip_users_all_status</p> <p>backup_user_list</p> <p>convert_and_migrate_from_legacy_config</p> <p>get_users_with_backup_metadata</p> <p>list_cparchive_files</p> | <p>monitored</p> | <p><i>Boolean</i></p> | <p>Whether to monitor the service in WHM's <i>Service Status</i> interface (<i>WHM >> Home >> Server Status >> Service Status</i>).</p> <p>If you do not use this parameter, the function will not change the monitoring status of the service.</p> | <ul style="list-style-type: none"> • 1 — Monitor the service. • 0 — Do not monitor the service. | <p>1</p> |
| <p>start_background_package</p> <p>toggle_user_backup_status</p> <p>▼ cPHulk</p> <p>cphulk_statuses</p> <p>create_cphulk_record</p> <p>delete_cphulk_record</p> <p>disable_cphulk</p> <p>enable_cphulk</p> <p>flush_cphulk_login_history</p> | <p>exim-altportnum</p> | <p><i>integer</i></p> | <p>The alternative port or ports on which Exim will listen for inbound connections.</p> <div data-bbox="732 1444 873 1963" style="border: 1px solid orange; padding: 5px;"> <p>Note:</p> <ul style="list-style-type: none"> • The function is only used. </div> | <p>A comma-separated list of integers.</p> | <p>26</p> |

flush_cphulk
_login_histo
ry_for_ips

get_countrie
s_with_kno
wn_ip_rang
es

get_cphulk_
brutes

get_cphulk_
excessive_b
rutes

get_cphulk_
failed_logins

get_cphulk_
user_brutes

load_cphulk
_config

read_cphulk
_records

save_cphulk
_config

set_cphulk_
config_key

▼ Databases

background
_mysql_upg
rade_status

current_mys
ql_version

installable_
mysql_versi
ons

latest_availa
ble_mysql_v
ersion

list_databas
e_users

list_databas
es

list_mysql_d
atabases_a
nd_users

remote_mys
ql_create_pr
ofile

remote_mys
ql_create_pr
ofile_via_ss
h

remote_mys
ql_delete_pr
ofile

remote_mys
ql_initiate_p
rofile_activat

h
i
s

p
a
r
a
m
e
t
e
r

i
f
y
o
u

s
e
t

e
x
i
m
-
a
l
t
p
o
r
t
a
s
t
h
e
s
e
r
v
i
c
e
p
a
r
a
m
e
t
e
r
'
s

v
a
l
u

ion

remote_mysql_monitor_profile_activation

remote_mysql_read_profile

remote_mysql_read_profiles

remote_mysql_update_profile

remote_mysql_validate_profile

rename_mysql_database

rename_mysql_user

rename_postgresql_database

rename_postgresql_user

set_local_mysql_root_password

set_mysql_password

set_postgresql_password

start_background_mysql_upgrade

e

- We introduced this parameter to replace Panel & WHM version 6.8.

This parameter defaults to 26.

▼ DNS

addns

addzonerecord

addzonerecord (Reverse DNS)

dumpzone

editzonerecord

get_nameserver_config

getzonerecord

has_local_authority

Returns

This function only returns metadata.

killdns
listmxs
listzones
lookupnsip
lookupnsips
removezone
record
resetzone
resolvedom
ainname
savemxs
setresolvers
update_nam
eservers_co
nfig

▼ EasyApache

ea4_get_cur
rently_install
ed_packages

ea4_get_ea
_pkgs_state

ea4_list_pro
files

ea4_metainf
o

ea4_migrati
on

ea4_pre_mi
grate_check

ea4_recom
mendations

ea4_save_p
rofile

ea4_tomcat
85_add

ea4_tomcat
85_list

ea4_tomcat
85_rem

▼ Greylisting

cpgreylist_is
_server_net
block_truste
d

cpgreylist_li
st_entries_f
or_common
_mail_provid
er

cpgreylist_lo
ad_common
_mail_provid

ers_config

cpgreylist_s
ave_commo
n_mail_provi
ders_config

cpgreylist_st
atus

cpgreylist_tr
ust_entries_
for_common
_mail_provid
er

cpgreylist_u
ntrust_entrie
s_for_comm
on_mail_pro
vider

create_cpgr
eylist_truste
d_host

delete_cpgr
eylist_truste
d_host

disable_cpgr
eylist

enable_cpgr
eylist

load_cpgreyl
ist_config

read_cpgrey
list_deferred
_entries

read_cpgrey
list_trusted_
host

save_cpgrey
list_config

▼ Integration

batch

cpanel

create_integ
ration_group

create_integ
ration_link

get_integrati
on_link_user
_config

list_integrati
on_groups

list_integrati
on_links

remove_inte
gration_grou
p

remove_inte

gration_link

update_inte
gration_link
_token

▼ IP Addresses

addips

delip

get_public_i
p

get_shared_
ip

ipv6_disable
_account

ipv6_enable
_account

ipv6_range_
add

ipv6_range_
edit

ipv6_range_
list

ipv6_range_
remove

ipv6_range_
usage

listips

nat_checkip

nat_set_pub
lic_ip

setsiteip

▼ Mail

disable_dki
m

disable_mail
_sni

emailtrack_s
earch

emailtrack_s
tats

emailtrack_u
ser_stats

enable_dkim

enable_mail
_sni

ensure_dki
m_keys_exi
st

exim_config
uration_che
ck

expunge_m

ailbox_messages
expunge_messages_for_mailbox_guid
fetch_dkim_private_keys
fetch_mail_queue
generate_mobileconfig
get_mailbox_status
get_mailbox_status_list
get_unique_recipient_count_per_sender_for_user
get_unique_sender_recipient_count_per_user
get_user_email_forward_destination
hold_outgoing_email
install_dkim_private_keys
install_spf_records
is_sni_supported
list_pops_for
mail_sni_status
rebuild_mail_sni_config
release_outgoing_email
save_spamd_config
set_user_email_forward_destination
suspend_outgoing_email
unsuspend_outgoing_email

validate_currency_installed_exim_configuration

validate_currency_dkims

validate_currency_ptrs

validate_currency_spfs

validate_exim_configuration_syntax

▼ Market

disable_market_provider

enable_market_provider

get_adjusted_market_providers_products

get_market_providers_commission_config

get_market_providers_list

get_market_providers_product_metadata

get_market_providers_products

set_market_product_attribute

set_market_provider_commission_id

▼ ModSecurity™

modsec_added_rule

modsec_added_vendor

modsec_assemble_configuration_text

modsec_batch_settings

modsec_check_rule

modsec_clone_rule

modsec_de
ploy_all_rule
_changes

modsec_de
ploy_rule_ch
anges

modsec_de
ploy_setting
s_changes

modsec_dis
able_rule

modsec_dis
able_vendor

modsec_dis
able_vendor
_configs

modsec_dis
able_vendor
_updates

modsec_dis
card_all_rul
e_changes

modsec_dis
card_rule_c
hanges

modsec_edit
_rule

modsec_en
able_vendor

modsec_en
able_vendor
_configs

modsec_en
able_vendor
_updates

modsec_get
_config_text

modsec_get
_configs

modsec_get
_configs_wit
h_changes_
pending

modsec_get
_log

modsec_get
_rules

modsec_get
_settings

modsec_get
_vendors

modsec_is_i
nstalled

modsec_ma
ke_config_a
ctive

modsec_make_config_inactive

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set_config_text

modsec_set_setting

modsec_disable_rule

modsec_update_vendor

▼ Packages

_getpkgextensionform

add_override_features_for_user

addpkg

addpkgext

changepackage

create_feature_relist

delete_feature_relist

delpkgext

editpkg

get_available_applications

get_available_featurelists

get_feature_metadata

get_feature_names

get_featurelist_data

get_featureli

sts

get_users_f
eatures_sett
ings

getfeaturelis
t

getpkginfo

killpkg

listpkgs

manage_fea
tures

matchpkgs

read_feature
list

remove_ove
rride_featu
res_for_user

update_feat
urelist

verify_user_
has_feature

▼ PHP

convert_all_
domains_to
_fpm

get_fpm_co
unt_and_util
ization

is_conversio
n_in_progre
ss

php_get_def
ault_accoun
ts_to_fpm

php_get_ha
ndlers

php_get_im
pacted_dom
ains

php_get_ins
talled_versio
ns

php_get_old
_fpm_flag

php_get_sys
tem_default
_version

php_get_vh
osts_by_ver
sion

php_get_vh
ost_versions

php_ini_get
_content

php_ini_get
_directives

php_ini_set
_content

php_ini_set
_directives

php_set_def
ault_accoun
ts_to_fpm

php_set_ha
ndler

php_set_old
_fpm_flag

php_set_ses
sion_save_p
ath

php_set_sys
tem_default
_version

php_set_vh
ost_versions

▼ Resellers

acctcounts

get_public_c
ontact

getresellerip
s

listacIs

listresellers

resellerstats

saveacllist

set_public_c
ontact

setacIs

setresellerip
s

setresellerli
mits

setresellerm
ainip

setresellern
ameservers

setresellerp
ackagelimit

setupreselle
r

suspendres
eller

terminateres
eller

unsetuprese

ller

unsuspendr
eseller

▼ RPM

delete_rpm_
version

edit_rpm_ve
rsion

get_rpm_ver
sion_data

install_rpm_
plugin

list_rpms

package_m
anager_fixc
ache

package_m
anager_get_
build_log

package_m
anager_get_
package_inf
o

package_m
anager_is_p
erforming_a
ctions

package_m
anager_list_
packages

package_m
anager_reso
lve_actions

package_m
anager_sub
mit_actions

package_m
anager_upgr
ade

uninstall_rp
m_plugin

▼ Script Hooks

delete_hook

edit_hook

list_hooks

reorder_hoo
ks

▼ Security

accesshash

authorizessh
key

check_remo
te_ssh_conn
ection

convertopen
sshtoputty

deletesshke
y

fetch_securi
ty_advice

generatessh
keypair

importsshke
y

listsshkeys

▼ Server

Administration

add_configcl
usterserver

configureba
ckgroundpro
cesskiller

configureser
vice

cors_proxy_
get

create_user
_session

delete_confi
gclusterserv
er

enable_mon
itor_all_ena
bled_service
s

get_all_cont
act_importa
nces

get_appconf
ig_applicatio
n_list

get_applicati
on_contact_
event_import
tance

get_applicati
on_contact_
importance

get_availabl
e_profiles

get_current_
profile

get_passwor
d_strength

get_remote_
access_has
h

get_service_
config

get_service_
config_key

get_tcp4_so
ckets

get_tcp6_so
ckets

get_tweakse
tting

get_udp4_s
ockets

get_udp6_s
ockets

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

loadavg

nvget

nvset

personalizati
on_get

personalizati
on_set

purchase_a
_license

reboot

remove_in_
progress_ex
im_config_e
dit

restartservic
e

restore_conf
ig_from_file

restore_conf
ig_from_upl
oad

run_cpkeyclt

send_test_p
osturl

send_test_p
ushbullet_n
ote

servicestatu

s

set_applicati
on_contact_
event_imp
ortance

set_applicati
on_contact_
importance

set_primary
_servernam
e

set_service_
config_key

set_tweakse
tting

sethostname

setminimum
passwordstr
engths

start_profile
_activation

system_nee
ds_reboot

systemloada
vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

fetchcrtinfo
fetchsslinfo
generatessl
get_autossl
_check_schedule
get_autossl
_log
get_autossl
_logs_catalog
get_autossl
_metadata
get_autossl
_pending_queue
get_autossl
_pending_queue_for_domain
get_autossl
_pending_queue_for_user
get_autossl
_problems_for_domain
get_autossl
_problems_for_user
get_autossl
_providers
get_best_ssl
domain_for_service
install_service_ssl_certificate
installssl
listcrts
rebuildinstall
edssldb
rebuildusers
sldb
reset_autossl_provider
reset_service_ssl_certificate
set_autossl_metadata
set_autossl_metadata_key

set_autossl_
provider

start_autossl_
check_for_
all_users

start_autossl_
check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_get_s
upport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

abort_transfer_session

analyze_transfer_session_remote

available_transfer_modules

create_remote_root_transfer_session

create_remote_user_transfer_session

delete_account_archives

enqueue_transfer_item

fetch_transfer_session_log

get_transfer_session_state

pause_transfer_session

remote_basic_credential_check

retrieve_transfer_session_remote_analysis

start_transfer_session

transfer_module_schema

validate_system_user

▼ Updates

accept_eula

get_available_tiers

get_current_lts_expiration_status

get_lts_expire

getlongterm support

installed_versions

set_cpanel_updates

set_tier

update_upd
ateconf

version