

WHM API 0 Functions - listaccls

Guide to WHM API 0

Return Data

Description

This function lists the reseller's [Access Control Lists \(ACLs\)](#) and each list's privileges.

Examples

Accounts

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/listaccls
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/listaccls
```

Command Line

```
whmapi0 listaccls
```

Notes:

- You **must** [URI-encode](#) values.
- For more information and additional output options, read our [Guide to WHM API 0](#) documentation or run the `whmapi0 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapi0` command:

```
/usr/local/cpanel/bin/whmapi0
```

Output (JSON)

```
{  "accls": {    "acl1": {      "allow-unlimited-disk-pkgs": 0,
```

Function information

About WHM API 0

WHM API 0 performs functions and accesses data in WHM.

Warning: WHM API 0 is deprecated. We strongly recommend using WHM API 1.

- accounts summary
- applist
- createacct
- domainuserdata
- editquota
- limitbw
- listaccls
- listsuspended
- modifyacct
- myprivs
- passwd
- removeacct
- showbw
- suspendacct
- unsuspendacct
- ▼ DNS
 - addns
 - addzonerecord
 - dumpzone
 - editzonerecord
 - getzonerecord
 - killdns
 - listzones
 - lookupnsip
 - lookupnsips
 - removezonerecord
 - resetzone
 - setresolvers
- ▼ IP Addresses
 - addip
 - delip

- listips
- setsiteip
- ▼ Mail
 - deliver_mail_queue
 - deliver_messages_mail_queue
 - exim_configuration_check
 - fetch_doc_key
 - purge_mail_queue
 - remove_in_progress_exim_config_edit
 - remove_messages_mail_queue
 - unfreeze_messages_mail_queue
 - validate_current_installed_exim_config
 - validate_exim_configuration_syntax
- ▼ Packages
 - addpkg
 - changepackage
 - editpkg
 - getfeaturelist
 - killpkg
 - listpkgs
- ▼ Resellers
 - acctcounts
 - getresellers
 - listacts
 - listresellers
 - resellerstats
 - saveacllist
 - setacts
 - setresellerip

```

"list-pkgs":0,

"basic-system-info":0,
,

"limit-bandwidth":0,
  "news":0,

"add-pkg-shell":0,

"allow-unlimited-pkgs":0,

"suspend-acct":0,

"manage-dns-records":0,

"generate-email-config":0,

"mysql-info":0,

"upgrade-account":0,

"allow-shell":0,

"basic-whm-functions":0,

"manage-api-tokens":0,
,

"acct-summary":0,
  "resftp":0,

"digest-auth":0,

"ns-config":0,

"demo-setup":0,

"list-accts":0,

"edit-account":0,

"create-user-session":0,

"clustering":0,

"create-dns":0,

```

Notes:

- Scro
- Yc
- mi
- us
- 20
- or
- 20
-)tc

Find a function

- WHM API 0 Functions - getresellerips
— This function lists a reseller's available IP addresses.

s

setresellerlimits

setresellermainip

setresellernameservers

setresellerpackagelimit

setupreseller

suspendreseller

terminatereseller

unsetupreseller

unsuspendreseller

▼ Server Administration

configureserver

gethostname

getlanglist

loadavg

nvget

nvset

reboot

restartservice

servicestatus

sethostname

▼ SSL

fetchsslinfo

generatessl

installssl

listcrts

▼ Updates

get_available_tiers

set_cpanel_updates

set_tier

version

```

"cpanel-api":0,
"cpanel-integration":0,
    "ssl-buy":0,
    "passwd":0,
    "status":0,
    "restart":0,
    "ssl":0,
"park-dns":0,
"locale-edit":0,
    "all":1,
"mailcheck":0,
    "edit-mx":0,
"edit-pkg":0,
"show-bandwidth":0,
    "quota":0,
"edit-dns":0,
"create-acct":0,
"ssl-gencrt":0,
"thirdparty":0,
    "stats":0,
"allow-parkedcreate":0,
"rearrange-accts":0,
"add-pkg-ip":0,
"kill-dns":0,
"cors-proxy-get":0,
"manage-styles":0,
"kill-acct":0,
"ssl-info":0,
"allow-unlimited-bw-pkgs":0,
"viewglobalpackages":

```

- WHM API 0 Functions - listresellers — This function lists the reseller accounts on the server.
- WHM API 0 Functions - resellerstats — This function lists statistics for a reseller's accounts.
- WHM API 0 Functions - setresellerips — This function adds IP addresses to a reseller's account.

```
0,
    "add-pkg":0,
    "manage-oidc":0,
    "allow-emaillimits-pkgs":0,
    "allow-addoncreate":0
    ,
    "track-email":0
```

```
}  
  }  
}
```

Output (XML)

```
<listacls>  
  <acls>  
  
    <suspend-acct>0</suspend-acct>  
  
    <list-accts>0</list-accts>  
  
    <mailcheck>0</mailcheck>  
  
    <resftp>0</resftp>  
  
    <kill-dns>0</kill-dns>  
  
    <allow-addoncreate>0</allow-addoncreate>  
  
    <ssl-gencrt>0</ssl-gencrt>  
  
    <allow-unlimited-bw-pkgs>0</allow-unlimited-bw-pkgs>  
  
    <create-dns>0</create-dns>  
  
    <edit-account>0</edit-account>  
  
    <clustering>0</clustering>  
  
    <limit-bandwidth>0</limit-bandwidth>  
  
    <allow-emaillimits-pkgs>0</allow-emaillimits-pkgs>  
  
    <kill-acct>0</kill-acct>
```

```
<quota>0</quota>

<add-pkg>0</add-pkg>

<edit-pkg>0</edit-pkg>
>

<status>0</status>

<create-acct>0</create-acct>

<edit-dns>0</edit-dns>
>

<allow-unlimited-pkgs>0</allow-unlimited-pkgs>
    <all>1</all>

<ssl-buy>0</ssl-buy>

<show-bandwidth>0</show-bandwidth>

<viewglobalpackages>0</viewglobalpackages>

<restart>0</restart>

<rearrange-accts>0</rearrange-accts>

<add-pkg-shell>0</add-pkg-shell>
    <ssl>0</ssl>

<allow-parkedcreate>0</allow-parkedcreate>

<stats>0</stats>

<allow-unlimited-disk-pkgs>0</allow-unlimited-disk-pkgs>

<add-pkg-ip>0</add-pkg-ip>

<passwd>0</passwd>

<locale-edit>0</locale-edit>
```

```
e-edit>

<demo-setup>0</demo-setup>

<frontpage>0</frontpage>

<thirdparty>0</thirdparty>

<park-dns>0</park-dns>

<cpanel-api>0</cpanel-api>

<upgrade-account>0</upgrade-account>

<news>0</news>

<edit-mx>0</edit-mx>

<allow-shell>0</allow-shell>

<acct-summary>0</acct-summary>

<basic-whm-functions>0</basic-whm-functions>

<create-user-session>0</create-user-session>

<digest-auth>0</digest-auth>

<cors-proxy-get>0</cors-proxy-get>

<generate-email-config>0</generate-email-config>

<manage-oidc>0</manage-oidc>

<cpanel-integration>0</cpanel-integration>
```

```
<manage-styles>0</manage-styles>
```

```
<basic-system-info>0</basic/system-info>
```

```
<list-pkgs>0</list-pkgs>
```

```
<track-email>0</track-email>
```

```
<mysql-info>0</mysql-info>
```

```
<ssl-info>0</ssl-info>
```

```
<manage-api-tokens>0</manage-api-tokens>
```

```
<manage-dns-records>0</manage-dns-records>
```

```
<ns-config>0</ns-conf
```



```
ig>
  </acIs>
</listacIs>
```

Parameters

This function does not accept parameters.

Returns

| Return | Type | Description | Possible values | Example |
|--------|------|-----------------------|--|---------|
| acIs | hash | A hash of privileges. | <p>In JSON output, this hash includes the name hash.</p> <p>In XML output, this hash includes one or more of the following returns:</p> <ul style="list-style-type: none">• acct-summary• add-pkg• add-pkg-ip• add-pkg-shell• all• allow-addoncreate• allow-parkedcreate• allow-unlimited-bw-pkgs• allow-unlimited-disk-pkgs• allow-unlimited-pkgs• allow-shell• basic-system-info• basic-whm-functions• clustering• cors-proxy-get• cpanel-api• cpanel-integration• create-account create-dns• create-user-session• demo-setup• digest-auth• disallow-shell• edit-account | |

| | | | | |
|------|-----------------------|--|--|------|
| | | | <ul style="list-style-type: none"> • edit-dns • edit-mx • edit-pkg • frontpage • generate-email-config • kill-act • kill-dns • list-accts • list-pkgs • locale-edit • limit-bandwidthmailcheck • manage-api-tokens • manage-dns-records • manage-oidc • manage-dns-records • manage-styles • mysql-info • news • ns-config • park-dns • passwd • quota • rearrange-accts • rearrange-accts • resftp • restart • show-bandwidth • ssl • ssl-buy • ssl-gencert • ssl-info • stats • status • suspend-account • thirdparty • track-email • upgrade-account • viewglobalpackages. <p>This hash also includes any third-party ACL privileges that exist for the user.</p> | |
| name | <i>hash or string</i> | <p>The ACL's name.</p> <p>The function returns this value in the <code>ac1s</code> hash.</p> | <p>In JSON output, this hash includes one or more of the following returns:</p> <ul style="list-style-type: none"> • acct-summary • add-pkg • add-pkg-ip • add-pkg-shell • all • allow-addoncreate • allow-parkedcreate • allow-unlimited-bw-pkgs • allow-unlimited-disk-pkgs | ac11 |

- allow-unl
imited-pk
gs
- allow-she
ll
- basic-sys
tem-info
- basic-whm
-function
s
- clusterin
g
- cors-prox
y-get
- cpanel-ap
i
- cpanel-in
tegration
- create-ac
ct create-
dns
- create-us
er-sessio
n
- demo-setu
p
- digest-au
th
- edit-acco
unt
- edit-dns
- edit-mx
- edit-pkg
- frontpage
- generate-
email-con
fig
- kill-act
- kill-dns
- list-acct
s
- list-pkgs
- locale-ed
it
- limit-ban
dwidth mai
lcheck
- manage-ap
i-tokens
- manage-dn
s-records
- manage-oi
dc
- manage-dn
s-records
- manage-st
yles
- mysql-inf
o
- news
- ns-config
- park-dns
- passwd
- quota
- rearrange
-accts
- rearrange
-accts
- resftp
- restart
- show-band
width
- ssl
- ssl-buy
- ssl-gencr
t
- ssl-info
- stats
- status
- suspend-a
cct
- thirdpart
y
- track-ema
il
- upgrade-a
ccount
- viewgloba
lpackages.

| | | | | |
|-----------------|----------------|---|---|---|
| | | | <p>This hash also includes any third-party ACL privileges that exist for the user.</p> <p>In XML output, this return's value is a valid string.</p> | |
| acct-summary | <i>Boolean</i> | <p>Whether to allow the reseller to view an account summary.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| add-pkg | <i>Boolean</i> | <p>Whether to allow the reseller to create packages.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| add-pkg-g-ip | <i>Boolean</i> | <p>Whether to allow the reseller to create packages with dedicated IP addresses.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| add-pkg-g-shell | <i>Boolean</i> | <p>Whether to allow the reseller to create packages with shell access.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| all | <i>Boolean</i> | <p>Whether to provide the reseller all privileges.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|--|----------------|---|---|---|
| al lo w- ad- do- nc- re- ate | <i>Boolean</i> | Whether to allow the reseller to create packages with addon domains. The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output. | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| al lo w- pa- rk- ed- cre- ate | <i>Boolean</i> | Whether to allow the reseller to create packages with parked domains (aliases). The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output. | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| al lo w- un- li- mi- te- d- bw- -p- kgs | <i>Boolean</i> | Whether to allow the reseller to create packages with unlimited bandwidth. The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output. | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| al lo w- un- li- mi- te- d- di- sk- -p- kgs | <i>Boolean</i> | Whether to allow the reseller to create packages with unlimited disk space quotas. The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output. | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| al lo w- un- li- mi- te- d- pk- gs | <i>Boolean</i> | Whether to allow the reseller to create packages with unlimited values for features (for example, unlimited email accounts). The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output. | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|---------------------|----------------|---|---|---|
| allow-shell | <i>Boolean</i> | <p>Whether to allow the reseller to create an account that possesses shell access.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow • 0 — Do not allow | 0 |
| basic-system-info | <i>Boolean</i> | <p>Whether to allow the reseller to retrieve basic system information.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| basic-whm-functions | <i>Boolean</i> | <p>Whether to allow the reseller to access to basic cPanel & WHM options.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|-----------------------------------|----------------|---|---|---|
| <pre> c1 us te ri ng </pre> | <i>Boolean</i> | <p>Whether to allow the reseller to configure DNS clusters.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| <pre> co rs -p ro xy -g et </pre> | <i>Boolean</i> | <p>Whether to allow the reseller to perform Cross-Origin Resource Sharing (CORS) HTTP requests.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 680 873 947" style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| <pre> cp an el -a pi </pre> | <i>Boolean</i> | <p>Whether to allow the reseller to execute cPanel API 1, cPanel API 2 and UAPI functions via WHM.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 1268 873 1535" style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|---------------------|----------------|---|---|---|
| cpanel-integration | <i>Boolean</i> | <p>Whether to allow the reseller to manage how their server and its services connect to other servers and services.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 443 873 705" style="border: 1px solid black; padding: 5px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| create-account | <i>Boolean</i> | <p>Whether to allow the reseller to create accounts.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| create-dns | <i>Boolean</i> | <p>Whether to allow the reseller to create DNS zones.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| create-user-session | <i>Boolean</i> | <p>Whether to allow the reseller to create a new temporary user session for a specified service.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 1472 873 1965" style="border: 1px solid black; padding: 5px;"> <p>Notes :</p> <ul style="list-style-type: none"> • This ACL privilege allows </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

s a n A P I t o k e n u s e r t o b y p a s s a n y r e s t r i c t i o n s t h a t y o u s e t o n t h e A P I t o k e n . F o r m o r e i n f o r m a t i o n , r e a d o u r M a

| | | | | |
|-------------|----------------|---|---|---|
| | | <p style="text-align: center;">n .</p> <ul style="list-style-type: none"> • We added this parameter in cPanel & WHM version 68. | | |
| demo-setup | <i>Boolean</i> | <p>Whether to allow the reseller to enable demo mode on accounts.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| digest-auth | <i>Boolean</i> | <p>Whether to allow the reseller to manage Digest Authentication support.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|-----------------------|-----------------------|---|---|----------|
| <p>disallow-shell</p> | <p><i>Boolean</i></p> | <p>Whether to allow the reseller to create accounts that possess shell access.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 401 873 667" style="border: 1px solid orange; padding: 5px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Do not allow. • 0 — Allow. | <p>0</p> |
| <p>edit-account</p> | <p><i>Boolean</i></p> | <p>Whether to allow the reseller to modify accounts.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 926 873 1759" style="border: 1px solid red; padding: 5px;"> <p>Warning: This privilege allows circumvention of account creation limits, gives shell access unless explicitly disallowed, and provides access to dedicated IP addresses, among other features.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | <p>0</p> |

| | | | | |
|-----------|----------------|--|---|---|
| edit-dns | <i>Boolean</i> | <p>Whether to allow the reseller to edit DNS zones.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| edit-mx | <i>Boolean</i> | <p>Whether to allow the reseller to edit MX entries.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| edit-pkg | <i>Boolean</i> | <p>Whether to allow the reseller to create and delete packages.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| frontpage | <i>Boolean</i> | <p>Whether to allow the reseller to manage Microsoft® FrontPage® Extensions for their domains.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 1121 873 1961" style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note: cPanel & WHM will ignore all Microsoft Front Page settings and parameters if either of the following statements are true:</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

• Your server runs cPanel & WHM version 11.44 and Frontpage extensions are not installed on your server.

| | | | | |
|----------------------|----------------|---|---|---|
| | | <p>• Your server runs cPanel & WHM version 11.46 or later.</p> | | |
| generate-mail-config | <i>Boolean</i> | <p>Whether to allow the reseller to generate a mobile configuration profile for an email account.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <p>Note: We added this return in cPanel & WHM version 68.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| kill-account | <i>Boolean</i> | <p>Whether to allow the reseller to delete his or her customers' accounts.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|---|----------------|--|---|---|
| ki ll -d ns | <i>Boolean</i> | <p>Whether to allow the reseller to delete DNS zones.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| li mi t- ba nd wi dt h | <i>Boolean</i> | <p>Whether to allow the reseller to modify bandwidth limits on his or her accounts.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div style="border: 1px solid red; padding: 5px; margin: 10px 0;"> <p>Warning: This will allow circumvention of account package limits if you do not use resource limits.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| li st -a cc ts | <i>Boolean</i> | <p>Whether to allow the reseller to list owned accounts.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| li st -p kg s | <i>Boolean</i> | <p>Whether to allow the reseller to view existing hosting plans (packages).</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|---|----------------|---|---|---|
| l o c a l e - e d i t | <i>Boolean</i> | <p>Whether to allow the reseller to create and modify locales on the server.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| m a i l c h e c k | <i>Boolean</i> | <p>Whether to allow the reseller to access WHM's <i>Mail Troubleshooter</i> interface (<i>Home >> Mail >> Mail Troubleshooter</i>).</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| m a n a g e - a p i - t o k e n s | <i>Boolean</i> | <p>Whether to allow the reseller to manage API tokens.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Notes</p> <p>:</p> <ul style="list-style-type: none"> • This privilege allows an API token user to bypass any reseller </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

t r i c t i o n s t h a t y o u s e t o n t h e A P I t o k e n . F o r m o r e i n f o r m a t i o n , r e a d o u r M a n a g e A P I T o k e n s d o c u m e n t a t i o

| | | | | |
|--------------------|----------------|---|---|---|
| | | <p style="text-align: center;">n . • We added this parameter in cPanel & WHM version 68 .</p> | | |
| manage-dns-records | <i>Boolean</i> | <p>Whether to allow the reseller to manage DNS records.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|-----------------------------------|----------------|---|---|---|
| mana ge- o id c | <i>Boolean</i> | <p>Whether to allow the reseller to manage external authentication for their accounts.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 401 873 667" style="border: 1px solid orange; padding: 5px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| mana ge- s ty le s | <i>Boolean</i> | <p>Whether to allow the reseller to manage their server's cPanel styles.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 968 873 1234" style="border: 1px solid orange; padding: 5px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| mysq l- in fo | <i>Boolean</i> | <p>Whether to allow the reseller to retrieve MySQL® database and user data.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 1535 873 1801" style="border: 1px solid orange; padding: 5px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|-------------|----------------|--|---|---|
| news | <i>Boolean</i> | <p>Whether to allow the reseller to send news messages to customers' accounts.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| nsconfig | <i>Boolean</i> | <p>Whether to allow the reseller to manage nameservers.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 659 875 926" style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| parkdomains | <i>Boolean</i> | <p>Whether to allow the reseller to park domains within WHM.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|----------|----------------|--|---|---|
| password | <i>Boolean</i> | <p>Whether to allow the reseller to modify passwords for customers' accounts.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 401 873 1152" style="border: 1px solid orange; padding: 5px;"> <p>Note: This ACL privilege allows an API token user to change account passwords and log in with a new password. For more information, read our Manage API Tokens documentation.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| quota | <i>Boolean</i> | <p>Whether to allow the reseller to modify disk space quotas for accounts.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div data-bbox="732 1476 873 1904" style="border: 1px solid red; padding: 5px;"> <p>Warning: This will allow circumvention of account package limits if you do not use resource limits.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|--|----------------|---|---|---|
| re ar rang e- acct s | <i>Boolean</i> | <p>Whether to allow the reseller to rearrange the locations of customer accounts in order to free up disk space.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| re s- cart | <i>Boolean</i> | <p>Whether to allow the reseller to reset shopping carts for their domain accounts.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <p>Note: We re move d this return in cPanel & WHM 11.46.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| re sf tp | <i>Boolean</i> | <p>Whether to allow the reseller to re-sync FTP account passwords.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| re st art | <i>Boolean</i> | <p>Whether to allow the reseller to restart services on the server, such as Apache or Exim.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| sh ow -b an d w id th | <i>Boolean</i> | <p>Whether to allow the reseller to view the bandwidth usage of accounts.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|---------------|---------|---|---|---|
| ssl | Boolean | <p>Whether to allow the reseller to manage the SSL certificates installed on domains.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| ssl-buy | Boolean | <p>Whether to allow the reseller to use WHM's <i>Purchase and Install an SSL Certificate</i> interface (<i>Home >> SSL/TLS >> Purchase and Install an SSL Certificate</i>).</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| ssl-generator | Boolean | <p>Whether to allow the reseller to use the SSL CSR/CRT generator.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| ssl-info | Boolean | <p>Whether to allow the reseller to view their server's SSL information.</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| stats | Boolean | <p>Whether to allow the reseller to view WHM's <i>Server Information</i> interface (<i>Home >> Server Status >> Server Information</i>).</p> <p>The function returns this value in the <code>acls</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|-------------------|----------------|--|---|---|
| status | <i>Boolean</i> | <p>Whether to allow the reseller to view WHM's <i>Service Status</i> interface (<i>Home >> Server Status >> Service Status</i>).</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| suspended-account | <i>Boolean</i> | <p>Whether to allow the reseller to suspend customers' accounts.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| third-party | <i>Boolean</i> | <p>Whether to allow the reseller to manage third-party service offerings.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| tracking-email | <i>Boolean</i> | <p>Whether to allow resellers to view reports about email message delivery attempts from their account.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note: We added this return in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |
| upgrade-account | <i>Boolean</i> | <p>Whether to allow the reseller to upgrade and downgrade customers' domain accounts.</p> <p>The function returns this value in the <code>ac1s</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 0 |

| | | | | |
|----------------------|----------------|--|--|---|
| view global packages | <i>Boolean</i> | <p>Whether to allow the reseller to use all global packages. For more information, read our reseller packages documentation.</p> <p>The function returns this value in the <code>aclis</code> hash for XML output or the <code>name</code> hash for JSON output.</p> | <ul style="list-style-type: none">• 1 — Allow.• 0 — Do not allow. | 0 |
|----------------------|----------------|--|--|---|