

# UAPI Functions - LangPHP::php\_get\_vhost\_versions

## Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

## Description

This function returns the PHP version of every virtual host that a reseller controls.

**Note:**  
This document **only** applies to systems that run EasyApache 4.

**Important:**  
In cPanel & WHM version 76 and later, when you disable the `WebServerRole`, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

## Examples

### ▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/LangPHP/php_get_vhost_versions
```

**Note:**  
This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

- Backup
  - Backup::fullbackup
  - p\_to\_ftp
  - Backup::fullbackup\_to\_homedir
  - Backup::fullbackup\_to\_scp\_with\_key
  - Backup::fullbackup\_to\_scp\_with\_password
  - Backup::list\_backups
- ▼ Bandwidth
  - Bandwidth::get\_enabled\_protocols
  - Bandwidth::get\_retention\_periods
  - Bandwidth::query
- ▼ Batch
  - Batch::strict
- ▼ Brand
  - Brand::read
- ▼ Branding
  - Branding::file
  - Branding::get\_applications
  - Branding::get\_application\_information
  - Branding::get\_available\_applications
  - Branding::get\_information\_for\_applications

## Function information

## About this module

The LangPHP module manages multi-PHP functionality.

## About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster
  - CacheBuster:: read
  - CacheBuster:: update
- Chkserverd
  - Chkserverd:: get\_exit\_ports
  - Chkserverd:: get\_exit\_ports\_ssl
- Chrome
  - Chrome:: get\_dom
- Contactus
  - Contactus:: is\_enabled
- cPAddons
  - cPAddons:: get\_available\_addons
  - cPAddons:: get\_instance\_settings
  - cPAddons:: list\_addon\_instances
- cPGreyList
  - cPGreyList:: disable\_all\_domains
  - cPGreyList:: disable\_domains
  - cPGreyList:: enable\_all\_domains
  - cPGreyList:: enable\_domains
  - cPGreyList:: has\_reylisting\_enabled
  - cPGreyList:: list\_domains
- DAV
  - DAV:: disable\_shared\_global\_addressbook
  - DAV:: enable\_shared\_global\_addressbook
  - DAV:: get\_calendar\_contacts\_config
  - DAV:: has\_shared\_global\_addressbook
  - DAV:: is\_dav\_service\_enabled

### LiveAPI PHP Class

```

$cpanel = new
CPANEL(); // Connect
to cPanel - only do
this once.

// List the user's
virtual hosts and PHP
versions.
$get_vhost_versions =
$cpanel->uapi(
    'LangPHP',
    'php_get_vhost_versions',
);

```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

### LiveAPI Perl Module

```

my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# List the user's
virtual hosts and PHP
versions.
my
$get_vhost_versions =
$cpliveapi->uapi(
    'LangPHP',
    'php_get_vhost_versions',
);

```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

#### Notes:

- The
- Ur
- int
- us
- 20
- or
- 20
- ).
- 20
- or
- 20
- ).

## Find a function

Lang PHP module manages multi-PHP functionality.

- DAV:: is\_horde\_enabled
- ▼ DCV
  - DCV:: check\_domains\_via\_dns
  - DCV:: check\_domains\_via\_http
  - DCV:: ensure\_domains\_can\_pass\_dcv
- ▼ DomainInfo
  - DomainInfo:: domains\_data
  - DomainInfo:: list\_domains
  - DomainInfo:: main\_domain\_builtin\_subdomain\_aliases
  - DomainInfo:: single\_domain\_data
- ▼ DNS
  - DNS:: ensure\_domains\_reside\_only\_locally
  - DNS:: has\_local\_authority
- ▼ DNSSEC
  - DNSSEC:: disable\_dnssec
  - DNSSEC:: enable\_dnssec
  - DNSSEC:: fetch\_dns\_records
  - DNSSEC:: set\_nsec3
  - DNSSEC:: unset\_nsec3
- ▼ Email
  - Email:: account\_name
  - Email:: add\_auto\_responder
  - Email:: add\_domain\_forwarder
  - Email:: add\_forwarder
  - Email:: add\_list
  - Email:: add\_mailman\_delegates
  - Email:: add\_mx
  - Email:: add\_pop
  - Email:: add\_spam\_filter

## ▼ cPanel Template Toolkit

```

<!-- Get a hash of all the data, then display the vhost values. -->
[% data = execute('LangPHP', 'php_get_vhost_versions' ); %]
[% FOREACH q = data.vhost %]
  <p>
    [% q %]
  </p>
[% END %]

<!-- Get only the account value. -->
[% execute('LangPHP', 'php_get_vhost_versions' ).data.account %]

```

**Note:**  
For more information, read our [Guide to Template Toolkit](#) documentation.

- UAPI Functions - LangPHP: :php\_get\_do\_main\_handler - This function returns a PHP version's assigned PHP handler.
- UAPI Functions - LangPHP: :php\_get\_installed\_versions - This function lists the system's PHP versions.

Email:: browse\_mailbox

Email:: change\_mx

Email:: check\_fastmail

Email:: check\_pipe\_forwarder

Email:: delete\_auto\_responder

Email:: delete\_domain\_forwarder

Email:: delete\_filter

Email:: delete\_forwarder

Email:: delete\_held\_messages

Email:: delete\_list

Email:: delete\_mx

Email:: delete\_pop

Email:: disable\_filter

Email:: disable\_mailbox\_autocreate

Email:: disable\_spam\_assassin

Email:: disable\_spam\_autodelete

Email:: disable\_spam\_box

Email:: dispatch\_client\_settings

Email:: edit\_pop\_quota

Email:: enable\_filter

Email:: enable\_mailbox\_autocreate

Email:: enable\_spam\_assassin

Email:: enable\_spam\_box

Email:: fetch\_charmaps

Email:: fts\_rescan\_mailbox

Email:: generate\_mailman\_opt

Email:: get\_auto\_responder

Email:: get\_chase

## Command Line

```
uapi --user=username
LangPHP
php_get_vhost_versions
```

### Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

## Output (JSON)

```
{
  "errors": null,
  "status": 1,
  "messages": null,
  "data": [
    {
      "main_domain": 1,
      "vhost": "blee.com",
      "version": "ea-php70",
      "account_owner": "root",
      "account": "blee",
      "documentroot": "/home/blee/public_html",
      "php_fpm": 1,
      "phpversion_source": {
```

- UAPI Functions - LangPHP: :php\_get\_system\_default\_version — This function lists the system's default PHP version.
- UAPI Functions - LangPHP: :php\_get\_vhost\_versions — This function returns the PHP version of every virtual host that a reseller controls.

ts  
Email: get\_client\_settings  
Email: get\_default\_email\_quota  
Email: get\_default\_email\_quota\_mib  
Email: get\_disk\_usage  
Email: get\_filter  
Email: get\_held\_message\_count  
Email: get\_mailbox\_autocreate  
Email: get\_mailman\_delegates  
Email: get\_main\_account\_disk\_usage  
Email: get\_main\_account\_disk\_usage\_bytes  
Email: get\_max\_email\_quota  
Email: get\_max\_email\_quota\_mib  
Email: get\_pop\_quota  
Email: get\_spam\_settings  
Email: get\_webmail\_settings  
Email: has\_delegated\_mailman\_lists  
Email: has\_plaintext\_authentication  
Email: hold\_outgoing  
Email: is\_integer  
Email: list\_autoresponders  
Email: list\_default\_address  
Email: list\_domain\_forwarders  
Email: list\_filters  
Email: list\_filters\_backups  
Email: list\_forwarders  
Email: list\_forward

```
"domain": "blee.com"
    },
    "homedir": "/home/blee",
    "php_fpm_pool_params": {
        "pm_process_idle_timeout": 10,
        "pm_max_requests": 20,
        "pm_max_children": 5
    },
    {
        "php_fpm": 0,
        "account": "blee",
        "documentroot": "/home/blee/first.blee.com",
        "php_fpm_pool_params": {
            },
            "phpversion_source": {
                "domain": "first.blee.com"
            },
            "homedir": "/home/blee",
            "version": "ea-php70",
            "main_domain": 0,
            "vhost": "first.blee.com",
            "account_owner": "root"
        },
        {
            "account_owner": "root"
```

ers\_backups  
Email: list\_lists  
Email: list\_mail\_domains  
Email: list\_mx  
Email: list\_pops  
Email: list\_pops\_with\_disk  
Email: list\_system\_filter\_info  
Email: passwd\_list  
Email: passwd\_pop  
Email: release\_outgoing  
Email: remove\_mailman\_delegates  
Email: reorder\_filters  
Email: set\_always\_accept  
Email: set\_default\_address  
Email: set\_list\_privacy\_options  
Email: stats\_db\_status  
Email: store\_filter  
Email: suspend\_incoming  
Email: suspend\_login  
Email: suspend\_outgoing  
Email: trace\_filter  
Email: unsuspend\_incoming  
Email: unsuspend\_login  
Email: unsuspend\_outgoing  
Email: verify\_password  
▼ EmailAuth  
EmailAuth: disable\_dkim  
EmailAuth: enable\_dkim  
EmailAuth: ensure\_dkim\_keys\_exist

```
",  
"vhost": "second.blee.com",  
"main_domain": 0,  
"version": "ea-php56",  
"phpversion_source": {  
  "system_default": 1  
},  
"homedir": "/home/blee",  
"php_fpm_pool_params": {  
  },  
  "php_fpm": 0,  
"documentroot": "/home/blee/second.blee.com",  
"account": "blee"  
  },  
  ],  
  "metadata": {  
    "transformed": 1
```

EmailAuth:: fetch\_  
dkim\_private\_keys

EmailAuth:: install\_  
\_dkim\_private\_key  
s

EmailAuth:: install\_  
\_spf\_records

EmailAuth:: validat  
e\_current\_dkims

EmailAuth:: validat  
e\_current\_ptrs

EmailAuth:: validat  
e\_current\_spfs

#### ExternalAuthenticat ion

ExternalAuthenticat  
ion:: add\_authn\_li  
nk

ExternalAuthenticat  
ion:: configured\_  
modules

ExternalAuthenticat  
ion:: get\_authn\_lin  
ks

ExternalAuthenticat  
ion:: has\_external\_  
\_auth\_modules\_co  
nfigured

ExternalAuthenticat  
ion:: remove\_auth  
n\_link

#### Features

Features:: get\_feat  
ure\_metadata

Features:: has\_fea  
ture

Features:: list\_feat  
ures

#### Fileman

Fileman:: autocom  
pletedir

Fileman:: empty\_tr  
ash

Fileman:: get\_file\_  
content

Fileman:: get\_file\_i  
nformation

Fileman:: list\_files

Fileman:: save\_file\_  
\_content

Fileman:: transcod  
e

Fileman:: upload\_fi  
les

```
},  
"warnings":null  
}
```

#### Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

## Parameters

This function does not accept parameters.

## Returns

Return	Type	Description	Possible values	Example
	<i>array of hashes</i>	An array of hashes of the virtual host's suspended status, versions, virtual hosts, and accounts.	An array of hashes that contains the documentroot, main_domain, homedir, account, account_owner, php_fpm, version, and vhost returns, the phpversion_source array, and the php_fpm_pool_parms hash.	

▼ Ftp

- Ftp:: add\_ftp
- Ftp:: allows\_anonymous\_ftp
- Ftp:: allows\_anonymous\_ftp\_incoming
- Ftp:: delete\_ftp
- Ftp:: ftp\_exists
- Ftp:: get\_ftp\_daemon\_info
- Ftp:: get\_port
- Ftp:: get\_quota
- Ftp:: get\_welcome\_message
- Ftp:: kill\_session
- Ftp:: list\_ftp
- Ftp:: list\_ftp\_with\_disk
- Ftp:: list\_sessions
- Ftp:: passwd
- Ftp:: server\_name
- Ftp:: set\_anonymous\_ftp
- Ftp:: set\_anonymous\_ftp\_incoming
- Ftp:: set\_homedir
- Ftp:: set\_quota
- Ftp:: set\_welcome\_message

▼ Integration

- Integration:: fetch\_url

▼ KnownHosts

- KnownHosts:: create
- KnownHosts:: delete
- KnownHosts:: update
- KnownHosts:: verify

▼ LangPHP

- LangPHP:: php\_get\_domain\_handler
- LangPHP:: php\_get\_impacted\_domains
- LangPHP:: php\_get\_installed\_version

documentroot	string	The virtual host's document root.  <b>Note</b> : We introduced this return in cPanel & WHM version 54.  The function returns this value in the unnamed array.	A valid document root path.	/home/blee/public_html
version	string	The virtual host's PHP version.  The function returns this value in the unnamed array.	<ul style="list-style-type: none"> <li>• ea-php54</li> <li>• ea-php55</li> <li>• ea-php56</li> <li>• ea-php70</li> <li>• ea-php71</li> <li>• ea-php72</li> <li>• inherit</li> <li>• Any custom PHP package name.</li> </ul>	ea-php70
vhost	string	The virtual host's name.  The function returns this value in the unnamed array.	A valid hostname.	blee.com
account	string	The account's name.  The function returns this value in the unnamed array.	A valid cPanel account on the server.	blee
account_owner	string	The account's owner.  The function returns this value in the unnamed array.	A valid cPanel account on the server.	blee
main_domain	Boolean		<ul style="list-style-type: none"> <li>• True — The primary domain.</li> <li>• False — Not the primary domain.</li> </ul>	True

**N**  
**o**  
**t**  
**e**  
**:**



s

LangPHP:: php\_get\_system\_default\_version

LangPHP:: php\_get\_vhost\_versions

LangPHP:: php\_ini\_get\_user\_basic\_directives

LangPHP:: php\_ini\_get\_user\_content

LangPHP:: php\_ini\_get\_user\_paths

LangPHP:: php\_ini\_set\_user\_basic\_directives

LangPHP:: php\_ini\_set\_user\_content

LangPHP:: php\_set\_vhost\_versions

▼ LastLogin

LastLogin:: get\_last\_or\_current\_logged\_in\_ip

▼ Locale

Locale:: get\_attributes

▼ Mailboxes

Mailboxes:: expunge\_mailbox\_messages

Mailboxes:: expunge\_messages\_for\_mailbox\_guid

Mailboxes:: get\_mailbox\_status

Mailboxes:: has\_utf8\_mailbox\_names

Mailboxes:: set\_utf8\_mailbox\_names

▼ Market

Market:: cancel\_pending\_ssl\_certificate

Market:: create\_shopping\_cart

Market:: get\_all\_products

Market:: get\_certificate\_status\_details

Market:: get\_login\_url

Market:: get\_pending\_ssl\_certificates

Whether the virtual host is the primary domain.

**Note**

: We introduced this return in cPanel & WHM version 54.

The function returns this value in the unnamed array.

I  
n  
c  
P  
a  
n  
e  
l  
&  
W  
H  
M  
v  
e  
r  
s  
i  
o  
n  
6  
0  
a  
n  
d  
e  
a  
r  
l  
i  
e  
r  
,  
t  
h  
i  
s  
f  
u  
n  
c  
t  
i  
o  
n  
r  
e  
t  
u  
r  
n  
s  
t  
h  
e  
f  
o  
l  
l  
o  
w  
i  
n  
g  
p  
o  
s  
s  
i  
b  
l  
e  
v  
a  
l  
u  
e  
s  
:

Market:: get\_provider\_specific\_dcvs\_constraints

Market:: get\_providers\_list

Market:: get\_ssl\_certificate\_if\_available

Market:: process\_ssl\_pending\_queue

Market:: request\_ssl\_certificates

Market:: set\_status\_of\_pending\_queue\_items

Market:: set\_url\_after\_checkout

Market:: validate\_login\_token

▼ Mime

Mime:: add\_handler

Mime:: add\_hotlink

Mime:: add\_mime

Mime:: add\_redirect

Mime:: delete\_handler

Mime:: delete\_hotlink

Mime:: delete\_mime

Mime:: delete\_redirect

Mime:: list\_handlers

Mime:: list\_hotlinks

Mime:: list\_mime

Mime:: list\_redirects

Mime:: redirect\_info

▼ ModSecurity

ModSecurity:: disable\_all\_domains

ModSecurity:: disable\_domains

ModSecurity:: enable\_all\_domains

ModSecurity:: enable\_domains

				<ul style="list-style-type: none"> <li>• 1 — The primary domain.</li> <li>• 0 — Not the primary domain.</li> </ul>
homedir	string	<p>The virtual host's home directory.</p> <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;"> <p><b>Note</b> : We introduced this return in cPanel &amp; WHM version 54.</p> </div> <p>The function returns this value in the unnamed array.</p>	A valid home directory.	/home/blee
php_fpm_pool_parms	hash	<p>A hash that contains the domain's PHP-FPM parameters.</p> <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;"> <p><b>Note</b> : We introduced this return in cPanel &amp; WHM version 58.</p> </div> <p>The function returns this value in the unnamed array.</p>	A hash that contains the pm_max_children, pm_process_idle_timeout, and pm_max_requests returns.	
pm_max_children	integer	<p>The maximum number of child pages per pool.</p> <p>The function returns this value in the php_fpm_pool_parms hash.</p>	A valid number of child pages.	5

ModSecurity:: has\_modsecurity\_installed

ModSecurity:: list\_domains

▼ Mysql

Mysql:: add\_host

Mysql:: add\_host\_note

Mysql:: check\_database

Mysql:: create\_database

Mysql:: create\_user

Mysql:: delete\_database

Mysql:: delete\_host

Mysql:: delete\_user

Mysql:: get\_host\_notes

Mysql:: get\_privileges\_on\_database

Mysql:: get\_restrictions

Mysql:: get\_server\_information

Mysql:: locate\_server

Mysql:: rename\_database

Mysql:: rename\_user

Mysql:: repair\_database

Mysql:: revoke\_access\_to\_database

Mysql:: set\_password

Mysql:: set\_privileges\_on\_database

▼ Notifications

Notifications:: get\_notifications\_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile\_relative\_uri

<p>p m - p r o c e s s - i d l e - t i m e o u t</p>	<p>integer</p>	<p>A specified time of idleness before the system kills an FPM child process.</p> <p>The function returns this value in the <code>php_fpm_pool_params</code> hash.</p>	<p>A valid timeout value.</p>	<p>10</p>
<p>p m - m a x - r e q u e s t s</p>	<p>integer</p>	<p>The maximum number of requests per pool.</p> <p>The function returns this value in the <code>php_fpm_pool_params</code> hash.</p>	<p>A valid number of requests.</p>	<p>20</p>
<p>php_fpm</p>	<p>Boolean</p>	<p>Whether FPM is enabled on the virtual host.</p> <div data-bbox="734 1129 870 1541" style="border: 1px solid orange; padding: 5px;"> <p><b>Note</b> : We introduced this return in cPanel &amp; WHM version 60.</p> </div> <p>The function returns this value in the unnamed array.</p>	<ul style="list-style-type: none"> <li>• True — PHP-FPM enabled.</li> <li>• False — PHP-FPM not enabled.</li> </ul> <div data-bbox="935 1226 1029 1965" style="border: 1px solid orange; padding: 5px;"> <p><b>Note</b> : :</p> </div>	<p>1</p>

- PassengerApps:: disable\_application
  - PassengerApps:: edit\_application
  - PassengerApps:: enable\_application
  - PassengerApps:: ensure\_deps
  - PassengerApps:: list\_applications
  - PassengerApps:: register\_application
  - PassengerApps:: unregister\_application
- PasswdStrength:: get\_required\_strength
- Personalization::set
  - Personalization::get
- Postgresql:: create\_database
  - Postgresql:: create\_user
  - Postgresql:: delete\_database
  - Postgresql:: get\_restrictions
  - Postgresql:: grant\_all\_privileges
  - Postgresql:: rename\_database
  - Postgresql:: rename\_user
  - Postgresql:: rename\_user\_no\_password
  - Postgresql:: revoke\_all\_privileges
  - Postgresql:: set\_password
- Pushbullet:: send\_test\_message
- Quota:: get\_quota\_info

IncPanel & WHM version 6.0 and earlier, this function returns the following positions:

- Resellers
  - Resellers:: list\_accounts
- ResourceUsage
  - ResourceUsage:: get\_usages
- Restore
  - Restore:: directory\_listing
  - Restore:: get\_users
  - Restore:: query\_file\_info
  - Restore:: restore\_file
- Session
  - Session:: create\_temp\_user
- SiteTemplates
  - SiteTemplates:: list\_site\_templates
  - SiteTemplates:: list\_user\_settings
  - SiteTemplates:: publish
- SpamAssassin
  - SpamAssassin :: clear\_spam\_box
  - SpamAssassin:: get\_symbolic\_test\_names
  - SpamAssassin:: get\_user\_preferences
  - SpamAssassin:: update\_user\_preference
- SSH
  - SSH:: get\_port
- SSL
  - SSL:: add\_autossl\_excluded\_domains
  - SSL:: can\_ssl\_redirect
  - SSL:: check\_shared\_cert
  - SSL:: delete\_cert
  - SSL:: delete\_csr
  - SSL:: delete\_key
  - SSL:: delete\_ssl
  - SSL :: disable\_mail\_sni

				<ul style="list-style-type: none"> <li>1 — PHP-FPM enabled.</li> <li>0 — PHP-FPM not enabled.</li> </ul>
phpversion_source	array	How the virtual host determines its PHP version.	<p><b>Note</b>:</p> <ul style="list-style-type: none"> <li>• We intend to produce this series returning cPanel &amp; WHM version 62.</li> </ul>	<p>An array that contains either the system default or domain in return.</p> <p><b>Note</b>: In cPanel &amp; WHM version 62, this function returns one of the following values:</p>

SSL:: enable\_mail\_sni  
 SSL:: fetch\_best\_for\_domain  
 SSL:: fetch\_cert\_info  
 SSL:: fetch\_certificates\_for\_fqdns  
 SSL:: fetch\_key\_and\_cabundle\_for\_certificate  
 SSL:: find\_certificates\_for\_key  
 SSL:: find\_csrs\_for\_key  
 SSL:: generate\_certificate  
 SSL:: generate\_csr  
 SSL:: generate\_key  
 SSL:: get\_autossl\_excluded\_domains  
 SSL:: get\_autossl\_pending\_queue  
 SSL:: get\_autossl\_problems  
 SSL:: get\_cabundle  
 SSL:: get\_cn\_name  
 SSL:: install\_ssl  
 SSL:: installed\_host  
 SSL:: installed\_hosts  
 SSL:: is\_autossl\_check\_in\_progress  
 SSL:: is\_mail\_sni\_supported  
 SSL:: is\_sni\_supported  
 SSL:: list\_certs  
 SSL:: list\_csrs  
 SSL:: list\_keys  
 SSL:: list\_ssl\_items  
 SSL:: mail\_sni\_status  
 SSL:: rebuild\_mail\_sni\_config

- I n c P a n e l & W H M v e r s i o n 6 4 a n d l a t e r , t h i s v a l u e r e t u r n s a n a r r a y .
- s y s t e m : d e f a u l t . A n y v a l i d d o m a i n n a m e , i n d o m a i n : e x a m p l e . c o m f o r m a t .

The function returns this value in the unnamed array.

<p>d o m a i n</p>	<p>string</p>	<p>The domain the virtual host inherits its PHP version from.</p> <p>The function returns this value in the <code>php_versions_source</code> array.</p>	<p>Any valid domain name on the system.</p>	<p>blee.com</p>
--------------------	---------------	---	---	-----------------

SSL:: rebuildssldb  
 SSL:: remove\_autossl\_excluded\_domains  
 SSL:: set\_autossl\_excluded\_domains  
 SSL:: set\_cert\_friendly\_name  
 SSL:: set\_csr\_friendly\_name  
 SSL:: set\_key\_friendly\_name  
 SSL:: set\_primary\_ssl  
 SSL:: set\_ssl\_share  
 SSL:: show\_cert  
 SSL:: show\_csr  
 SSL:: show\_key  
 SSL:: start\_autossl\_check  
 SSL:: toggle\_ssl\_redirects\_for\_domains  
 SSL:: upload\_cert  
 SSL:: upload\_key  
 ▾ StatsBar  
   StatsBar:: get\_stats  
 ▾ Styles  
   Styles:: current  
   Styles:: list  
   Styles:: set\_default  
   Styles:: update  
 ▾ SubDomain  
   SubDomain:: add\_subdomain  
 ▾ Themes  
   Themes:: get\_theme\_base  
   Themes:: list  
   Themes:: update  
 ▾ Tokens  
   Tokens:: create\_full\_access  
   Tokens:: list  
   Tokens:: rename  
   Tokens:: revoke

<p>system default</p>	<p><i>integer</i></p>	<p>Whether the virtual host uses the system's default PHP version.</p> <p>The function returns this value in the <code>php_version_source</code> array.</p>	<ul style="list-style-type: none"> <li>1 — Uses the system default PHP version.</li> </ul> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p><b>Note</b> : The function <b>only</b> returns this value if true.</p> </div>	<p>1</p>
-----------------------	-----------------------	---	---	----------

▼ TwoFactorAuth

TwoFactorAuth:: generate\_user\_configuration

TwoFactorAuth:: get\_user\_configuration

TwoFactorAuth:: remove\_user\_configuration

TwoFactorAuth:: set\_user\_configuration

▼ UserManager

UserManager:: check\_account\_conflicts

UserManager:: create\_user

UserManager:: delete\_user

UserManager:: dismiss\_user

UserManager:: edit\_user

UserManager:: list\_users

UserManager:: lookup\_service\_account

UserManager:: lookup\_user

UserManager:: merge\_service\_account

UserManager:: unlink\_service\_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create



VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete\_user

WebDisk:: set\_homedir

WebDisk:: set\_password

WebDisk:: set\_permissions

▼ WebmailApps

WebmailApps:: list\_webmailapps

▼ WebVhosts

WebVhost:: list\_domains

WebVhost:: list\_ssl\_capable\_domains

▼ WordPressBackup

WordPressBackup:: any\_running

WordPressBackup:: cancel

WordPressBackup:: cleanup

WordPressBackup:: get\_available\_backups

WordPressBackup:: is\_running

WordPressBackup:: start

▼ WordPressInstance

Manager

WordPressInstanceManager:: cancel\_scan

WordPressInstanceManager:: cleanup\_scan

WordPressInstanceManager:: change\_admin\_password

WordPressInstanceManager:: configure\_autoupdate

WordPressInstanceManager:: get\_api\_version

WordPressInstanceManager:: get\_in

stance\_by\_id

WordPressInstanceManager::get\_instances

WordPressInstanceManager::get\_latest\_wordpress\_version\_from\_wordpress\_org

WordPressInstanceManager::get\_scan\_results

WordPressInstanceManager::is\_installable\_addon\_available

WordPressInstanceManager::start\_scan

▼ WordPressRestore

WordPressRestore::any\_running

WordPressRestore::cleanup

WordPressRestore::start