

cPanel API 1 Functions - BoxTrapper::messageaction

Guide to cPanel API 1

Return Data

cPanel Tags
(deprecated)

Bandwidth:
displayheader

Bandwidth:
displaybw

Bandwidth:
displayday

Bandwidth:
displaymainbwheder

BoxTrapper

BoxTrapper::chan
gestatus

BoxTrapper::clean
cfgfilelist

BoxTrapper::edit
msg

BoxTrapper::fetch
cfgfile

BoxTrapper::getb
oxconfdir

BoxTrapper::listm
sgs

BoxTrapper::logco
ntrols

BoxTrapper::mess
ageaction

BoxTrapper::multi
messageaction

BoxTrapper::reset
msg

BoxTrapper::save
cfgfile

BoxTrapper::save
conf

BoxTrapper::show
autowhitelist

BoxTrapper::show
emails

BoxTrapper::show
fromname

BoxTrapper::show
log

Description

This function performs an action on a message in the BoxTrapper queue.

Warning:

cPanel API 1 is **deprecated**. We **strongly** recommend that you **do not use** cPanel API 1. However, no equivalent function exists in our newer APIs.

Important:

In cPanel & WHM version 76 and later, when you disable the MailReceive role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
$boxtrapper_message_a  
ction =  
$cpanel->apil('BoxTra  
pper',  
'messageaction',  
array('user@example.c  
om', '',  
'example.msg',  
'deliverall,whitelist  
function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Function information

About this module

The Box Trapper module manages the BoxTrapper subsystem.

Note:

This module is a *BoxTrapper* feature.

```
BoxTrapper:: show
message

BoxTrapper:: show
queue

BoxTrapper:: show
queuesearch

BoxTrapper:: show
queuetime

BoxTrapper:: statu
s

BoxTrapper:: statu
sbutton
```

Branding

```
Branding:: file

Branding:: image

Branding:: killing

Branding:: setbran
dingpkg

Branding:: setmya
cctspkg

Branding:: setupdir
s

Branding:: tempset
brandingpkg
```

Cgi

```
Cgi:: backuplink

Cgi:: displayurchin

Cgi:: phpmyadminl
ink
```

Chkserverd

```
Chkserverd:: getexi
mport

Chkserverd:: getexi
mport_ssl
```

ClamScanner

```
ClamScanner:: bar
s
```

cPAddons

```
cPAddons:: mainp
g
```

Cron

```
Cron:: crontab_per
ms
```

CustInfo

```
CustInfo:: getemail
```

Denylp

```
Denylp:: adddenyi
p

Denylp:: deldenyip

Denylp:: listdenyi
ps
```

LiveAPI Perl Module

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

my
$boxtrapper_message_a
ction =
$cpliveapi->apil('Box
Trapper',
'messageaction',
['user@example.com',
'', 'example.msg',
'deliverall,whitelist
']) ; # Call the
function.
```

Note:
For more information, read our [Guide to the LiveAPI System](#).

cPanel Tag System (deprecated)

Warning:
In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We provide this example to help developers move from the old cPanel tag system to our [LiveAPI](#) system. We **strongly** recommend that you **only** use the LiveAPI system to call the cPanel APIs.

```
<cpanel
Module="BoxTrapper::m
essageaction(
$FORM('account','logd
ate','queuefile','act
ion') )">
```

About cPanel API 1

cPanel API 1 accesses information about cPanel accounts.

Warning:
cPanel API 1 is deprecated. We strongly recommend you use the cPanel API or UAPI instead.

Notes:

- The file `int` `ur` `mt` `us` `20` `or` `20` `).` `20` `or` `20` `).`

Find a function

- DiskUsage: show manager
- Email: addautoresponder
 - Email: addforward
 - Email: addfilter
 - Email: addlist
 - Email: addmx
 - Email: addpop
 - Email: addspam
 - Email: addspambox
 - Email: addspamfilter
 - Email: changemx
 - Email: checkfastmail
 - Email: checkpipewd
 - Email: clearspambox
 - Email: delautoresponder
 - Email: deldforward
 - Email: delfilter
 - Email: dellist
 - Email: delmx
 - Email: delpop
 - Email: delspam
 - Email: delspambox
 - Email: disable_spam_autodelete
 - Email: editquota
 - Email: enable_spam_autodelete
 - Email: getaging
 - Email: getarsbody
 - Email: getarscharset
 - Email: getarsfrom
 - Email: getarshtml
 - Email: getarsinterval

Command Line

```

cpapil
--user=username
BoxTrapper
messageaction
user@example.com ''
example.msg
deliverall,whitelist
```

Notes:

- You **must** URI-encode these values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to cPanel API 1 documentation](#) or run the `cpapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapil` command:

```

/usr/local
/cpanel/bin/cpapil
```

Output (none)

This function does not return output.

Parameters

Parameter	Type	Description	Possible values	Example
account	string	Required The account's email address.	A valid email address on the server.	user@example.com
logdate	string	Required The system does not use this parameter, and will ignore the value.	Any placeholder value.	''
queuefile	string	Required The email message's filename.	A valid filename.	example.msg

- This function enables Apache SpamAssassin™ for a cPanel account.
- **cPanel API 1 Functions - Email: addspamfilter** — This function modifies the minimum Apache SpamAssassin™ spam score.

Email: [getarsstart](#)
 Email: [getarsstop](#)
 Email: [getarssubject](#)
 Email: [getmailserver](#)
 Email: [getmailserveruser](#)
 Email: [getpopquota](#)
 Email: [has_spam_as_acl](#)
 Email: [has_spam_autodelete](#)
 Email: [listmaildomains](#)
 Email: [listmaildomainsopt](#)
 Email: [listmaildomainsoptndef](#)
 Email: [mainacctdiskused](#)
 Email: [passwdlist](#)
 Email: [passwdpop](#)
 Email: [setmxaccept](#)
 Email: [spamboxstatus](#)
 Email: [spamstatus](#)
 Email: [tracefilter](#)

▼ [Fileman](#)

Fileman: [changeperm](#)
 Fileman: [delfile](#)
 Fileman: [dofileop](#)
 Fileman: [emptytrash](#)
 Fileman: [extractfile](#)
 Fileman: [fileimg](#)
 Fileman: [fmmkdir](#)
 Fileman: [fmmkfile](#)
 Fileman: [fmpushfile](#)
 Fileman: [fmrename](#)
 Fileman: [fmsavefile](#)
 Fileman: [fmsaveht](#)

action	string	<p>Required</p> <p>The desired action.</p> <p>This parameter accepts multiple actions as a comma-separated list.</p>	<ul style="list-style-type: none"> blacklist — Blacklist the sender. delete — Delete the message. deleteall — Delete all messages from the sender. deliver — Deliver the message. deliverall — Deliver all messages from the sender. ignorelist — Add the sender to the ignore list. whitelist — Whitelist the sender. 	deliverall,whitelist
--------	--------	---	--	----------------------

Returns

This function does not return output.

- [cPanel API 1 Functions - Email:spamboxstatus](#) — This function checks whether Apache SpamAssassin™ Spam Box is enabled.
- [cPanel API 1 Functions - SpamAssassin::config](#) — This function prints the cPanel account's Apache SpamAssassin's™ default values.

mfile

Fileman:: fullbacku
p

Fileman:: getfile

Fileman:: htmledito
r

Fileman:: killdir

Fileman:: listfiles

Fileman:: listfullba
ckups

Fileman:: listtempl
ates

Fileman:: restoreaf

Fileman:: restored
b

Fileman:: restorefil
e

Fileman:: restorefil
es

Fileman:: savehtml
file

Fileman:: showper
m

Fileman:: uploadfil
es

Fileman:: viewfile

Frontpage

FrontPage:: addfp

FrontPage:: delfp

FrontPage:: fpstat
us

Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: ftpquota

Ftp:: ftpservernam
e

Ftp:: ftpstatslogin

Ftp:: get_anonftp

Ftp:: get_anonftpin

Ftp:: get_welcome
msg

Ftp:: getftpquota

Ftp:: kill_ftp_sessi
on

Ftp:: listftpstatsurl

Ftp:: passwdftp

- cPanel API 1 Modules - SpamAssassin — The SpamAssassin module modifies Apache SpamAssassin™ settings.

Ftp:: set_anonftp

Ftp:: set_anonftpin

Ftp:: set_welcome
msg

▼ Gpg

Gpg:: deletekey

Gpg:: exportkey

Gpg:: exportsecret
key

Gpg:: genkey

Gpg:: importkeys

▼ Htaccess

Htaccess:: checkpr
otected

Htaccess:: del_use
r

Htaccess:: getinde
x

Htaccess:: htdirls

Htaccess:: number
_of_users

Htaccess:: phpsele
ctable

Htaccess:: resnam
e

Htaccess:: set_pas
s

Htaccess:: set_pro
tect

Htaccess:: setinde
x

Htaccess:: setphpr
eference

Htaccess:: showus
ers

▼ ImageManager

ImageManager:: c
onvert

ImageManager:: di
mensions

ImageManager:: h
dimension

ImageManager:: s
cale

ImageManager:: th
umbnail

ImageManager:: w
dimension

▼ LastLogin

LastLogin:: lastlogi
n

▼ LeechProtect

LeechProtect:: disable

LeechProtect:: enable

LeechProtect:: setup

LeechProtect:: showpasswdfile

LeechProtect:: status

▼ LogManager

LogManager:: listdownloads

LogManager:: save settings

LogManager:: show settings

▼ MagicRevision

MagicRevision:: uri

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: del_handler

Mime:: del_hotlink

Mime:: del_mime

Mime:: del_redirect

Mime:: linkallownull

Mime:: linkenable

Mime:: linkexts

Mime:: linkrurl

Mime:: linkurls

▼ Mysql

Mysql:: adddb

Mysql:: addhost

Mysql:: adduser

Mysql:: adduserdb

Mysql:: checkdb

Mysql:: deldb

Mysql:: delhost

Mysql:: deluser

Mysql:: deluserdb

Mysql:: gethost
Mysql:: initcache
Mysql:: listdbs
Mysql:: listdbsopt
Mysql:: listusers
Mysql:: listusersopt
Mysql:: number_of
_dbs
Mysql:: number_of
_users
Mysql:: repairdb
Mysql:: routines
Mysql:: updatepriv
s

▼ Net

Net:: dnslookup
Net:: dnszone
Net:: sethastracero
ute

▼ News

News:: displaynew
s

▼ NVData

NVData:: set

▼ OptimizeWS

OptimizeWS:: load
optimizesettings
OptimizeWS:: load
optimizesettings (b
ytes)
OptimizeWS:: opti
mizews

▼ Park

Park:: disabledir
ect
Park:: getredirectu
rl
Park:: park
Park:: setredirectur
l
Park:: unpark

▼ Postgres

Postgres:: adddb
Postgres:: adduser
Postgres:: adduser
db
Postgres:: deldb
Postgres:: deluser

Postgres:: deluser
db

Postgres:: initcach
e

Postgres:: listdbso
pt

Postgres:: listusers
opt

Postgres:: number
_of_dbs

Postgres:: number
_of_users

▼ ProxyUtils

ProxyUtils:: proxya
ddress

▼ Resellers

Resellers:: accoun
tlistopt

Resellers:: themeli
stopt

▼ Serverinfo

Serverinfo:: servic
estatus

▼ SetLang

SetLang:: listlangs
opt

SetLang:: setlang

▼ SpamAssassin

SpamAssassin:: co
nfig

SpamAssassin:: sa
veconfig

▼ SSH

SSH:: getport

▼ SSL

SSL:: delete

SSL:: deletectr

SSL:: deletecsr

SSL:: deletekey

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcabundle

SSL:: getcname

SSL:: install

SSL:: installedhost

SSL:: listkeysopt

SSL:: showcrt

SSL:: showcsr

SSL:: showkey

SSL:: sslsharedsta
tus

SSL:: uploadcrt

SSL:: uploadkey

▼ StatManager

StatManager:: doF
orm

StatManager:: upd
ateUserConfig

▼ Stats

Stats:: analoglist

Stats:: awstats

Stats:: bwbar

Stats:: errlog

Stats:: lastvisitors

Stats:: showbandw
idth

Stats:: webalizer

Stats:: webalizerftp

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: cplist
subdomains

SubDomain:: disab
lesubrd

SubDomain:: listsu
bdomainsop

SubDomain:: setsu
burl

▼ UI

UI:: confirm

UI:: redirect

UI:: showresult