

# cPanel API 2 Functions - Ftp::delftp

Guide to cPanel API 2

Return Data

Filter and Sort Output

Paginate Output

Output Columns

Calls from the WHM API

cPanel Tags  
(**deprecated**)

AddonDo  
main:: add  
daddond

omain

AddonDomain:: del  
addondomain

AddonDomain:: list  
addondomains

## Backups

Backups:: listfullba  
ckups

## Bandwidth

Bandwidth:: addhtt  
pbandwidth

Bandwidth:: getbw  
data

Bandwidth:: getho  
urlyaveragebwover  
year

## BoxTrapper

BoxTrapper:: acco  
untmanagelist

## Branding

Branding:: addbra  
ndingobj

Branding:: applist

Branding:: brandin  
geditor

Branding:: createp  
kg

Branding:: cssmer  
ge

Branding:: delbran  
dingobj

Branding:: delpkg

Branding:: gensprit  
es

## Description

This function deletes an FTP account.

### Warning:

We **strongly** recommend that you use the following [UAPI](#) function instead of this function:

- `Ftp::delete_ftp` — This function deletes an FTP account.

### Important:

In cPanel & WHM version 76 and later, when you disable the `FTP` role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

## Examples [AddonDomain](#)

### WHM API (JSON)

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?cpanel_jsonapi_user=user&cpanel_jsonapi_version=2&cpanel_jsonapi_module=Ftp&cpanel_jsonapi_func=delftp&user=user&destroy=1
```

### Note:

For more information, read our [Calls from the WHM API](#) documentation.

## Function information

## About this module

The `Ftp` module manages FTP users, connections, and services.

Branding:: getbrandingpkg

Branding:: getbrandingpkgstatus

Branding:: getdefaultbrandingpkg

Branding:: installbrandingpkgs

Branding:: installimages

Branding:: killimages

Branding:: listingtypes

Branding:: listobjecttypes

Branding:: preloadconf

Branding:: resetall

Branding:: resetscss

Branding:: resethtml

Branding:: resolve\_file

Branding:: resolveocalcss

Branding:: saveocalcss

Branding:: setbrandingpkgstatus

Branding:: showpackages

Branding:: spritelist

#### ▼ CSVImport

CSVImport:: columnchoices

CSVImport:: configimport

CSVImport:: data

CSVImport:: fetchimportdata

CSVImport:: isenabled

CSVImport:: loaddata

CSVImport:: processdata

CSVImport:: sendcontact

CSVImport:: uploadimport

#### ▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.
```

```
// Delete the FTP  
user "user" along  
with its home  
directory  
$destroy_account =  
$cpanel->api2(  
    'ftp', 'delftp',  
    array(  
        'user' =>  
        'user',  
        'destroy' =>  
        '1',  
    )  
);
```

#### Note:

For more information, read our [Guide to the LiveAPI System](#).

## About cPanel API 2

cPanel API 2 accesses and modifies data for cPanel accounts.

#### Notes:

- The  
Fe  
  
int  
• Ur  
mi  
us  
20  
or  
20  
)'.  
20  
or  
20  
).

## Find a function

- Contactus:: isenab led
    - Contactus:: sendc ontact
  - Cron
    - Cron:: add\_line
    - Cron:: edit\_line
    - Cron:: fetchcron
    - Cron:: get\_email
    - Cron:: listcron
    - Cron:: remove\_line
    - Cron:: set\_email
  - CustInfo
    - CustInfo:: contacte mails
    - CustInfo:: contactp refs
    - CustInfo:: displayc ontactinfo
    - CustInfo:: savecon tactinfo
  - DBmap
    - DBmap:: status
    - DBmap:: version
  - DKIMUI
    - DKIMUI:: available
    - DKIMUI:: getrecor ds
    - DKIMUI:: install
    - DKIMUI:: installed
    - DKIMUI:: uninstall
  - Denylp
    - Denylp:: listdenyip s
  - DiskCounter
    - DiskCounter:: disk \_counter
  - DiskUsage
    - DiskUsage:: buildc ache
    - DiskUsage:: clearc ache
    - DiskUsage:: fetch\_ raw\_disk\_usage
    - DiskUsage:: fetchd iskusage
    - DiskUsage:: fetchd iskusagewithextras

## LiveAPI Perl Module

```

my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Delete the FTP user
"user" along with its
home directory
my $destroy_account =
$cpliveapi->api2(
'Ftp', 'delftp',
{
'user' =>
'user',
'destroy' =>
'1',
}
);

```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

## cPanel Tag System (deprecated)

**Warnings:**

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecat ed**. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Dep recated cPanel Tag Usage](#) docume ntation.

- cPan el API 2 Mod ules - FTP — The Ftp mod ule man ages FTP user s, conn ectio ns, and servi ces
- cPan el API 2 Func tions - Ftp:: addft p — This functi on creat es an FTP acco unt.
- cPan el API 2 Func tions - Ftp:: delft p — This functi on delet es an FTP acco unt.

### ▼ DnsLookup

DnsLookup:: name  
2ip

### ▼ DomainLookup

DomainLookup:: c  
ountbaseddomains

DomainLookup:: g  
etbaseddomains

DomainLookup:: g  
etdocroot

DomainLookup:: g  
etdocroots

DomainLookup:: g  
etmaindomain

### ▼ Email

Email:: accountna  
me

Email:: adddomain  
forward

Email:: addforward

Email:: addmx

Email:: addpop

Email:: browsebox  
es

Email:: changemx

Email:: checkmain  
discard

Email:: clearpopca  
che

Email:: deletefilter

Email:: delforward

Email:: delmx

Email:: delpop

Email:: disablefilter

Email:: editquota

Email:: enablefilter

Email:: fetchautore  
sponder

Email:: fetchcharm  
aps

Email:: filteractions

Email:: filterlist

Email:: filtername

Email:: filterrules

Email:: get\_archivi  
ng\_configuration

Email:: get\_archivi  
ng\_default\_configu

### ▼ Command Line

```
cpapi2  
--user=username Ftp  
delftp user=user  
destroy=1
```

#### Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- You **must** run the `--user=username` command.
- For more information and additional output options, read our [Guide to cPanel API 2](#) documentation or run the `cpapi2 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapi2` command:

```
/usr/local  
/cpanel/bi  
n/cpapi2
```

### ▼ Output (JSON)

```
{  
  "cpanelresult": {  
    "apiversion": 2,  
    "func": "delftp",  
    "data": [  
      {  
        "reason":  
"OK",  
        "result": 1  
      }  
    ],  
    "event": {  
      "result": 1  
    },  
    "module": "Ftp"  
  }  
}
```

- cPanel API 2 Functions - Ftp::listftp  
— This function lists an account's FTP users.
- cPanel API 2 Functions - Ftp::listftp sessions  
— This function lists an account's active FTP sessions.

ration

Email: `get_archiving_types`

Email: `get_default_email_quota`

Email: `get_email_signing`

Email: `get_max_email_quota`

Email: `getabsbrowsedir`

Email: `getalwaysaccept`

Email: `getdiskusage`

Email: `getmxcheck`

Email: `has_delegated_mailman_lists`

Email: `list_system_filter_info`

Email: `listaliasbackups`

Email: `listautoresponders`

Email: `listdefaultaddresses`

Email: `listdomainforwards`

Email: `listfilterbackups`

Email: `listfilters`

Email: `listforwards`

Email: `listlists`

Email: `listmaildomains`

Email: `listmx`

Email: `listmxs`

Email: `listpops`

Email: `listpopssingle`

Email: `listpopswithdisk`

Email: `listpopswithimage`

Email: `loadfilter`

Email: `passwdpop`

Email: `reorderfilters`

**Note:**

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

## Parameters

Parameters	Type	Description	Possible values	Example
<code>user</code>	<i>string</i>	<b>Required</b> The FTP account's username.	Any valid username.	<code>user</code>
<code>domain</code>	<i>string</i>	The user's associated domain.  This parameter defaults to the cPanel account's primary domain.	A domain that the cPanel account owns.	<code>example.com</code>
<code>destroy</code>	<i>Boolean</i>	<b>Required</b> Whether to delete the account's FTP directory.	<ul style="list-style-type: none"><li>1 — Delete the FTP directory.</li><li>0 — Maintain the FTP directory.</li></ul>	<code>1</code>

## Returns

Return	Type	Description	Possible values	Example
<code>reason</code>	<i>string</i>	A reason for failure.  <b>Note:</b> This function only returns a reason value if it failed.	A string that describes the error.	This is an error message.

Email:: `set_archiving_configuration`

Email:: `set_archiving_default_configuration`

Email:: `set_email_signing`

Email:: `setalwaysaccept`

Email:: `setdefaultaddress`

Email:: `setmxcheck`

Email:: `storefilter`

Email:: `tracefilter`

▼ EmailTrack

EmailTrack:: `search`

EmailTrack:: `stats`

EmailTrack:: `trace`

▼ Encoding

Encoding:: `get_encodings`

Encoding:: `guess_file`

Encoding:: `guess_file_opts`

▼ FSTest

FSTest:: `dirisempty`

▼ Fileman

Fileman:: `autocomplete_dir`

Fileman:: `fileop`

Fileman:: `getabsdir`

Fileman:: `getdir`

Fileman:: `getdiractions`

Fileman:: `getdiskinfo`

Fileman:: `geteditty_pe`

Fileman:: `getfileactions`

Fileman:: `getpath`

Fileman:: `listfiles`

Fileman:: `mkdir`

Fileman:: `mkfile`

Fileman:: `savefile`

result	<i>Boolean</i>	Whether the function succeeded.	<ul style="list-style-type: none"><li>• 1 — The function succeeded.</li><li>• 0 — The function failed.</li></ul>	1
--------	----------------	---------------------------------	--	---

Fileman:: search

Fileman:: statfiles

Fileman:: uploadfiles

Fileman:: viewfile

▼ ForcePassword

ForcePassword:: get\_force\_password\_flags

ForcePassword:: update\_force\_password\_flags

▼ Frontpage

Frontpage:: fpenabled

Frontpage:: list

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: listftp

Ftp:: listftpsessions

Ftp:: listftpwithdisk

Ftp:: passwd

Ftp:: setquota

▼ Gpg

Gpg:: listgpgkeys

Gpg:: listsecretgpgkeys

Gpg:: number\_of\_private\_keys

Gpg:: number\_of\_public\_keys

▼ Htaccess

Htaccess:: listuser

Htaccess:: listusers

▼ HttpUtils

HttpUtils:: getdirindices

▼ ImageManager

ImageManager:: thumbnail

▼ LVEInfo

LVEInfo:: getUsage

▼ LangMods

LangMods:: getarcname

LangMods:: getkey

LangMods:: getpre  
fix

LangMods:: install

LangMods:: langlis  
t

LangMods:: list\_av  
ailable

LangMods:: list\_in  
stalled

LangMods:: magic  
\_status

LangMods:: pre\_ru  
n

LangMods:: search

LangMods:: setup

LangMods:: uninst  
all

LangMods:: updat  
e

▼ LeechProtect

LeechProtect:: set  
up

▼ Locale

Locale:: get\_encod  
ing

Locale:: get\_html\_  
dir\_attr

Locale:: get\_locale  
\_name

Locale:: get\_user\_  
locale

Locale:: get\_user\_  
locale\_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse  
r

Logaholic:: adduse  
rprofile

Logaholic:: deleteu  
ser

Logaholic:: deleteu  
serprofile

Logaholic:: edituse  
r

Logaholic:: fetchus  
er

Logaholic:: listuser  
profiles

Logaholic:: logahol  
iclink



Logaholic:: proces  
sstats

▼ Mime

Mime:: list\_hotlinks

Mime:: listhandlers

Mime:: listmime

Mime:: listredirects

Mime:: redirectname

Mime:: redirecturlname

▼ MysqlFE

MysqlFE:: authorizehost

MysqlFE:: change  
dbuserpassword

MysqlFE:: created  
b

MysqlFE:: created  
buser

MysqlFE:: dbuserexists

MysqlFE:: deauthorizehost

MysqlFE:: deleted  
b

MysqlFE:: deleted  
buser

MysqlFE:: getalldb  
sinfo

MysqlFE:: getalldb  
usersanddbs

MysqlFE:: getdbuserprivileges

MysqlFE:: getdbusers

MysqlFE:: gethosts

MysqlFE:: getmysqlprivileges

MysqlFE:: getmysqlserverprivileges

MysqlFE:: has\_my  
cnf\_for\_cpuser

MysqlFE:: listdbs

MysqlFE:: listdbsback  
up

MysqlFE:: listhosts

MysqlFE:: listusers

MysqlFE:: listusers  
indb

MysqlFE:: revoked  
buserprivileges

MysqlFE:: setdbu  
erprivileges

MysqlFE:: userdbp  
rivs

▼ MysqlOptimizer

MysqlOptimizer:: f  
etch\_slow\_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does\_news  
\_exist

News:: does\_news  
\_type\_exist

News:: get\_news

▼ PHPINI

PHPINI:: getallopti  
ons

PHPINI:: getoption  
s

▼ Park

Park:: listaddondo  
mains

Park:: listparkeddo  
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change\_  
password

Passwd:: set\_dige  
st\_auth

▼ PasswdStrength

PasswdStrength::  
appstrengths

PasswdStrength::  
get\_password\_stre  
ngth

PasswdStrength::  
get\_required\_stren  
gth

▼ Postgres

Postgres:: listdbs

Postgres:: listusers

Postgres:: listusers  
indb

Postgres:: userexi  
sts

▼ Rand

Rand:: getranddat  
a

▼ Resellers

Resellers:: get\_su  
b\_accounts

▼ RoR

RoR:: addapp

RoR:: changeapp

RoR:: importrails

RoR:: listapps

RoR:: listrewrites

RoR:: needsimport

RoR:: removeapp

RoR:: removerewri  
te

RoR:: restartapp

RoR:: setuprewrite

RoR:: softrestartap  
p

RoR:: startapp

RoR:: stopapp

▼ SetLang

SetLang:: setlocale

▼ SourceIPCheck

SourceIPCheck:: a  
ddip

SourceIPCheck:: d  
elip

SourceIPCheck:: g  
etaccount

SourceIPCheck:: li  
stips

SourceIPCheck:: l  
oadsecquestions

SourceIPCheck:: r  
esetsecquestions

SourceIPCheck:: s  
amplequestions

SourceIPCheck:: s  
avesecquestions

▼ SPFUJ

SPFUJ:: available

SPFUJ:: count\_sett  
ings

SPFUI:: entries\_co  
mplete

SPFUI:: get\_raw\_r  
ecord

SPFUI:: getmainse  
rverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list\_settin  
gs

SPFUI:: load\_curr  
ent\_values

SPFUI:: uninstall

▼ SSH

SSH:: authkey

SSH:: converttopp  
k

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey\_leg  
acy

SSH:: importkey

SSH:: listkeys

▼ SSL

SSL:: fetchcabundl  
e

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcnname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

▼ SSLInfo

SSLInfo:: fetchinfo

▼ StatCache

StatCache:: clearc  
ache

▼ Stats

Stats:: getmonthly

bandwidth

Stats:: getmonthly  
domainbandwidth

Stats:: getthismont  
hsbwusage

Stats:: lastapache  
hits

Stats:: lastvisitors

Stats:: listanalog

Stats:: listawstats

Stats:: listlastvisito  
rs

Stats:: listrawlogs

Stats:: listurchin

Stats:: listwebalize  
r

▼ StatsBar

StatsBar:: getrowc  
ounter

StatsBar:: rowcoun  
ter

StatsBar:: setrowc  
ounter

StatsBar:: stat

▼ SubDomain

SubDomain:: adds  
ubdomain

SubDomain:: chan  
gedocroot

SubDomain:: delsu  
bdomain

SubDomain:: getre  
servedsubdomains

SubDomain:: listsu  
bdomains

SubDomain:: validr  
egex

▼ Themes

Themes:: apply\_n  
ew\_theme

Themes:: does\_cp  
anel\_theme\_exist

Themes:: get\_avail  
able\_themes

Themes:: get\_the  
mes\_list

Themes:: restore\_  
saved\_theme

▼ UI

UI:: dynamicinclud  
elist

UI:: includelist

UI:: listform

UI:: paginate

UI:: paginate\_list

▼ UserHttpUtils

UserHttpUtils:: get  
dirindices

▼ WebDisk

WebDisk:: addweb  
disk

WebDisk:: delweb  
disk

WebDisk:: hasdige  
st

WebDisk:: listwebd  
isks

WebDisk:: passwd  
webdisk

WebDisk:: set\_dig  
est\_auth

WebDisk:: set\_ho  
mdir

WebDisk:: set\_per  
ms

WebDisk:: setstatu  
s

▼ WebmailApps

WebmailApps:: list  
webmailapps

▼ ZoneEdit

ZoneEdit:: add\_zo  
ne\_record

ZoneEdit:: edit\_zo  
ne\_record

ZoneEdit:: fetch\_c  
panel\_generated\_  
domains

ZoneEdit:: fetchzo  
ne

ZoneEdit:: fetchzo  
ne\_records

ZoneEdit:: fetchzo  
nes

ZoneEdit:: get\_zon  
e\_record

ZoneEdit:: remove  
\_zone\_record

ZoneEdit:: resetzo  
ne

