

WHM API 1 - Filter Output

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

Introduction

You can use additional variables to filter WHM API 1 output.

Notes:

You can test WHM API 1 functions in WHM's *API Shell* interface (*Home >> Development >> API Shell*). Click *Show Sort/Filter/Paginate Options* to display the additional text boxes.

Filter output

WHM API 1 filters use four basic variables:

Variable	Type	Description	Possible values
<code>api.filter.enable</code>	<i>Boolean</i>	Whether to enable filtering.	<ul style="list-style-type: none">1 — Enable filtering.0 — Disable filtering.
<code>api.filter.a.field</code>	<i>string</i>	The return to match against.	The name of one of the function's returns.
<code>api.filter.a.arg0</code>	<i>string</i>	The return value to match.	An integer or string value.

- Account Restoration on restore_modules_summary
- restore_queue_activate
- restore_queue_add_task
- restore_queue_clear_all_completed_tasks
- restore_queue_clear_all_failed_tasks
- restore_queue_clear_all_pending_tasks
- restore_queue_clear_all_tasks
- restore_queue_clear_completed_task
- restore_queue_clear_pending_task
- restore_queue_is_active
- restore_queue_list_active
- restore_queue_list_completed
- restore_queue

WHM API 1 Basics

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Sc
- ro
- us
- Yc
- mi
- us
- 20
- or
- 20
-) t

Related Documentation

- ue_list_pending
- restore_queue_state
- restoreaccount
- verify_new_username_for_restore
- ▼ Accounts
- accountsummary
- applist
- createacct
- domainuserdata
- editquota
- forcepasswordchange
- get_disk_usage
- get_domain_info
- getdomainowner
- has_digest_auth
- has_myconf_or_cpuser
- limitbw
- list_users
- listaccts
- listlockedaccounts
- listsuspended
- modifyacct
- myprivs
- passwd
- quota_enabled
- removeacct
- set_digest_auth
- showbw
- suspendacct
- unsuspendacct
- untrack_acct

api.filter.a.type	<i>string</i>	<p>The match type.</p> <ul style="list-style-type: none"> • If the <code>api.filter.a.arg0</code> value is a string, use a string operator. • If the <code>api.filter.a.arg0</code> value is an integer, use a numeric operator. <p>This variable defaults to <code>contains</code>.</p>	<p>Numeric operators:</p> <ul style="list-style-type: none"> • <code>==</code> — The numeric value is equal to the match value. • <code>lt</code> — The value is less than the match value. This match type can not handle unlimited values. • <code>lt_handle_unlimited</code> — The value is less than the match value. This match type can handle unlimited values. • <code>gt</code> — The value is greater than the match value. This match type can not handle unlimited values. • <code>gt_handle_unlimited</code> — The value is greater than the match value. This match type can handle unlimited values. <p>String operators:</p> <ul style="list-style-type: none"> • <code>begins</code> — The value begins with the match value's string. • <code>contains</code> — The value contains the match value's string. • <code>eq</code> — The string value is equal to the match value.
-------------------	---------------	--	--

Examples

The following example function calls execute the `listaccts` function and filter the results to return only accounts with a maximum of 400 subdomains:

JSON API XML APICommand Line

```

json-api/listaccts?api.version=1&api.filter.a.field=maxsub&api.filter.a.arg0=400&api.filter.a.type=%3D%3D&api.filter.enable=1
```

Important:

- WHM API 1 Functions - list_config_cluster_servers — This function lists the servers in the server's configuration cluster.
- WHM API 1 Functions - update_config_cluster_server — This function updates the username or remote access key for a cluster server.

_id
verify_new_username

▼ Addon Domains

convert_addon_fetch_conversion_details

convert_addon_fetch_domain_details

convert_addon_get_conversion_status

convert_addon_initiate_conversion

convert_addon_list_domains

convert_addon_list_conversions

▼ Authentication

api_token_create

api_token_list

api_token_revoke

api_token_update

disable_authentication_provider

disable_failing_authentication_providers

enable_authentication_provider

get_available_authentication_providers

get_login_url

get_provider_client_configurations

get_provider_configuration_fields

get_provider_display_co

cPanel & WHM version 66 **deprecated** XML output.

```
xml-api/listaccts?api.version=1&api.filter.a.field=maxsub&api.filter.a.arg0=400&api.filter.a.type=%3D%3D&api.filter.enable=1
```

```
whmapil listaccts api.filter.enable=1  
api.filter.a.field=maxsub  
api.filter.a.arg0=400  
api.filter.a.type=%3D%3D
```

Use multiple filters

To use multiple filters on a single WHM API 1 call, increment the letter in each filter variable.

For example, use the following variables to pass two sets of filter information:

- Pass the first set of filter information to the `api.filter.a.field`, `api.filter.a.arg0`, and `api.filter.a.type` variables.
- Pass the second set of filter information to the `api.filter.b.field`, `api.filter.b.arg0`, and `api.filter.b.type` variables

Note:

Do **not** include more than one `api.filter.enable` Boolean variable.

Examples

The following example function calls execute the `listaccts` function and filter the results to return only accounts with a maximum of 400 subdomains that use the `paper_lantern` theme:

JSON API XML API Command Line

```
json-api/listaccts?api.version=1&api.filter.a.field=maxsub&api.filter.a.arg0=400&api.filter.a.type=%3D%3D&api.filter.b.field=theme&api.filter.b.arg0=paper_lantern&api.filter.b.type=eq&api.filter.enable=1
```

Remember:

cPanel & WHM version 66 **deprecated** XML output.

- WHM API 1 Functions - delete_configmaster_server — This function removes a server from a configuration cluster.
- WHM API 1 Functions - add_configmaster_server — This function adds a server to a configuration cluster.

nfigurations

get_users_authn_linked_accounts

link_user_authn_provider

set_provider_client_configurations

set_provider_display_configurations

twofactorauth_disable_policy

twofactorauth_enable_policy

twofactorauth_generate_tfa_config

twofactorauth_get_issuer

twofactorauth_get_user_configs

twofactorauth_policy_status

twofactorauth_remove_user_config

twofactorauth_set_issuer

twofactorauth_set_tfa_config

unlink_user_authn_provider

validate_login_token

▼ Backups

backup_config_get

backup_config_set

backup_data_list

backup_destination_add

backup_destination_delete

```
xml-api/listaccts?api.version=1&api.filter.a.field=maxsub&api.filter.a.arg0=400&api.filter.a.type=%3D%3D&api.filter.b.field=theme&api.filter.b.arg0=paper_lantern&api.filter.b.type=eq&api.filter.enable=1
```

```
whmapi1 listaccts api.filter.enable=1  
api.filter.a.field=maxsub  
api.filter.a.arg0=400  
api.filter.a.type=%3D%3D  
api.filter.b.field=theme  
api.filter.b.arg=paper_lantern  
api.filter.b.type=eq
```

- WHM API 1 Functions - abort_transfer_session — This function aborts an active transfer session.

backup_dest
ination_get

backup_dest
ination_list

backup_dest
ination_set

backup_dest
ination_valid
ate

backup_get
_transport_s
tatus

backup_list_
transported

backup_set_
list

backup_set_
list_combine
d

backup_skip
_users_all

backup_skip
_users_all_s
tatus

backup_use
r_list

convert_and
_migrate_fro
m_legacy_c
onfig

get_users_w
ith_backup_
metadata

list_cparchiv
e_files

start_backgr
ound_pkgac
t

toggle_user
_backup_sta
te

▼ cPHulk

cphulk_statu
s

create_cphu
lk_record

delete_cphu
lk_record

disable_cph
ulk

enable_cph
ulk

flush_cphulk
_login_histo
ry

flush_cphulk
_login_histo
ry_for_ips

get_countrie
s_with_kno
wn_ip_rang
es

get_cphulk_
brutes

get_cphulk_
excessive_b
rutes

get_cphulk_
failed_logins

get_cphulk_
user_brutes

load_cphulk
_config

read_cphulk
_records

save_cphulk
_config

set_cphulk_
config_key

▼ Databases

background
_mysql_upg
rade_status

current_mys
ql_version

installable_
mysql_versi
ons

latest_availa
ble_mysql_v
ersion

list_databas
e_users

list_databas
es

list_mysql_d
atabases_a
nd_users

remote_mys
ql_create_pr
ofile

remote_mys
ql_create_pr
ofile_via_ss
h

remote_mys
ql_delete_pr
ofile

remote_mys
ql_initiate_p
rofile_activat

ion

remote_mysql_monitor_profile_activation

remote_mysql_read_profile

remote_mysql_read_profiles

remote_mysql_update_profile

remote_mysql_validate_profile

rename_mysql_database

rename_mysql_user

rename_postgresql_database

rename_postgresql_user

set_local_mysql_root_password

set_mysql_password

set_postgresql_password

start_background_mysql_upgrade

▼ DNS

adddns

addzonerecord

addzonerecord
(Reverse DNS)

dumpzone

editzonerecord

get_nameserver_config

getzonerecord

has_local_authority

killdns
listmxs
listzones
lookupnsip
lookupnsips
removezone
record
resetzone
resolvedom
ainname
savemxs
setresolvers
update_nam
eservers_co
nfig

▼ EasyApache

ea4_get_cur
rently_install
ed_packages

ea4_get_ea
_pkgs_state

ea4_list_pro
files

ea4_metainf
o

ea4_migrati
on

ea4_pre_mi
grate_check

ea4_recom
mendations

ea4_save_p
rofile

ea4_tomcat
85_add

ea4_tomcat
85_list

ea4_tomcat
85_rem

▼ Greylisting

cpgreylist_is
_server_net
block_truste
d

cpgreylist_li
st_entries_f
or_common
_mail_provid
er

cpgreylist_lo
ad_common
_mail_provid

ers_config

cpgreylist_s
ave_commo
n_mail_provi
ders_config

cpgreylist_st
atus

cpgreylist_tr
ust_entries_
for_common
_mail_provid
er

cpgreylist_u
ntrust_entrie
s_for_comm
on_mail_pro
vider

create_cpgr
eylist_truste
d_host

delete_cpgr
eylist_truste
d_host

disable_cpgr
eylist

enable_cpgr
eylist

load_cpgreyl
ist_config

read_cpgrey
list_deferred
_entries

read_cpgrey
list_trusted_
host

save_cpgrey
list_config

▼ Integration

batch

cpanel

create_integ
ration_group

create_integ
ration_link

get_integrati
on_link_user
_config

list_integrati
on_groups

list_integrati
on_links

remove_inte
gration_grou
p

remove_inte

gration_link

update_inte
gration_link
_token

▼ IP Addresses

addips

delip

get_public_i
p

get_shared_
ip

ipv6_disable
_account

ipv6_enable
_account

ipv6_range_
add

ipv6_range_
edit

ipv6_range_
list

ipv6_range_
remove

ipv6_range_
usage

listips

nat_checkip

nat_set_pub
lic_ip

setsiteip

▼ Mail

disable_dki
m

disable_mail
_sni

emailtrack_s
earch

emailtrack_s
tats

emailtrack_u
ser_stats

enable_dkim

enable_mail
_sni

ensure_dki
m_keys_exi
st

exim_config
uration_che
ck

expunge_m

ailbox_messages
expunge_messages_for_mailbox_guid
fetch_dkim_private_keys
fetch_mail_queue
generate_mobileconfig
get_mailbox_status
get_mailbox_status_list
get_unique_recipient_count_per_sender_for_user
get_unique_sender_recipient_count_per_user
get_user_email_forward_destination
hold_outgoing_email
install_dkim_private_keys
install_spf_records
is_sni_supported
list_pops_for
mail_sni_status
rebuild_mail_sni_config
release_outgoing_email
save_spamd_config
set_user_email_forward_destination
suspend_outgoing_email
unsuspend_outgoing_email

validate_currency_installed_exim_configuration

validate_currency_dkims

validate_currency_ptrs

validate_currency_spfs

validate_exim_configuration_syntax

▼ Market

disable_market_provider

enable_market_provider

get_adjusted_market_providers_products

get_market_providers_commission_config

get_market_providers_list

get_market_providers_product_metadata

get_market_providers_products

set_market_product_attribute

set_market_provider_commission_id

▼ ModSecurity™

modsec_add_rule

modsec_add_vendor

modsec_assemble_config_text

modsec_batch_settings

modsec_check_rule

modsec_clone_rule

modsec_de
ploy_all_rule
_changes

modsec_de
ploy_rule_ch
anges

modsec_de
ploy_setting
s_changes

modsec_dis
able_rule

modsec_dis
able_vendor

modsec_dis
able_vendor
_configs

modsec_dis
able_vendor
_updates

modsec_dis
card_all_rul
e_changes

modsec_dis
card_rule_c
hanges

modsec_edit
_rule

modsec_en
able_vendor

modsec_en
able_vendor
_configs

modsec_en
able_vendor
_updates

modsec_get
_config_text

modsec_get
_configs

modsec_get
_configs_wit
h_changes_
pending

modsec_get
_log

modsec_get
_rules

modsec_get
_settings

modsec_get
_vendors

modsec_is_i
nstalled

modsec_ma
ke_config_a
ctive

modsec_make_config_inactive

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set_config_text

modsec_set_setting

modsec_disable_rule

modsec_update_vendor

▼ Packages

_getpkgextensionform

add_override_features_for_user

addpkg

addpkgext

changepackage

create_feature_relist

delete_feature_relist

delpkgext

editpkg

get_available_applications

get_available_featurelists

get_feature_metadata

get_feature_names

get_featurelist_data

get_featureli

sts

get_users_f
eatures_sett
ings

getfeaturelis
t

getpkginfo

killpkg

listpkgs

manage_fea
tures

matchpkgs

read_feature
list

remove_ove
rride_featu
res_for_user

update_feat
urelist

verify_user_
has_feature

▼ PHP

convert_all_
domains_to
_fpm

get_fpm_co
unt_and_util
ization

is_conversio
n_in_progre
ss

php_get_def
ault_accoun
ts_to_fpm

php_get_ha
ndlers

php_get_im
pacted_dom
ains

php_get_ins
talled_versio
ns

php_get_old
_fpm_flag

php_get_sys
tem_default
_version

php_get_vh
osts_by_ver
sion

php_get_vh
ost_versions

php_ini_get
_content

php_ini_get
_directives

php_ini_set
_content

php_ini_set
_directives

php_set_def
ault_accoun
ts_to_fpm

php_set_ha
ndler

php_set_old
_fpm_flag

php_set_ses
sion_save_p
ath

php_set_sys
tem_default
_version

php_set_vh
ost_versions

▼ Resellers

acctcounts

get_public_c
ontact

getresellerip
s

listacIs

listresellers

resellerstats

saveacllist

set_public_c
ontact

setacIs

setresellerip
s

setresellerli
mits

setresellerm
ainip

setresellern
ameservers

setresellerp
ackagelimit

setupreselle
r

suspendres
eller

terminateres
eller

unsetuprese

ller

unsuspendr
eseller

▼ RPM

delete_rpm_
version

edit_rpm_ve
rsion

get_rpm_ver
sion_data

install_rpm_
plugin

list_rpms

package_m
anager_fixc
ache

package_m
anager_get_
build_log

package_m
anager_get_
package_inf
o

package_m
anager_is_p
erforming_a
ctions

package_m
anager_list_
packages

package_m
anager_reso
lve_actions

package_m
anager_sub
mit_actions

package_m
anager_upgr
ade

uninstall_rp
m_plugin

▼ Script Hooks

delete_hook

edit_hook

list_hooks

reorder_hoo
ks

▼ Security

accesshash

authorizessh
key

check_remo
te_ssh_conn
ection

convertopen
sshtoputty

deletesshke
y

fetch_securi
ty_advice

generatessh
keypair

importsshke
y

listsshkeys

▼ Server

Administration

add_configcl
usterserver

configureba
ckgroundpro
cesskiller

configureser
vice

cors_proxy_
get

create_user
_session

delete_conf
gclusterserv
er

enable_mon
itor_all_ena
bled_service
s

get_all_cont
act_importa
nces

get_appconf
ig_applicatio
n_list

get_applicati
on_contact_
event_import
tance

get_applicati
on_contact_
importance

get_availabl
e_profiles

get_current_
profile

get_passwor
d_strength

get_remote_
access_has
h

get_service_
config

get_service_
config_key

get_tcp4_so
ckets

get_tcp6_so
ckets

get_tweakse
tting

get_udp4_s
ockets

get_udp6_s
ockets

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

loadavg

nvget

nvset

personalizati
on_get

personalizati
on_set

purchase_a
_license

reboot

remove_in_
progress_ex
im_config_e
dit

restartservic
e

restore_conf
ig_from_file

restore_conf
ig_from_upl
oad

run_cpkeyclt

send_test_p
osturl

send_test_p
ushbullet_n
ote

servicestatu

s

set_applicati
on_contact_
event_imp
ortance

set_applicati
on_contact_
importance

set_primary
_servenam
e

set_service_
config_key

set_tweakse
tting

sethostname

setminimum
passwordstr
engths

start_profile
_activation

system_nee
ds_reboot

systemloada
vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

fetchcrtinfo
fetchsslinfo
generatessl
get_autossl
_check_schedule
get_autossl
_log
get_autossl
_logs_catalog
get_autossl
_metadata
get_autossl
_pending_queue
get_autossl
_pending_queue_for_domain
get_autossl
_pending_queue_for_user
get_autossl
_problems_for_domain
get_autossl
_problems_for_user
get_autossl
_providers
get_best_ssl
domain_for_service
install_service_ssl_certificate
installssl
listcrts
rebuildinstall
edssldb
rebuildusers
sldb
reset_autossl_provider
reset_service_ssl_certificate
set_autossl_metadata
set_autossl_metadata_key

set_autossl_
provider

start_autossl_
check_for_
all_users

start_autossl_
check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_get_s
upport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

abort_transfer_session

analyze_transfer_session_remote

available_transfer_modules

create_remote_root_transfer_session

create_remote_user_transfer_session

delete_account_archives

enqueue_transfer_item

fetch_transfer_session_log

get_transfer_session_state

pause_transfer_session

remote_basic_credential_check

retrieve_transfer_session_remote_analysis

start_transfer_session

transfer_module_schema

validate_system_user

▼ Updates

accept_eula

get_available_tiers

get_current_lts_expiration_status

get_lts_expire

getlongterm support

installed_versions

set_cpanel_updates

set_tier

update_upd
ateconf

version