

# cPanel API 2 Functions - Email::listautoresponders

## Guide to cPanel API 2

Return Data

Filter and Sort Output

Paginate Output

Output Columns

Calls from the WHM API

cPanel Tags (deprecated)

AddonDomain:: adddondomain

omains

AddonDomain:: listaddondomains

AddonDomain:: listaddondomains

### Backups

Backups:: listfullbackups

### Bandwidth

Bandwidth:: addhttpbandwidth

Bandwidth:: getbandwidth

Bandwidth:: gethourlyaveragebandwidth

### BoxTrapper

BoxTrapper:: accountmanagelist

### Branding

Branding:: addbrandingobj

Branding:: applybranding

Branding:: brandingeditor

Branding:: createpackage

Branding:: cssmerge

Branding:: delbrandingobj

Branding:: delpackage

## Description

This function lists the cPanel account's autoresponders.

### Warning:

We **strongly** recommend that you use the following UAPI function instead of this function:

- `Email::list_auto_responders` — This function lists a domain's autoresponders.

## Examples

### WHM API (JSON)

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?cpanel_jsonapi_user=user&cpanel_jsonapi_version=2&cpanel_jsonapi_module=Email&cpanel_jsonapi_func=listautoresponders&domain="example.com"&regex="vacation"
```

### Note:

For more information, read our [Calls from the WHM API](#) documentation.

## Function information

## About this module

The Email module modifies cPanel email account settings.

Branding:: gensprites

Branding:: getbrandingpkg

Branding:: getbrandingpkgstatus

Branding:: getdefaultbrandingpkg

Branding:: installbrandingpkgs

Branding:: installimages

Branding:: killimages

Branding:: listingtypes

Branding:: listobjecttypes

Branding:: preloadconf

Branding:: resetall

Branding:: resetscss

Branding:: resethtml

Branding:: resolve\_file

Branding:: resolveocalcss

Branding:: saveocalcss

Branding:: setbrandingpkgstatus

Branding:: showpkgs

Branding:: spritelist

#### ▼ CSVImport

CSVImport:: columnchoices

CSVImport:: configimport

CSVImport:: data

CSVImport:: fetchimportdata

CSVImport:: isenabled

CSVImport:: loaddata

CSVImport:: processdata

CSVImport:: sendcontact

#### ▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// List example.com's  
autoresponders that  
include "vacation".  
$list_autoresponders  
= $cpanel->api2(  
    'Email',  
    'listautoresponders',  
  
    array(  
        'domain'  
=> 'example.com',  
        'regex'  
=> 'vacation',  
    )  
);
```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

## About cPanel API 2

cPanel API 2 accesses and modifies data for cPanel accounts.

#### Notes:

- The  
Fe  
  
int  
• Ur  
mi  
us  
20  
or  
20  
).`  
20  
or  
20  
).

## Find a function

•

- CSVImport:: uploadimport
- Contactus:: isenabled
    - Contactus:: sendcontact
  - Cron:: add\_line
    - Cron:: edit\_line
    - Cron:: fetchcron
    - Cron:: get\_email
    - Cron:: listcron
    - Cron:: remove\_line
    - Cron:: set\_email
  - CustInfo:: contactemails
    - CustInfo:: contactrefs
    - CustInfo:: displaycontactinfo
    - CustInfo:: savecontactinfo
  - DBmap:: status
    - DBmap:: version
  - DKIMUI:: available
    - DKIMUI:: getrecords
    - DKIMUI:: install
    - DKIMUI:: installed
    - DKIMUI:: uninstall
  - DenyIp:: listdenyps
  - DiskCounter:: disk\_counter
  - DiskUsage:: buildcache
    - DiskUsage:: clearcache
    - DiskUsage:: fetch\_raw\_disk\_usage
    - DiskUsage:: fetchdiskusage

## LiveAPI Perl Module

```

my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# List example.com's
autoresponders that
include "vacation".
my
$list_autoresponders
= $cpliveapi->api2(
'Email',
'listautoresponders',
{
'domain'
=> 'example.com',
'regex'
=> 'vacation',
}
);

```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

## cPanel Tag System (deprecated)

**Warnings:**

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Deprecated cPanel Tag Usage](#) documentation.

- cPanel API 2 Functions - Email::editquota — This function modifies an email account's quota.
- cPanel API 2 Functions - Email::passwordop — This function modifies an email account's password.

DiskUsage:: fetchdiskusagewithextras

#### ▼ DnsLookup

DnsLookup:: name2ip

#### ▼ DomainLookup

DomainLookup:: countbaseddomains

DomainLookup:: getbaseddomains

DomainLookup:: getdocroot

DomainLookup:: getdocroots

DomainLookup:: getmaindomain

#### ▼ Email

Email:: accountname

Email:: adddomainforward

Email:: addforward

Email:: addmx

Email:: addpop

Email:: browseboxes

Email:: changemx

Email:: checkmaindiscard

Email:: clearpopcache

Email:: deletefilter

Email:: delforward

Email:: delmx

Email:: delpop

Email:: disablefilter

Email:: editquota

Email:: enablefilter

Email:: fetchautoresponder

Email:: fetchcharmaps

Email:: filteractions

Email:: filterlist

Email:: filtername

Email:: filterrules

Email:: get\_archiving\_configuration

#### ▼ Command Line

```
cpapi2
--user=username Email
listautoresponders
domain=example.com
regex=vacation
```

#### Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- You **must** run the `--user=username` command.
- For more information and additional output options, read our [Guide to cPanel API 2](#) documentation or run the `cpapi2 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapi2` command:

```
/usr/local
/cpanel/bin/cpapi2
```

- cPanel API 2 Functions - Email::listdefaultaddresses

This function retrieves the domain's default address and its rules.

- cPanel API 2 Functions - Email::listaliasbackups

This function retrieves a list of the account's domains that use aliases and custom default addresses.

Email: `get_archiving_default_configuration`

Email: `get_archiving_types`

Email: `get_default_email_quota`

Email: `get_email_signing`

Email: `get_max_email_quota`

Email: `gettabsbrowserdir`

Email: `getalwaysaccept`

Email: `getdiskusage`

Email: `getmxcheck`

Email: `has_delegated_mailman_lists`

Email: `list_system_filter_info`

Email: `listaliasbackups`

Email: `listautoresponders`

Email: `listdefaultaddresses`

Email: `listdomainforwards`

Email: `listfilterbackups`

Email: `listfilters`

Email: `listforwards`

Email: `listlists`

Email: `listmaildomains`

Email: `listmx`

Email: `listmxs`

Email: `listpops`

Email: `listpopssingle`

Email: `listpopswitchdisk`

Email: `listpopswitchimage`

Email: `loadfilter`

Email: `passwdpop`

## Output (JSON)

```
{
  "cpanelresult": {
    "apiversion": 2,
    "func":
"listautoresponders",
    "data": [
      {
        "email":
"bob@example.com",
        "subject": "I
am on vacation
today."
      }
      {
        "email":
"malcolm@example.com"
,
        "subject":
"Out on vacation
until Monday."
      }
    ],
    "event": {
      "result": 1
    },
    "module": "Email"
  }
}
```

### Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

## Parameters

Parameter	Type	Description	Possible values	Example
<code>domain</code>	<i>string</i>	The domain to query.  If you do not use this parameter, the function lists all of the account's autoresponders.	A valid domain on the cPanel account.	<code>example.com</code>

Email:: reorderfilters

Email:: set\_archiving\_configuration

Email:: set\_archiving\_default\_configuration

Email:: set\_email\_signing

Email:: setalwaysaccept

Email:: setdefaultaddress

Email:: setmxcheck

Email:: storefilter

Email:: tracefilter

▼ EmailTrack

EmailTrack:: search

EmailTrack:: stats

EmailTrack:: trace

▼ Encoding

Encoding:: get\_encodings

Encoding:: guess\_file

Encoding:: guess\_file\_opts

▼ FSTest

FSTest:: dirisempty

▼ Fileman

Fileman:: autocompletedir

Fileman:: fileop

Fileman:: getabsdir

Fileman:: getdir

Fileman:: getdiractions

Fileman:: getdiskinfo

Fileman:: geteditty

Fileman:: getfileactions

Fileman:: getpath

Fileman:: listfiles

Fileman:: mkdir

Fileman:: mkfile

regex	string	A Perl Compatible Regular Expression (PCRE) that filters the results.  If you do not use this parameter, the function lists all of the account or domain's autoresponders.	A valid PCRE.	vacation
-------	--------	--	---------------	----------

## Returns

Return	Type	Description	Possible values	Example
email	string	The autoresponder's email address.	A valid email address on the cPanel account.	bob@example.com
subject	string	The autoresponder's subject.	A string value.	I am on vacation today.
reason	string	A reason for failure.  <b>Note</b> : This function <b>only</b> returns a reason value if it failed.	A string that describes the error.	This is an error message.
result	Boolean	Whether the function succeeded.	<ul style="list-style-type: none"> <li>1 — The function succeeded.</li> <li>0 — The function failed.</li> </ul>	1

Fileman:: savefile

Fileman:: search

Fileman:: statfiles

Fileman:: uploadfiles

Fileman:: viewfile

▼ ForcePassword

ForcePassword:: get\_force\_password\_flags

ForcePassword:: update\_force\_password\_flags

▼ Frontpage

Frontpage:: fpenabled

Frontpage:: list

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: listftp

Ftp:: listftpsessions

Ftp:: listftpwithdisk

Ftp:: passwd

Ftp:: setquota

▼ Gpg

Gpg:: listgpgkeys

Gpg:: listsecretgpgkeys

Gpg:: number\_of\_private\_keys

Gpg:: number\_of\_public\_keys

▼ Htaccess

Htaccess:: listusers

Htaccess:: listusers

▼ HttpUtils

HttpUtils:: getdirindices

▼ ImageManager

ImageManager:: thumbnail

▼ LVEInfo

LVEInfo:: getUsage

▼ LangMods

LangMods:: getarchname

LangMods:: getkey

LangMods:: getpre  
fix

LangMods:: install

LangMods:: langlis  
t

LangMods:: list\_av  
ailable

LangMods:: list\_in  
stalled

LangMods:: magic  
\_status

LangMods:: pre\_ru  
n

LangMods:: search

LangMods:: setup

LangMods:: uninst  
all

LangMods:: updat  
e

▼ LeechProtect

LeechProtect:: set  
up

▼ Locale

Locale:: get\_encod  
ing

Locale:: get\_html\_  
dir\_attr

Locale:: get\_locale  
\_name

Locale:: get\_user\_  
ocale

Locale:: get\_user\_  
ocale\_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse  
r

Logaholic:: adduse  
rprofile

Logaholic:: deleteu  
ser

Logaholic:: deleteu  
serprofile

Logaholic:: edituse  
r

Logaholic:: fetchus  
er

Logaholic:: listuser  
profiles

Logaholic:: logahol

iclink

Logaholic:: proces  
sstats

▼ Mime

Mime:: list\_hotlinks

Mime:: listhandlers

Mime:: listmime

Mime:: listredirects

Mime:: redirectna  
me

Mime:: redirecturln  
ame

▼ MysqlFE

MysqlFE:: authoriz  
ehost

MysqlFE:: change  
dbuserpassword

MysqlFE:: created  
b

MysqlFE:: created  
buser

MysqlFE:: dbusere  
xists

MysqlFE:: deautho  
rizehost

MysqlFE:: deleted  
b

MysqlFE:: deleted  
buser

MysqlFE:: getalldb  
sinfo

MysqlFE:: getalldb  
usersanddbs

MysqlFE:: getdbus  
erprivileges

MysqlFE:: getdbus  
ers

MysqlFE:: gethosts

MysqlFE:: getmys  
qlprivileges

MysqlFE:: getmys  
qlserverprivileges

MysqlFE:: has\_my  
cnf\_for\_cpuser

MysqlFE:: listdbs

MysqlFE:: listdbsb  
ackup

MysqlFE:: listhosts

MysqlFE:: listusers

MysqlFE:: listusers

indb

MysqlFE:: revoked  
buserprivileges

MysqlFE:: setdbu  
erprivileges

MysqlFE:: userdbp  
rivs

▼ MysqlOptimizer

MysqlOptimizer:: f  
etch\_slow\_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does\_news  
\_exist

News:: does\_news  
\_type\_exist

News:: get\_news

▼ PHPINI

PHPINI:: getallopti  
ons

PHPINI:: getoption  
s

▼ Park

Park:: listaddondo  
mains

Park:: listparkeddo  
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change\_  
password

Passwd:: set\_dige  
st\_auth

▼ PasswdStrength

PasswdStrength::  
appstrengths

PasswdStrength::  
get\_password\_stre  
ngth

PasswdStrength::  
get\_required\_stren  
gth

▼ Postgres

Postgres:: listdbs

Postgres:: listusers

Postgres:: listusers  
indb

Postgres:: userexists

▼ Rand

Rand:: getranddata

▼ Resellers

Resellers:: get\_sub\_accounts

▼ RoR

RoR:: addapp

RoR:: changeapp

RoR:: importrails

RoR:: listapps

RoR:: listrewrites

RoR:: needsimport

RoR:: removeapp

RoR:: removerewrite

RoR:: restartapp

RoR:: setuprewrite

RoR:: softrestartapp

RoR:: startapp

RoR:: stopapp

▼ SetLang

SetLang:: setlocale

▼ SourceIPCheck

SourceIPCheck:: addip

SourceIPCheck:: delip

SourceIPCheck:: getaccount

SourceIPCheck:: listips

SourceIPCheck:: loadsecquestions

SourceIPCheck:: resetsecquestions

SourceIPCheck:: samplequestions

SourceIPCheck:: savesecquestions

▼ SPFUI

SPFUI:: available

SPFUI:: count\_settings

SPFUI:: entries\_complete

SPFUI:: get\_raw\_record

SPFUI:: getmainserverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list\_settings

SPFUI:: load\_current\_values

SPFUI:: uninstall

▼ SSH

SSH:: authkey

SSH:: converttopk

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey\_legacy

SSH:: importkey

SSH:: listkeys

▼ SSL

SSL:: fetchcertificate

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcnname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

▼ SSLInfo

SSLInfo:: fetchinfo

▼ StatCache

StatCache:: clearcache

▼ Stats

- Stats:: getmonthly bandwidth
- Stats:: getmonthly domainbandwidth
- Stats:: getthismont hsbwusage
- Stats:: lastapache hits
- Stats:: lastvisitors
- Stats:: listanalog
- Stats:: listawstats
- Stats:: listlastvisitors
- Stats:: listrawlogs
- Stats:: listurchin
- Stats:: listwebalizer

▼ StatsBar

- StatsBar:: getrowcounter
- StatsBar:: rowcounter
- StatsBar:: setrowcounter
- StatsBar:: stat

▼ SubDomain

- SubDomain:: adds ubdomain
- SubDomain:: changedocroot
- SubDomain:: delsubdomain
- SubDomain:: getservedsubdomains
- SubDomain:: listsubdomains
- SubDomain:: validregex

▼ Themes

- Themes:: apply\_new\_theme
- Themes:: does\_cpanel\_theme\_exist
- Themes:: get\_available\_themes
- Themes:: get\_themes\_list
- Themes:: restore\_saved\_theme

▼ UI

- UI:: dynamicincludelist
- UI:: includelist
- UI:: listform
- UI:: paginate
- UI:: paginate\_list

▼ UserHttpUtils

- UserHttpUtils:: getdirindices

▼ WebDisk

- WebDisk:: addwebdisk
- WebDisk:: delwebdisk
- WebDisk:: hasdigest
- WebDisk:: listwebdisks
- WebDisk:: passwdwebdisk
- WebDisk:: set\_digest\_auth
- WebDisk:: set\_home\_dir
- WebDisk:: set\_perms
- WebDisk:: setstatus

▼ WebmailApps

- WebmailApps:: listwebmailapps

▼ ZoneEdit

- ZoneEdit:: add\_zone\_record
- ZoneEdit:: edit\_zone\_record
- ZoneEdit:: fetch\_cpanel\_generated\_domains
- ZoneEdit:: fetchzone
- ZoneEdit:: fetchzone\_records
- ZoneEdit:: fetchzones
- ZoneEdit:: get\_zone\_record
- ZoneEdit:: remove\_zone\_record
- ZoneEdit:: resetzone

