

# cPanel API 2 Functions - MysqlFE::getalldbsinfo

Guide to cPanel API 2

Return Data

Filter and Sort Output

Paginate Output

Output Columns

Calls from the WHM API

cPanel Tags (deprecated)

## Description

This function retrieves information about all of an account's databases.

### Warning:

We **strongly** recommend that you use [UAPI](#) instead of cPanel API 2. However, no equivalent UAPI function exists.

### Important:

In cPanel & WHM version 76 and later, when you disable the MySQL role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

## Examples

[AddonDomain](#)

### WHM API (JSON)

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?cpanel_jsonapi_user=user&cpanel_jsonapi_api_version=2&cpanel_jsonapi_module=MysqlFE&cpanel_jsonapi_function=getalldbsinfo
```

### Note:

For more information, read our [Calls from the WHM API](#) documentation.

## Function information

## About this module

The MysqlFE module manages MySQL databases, users, and services.

- AddonDomain: `addomain`
- AddonDomain: `deladdondomain`
- AddonDomain: `listaddondomains`
- Backups: `listfullbackups`
- Bandwidth: `addhttpbandwidth`
- Bandwidth: `getbwdata`
- Bandwidth: `gethourlyaveragebwoveryear`
- BoxTrapper: `accountmanagelist`
- Branding: `addbrandingobj`
- Branding: `applist`
- Branding: `brandingeditor`
- Branding: `createpkg`
- Branding: `cssmerge`
- Branding: `delbrandingobj`
- Branding: `delpkg`
- Branding: `gensprites`

Branding:: getbrandingpkg

Branding:: getbrandingpkgstatus

Branding:: getdefaultbrandingpkg

Branding:: installbrandingpkgs

Branding:: installimages

Branding:: killimages

Branding:: listingtypes

Branding:: listobjecttypes

Branding:: preloadconf

Branding:: resetall

Branding:: resetscripts

Branding:: resethtml

Branding:: resolvefile

Branding:: resolveocalcss

Branding:: saveocalcss

Branding:: setbrandingpkgstatus

Branding:: showpackages

Branding:: spriteslist

#### ▼ CSVImport

CSVImport:: columnchoices

CSVImport:: configimport

CSVImport:: data

CSVImport:: fetchimportdata

CSVImport:: isenabled

CSVImport:: loaddata

CSVImport:: processdata

CSVImport:: sendcontact

CSVImport:: uploadimport

#### ▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// Retrieve all  
information about the  
databases and  
database users  
$get_dbinfo =  
$cpanel->api2(  
    'MysqlFE',  
    'getalldbsinfo'  
);
```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

#### ▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
  
# Retrieve all  
information about the  
databases and  
database users  
my $get_dbinfo =  
$cpliveapi->api2(  
    'MysqlFE',  
    'getalldbsinfo',  
);
```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

## About cPanel API 2

cPanel API 2 accesses and modifies data for cPanel accounts.

#### Notes:

- The  
Fe  
  
int  
• Ur  
mu  
us  
20  
or  
20  
).`  
20  
or  
20  
).

## Find a function

•

- Contactus:: isenab  
led
    - Contactus:: sendc  
ontact
  - Cron:: add\_line
    - Cron:: edit\_line
    - Cron:: fetchcron
    - Cron:: get\_email
    - Cron:: listcron
    - Cron:: remove\_line
    - Cron:: set\_email
  - CustInfo:: contacte  
mails
    - CustInfo:: contactp  
refs
    - CustInfo:: display  
ontactinfo
    - CustInfo:: savecon  
tactinfo
  - DBmap:: status
    - DBmap:: version
  - DKIMUI:: available
    - DKIMUI:: getrecor  
ds
    - DKIMUI:: install
    - DKIMUI:: installed
    - DKIMUI:: uninstall
  - Denylp:: listdenyip  
s
  - DiskCounter:: disk  
\_counter
  - DiskUsage:: buildc  
ache
    - DiskUsage:: clearc  
ache
    - DiskUsage:: fetch\_  
raw\_disk\_usage
    - DiskUsage:: fetchd  
iskusage
    - DiskUsage:: fetchd  
iskusagewithextras

## ▼ cPanel Tag System (deprecated)

### Warnings:

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecat**ed. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Deprecat](#)ed cPanel Tag Usage docume  
ntation.

## ▼ Command Line

```
cpapi2
--user=username
MysqlFE getalldbsinfo
```

### Notes:

- You **must** [URI-encode](#) values.
- username represents your account-level username.
- You **must** run the `--user=username` command.
- For more information and additional output options, read our [Guide to cPanel API 2](#) documentation or run the `cpapi2 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapi2` command:

```
/usr/local
/cpanel/bi
n/cpapi2
```

- cPan  
el  
API  
2  
Mod  
ules  
-  
Mysq  
LFE  
—  
The  
Mysq  
LFE  
mod  
ule  
man  
ages  
MyS  
QL®  
data  
base  
s,  
user  
s,  
and  
servi  
ces.
- cPan  
el  
API  
2  
Func  
tions  
-  
Mysq  
LFE::  
auth  
orize  
host  
—  
This  
functi  
on  
auth  
orize  
s a  
host  
for  
remo  
te  
acce  
ss to  
the  
acco  
unt's  
data  
base  
.

- ▼ DnsLookup
  - DnsLookup:: name2ip
- ▼ DomainLookup
  - DomainLookup:: countbaseddomains
  - DomainLookup:: getbaseddomains
  - DomainLookup:: getdocroot
  - DomainLookup:: getdocroots
  - DomainLookup:: getmaindomain
- ▼ Email
  - Email:: accountname
  - Email:: adddomainforward
  - Email:: addforward
  - Email:: addmx
  - Email:: addpop
  - Email:: browseboxes
  - Email:: changemx
  - Email:: checkmaindiscard
  - Email:: clearpopcache
  - Email:: deletefilter
  - Email:: delforward
  - Email:: delmx
  - Email:: delpop
  - Email:: disablefilter
  - Email:: editquota
  - Email:: enablefilter
  - Email:: fetchautosponder
  - Email:: fetchcharmaps
  - Email:: filteractions
  - Email:: filterlist
  - Email:: filtername
  - Email:: filterrules
  - Email:: get\_archiving\_configuration
  - Email:: get\_archiving\_default\_configu

## ▼ Output (JSON)

```

{
  "cpanelresult": {
    "apiversion": 2,
    "data": [
      {
        "dbusers": [
          "example_fred"
        ],
        "db": "example_freddb",
        "size": "0"
      },
      {
        "dbusers": [
          "example_username"
        ],
        "db": "example_testdb",
        "size": "0"
      },
      {
        "dbusers": [
          "example_walterdb"
        ],
        "db": "example_walterdb",
        "size": "0"
      }
    ],
    "func": "getalldbsinfo",
    "event": {
      "result": 1
    },
    "module": "MysqlFE"
  }
}

```

**Note:**  
 Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

- cPanel API 2 Functions - MysqlFE:: changeuserpassword - This function changes a database user's password.
- cPanel API 2 Functions - MysqlFE:: createedb - This function creates a database.

ration

Email: [get\\_archiving\\_types](#)

Email: [get\\_default\\_email\\_quota](#)

Email: [get\\_email\\_signing](#)

Email: [get\\_max\\_email\\_quota](#)

Email: [getabsbrowsedir](#)

Email: [getalwaysaccept](#)

Email: [getdiskusage](#)

Email: [getmxcheck](#)

Email: [has\\_delegated\\_mailman\\_lists](#)

Email: [list\\_system\\_filter\\_info](#)

Email: [listaliasbackups](#)

Email: [listautoresponders](#)

Email: [listdefaultaddresses](#)

Email: [listdomainforwards](#)

Email: [listfilterbackups](#)

Email: [listfilters](#)

Email: [listforwards](#)

Email: [listlists](#)

Email: [listmaildomains](#)

Email: [listmx](#)

Email: [listmxs](#)

Email: [listpops](#)

Email: [listpopssingle](#)

Email: [listpopswithdisk](#)

Email: [listpopswithimage](#)

Email: [loadfilter](#)

Email: [passwdpop](#)

Email: [reorderfilters](#)

## Parameters

This function does not accept parameters.

## Returns

Return	Type	Description	Possible values	Example
	<i>array of hashes</i>	An array of hashes that contain information about each database.	Each hash contains the <code>db</code> and <code>size</code> returns and the <code>dbusers</code> array.	
<code>dbusers</code>	<i>array</i>	An array of database users that are authorized to access the database.  The function returns this value in the unnamed hash.	One or more valid usernames.	<code>example_user1</code>
<code>db</code>	<i>string</i>	The database's name.  The function returns this value in the unnamed hash.	A valid database name.	<code>example_database</code>
<code>size</code>	<i>integer</i>	The size of the database.  The function returns this value in the unnamed hash.	An integer that represents the database size, in bytes.	<code>0</code>
<code>reason</code>	<i>string</i>	A reason for failure.  <div style="border: 1px solid orange; padding: 5px; width: fit-content; margin: 10px auto;"><b>Note</b> : This function only returns a reason value if it failed.</div>	A string that describes the error.	This is an error message.
<code>result</code>	<i>Boolean</i>	Whether the function succeeded.	<ul style="list-style-type: none"> <li>• <code>1</code> — The function succeeded.</li> <li>• <code>0</code> — The function failed.</li> </ul>	<code>1</code>

Email:: set\_archiving\_configuration

Email:: set\_archiving\_default\_configuration

Email:: set\_email\_signing

Email:: setalwaysaccept

Email:: setdefaultaddress

Email:: setmxcheck

Email:: storefilter

Email:: tracefilter

▼ EmailTrack

EmailTrack:: search

EmailTrack:: stats

EmailTrack:: trace

▼ Encoding

Encoding:: get\_encodings

Encoding:: guess\_file

Encoding:: guess\_file\_opts

▼ FSTest

FSTest:: dirisempty

▼ Fileman

Fileman:: autocompletedir

Fileman:: fileop

Fileman:: getabsdir

Fileman:: getdir

Fileman:: getdiractions

Fileman:: getdiskinfo

Fileman:: getedittype

Fileman:: getfileactions

Fileman:: getpath

Fileman:: listfiles

Fileman:: mkdir

Fileman:: mkfile

Fileman:: savefile

Fileman:: search

Fileman:: statfiles

Fileman:: uploadfiles

Fileman:: viewfile

▼ ForcePassword

ForcePassword:: get\_force\_password\_flags

ForcePassword:: update\_force\_password\_flags

▼ Frontpage

Frontpage:: fpenabled

Frontpage:: list

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: listftp

Ftp:: listftpsessions

Ftp:: listftpwithdisk

Ftp:: passwd

Ftp:: setquota

▼ Gpg

Gpg:: listgpgkeys

Gpg:: listsecretgpgkeys

Gpg:: number\_of\_private\_keys

Gpg:: number\_of\_public\_keys

▼ Htaccess

Htaccess:: listuser

Htaccess:: listusers

▼ HttpUtils

HttpUtils:: getdirindices

▼ ImageManager

ImageManager:: thumbnail

▼ LVEInfo

LVEInfo:: getUsage

▼ LangMods

LangMods:: getarcname

LangMods:: getkey

LangMods:: getpre  
fix

LangMods:: install

LangMods:: langlis  
t

LangMods:: list\_av  
ailable

LangMods:: list\_in  
stalled

LangMods:: magic  
\_status

LangMods:: pre\_ru  
n

LangMods:: search

LangMods:: setup

LangMods:: uninst  
all

LangMods:: updat  
e

▼ LeechProtect

LeechProtect:: set  
up

▼ Locale

Locale:: get\_encod  
ing

Locale:: get\_html\_  
dir\_attr

Locale:: get\_locale  
\_name

Locale:: get\_user\_  
ocale

Locale:: get\_user\_  
ocale\_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse  
r

Logaholic:: adduse  
rprofile

Logaholic:: deleteu  
ser

Logaholic:: deleteu  
serprofile

Logaholic:: edituse  
r

Logaholic:: fetchus  
er

Logaholic:: listuser  
profiles

Logaholic:: logahol  
iclink



Logaholic:: proces  
sstats

▼ Mime

Mime:: list\_hotlinks

Mime:: listhandlers

Mime:: listmime

Mime:: listredirects

Mime:: redirectname

Mime:: redirecturlname

▼ MysqlFE

MysqlFE:: authorizehost

MysqlFE:: change  
dbuserpassword

MysqlFE:: created  
b

MysqlFE:: created  
buser

MysqlFE:: dbuserexists

MysqlFE:: deauthorizehost

MysqlFE:: deleted  
b

MysqlFE:: deleted  
buser

MysqlFE:: getalldb  
sinfo

MysqlFE:: getalldb  
usersanddbs

MysqlFE:: getdatabasesprivileges

MysqlFE:: getdatabases

MysqlFE:: gethosts

MysqlFE:: getmysqlprivileges

MysqlFE:: getmysqlserverprivileges

MysqlFE:: has\_my  
cnf\_for\_cpuser

MysqlFE:: listdbs

MysqlFE:: listdatabasesackup

MysqlFE:: listhosts

MysqlFE:: listusers

MysqlFE:: listusers  
indb

MysqlFE:: revoked  
buserprivileges

MysqlFE:: setdbu  
sprivileges

MysqlFE:: userdbp  
rivs

▼ MysqlOptimizer

MysqlOptimizer:: f  
etch\_slow\_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does\_news  
\_exist

News:: does\_news  
\_type\_exist

News:: get\_news

▼ PHPINI

PHPINI:: getallopti  
ons

PHPINI:: getoption  
s

▼ Park

Park:: listaddondo  
mains

Park:: listparkeddo  
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change\_  
password

Passwd:: set\_dige  
st\_auth

▼ PasswdStrength

PasswdStrength::  
appstrengths

PasswdStrength::  
get\_password\_stre  
ngth

PasswdStrength::  
get\_required\_stren  
gth

▼ Postgres

Postgres:: listdbs

Postgres:: listusers

Postgres:: listusers  
indb

Postgres:: userexi  
sts

▼ Rand

Rand:: getranddat  
a

▼ Resellers

Resellers:: get\_su  
b\_accounts

▼ RoR

RoR:: addapp

RoR:: changeapp

RoR:: importrails

RoR:: listapps

RoR:: listrewrites

RoR:: needsimport

RoR:: removeapp

RoR:: removerewri  
te

RoR:: restartapp

RoR:: setuprewrite

RoR:: softrestartap  
p

RoR:: startapp

RoR:: stopapp

▼ SetLang

SetLang:: setlocale

▼ SourceIPCheck

SourceIPCheck:: a  
ddip

SourceIPCheck:: d  
elip

SourceIPCheck:: g  
etaccount

SourceIPCheck:: li  
stips

SourceIPCheck:: l  
oadsecquestions

SourceIPCheck:: r  
esetsecquestions

SourceIPCheck:: s  
amplequestions

SourceIPCheck:: s  
avesecquestions

▼ SPFUJ

SPFUJ:: available

SPFUJ:: count\_sett  
ings

SPFUI:: entries\_co  
mplete

SPFUI:: get\_raw\_r  
ecord

SPFUI:: getmainse  
rverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list\_settin  
gs

SPFUI:: load\_curr  
ent\_values

SPFUI:: uninstall

▼ SSH

SSH:: authkey

SSH:: converttopp  
k

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey\_leg  
acy

SSH:: importkey

SSH:: listkeys

▼ SSL

SSL:: fetchcabundl  
e

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcnname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

▼ SSLInfo

SSLInfo:: fetchinfo

▼ StatCache

StatCache:: clearc  
ache

▼ Stats

Stats:: getmonthly

bandwidth

Stats:: getmonthly  
domainbandwidth

Stats:: getthismont  
hsbwusage

Stats:: lastapache  
hits

Stats:: lastvisitors

Stats:: listanalog

Stats:: listawstats

Stats:: listlastvisito  
rs

Stats:: listrawlogs

Stats:: listurchin

Stats:: listwebalize  
r

▼ StatsBar

StatsBar:: getrowc  
ounter

StatsBar:: rowcoun  
ter

StatsBar:: setrowc  
ounter

StatsBar:: stat

▼ SubDomain

SubDomain:: adds  
ubdomain

SubDomain:: chan  
gedocroot

SubDomain:: delsu  
bdomain

SubDomain:: getre  
servedsubdomains

SubDomain:: listsu  
bdomains

SubDomain:: validr  
egex

▼ Themes

Themes:: apply\_n  
ew\_theme

Themes:: does\_cp  
anel\_theme\_exist

Themes:: get\_avail  
able\_themes

Themes:: get\_the  
mes\_list

Themes:: restore\_  
saved\_theme

▼ UI

UI:: dynamicinclud  
elist

UI:: includelist

UI:: listform

UI:: paginate

UI:: paginate\_list

▼ UserHttpUtils

UserHttpUtils:: get  
dirindices

▼ WebDisk

WebDisk:: addweb  
disk

WebDisk:: delweb  
disk

WebDisk:: hasdige  
st

WebDisk:: listwebd  
isks

WebDisk:: passwd  
webdisk

WebDisk:: set\_dig  
est\_auth

WebDisk:: set\_ho  
mdir

WebDisk:: set\_per  
ms

WebDisk:: setstatu  
s

▼ WebmailApps

WebmailApps:: list  
webmailapps

▼ ZoneEdit

ZoneEdit:: add\_zo  
ne\_record

ZoneEdit:: edit\_zo  
ne\_record

ZoneEdit:: fetch\_c  
panel\_generated\_  
domains

ZoneEdit:: fetchzo  
ne

ZoneEdit:: fetchzo  
ne\_records

ZoneEdit:: fetchzo  
nes

ZoneEdit:: get\_zon  
e\_record

ZoneEdit:: remove  
\_zone\_record

ZoneEdit:: resetzo  
ne

