

WHM API 0 Functions - remove_messages_mail_queue

Guide to WHM API 0

Return Data

Description

This function removes messages from the mail server's queue.

Examples

Accounts

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/remove_messages_mail_queue
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/remove_messages_mail_queue
```

Command Line

```
whmapi0  
remove_messages_mail_queue
```

Notes:

- You **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 0](#) documentation or run the `whmapi0 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapi0` command:

```
/usr/local  
/cpanel/bin/whmapi0
```

Function information

About WHM API 0

WHM API 0 performs functions and accesses data in WHM.

Warning:
WHM API 0 is deprecated.
We strongly recommend using WHM API 1.

- accounts summary
- applist
- createacct
- domainuserdata
- editquota
- limitbw
- listaccts
- listsuspended
- modifyacct
- myprivs
- passwd
- removeacct
- showbw
- suspendacct
- unsuspendacct
- ▼ DNS
 - adddns
 - addzonerecord
 - dumpzone
 - editzonerecord
 - getzonerecord
 - killdns
 - listzones
 - lookupnsip
 - lookupnsips
 - removezonerecord
 - resetzone
 - setresolvers
- ▼ IP Addresses
 - addip

- delip
- listips
- setsiteip
- deliver_mail_queue
 - deliver_messages_mail_queue
 - exim_configuration_check
 - fetch_doc_key
 - purge_mail_queue
 - remove_in_progress_exim_configuration
 - remove_messages_mail_queue
 - unfreeze_messages_mail_queue
 - validate_current_installed_exim_configuration_syntax
 - validate_exim_configuration_syntax
- addpkg
 - changepackage
 - editpkg
 - getfeaturelist
 - killpkg
 - listpkgs
 - acctcounts
 - getresellers
 - listacts
 - listresellers
 - resellerstats
 - saveacllist
 - setacts

Output (JSON)

```
{
  "statusmsg": "Mail queue remove started in background",
  "status": 1,
  "data": "Removal Run Started"
}
```

Output (XML)

```
<purge_mail_queue>
  <data>Removal Run Started</data>

  <status>1</status>
  <statusmsg>Mail queue remove started in background</statusmsg>
</purge_mail_queue>
```

Notes:

- Scro
- Yomius
- 20
- or
- 20
-)tc

Find a function

Parameters

This function does not accept parameters.

Returns

Return	Type	Description	Possible values	Example
data	string	The mail server's response.	A valid string.	Removal Run Started
status	Boolean	Whether the function succeeded.	<ul style="list-style-type: none"> • 1 — Success. • 0 — Failure. 	1
statusmsg	string	The function's status.	A valid string.	Mail queue remove started in background

C o n t e n t b y l a b e l

T
h
e
r
e
i
s
n
o
c
o
n
t
e
n
t
w
i
t
h
t
h
e
s
p
e
c
i
f
i
e
d
l
a
b
e
l
s

setresellerip
s

setresellerli
mits

setresellerm
ainip

setresellern
ameservers

setresellerp
ackagelimit

setupreselle
r

suspendres
eller

terminateres
eller

unsetuprese
ller

unsuspendr
eseller

▼ Server

Administration

configureser
vice

gethostnam
e

getlanglist

loadavg

nvget

nvset

reboot

restartservic
e

servicestatu
s

sethostnam
e

▼ SSL

fetchsslinfo

generatessl

installssl

listcrts

▼ Updates

get_availabl
e_tiers

set_cpanel_
updates

set_tier

version

