

UAPI Functions - Market::set_url_after_checkout

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup::
fullbackup

p_to_ftp

Backup:: fullbacku
p_to_homedir

Backup:: fullbacku
p_to_scp_with_key

Backup:: fullbacku
p_to_scp_with_pa
ssword

Backup:: list_back
ups

Bandwidth

Bandwidth:: get_e
nabled_protocols

Bandwidth:: get_re
tention_periods

Bandwidth:: query

Batch

Batch:: strict

Brand

Brand:: read

Branding

Branding:: file

Branding:: get_app
lications

Branding:: get_app
lication_informatio
n

Branding:: get_ava
ilable_applications

Branding:: get_info

Description

This function updates the URL to which a provider sends a user after they check out.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/Market/set_url_after_checkout?provider=cPStore&access_token=725431a1-d5bc-11e5-a28b-8b0e09a93f05&order_id=12345&url_after_checkout=http%3A%2F%2Fcheckout.example.com
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

Function information

About this module

The Market module manages connections to cPanel Market providers.

About UAPI

information_for_applications

Branding:: image

Branding:: include

Branding:: spritelist

CacheBuster

CacheBuster:: read

CacheBuster:: update

Chkserverd

Chkserverd:: get_external_ports

Chkserverd:: get_external_ports_ssl

Chrome

Chrome:: get_domain

Contactus

Contactus:: is_enabled

cPAddons

cPAddons:: get_available_addons

cPAddons:: get_instance_settings

cPAddons:: list_addon_instances

cPGreyList

cPGreyList:: disable_all_domains

cPGreyList:: disable_domains

cPGreyList:: enable_all_domains

cPGreyList:: enable_domains

cPGreyList:: has_greylisting_enabled

cPGreyList:: list_domains

DAV

DAV:: disable_shared_global_addressbook

DAV:: enable_shared_global_addressbook

DAV:: get_calendar_contacts_config

DAV:: has_shared_global_addressbook

LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.
```

```
// Set  
url_after_checkout  
for order 12345 to  
http://checkout.example.com  
$set_url =  
$cpanel->uapi(  
    'Market',  
    'set_url_after_checkout',  
    array(  
        'provider'  
=> 'cPStore',  
  
        'access_token'  
=>  
    '725431a1-d5bc-11e5-a  
28b-8b0e09a93f05',  
        'order_id'  
=> '12345',  
  
        'url_after_checkout'  
=>  
    'http://checkout.example.com'  
    )  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

UAPI accesses and modifies data for cPanel accounts.

Notes:

- This function uses the `uapi()` method.

Find a function

- UAPI Functions - SSL: delete_ssl — This function removes SSL from a domain.

DAV:: is_dav_service_enabled

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# Set  
url_after_checkout  
for order 12345 to  
http://checkout.example.com  
my $set_url =  
$cpliveapi->uapi(  
    'Market',  
    'set_url_after_checkout',  
    {  
        'provider'  
=> 'cPStore',  
        'access_token'  
=>  
    '725431a1-d5bc-11e5-a  
28b-8b0e09a93f05',  
        'order_id'  
=> '12345',  
        'url_after_checkout'  
=>  
    'http://checkout.example.com'  
    }  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

- UAPI Functions - SSL: :fetch_best_for_domain — This function retrieves the best-available certificate for the domain.
- UAPI Functions - SSL: :fetch_certificate — This function retrieves all of a certificate's available information.

Email:: add_spam_filter
Email:: browse_mailbox
Email:: change_mx
Email:: check_fast_mail
Email:: check_pipe_forwarder
Email:: delete_auto_responder
Email:: delete_domain_forwarder
Email:: delete_filter
Email:: delete_forwarder
Email:: delete_held_messages
Email:: delete_list
Email:: delete_mx
Email:: delete_pop
Email:: disable_filter
Email:: disable_mailbox_autocreate
Email:: disable_spam_assassin
Email:: disable_spam_autodelete
Email:: disable_spam_box
Email:: dispatch_client_settings
Email:: edit_pop_quota
Email:: enable_filter
Email:: enable_mailbox_autocreate
Email:: enable_spam_assassin
Email:: enable_spam_box
Email:: fetch_charmaps
Email:: fts_rescan_mailbox
Email:: generate_mailman_otp
Email:: get_auto_r

▼ cPanel Template Toolkit

```
<!-- Set url_after_checkout for order 12345 to http://checkout.example.com -->[% execute('Market', 'set_url_after_checkout', { provider => 'cPStore', access_token => '725431a1-d5bc-11e5-a28b-8b0e09a93f05', order_id => '12345', url_after_checkout => 'http://checkout.example.com'}) %]
```

Note:

For more information, read our [Guide to Template Toolkit documentation](#).

- UAPI Functions - SSL: :fetch_key_and_certificate — This function extracts the private key and CA bundle information from a certificate.

esponder

Email: get_charse
ts

Email: get_client_
settings

Email: get_default_
_email_quota

Email: get_default_
_email_quota_mib

Email: get_disk_u
sage

Email: get_filter

Email: get_held_
message_count

Email: get_mailbo
x_autocreate

Email: get_mailm
an_delegates

Email: get_main_
account_disk_usa
ge

Email: get_main_
account_disk_usa
ge_bytes

Email: get_max_e
mail_quota

Email: get_max_e
mail_quota_mib

Email: get_pop_q
uota

Email: get_spam_
settings

Email: get_webm
ail_settings

Email: has_deleg
ated_mailman_list
s

Email: has_plainte
xt_authentication

Email: hold_outgo
ing

Email: is_integer

Email: list_auto_r
esponders

Email: list_default_
_address

Email: list_domain_
_forwarders

Email: list_filters

Email: list_filters_
backups

Email: list_forward

Command Line

```
uapi --user=username  
Market  
set_url_after_checkou  
t_provider=cPStore  
access_token=725431a1  
-d5bc-11e5-a28b-8b0e0  
9a93f05  
order_id=12345  
url_after_checkout=ht  
tp%3A%2F%2Fcheckout.e  
xample.com
```

Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local  
/cpanel/bi  
n/uapi
```

Output (JSON)

```
{  
  "result": {  
    "errors": null,  
  
    "messages": null,  
    "status": 1,  
    "metadata": {  
      },  
    },  
}
```

Note:

Use cPanel's *API Shell* interface (`cPanel >> Home >> Advanced >> API Shell`) to directly test cPanel API calls.

ers

Email:: list_forward_ers_backups

Email:: list_lists

Email:: list_mail_domains

Email:: list_mx

Email:: list_pops

Email:: list_pops_with_disk

Email:: list_system_filter_info

Email:: passwd_list

Email:: passwd_pop

Email:: release_outgoing

Email:: remove_mailman_delegates

Email:: reorder_filters

Email:: set_always_accept

Email:: set_default_address

Email:: set_list_privacy_options

Email:: stats_db_status

Email:: store_filter

Email:: suspend_incoming

Email:: suspend_login

Email:: suspend_outgoing

Email:: trace_filter

Email:: unsuspend_incoming

Email:: unsuspend_login

Email:: unsuspend_outgoing

Email:: verify_password

▼ EmailAuth

EmailAuth:: disable_dkim

EmailAuth:: enable_dkim

Parameters

Parameter	Type	Description	Possible values	Example
provider	<i>string</i>	Required The cPanel Market provider's name.	A valid string.	cPStore
access_token	<i>string</i>	Required The access token for the session to the cPanel Market provider.	A valid access token.	725431a1-d5bc-11e5-a28b-8b0e09a93f05
order_id	<i>integer</i>	Required The order ID that the cPanel Market provider assigned.	A positive integer.	123456
url_after_checkout	<i>string</i>	Required The URL to send the browser after the user checks out.	A valid URL that cannot contain a query string.	http://checkout.example.com

Returns

Parameter	Type	Description	Possible values	Example
error_type	<i>string</i>	Any errors that the function encounters. <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;">Notes:</div>	A valid string.	My dog has no nose.

EmailAuth:: ensure_dkim_keys_exist

EmailAuth:: fetch_dkim_private_keys

EmailAuth:: install_dkim_private_keys

EmailAuth:: install_spf_records

EmailAuth:: validate_current_dkims

EmailAuth:: validate_current_ptrs

EmailAuth:: validate_current_spfs

ExternalAuthenticat
ion

ExternalAuthenticat
ion:: add_authn_li
nk

ExternalAuthenticat
ion:: configured_
modules

ExternalAuthenticat
ion:: get_authn_lin
ks

ExternalAuthenticat
ion:: has_external_
_auth_modules_co
nfigured

ExternalAuthenticat
ion:: remove_auth
n_link

Features

Features:: get_feat
ure_metadata

Features:: has_fea
ture

Features:: list_feat
ures

Fileman

Fileman:: autocom
pletedir

Fileman:: empty_tr
ash

Fileman:: get_file_
content

Fileman:: get_file_
information

Fileman:: list_files

Fileman:: save_file_
_content

Fileman:: transcod
e

• We
e
i
n
t
r
o
d
u
c
e
d
t
h
i
s
r
e
t
u
r
n
i
n
c
P
a
n
e
l
&
W
H
M
v
e
r
s
i
o
n
1
1
.
5
6
.
1
.
• The
f
u
n
c
t
i
o
n
o
n
l
y
r
e
t
u
r
n
s
t
h
i
s
v
a
l
u
e

- Fileman:: upload_files
- Ftp:: add_ftp
 - Ftp:: allows_anonymous_ftp
 - Ftp:: allows_anonymous_ftp_incoming
 - Ftp:: delete_ftp
 - Ftp:: ftp_exists
 - Ftp:: get_ftp_daemon_info
 - Ftp:: get_port
 - Ftp:: get_quota
 - Ftp:: get_welcome_message
 - Ftp:: kill_session
 - Ftp:: list_ftp
 - Ftp:: list_ftp_with_disk
 - Ftp:: list_sessions
 - Ftp:: passwd
 - Ftp:: server_name
 - Ftp:: set_anonymous_ftp
 - Ftp:: set_anonymous_ftp_incoming
 - Ftp:: set_homedir
 - Ftp:: set_quota
 - Ftp:: set_welcome_message
 - Integration
 - Integration:: fetch_url
 - KnownHosts
 - KnownHosts:: create
 - KnownHosts:: delete
 - KnownHosts:: update
 - KnownHosts:: verify
 - LangPHP
 - LangPHP:: php_get_domain_handler
 - LangPHP:: php_get_impacted_domains

i
f
t
h
e
m
o
d
u
l
e
r
e
t
u
r
n
s
a
n
e
x
c
e
p
t
i
o
n
b
e
c
a
u
s
e
t
h
e
p
r
o
v
i
d
e
r
u
s
e
r
d
o
e
s
n
o
t
p
o
s
s
e
s
s
t
h
e
o
r
d
e
r
_
i
d
o
r
d

LangPHP:: php_get_installed_versions

LangPHP:: php_get_system_default_version

LangPHP:: php_get_vhost_versions

LangPHP:: php_ini_get_user_basic_directives

LangPHP:: php_ini_get_user_content

LangPHP:: php_ini_get_user_paths

LangPHP:: php_ini_set_user_basic_directives

LangPHP:: php_ini_set_user_content

LangPHP:: php_set_vhost_versions

▼ LastLogin

LastLogin:: get_last_or_current_logged_in_ip

▼ Locale

Locale:: get_attributes

▼ Mailboxes

Mailboxes:: expunge_messages

Mailboxes:: expunge_messages_for_mailbox_guid

Mailboxes:: get_mailbox_status

Mailboxes:: has_utf8_mailbox_names

Mailboxes:: set_utf8_mailbox_names

▼ Market

Market:: cancel_pending_ssl_certificate

Market:: create_shopping_cart

Market:: get_all_products

Market:: get_certificate_status_details

Market:: get_login_url

Market:: get_pending_ssl_certificates

--	--	--	--	--

Market:: get_provider_specific_dcv_constraints

Market:: get_providers_list

Market:: get_ssl_certificate_if_available

Market:: process_ssl_pending_queue

Market:: request_ssl_certificates

Market:: set_status_of_pending_queue_items

Market:: set_url_after_checkout

Market:: validate_login_token

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: delete_handler

Mime:: delete_hotlink

Mime:: delete_mime

Mime:: delete_redirect

Mime:: list_handlers

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirects

Mime:: redirect_info

▼ ModSecurity

ModSecurity:: disable_all_domains

ModSecurity:: disable_domains

ModSecurity:: enable_all_domains

ModSecurity:: enable_domains

ModSecurity:: has_modsecurity_installed

ModSecurity:: list_domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_note

Mysql :: check_database

Mysql:: create_database

Mysql:: create_user

Mysql:: delete_database

Mysql:: delete_host

Mysql:: delete_user

Mysql:: get_host_notes

Mysql:: get_privileges_on_database

Mysql:: get_restrictions

Mysql:: get_server_information

Mysql:: locate_server

Mysql:: rename_database

Mysql:: rename_user

Mysql:: repair_database

Mysql:: revoke_access_to_database

Mysql:: set_password

Mysql:: set_privileges_on_database

▼ Notifications

Notifications:: get_notifications_count

▼ NVData

NVData:: get

NVData:: set

- ▼ Parser
 - Parser:: firstfile_rel
ative_uri
- ▼ PassengerApps
 - PassengerApps:: d
isable_application
 - PassengerApps:: e
dit_application
 - PassengerApps:: e
nable_application
 - PassengerApps:: e
nsure_deps
 - PassengerApps:: li
st_applications
 - PassengerApps:: r
egister_application
 - PassengerApps:: u
nregister_applicati
on
- ▼ PasswdStrength
 - PasswdStrength::
get_required_stren
gth
- ▼ Personalization
 - Personalization::se
t
 - Personalization ::g
et
- ▼ Postgresql
 - Postgresql:: create
_database
 - Postgresql:: create
_user
 - Postgresql:: delete
_database
 - Postgresql:: get_re
strictions
 - Postgresql:: grant_
all_privileges
 - Postgresql:: renam
e_database
 - Postgresql:: renam
e_user
 - Postgresql:: renam
e_user_no_passw
ord
 - Postgresql:: revok
e_all_privileges
 - Postgresql:: set_p
assword
- ▼ Pushbullet
 - Pushbullet:: send_
test_message

- ▼ Quota
 - Quota:: get_quota_info
- ▼ Resellers
 - Resellers:: list_accounts
- ▼ ResourceUsage
 - ResourceUsage:: get_usages
- ▼ Restore
 - Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- ▼ Session
 - Session:: create_temp_user
- ▼ SiteTemplates
 - SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- ▼ SpamAssassin
 - SpamAssassin :: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key

SSL:: delete_ssl

SSL:: disable_mail_sni

SSL:: enable_mail_sni

SSL:: fetch_best_for_domain

SSL:: fetch_cert_info

SSL:: fetch_certificates_for_fqdns

SSL:: fetch_key_and_cabundle_for_certificate

SSL:: find_certificates_for_key

SSL:: find_csrs_for_key

SSL:: generate_certificate

SSL:: generate_csr

SSL:: generate_key

SSL:: get_autossl_excluded_domains

SSL:: get_autossl_pending_queue

SSL:: get_autossl_problems

SSL:: get_cabundle

SSL:: get_cn_name

SSL:: install_ssl

SSL:: installed_hosts

SSL:: installed_hosts

SSL:: is_autossl_check_in_progress

SSL:: is_mail_sni_supported

SSL:: is_sni_supported

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_items

SSL:: mail_sni_status

tus

SSL:: rebuild_mail
_snl_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDepl

oyment

VersionControlDep
loyment:: **create**

VersionControlDep
loyment:: **delete**

VersionControlDep
loyment:: **retrieve**

▼ WebDisk

WebDisk:: **delete_**
user

WebDisk:: **set_ho**
medir

WebDisk:: **set_pas**
sword

WebDisk:: **set_per**
missions

▼ WebmailApps

WebmailApps:: **list**
webmailapps

▼ WebVhosts

WebVhost:: **list_do**
mains

WebVhost:: **list_ssl**
_capable_domains

▼ WordPressBackup

WordPressBackup
:: **any_running**

WordPressBackup
:: **cancel**

WordPressBackup
:: **cleanup**

WordPressBackup
:: **get_available_ba**
ckups

WordPressBackup
:: **is_running**

WordPressBackup
:: **start**

▼ WordPressInstance

Manager

WordPressInstanc
eManager:: **cancel**
_scan

WordPressInstanc
eManager:: **cleanu**
p_scan

WordPressInstanc
eManager:: **chang**
e_admin_passwor
d

WordPressInstanc
eManager:: **config**
ure_autoupdate

WordPressInstanc
eManager:: **get_ap**

i_version

WordPressInstanceManager:: **get_instance_by_id**

WordPressInstanceManager:: **get_instances**

WordPressInstanceManager:: **get_latest_wordpress_version_from_wordpress_org**

WordPressInstanceManager:: **get_scan_results**

WordPressInstanceManager:: **is_installable_addon_available**

WordPressInstanceManager:: **start_scan**

▼ WordPressRestore

WordPressRestore:: **any_running**

WordPressRestore:: **cleanup**

WordPressRestore:: **start**