

# WHM API 0 Functions - editquota

## Guide to WHM API 0

Return Data

## Description

This function modifies a user's disk quota.

## Examples

### Accounts

#### JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/editquota?user=user&quota=500
```

#### XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/editquota?user=user&quota=500
```

#### Command Line

```
whmapi0  
domainuserdata  
domain=example.com
```

#### Notes:

- You **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 0](#) documentation or run the `whmapi0 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapi0` command:

```
/usr/local  
/cpanel/bin  
/whmapi0
```

## Function information

## About WHM API 0

WHM API 0 performs functions and accesses data in WHM.

- accounts ummary
- applist
- createacct
- domainuserdata
- editquota
- limitbw
- listaccts
- listsuspended
- modifyacct
- myprivs
- passwd
- removeacct
- showbw
- suspendacct
- unsuspendacct
- ▼ DNS
  - adddns
  - addzonerecord
  - dumpzone
  - editzonerecord
  - getzonerecord
  - killdns
  - listzones
  - lookupnsip
  - lookupnsips
  - removezonerecord
  - resetzone
  - setresolvers
- ▼ IP Addresses
  - addip

- delip
- listips
- setsiteip
- Mail
    - deliver\_mail\_queue
    - deliver\_messages\_mail\_queue
    - exim\_configuration\_check
    - fetch\_doc\_key
    - purge\_mail\_queue
    - remove\_in\_progress\_exim\_configuration\_dit
    - remove\_messages\_mail\_queue
    - unfreeze\_messages\_mail\_queue
    - validate\_current\_installed\_exim\_config
    - validate\_exim\_configuration\_syntax
  - Packages
    - addpkg
    - changepackage
    - editpkg
    - getfeaturelist
    - killpkg
    - listpkgs
  - Resellers
    - acctcounts
    - getresellers
    - listaccts
    - listresellers
    - resellerstats
    - saveacctlist
    - setaccts

### Output (JSON)

```
{
  "output": "Using
Universal Quota
Support
(quota=512000)\n",
  "result": [
    {
      "statusmsg": "Set
quota for user.",
      "status": 1
    }
  ]
}
```

### Output (XML)

```
<editquota>
  <output>Using
Universal Quota
Support
(quota=512000)</output>
  <result>
    <status>1</status>
    <statusmsg>Set quota
for user.</statusmsg>
  </result>
</editquota>
```

## Parameters

Parameter	Type	Description	Possible values	Example
user	string	<b>Required</b> The cPanel account username.	A valid cPanel username on the server.	user

**Warning:**  
WHM API ( deprecated )  
We strongly

#### Notes:

- Scro
- Yc
- m
- us
- 20
- or
- 20
- ) t

## Find a function

- WHM API 0 Functions - gethostname - This function retrieves the server's hostname.

setresellerips  
 setresellerimits  
 setresellermainip  
 setresellernameservers  
 setresellerpackagelimit  
 setupreseller

suspendreseller  
 terminatereseller  
 unsetupreseller  
 unsuspendreseller

Server Administration

configureSERVICE  
 gethostname  
 getlanglist  
 loadavg  
 nvget  
 nvset  
 reboot  
 restartSERVICE  
 servicestatus  
 sethostname

SSL

fetchsslinfo  
 generatessl  
 installssl  
 listcerts

Updates

get\_available\_tiers  
 set\_cpanel\_updates  
 set\_tier  
 version

quota	string	<b>Required</b> The account's new quota.	<ul style="list-style-type: none"> <li>A positive integer that represents the maximum amount of disk space, in Megabytes (MB).</li> <li>0 or unlimited grants the account unlimited disk space.</li> </ul>	500
-------	--------	---	--	-----

Returns

Return	Type	Description	Possible values	Example
result	array of hashes	An array of hashes of function status information.	Each hash includes the status and statusmsg returns.	
status	Boolean	Whether the function succeeded.  The function returns this value in the result hash.	<ul style="list-style-type: none"> <li>1 — Success.</li> <li>0 — Failure.</li> </ul>	1
statusmsg	string	A message of success or a reason for failure.  The function returns this value in the result hash.	<ul style="list-style-type: none"> <li>Set quota for user.</li> <li>An error message.</li> </ul>	Set quota for user.
output	string	A message about the function.	<ul style="list-style-type: none"> <li>A message of success.</li> <li>An error message.</li> </ul>	Using Universal Quota Support (quota=512000)\n

- WHM API 0 Functions - createacct — This function creates a cPanel account.
- WHM API 0 Functions - domainquota — This function retrieves domain data.
- WHM API 0 Functions - editquota — This function modifies a user's disk quota.

