

cPanel API 2 Modules - MysqlFE

Guide to cPanel API 2

[Return Data](#)

[Filter and Sort Output](#)

[Paginate Output](#)

[Output Columns](#)

[Calls from the WHM API](#)

[cPanel Tags \(deprecated\)](#)

[AddonDomain:: adddondomain](#)

[omain](#)

[AddonDomain:: deladdondomain](#)

[AddonDomain:: listaddondomains](#)

Backups

[Backups:: listfullbackups](#)

Bandwidth

[Bandwidth:: addhttpbandwidth](#)

[Bandwidth:: getbwdata](#)

[Bandwidth:: gethourlyaveragebwoveryear](#)

BoxTrapper

[BoxTrapper:: accountmanagerlist](#)

Branding

[Branding:: addbrandingobj](#)

[Branding:: applist](#)

[Branding:: brandingeditor](#)

[Branding:: createpkg](#)

[Branding:: cssmerge](#)

[Branding:: delbrandingobj](#)

[Branding:: delpkg](#)

[Branding:: gensprites](#)

Introduction

The MysqlFE module manages MySQL® databases, users, and services.

Important:

In cPanel & WHM version 76, we introduced server profiles and roles. When you enable a non-*Standard Node* server profile, the system **disables** API calls associated with that profile's disabled roles.

Available functions

- [cPanel API 2 Functions - MysqlFE::authorizehost](#) — This function authorizes a host for remote access to the account's database.
- [cPanel API 2 Functions - MysqlFE::changedbuserpassword](#) — This function changes a database user's password.
- [cPanel API 2 Functions - MysqlFE::createdb](#) — This function creates a database.
- [cPanel API 2 Functions - MysqlFE::createdbuser](#) — This function creates a database user.
- [cPanel API 2 Functions - MysqlFE::dbuserexists](#) — This function checks whether a database user exists.
- [cPanel API 2 Functions - MysqlFE::deauthorizehost](#) — This function removes a remote host's authorization.
- [cPanel API 2 Functions - MysqlFE::deletedb](#) — This function deletes a database.
- [cPanel API 2 Functions - MysqlFE::deletedbuser](#) — This function deletes a database user.
- [cPanel API 2 Functions - MysqlFE::getalldbinfo](#) — This function retrieves information about all of an account's databases.
- [cPanel API 2 Functions - MysqlFE::getalldbusersanddbs](#) — This function lists the databases for which a user has authorization.
- [cPanel API 2 Functions - MysqlFE::getdbuserprivileges](#) — This function lists a database user's privileges on a database.
- [cPanel API 2 Functions - MysqlFE::getdbusers](#) — This function lists MySQL® database users.
- [cPanel API 2 Functions - MysqlFE::gethosts](#) — This function lists authorized remote hosts for the account's databases.
- [cPanel API 2 Functions - MysqlFE::getmysqlprivileges](#) — This function lists the account's MySQL® privileges.
- [cPanel API 2 Functions - MysqlFE::getmysqlserverprivileges](#) — This function lists the MySQL® server's available privileges.
- [cPanel API 2 Functions - MysqlFE::has_myconf_for_cpuser](#) — This function checks whether a valid .my.cnf file exists in the account's home directory.
- [cPanel API 2 Functions - MysqlFE::listdbs](#) — This function lists the account's databases.
- [cPanel API 2 Functions - MysqlFE::listdbsbackup](#) — This function lists the account's database backups.
- [cPanel API 2 Functions - MysqlFE::listhosts](#) — This function lists remote MySQL® connection hosts.
- [cPanel API 2 Functions - MysqlFE::listusers](#) — This function lists an account's MySQL® database users.
- [cPanel API 2 Functions - MysqlFE::listusersindb](#) — This function lists MySQL® database users that are authorized to use a database.
- [cPanel API 2 Functions - MysqlFE::revokeuserprivileges](#) — This function revokes a user's privileges from a database.
- [cPanel API 2 Functions - MysqlFE::setdbuserprivileges](#) — This function grants privileges to a user on a database.

cPanel API 2 Basics

About cPanel API 2

cPanel API 2 accesses and modifies data for cPanel accounts.

Notes:

- Th Fe
- int
- Ur mu us 20 or 20).` 20 or 20).

Branding:: [getbrandingpkg](#)

Branding:: [getbrandingpkgstatus](#)

Branding:: [getdefaultbrandingpkg](#)

Branding:: [installbrandingpkgs](#)

Branding:: [installimages](#)

Branding:: [killimages](#)

Branding:: [listingtypes](#)

Branding:: [listobjecttypes](#)

Branding:: [preloadconf](#)

Branding:: [resetall](#)

Branding:: [resetcss](#)

Branding:: [resethtml](#)

Branding:: [resolve_file](#)

Branding:: [resolvelocalcss](#)

Branding:: [savelocalcss](#)

Branding:: [setbrandingpkgstatus](#)

Branding:: [showpackages](#)

Branding:: [spritelist](#)

▼ CSVImport

CSVImport:: [columnchoices](#)

CSVImport:: [configimport](#)

CSVImport:: [data](#)

CSVImport:: [fetchimportdata](#)

CSVImport:: [isenabled](#)

CSVImport:: [loaddata](#)

CSVImport:: [processdata](#)

CSVImport:: [sendcontact](#)

CSVImport:: [uploadimport](#)

- [cPanel API 2 Functions - MySQLFE::userdbprivs](#) — This function lists a user's privileges on a MySQL® database.

Related Documentation

- [Use WHM API to Call cPanel API and UAPI](#) — You can call cPanel API and UAPI functions through the WHM API.
- [Guide to the Manage2 API](#) — The Manage2 API automates cPanel license management procedures.

- ▼ **Contactus**
 - Contactus:: isenab
led
 - Contactus:: sendc
ontact
 - ▼ **Cron**
 - Cron:: add_line
 - Cron:: edit_line
 - Cron:: fetchcron
 - Cron:: get_email
 - Cron:: listcron
 - Cron:: remove_line
 - Cron:: set_email
 - ▼ **CustInfo**
 - CustInfo:: contacte
mails
 - CustInfo:: contactp
refs
 - CustInfo:: displayc
ontactinfo
 - CustInfo:: savecon
tactinfo
 - ▼ **DBmap**
 - DBmap:: status
 - DBmap:: version
 - ▼ **DKIMUI**
 - DKIMUI:: available
 - DKIMUI:: getrecor
ds
 - DKIMUI:: install
 - DKIMUI:: installed
 - DKIMUI:: uninstall
 - ▼ **Denylp**
 - Denylp:: listdenyip
s
 - ▼ **DiskCounter**
 - DiskCounter:: disk
_counter
 - ▼ **DiskUsage**
 - DiskUsage:: buildc
ache
 - DiskUsage:: clearc
ache
 - DiskUsage:: fetch_
raw_disk_usage
 - DiskUsage:: fetchd
iskusage
 - DiskUsage:: fetchd
iskusagewithextras

- [Guide to UAPI — UAPI accesses the cPanel interface's features.](#)
- [Guide to WHM API 0 — WHM API 0 accesses the WHM interface's features.](#)
- [Guide to cPanel API 2 — cPanel API 2 accesses cPanel account information and modifies settings.](#)

▼ DnsLookup

DnsLookup:: name
2ip

▼ DomainLookup

DomainLookup:: c
ountbaseddomains

DomainLookup:: g
etbaseddomains

DomainLookup:: g
etdocroot

DomainLookup:: g
etdocroots

DomainLookup:: g
etmaindomain

▼ Email

Email:: accountna
me

Email:: adddomain
forward

Email:: addforward

Email:: addmx

Email:: addpop

Email:: browsebox
es

Email:: changemx

Email:: checkmain
discard

Email:: clearpopca
che

Email:: deletefilter

Email:: delforward

Email:: delmx

Email:: delpop

Email:: disablefilter

Email:: editquota

Email:: enablefilter

Email:: fetchautore
sponder

Email:: fetchcharm
aps

Email:: filteractions

Email:: filterlist

Email:: filtername

Email:: filterrules

Email:: get_archivi
ng_configuration

Email:: get_archivi
ng_default_configu

ration

Email:: get_archiving_types

Email:: get_default_email_quota

Email:: get_email_signing

Email:: get_max_email_quota

Email:: getabsbrowse_dir

Email:: getalwaysaccept

Email:: getdiskusage

Email:: getmxcheck

Email:: has_delegated_mailman_lists

Email:: list_system_filter_info

Email:: listaliasesbackups

Email:: listautoresponders

Email:: listdefaultaddresses

Email:: listdomainforwards

Email:: listfilterbackups

Email:: listfilters

Email:: listforwards

Email:: listlists

Email:: listmaildomains

Email:: listmx

Email:: listmxs

Email:: listpops

Email:: listpopssingle

Email:: listpopswitdisk

Email:: listpopswithimage

Email:: loadfilter

Email:: passwdpop

Email:: reorderfilters

Email:: set_archiving_configuration

Email:: set_archiving_default_configuration

Email:: set_email_signing

Email:: setalwaysaccept

Email:: setdefaultaddress

Email:: setmxcheck

Email:: storefilter

Email:: tracefilter

▼ EmailTrack

EmailTrack:: search

EmailTrack:: stats

EmailTrack:: trace

▼ Encoding

Encoding:: get_encodings

Encoding:: guess_file

Encoding:: guess_file_opts

▼ FSTest

FSTest:: dirisempty

▼ Fileman

Fileman:: autocompletedir

Fileman:: fileop

Fileman:: getabsdir

Fileman:: getdir

Fileman:: getdiractions

Fileman:: getdiskinfo

Fileman:: geteditty

Fileman:: getfileactions

Fileman:: getpath

Fileman:: listfiles

Fileman:: mkdir

Fileman:: mkfile

Fileman:: savefile

Fileman:: search

Fileman:: statfiles

Fileman:: uploadfiles

Fileman:: viewfile

▼ ForcePassword

ForcePassword:: get_force_password_flags

ForcePassword:: update_force_password_flags

▼ Frontpage

Frontpage:: fpenabled

Frontpage:: list

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: listftp

Ftp:: listftpsessions

Ftp:: listftpwithdisk

Ftp:: passwd

Ftp:: setquota

▼ Gpg

Gpg:: listgpgkeys

Gpg:: listsecretgpgkeys

Gpg:: number_of_private_keys

Gpg:: number_of_public_keys

▼ Htaccess

Htaccess:: listuser

Htaccess:: listusers

▼ HttpUtils

HttpUtils:: getdirindices

▼ ImageManager

ImageManager:: thumbnail

▼ LVEInfo

LVEInfo:: getUsage

▼ LangMods

LangMods:: getarcname

LangMods:: getkey

LangMods:: getpre
fix

LangMods:: install

LangMods:: langlis
t

LangMods:: list_av
ailable

LangMods:: list_in
stalled

LangMods:: magic
_status

LangMods:: pre_ru
n

LangMods:: search

LangMods:: setup

LangMods:: uninst
all

LangMods:: updat
e

▼ LeechProtect

LeechProtect:: set
up

▼ Locale

Locale:: get_encod
ing

Locale:: get_html_
dir_attr

Locale:: get_locale
_name

Locale:: get_user_
locale

Locale:: get_user_
locale_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse
r

Logaholic:: adduse
rprofile

Logaholic:: deleteu
ser

Logaholic:: deleteu
serprofile

Logaholic:: edituse
r

Logaholic:: fetchus
er

Logaholic:: listuser
profiles

Logaholic:: logahol
iclink

Logaholic:: proces
sstats

▼ Mime

Mime:: list_hotlinks

Mime:: listhandlers

Mime:: listmime

Mime:: listredirects

Mime:: redirectname

Mime:: redirecturlname

▼ MysqlFE

MysqlFE:: authorizehost

MysqlFE:: change
dbuserpassword

MysqlFE:: created
b

MysqlFE:: created
buser

MysqlFE:: dbuserexists

MysqlFE:: deauthorizehost

MysqlFE:: deleted
b

MysqlFE:: deleted
buser

MysqlFE:: getalldb
sinfo

MysqlFE:: getalldb
usersanddbs

MysqlFE:: getdbuserprivileges

MysqlFE:: getdbusers

MysqlFE:: gethosts

MysqlFE:: getmysqlprivileges

MysqlFE:: getmysqlserverprivileges

MysqlFE:: has_my
cnf_for_cpuser

MysqlFE:: listdbs

MysqlFE:: listdbsback
up

MysqlFE:: listhosts

MysqlFE:: listusers

MysqlFE:: listusers
indb

MysqlIFE:: revoked
buserprivileges

MysqlIFE:: setdbus
erprivileges

MysqlIFE:: userdbp
rivs

▼ MysqlOptimizer

MysqlOptimizer:: f
etch_slow_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does_news
_exist

News:: does_news
_type_exist

News:: get_news

▼ PHPINI

PHPINI:: getallopti
ons

PHPINI:: getoption
s

▼ Park

Park:: listaddondo
mains

Park:: listparkeddo
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change_
password

Passwd:: set_dige
st_auth

▼ PasswdStrength

PasswdStrength::
appstrengths

PasswdStrength::
get_password_stre
ngth

PasswdStrength::
get_required_stren
gth

▼ Postgres

Postgres:: listdbs

Postgres:: listusers

Postgres:: listusers
indb

Postgres:: userexi
sts

▼ Rand

Rand:: getranddat
a

▼ Resellers

Resellers:: get_su
b_accounts

▼ RoR

RoR:: addapp

RoR:: changeapp

RoR:: importrails

RoR:: listapps

RoR:: listrewrites

RoR:: needsimport

RoR:: removeapp

RoR:: removerewri
te

RoR:: restartapp

RoR:: setuprewrite

RoR:: softrestartap
p

RoR:: startapp

RoR:: stopapp

▼ SetLang

SetLang:: setlocale

▼ SourceIPCheck

SourceIPCheck:: a
ddip

SourceIPCheck:: d
elip

SourceIPCheck:: g
etaccount

SourceIPCheck:: li
stips

SourceIPCheck:: l
oadsecquestions

SourceIPCheck:: r
esetsecquestions

SourceIPCheck:: s
amplequestions

SourceIPCheck:: s
avesecquestions

▼ SPFUJ

SPFUJ:: available

SPFUJ:: count_sett
ings

SPFUI:: entries_co
mplete

SPFUI:: get_raw_r
ecord

SPFUI:: getmainse
rverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list_settin
gs

SPFUI:: load_curr
ent_values

SPFUI:: uninstall

▼ SSH

SSH:: authkey

SSH:: converttopp
k

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey_leg
acy

SSH:: importkey

SSH:: listkeys

▼ SSL

SSL:: fetchcabundl
e

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcnname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

▼ SSLInfo

SSLInfo:: fetchinfo

▼ StatCache

StatCache:: clearc
ache

▼ Stats

Stats:: getmonthly

bandwidth

Stats:: getmonthly
domainbandwidth

Stats:: getthismont
hsbwusage

Stats:: lastapache
hits

Stats:: lastvisitors

Stats:: listanalog

Stats:: listawstats

Stats:: listlastvisito
rs

Stats:: listrawlogs

Stats:: listurchin

Stats:: listwebalize
r

▼ StatsBar

StatsBar:: getrowc
ounter

StatsBar:: rowcoun
ter

StatsBar:: setrowc
ounter

StatsBar:: stat

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: chan
gedocroot

SubDomain:: delsu
bdomain

SubDomain:: getre
servedsubdomains

SubDomain:: listsu
bdomains

SubDomain:: validr
egex

▼ Themes

Themes:: apply_n
ew_theme

Themes:: does_cp
anel_theme_exist

Themes:: get_avail
able_themes

Themes:: get_the
mes_list

Themes:: restore_
saved_theme

▼ UI

UI:: dynamicinclud
elist

UI:: includelist

UI:: listform

UI:: paginate

UI:: paginate_list

▼ UserHttpUtils

UserHttpUtils:: get
dirindices

▼ WebDisk

WebDisk:: addweb
disk

WebDisk:: delweb
disk

WebDisk:: hasdige
st

WebDisk:: listwebd
isks

WebDisk:: passwd
webdisk

WebDisk:: set_dig
est_auth

WebDisk:: set_ho
mdir

WebDisk:: set_per
ms

WebDisk:: setstatu
s

▼ WebmailApps

WebmailApps:: list
webmailapps

▼ ZoneEdit

ZoneEdit:: add_zo
ne_record

ZoneEdit:: edit_zo
ne_record

ZoneEdit:: fetch_c
panel_generated_
domains

ZoneEdit:: fetchzo
ne

ZoneEdit:: fetchzo
ne_records

ZoneEdit:: fetchzo
nes

ZoneEdit:: get_zon
e_record

ZoneEdit:: remove
_zone_record

ZoneEdit:: resetzo
ne

