

# UAPI Functions - DAV::enable\_shared\_global\_addressbook

## Guide to UAPI

Return Data  
Filter Output  
Sort Output  
Paginate Output  
Output Columns  
Calls from the WHM API  
Custom UAPI Modules

Backup  
Backup::fullbackup  
p\_to\_ftp  
Backup::fullbackup\_to\_homedir  
Backup::fullbackup\_to\_scp\_with\_key

Backup::fullbackup\_to\_scp\_with\_password  
Backup::list\_backups

Bandwidth  
Bandwidth::get\_enabled\_protocols  
Bandwidth::get\_retention\_periods  
Bandwidth::query

Batch  
Batch::strict

Brand  
Brand::read

Branding  
Branding::file  
Branding::get\_applications  
Branding::get\_application\_information  
Branding::get\_available\_applications  
Branding::get\_info

## Description

This function enables the shared global address book for the current cPanel account's webmail accounts.

## Examples

### ▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/DAV/enable_shared_global_addressbook?name=user
```

#### Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

### ▼ LiveAPI PHP Class

```
$cpanel = new CPANEL(); // Connect to cPanel - only do this once.  
  
// Share the global address book.  
$DAV = $cpanel->uapi('DAV', 'enable_shared_global_addressbook', array('name' => 'user', ));
```

#### Note:

For more information, read our [Guide to the LiveAPI System](#).

## Function information

## About this module

The DAV module provides cPanel *Calendar and Contacts* settings, and provides tools for file lock management to the DAV server.

information\_for\_applications

Branding:: image

Branding:: include

Branding:: spritelist

#### CacheBuster

CacheBuster:: read

CacheBuster:: update

#### Chkserverd

Chkserverd:: get\_exit\_ports

Chkserverd:: get\_exit\_ports\_ssl

#### Chrome

Chrome:: get\_domain

#### Contactus

Contactus:: is\_enabled

#### cPAddons

cPAddons:: get\_available\_addons

cPAddons:: get\_instance\_settings

cPAddons:: list\_addon\_instances

#### cPGreyList

cPGreyList:: disable\_all\_domains

cPGreyList:: disable\_domains

cPGreyList:: enable\_all\_domains

cPGreyList:: enable\_domains

cPGreyList:: has\_greylisting\_enabled

cPGreyList:: list\_domains

#### DAV

DAV:: disable\_shared\_global\_addressbook

DAV:: enable\_shared\_global\_addressbook

DAV:: get\_calendar\_contacts\_config

DAV:: has\_shared\_global\_addressbook

### LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# Share the global  
address book.  
my  
$enable_shared_global  
_addressbook =  
$cpliveapi->uapi(  
    'DAV',  
    'enable_shared_global  
_addressbook',  
    {  
        'name' => 'user',  
    }  
);
```

#### Note:

For more information, read our [Guide to the LiveAPI System](#).

### cPanel Template Toolkit

```
<!-- Verify that the  
system enables the  
global address book.  
-->  
[% data = execute(  
    'DAV',  
    'enable_shared_global  
_addressbook' { 'name'  
=> 'user' } ); %]  
[% FOREACH q = data  
    %]  
    <p>  
        [% q %]  
    </p>  
[% END %]
```

#### Note:

For more information, read our [Guide to Template Toolkit documentation](#).

## About UAPI

UAPI accesses and modifies data for cPanel accounts.

#### Notes:

- The *Fe* int
- Ur **mi** us 20 or 20 ). ` 20 or 20 ).

## Find a function

DAV:: is\_dav\_service\_enabled

DAV:: is\_horde\_enabled

#### DCV

DCV:: check\_domains\_via\_dns

DCV:: check\_domains\_via\_http

DCV:: ensure\_domains\_can\_pass\_dcv

#### DomainInfo

DomainInfo:: domains\_data

DomainInfo:: list\_domains

DomainInfo:: main\_domain\_builtin\_subdomain\_aliases

DomainInfo:: single\_domain\_data

#### DNS

DNS:: ensure\_domains\_reside\_only\_locally

DNS:: has\_local\_authority

#### DNSSEC

DNSSEC:: disable\_dnssec

DNSSEC:: enable\_dnssec

DNSSEC:: fetch\_dns\_records

DNSSEC:: set\_nsec3

DNSSEC:: unset\_nsec3

#### Email

Email:: account\_name

Email:: add\_auto\_responder

Email:: add\_domain\_forwarder

Email:: add\_forwarder

Email:: add\_list

Email:: add\_mailman\_delegates

Email:: add\_mx

Email:: add\_pop

#### Command Line

```
uapi --user=username  
DAV  
enable_shared_global_  
addressbook name=user
```

#### Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local  
/cpanel/bin/  
uapi
```

#### Output (JSON)

```
{  
  "messages": null,  
  "data": {  
    "shared": "1"  
  },  
  "errors": null,  
  "status": 1,  
  "metadata": {  
  }  
}
```

#### Note:

Use cPanel's *API Shell* interface (`cPanel >> Home >> Advanced >> API Shell`) to directly test cPanel API calls.

- UAPI Functions - `Style::list` — This function lists information about a reseller account's available styles.

- UAPI Functions - `Style::set_default` — This function sets a customer's default style.

- UAPI Functions - `Style::update` — This function applies a new style to the cPanel interface.

## Parameters

Email:: add\_spam\_filter

Email:: browse\_mailbox

Email:: change\_mx

Email:: check\_fastmail

Email:: check\_pipe\_forwarder

Email:: delete\_auto\_responder

Email:: delete\_domain\_forwarder

Email:: delete\_filter

Email:: delete\_forwarder

Email:: delete\_held\_messages

Email:: delete\_list

Email:: delete\_mx

Email:: delete\_pop

Email:: disable\_filter

Email:: disable\_mailbox\_autocreate

Email:: disable\_spam\_assassin

Email:: disable\_spam\_autodelete

Email:: disable\_spam\_box

Email:: dispatch\_client\_settings

Email:: edit\_pop\_quota

Email:: enable\_filter

Email:: enable\_mailbox\_autocreate

Email:: enable\_spam\_assassin

Email:: enable\_spam\_box

Email:: fetch\_charmaps

Email:: fts\_rescan\_mailbox

Email:: generate\_mailman\_otp

Email:: get\_auto\_r

| Parameter | Type          | Description  | Possible values   | Example |
|-----------|---------------|--|-------------------|---------|
| name      | <i>string</i> | A cPanel account username or a Webmail user's email address.<br><br>If you do not specify a user, this parameter defaults to the currently-authenticated user. | A valid username. | user    |

## Returns

| Return | Type           | Description                                | Possible values  | Example |
|--------|----------------|--|--|---------|
| shared | <i>Boolean</i> | Whether the global address book is shared. | <ul style="list-style-type: none"> <li>1 — Shared.</li> <li>0 — Not shared.</li> </ul> | 1       |

- UAPI Functions - The mes: update — This function applies a new style to the cPanel interface.

esponder

Email:: get\_charges

Email:: get\_client\_settings

Email:: get\_default\_email\_quota

Email:: get\_default\_email\_quota\_mib

Email:: get\_disk\_usage

Email:: get\_filter

Email:: get\_held\_message\_count

Email:: get\_mailbox\_autocreate

Email:: get\_mailman\_delegates

Email:: get\_main\_account\_disk\_usage

Email:: get\_main\_account\_disk\_usage\_bytes

Email:: get\_max\_email\_quota

Email:: get\_max\_email\_quota\_mib

Email:: get\_pop\_quota

Email:: get\_spam\_settings

Email:: get\_webmail\_settings

Email:: has\_delegated\_mailman\_lists

Email:: has\_plaintext\_authentication

Email:: hold\_outgoing

Email:: is\_integer

Email:: list\_auto\_responders

Email:: list\_default\_address

Email:: list\_domain\_forwarders

Email:: list\_filters

Email:: list\_filters\_backups

Email:: list\_forward

ers

Email:: list\_forward  
ers\_backups

Email:: list\_lists

Email:: list\_mail\_d  
omains

Email:: list\_mxs

Email:: list\_pops

Email:: list\_pops\_  
with\_disk

Email:: list\_system  
\_filter\_info

Email:: passwd\_list

Email:: passwd\_po  
p

Email:: release\_ou  
tgoing

Email:: remove\_m  
ailman\_delegates

Email:: reorder\_filt  
ers

Email:: set\_always  
\_accept

Email:: set\_default  
\_address

Email:: set\_list\_pri  
vacy\_options

Email:: stats\_db\_st  
atus

Email:: store\_filter

Email:: suspend\_in  
coming

Email:: suspend\_lo  
gin

Email:: suspend\_o  
utgoing

Email:: trace\_filter

Email:: unsuspend  
\_incoming

Email:: unsuspend  
\_login

Email:: unsuspend  
\_outgoing

Email:: verify\_pass  
word

▼ EmailAuth

EmailAuth:: disabl  
e\_dkim

EmailAuth:: enable  
\_dkim

EmailAuth:: ensure  
\_dkim\_keys\_exist

EmailAuth:: fetch\_  
dkim\_private\_keys

EmailAuth:: install  
\_dkim\_private\_key  
s

EmailAuth:: install  
\_spf\_records

EmailAuth:: validat  
e\_current\_dkims

EmailAuth:: validat  
e\_current\_ptrs

EmailAuth:: validat  
e\_current\_spfs

#### ExternalAuthenticat ion

ExternalAuthentic  
ation:: add\_authn\_li  
nk

ExternalAuthentic  
ation:: configured\_  
modules

ExternalAuthentic  
ation:: get\_authn\_lin  
ks

ExternalAuthentic  
ation:: has\_external  
\_auth\_modules\_co  
nfigured

ExternalAuthentic  
ation:: remove\_auth  
n\_link

#### Features

Features:: get\_feat  
ure\_metadata

Features:: has\_fea  
ture

Features:: list\_feat  
ures

#### Fileman

Fileman:: autocom  
pletedir

Fileman:: empty\_tr  
ash

Fileman:: get\_file\_  
content

Fileman:: get\_file\_i  
nformation

Fileman:: list\_files

Fileman:: save\_file  
\_content

Fileman:: transcod  
e

Fileman:: upload\_files

▼ Ftp

Ftp:: add\_ftp

Ftp:: allows\_anonymous\_ftp

Ftp:: allows\_anonymous\_ftp\_incoming

Ftp:: delete\_ftp

Ftp:: ftp\_exists

Ftp:: get\_ftp\_daemon\_info

Ftp:: get\_port

Ftp:: get\_quota

Ftp:: get\_welcome\_message

Ftp:: kill\_session

Ftp:: list\_ftp

Ftp:: list\_ftp\_with\_disk

Ftp:: list\_sessions

Ftp:: passwd

Ftp:: server\_name

Ftp:: set\_anonymous\_ftp

Ftp:: set\_anonymous\_ftp\_incoming

Ftp:: set\_homedir

Ftp:: set\_quota

Ftp:: set\_welcome\_message

▼ Integration

Integration:: fetch\_url

▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

▼ LangPHP

LangPHP:: php\_get\_domain\_handler

LangPHP:: php\_get\_impacted\_domains



LangPHP:: php\_get\_installed\_versions

LangPHP:: php\_get\_system\_default\_version

LangPHP:: php\_get\_vhost\_versions

LangPHP:: php\_ini\_get\_user\_basic\_directives

LangPHP:: php\_ini\_get\_user\_content

LangPHP:: php\_ini\_get\_user\_paths

LangPHP:: php\_ini\_set\_user\_basic\_directives

LangPHP:: php\_ini\_set\_user\_content

LangPHP:: php\_set\_vhost\_versions

#### ▼ LastLogin

LastLogin:: get\_last\_or\_current\_logged\_in\_ip

#### ▼ Locale

Locale:: get\_attributes

#### ▼ Mailboxes

Mailboxes:: expunge\_messages

Mailboxes:: expunge\_messages\_for\_mailbox\_guid

Mailboxes:: get\_mailbox\_status

Mailboxes:: has\_utf8\_mailbox\_names

Mailboxes:: set\_utf8\_mailbox\_names

#### ▼ Market

Market:: cancel\_pending\_ssl\_certificate

Market:: create\_shopping\_cart

Market:: get\_all\_products

Market:: get\_certificate\_status\_details

Market:: get\_login\_url

Market:: get\_pending\_ssl\_certificates

Market:: get\_provider\_specific\_dcv\_constraints

Market:: get\_providers\_list

Market:: get\_ssl\_certificate\_if\_available

Market:: process\_ssl\_pending\_queue

Market:: request\_ssl\_certificates

Market:: set\_status\_of\_pending\_queue\_items

Market:: set\_url\_after\_checkout

Market:: validate\_login\_token

#### ▼ Mime

Mime:: add\_handler

Mime:: add\_hotlink

Mime:: add\_mime

Mime:: add\_redirect

Mime:: delete\_handler

Mime:: delete\_hotlink

Mime:: delete\_mime

Mime:: delete\_redirect

Mime:: list\_handlers

Mime:: list\_hotlinks

Mime:: list\_mime

Mime:: list\_redirects

Mime:: redirect\_info

#### ▼ ModSecurity

ModSecurity:: disable\_all\_domains

ModSecurity:: disable\_domains

ModSecurity:: enable\_all\_domains

ModSecurity:: enable\_domains

ModSecurity:: has\_modsecurity\_installed

ModSecurity:: list\_domains

▼ Mysql

Mysql:: add\_host

Mysql:: add\_host\_note

Mysql :: check\_database

Mysql:: create\_database

Mysql:: create\_user

Mysql:: delete\_database

Mysql:: delete\_host

Mysql:: delete\_user

Mysql:: get\_host\_notes

Mysql:: get\_privileges\_on\_database

Mysql:: get\_restrictions

Mysql:: get\_server\_information

Mysql:: locate\_server

Mysql:: rename\_database

Mysql:: rename\_user

Mysql:: repair\_database

Mysql:: revoke\_access\_to\_database

Mysql:: set\_password

Mysql:: set\_privileges\_on\_database

▼ Notifications

Notifications:: get\_notifications\_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile\_relati  
ative\_uri

▼ PassengerApps

PassengerApps:: d  
isable\_application

PassengerApps:: e  
dit\_application

PassengerApps:: e  
nable\_application

PassengerApps:: e  
nsure\_deps

PassengerApps:: li  
st\_applications

PassengerApps:: r  
egister\_application

PassengerApps:: u  
nregister\_applicati  
on

▼ PasswdStrength

PasswdStrength::  
get\_required\_stren  
gth

▼ Personalization

Personalization::se  
t

Personalization ::g  
et

▼ Postgresql

Postgresql:: create  
\_database

Postgresql:: create  
\_user

Postgresql:: delete  
\_database

Postgresql:: get\_re  
strictions

Postgresql:: grant\_  
all\_privileges

Postgresql:: renam  
e\_database

Postgresql:: renam  
e\_user

Postgresql:: renam  
e\_user\_no\_passw  
ord

Postgresql:: revok  
e\_all\_privileges

Postgresql:: set\_p  
assword

▼ Pushbullet

Pushbullet:: send\_  
test\_message

- ▼ Quota
  - Quota:: get\_quota\_info
- ▼ Resellers
  - Resellers:: list\_accounts
- ▼ ResourceUsage
  - ResourceUsage:: get\_usages
- ▼ Restore
  - Restore:: directory\_listing
  - Restore:: get\_users
  - Restore:: query\_file\_info
  - Restore:: restore\_file
- ▼ Session
  - Session:: create\_temp\_user
- ▼ SiteTemplates
  - SiteTemplates:: list\_site\_templates
  - SiteTemplates:: list\_user\_settings
  - SiteTemplates:: publish
- ▼ SpamAssassin
  - SpamAssassin :: clear\_spam\_box
  - SpamAssassin:: get\_symbolic\_test\_names
  - SpamAssassin:: get\_user\_preferences
  - SpamAssassin:: update\_user\_preference
- ▼ SSH
  - SSH:: get\_port
- ▼ SSL
  - SSL:: add\_autossl\_excluded\_domains
  - SSL:: can\_ssl\_redirect
  - SSL:: check\_shared\_cert
  - SSL:: delete\_cert
  - SSL:: delete\_csr
  - SSL:: delete\_key

SSL:: delete\_ssl

SSL:: disable\_mail\_sni

SSL:: enable\_mail\_sni

SSL:: fetch\_best\_for\_domain

SSL:: fetch\_cert\_info

SSL:: fetch\_certificates\_for\_fqdns

SSL:: fetch\_key\_and\_cabundle\_for\_certificate

SSL:: find\_certificates\_for\_key

SSL:: find\_csrs\_for\_key

SSL:: generate\_certificate

SSL:: generate\_csr

SSL:: generate\_key

SSL:: get\_autossl\_excluded\_domains

SSL:: get\_autossl\_pending\_queue

SSL:: get\_autossl\_problems

SSL:: get\_cabundle

SSL:: get\_cn\_name

SSL:: install\_ssl

SSL:: installed\_host

SSL:: installed\_hosts

SSL:: is\_autossl\_check\_in\_progress

SSL:: is\_mail\_sni\_supported

SSL:: is\_sni\_supported

SSL:: list\_certs

SSL:: list\_csrs

SSL:: list\_keys

SSL:: list\_ssl\_items

SSL:: mail\_sni\_status

tus

SSL:: rebuild\_mail  
\_snl\_config

SSL:: rebuildssldb

SSL:: remove\_aut  
ossl\_excluded\_do  
mains

SSL:: set\_autossl\_  
excluded\_domains

SSL:: set\_cert\_frie  
ndly\_name

SSL:: set\_csr\_frien  
dly\_name

SSL:: set\_key\_frie  
ndly\_name

SSL:: set\_primary  
\_ssl

SSL:: set\_ssl\_shar  
e

SSL:: show\_cert

SSL:: show\_csr

SSL:: show\_key

SSL:: start\_autossl\_  
\_check

SSL:: toggle\_ssl\_r  
edirects\_for\_doma  
ins

SSL:: upload\_cert

SSL:: upload\_key

▼ StatsBar

StatsBar:: get\_stat  
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

▼ SubDomain

SubDomain:: adds  
ubdomain

▼ Themes

Themes:: get\_the  
me\_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create\_fu  
ll\_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate\_user\_configuration

TwoFactorAuth:: get\_user\_configuration

TwoFactorAuth:: remove\_user\_configuration

TwoFactorAuth:: set\_user\_configuration

▼ UserManager

UserManager:: check\_account\_conflicts

UserManager:: create\_user

UserManager:: delete\_user

UserManager:: dismiss\_user

UserManager:: edit\_user

UserManager:: list\_users

UserManager:: lookup\_service\_account

UserManager:: lookup\_user

UserManager:: merge\_service\_account

UserManager:: unlink\_service\_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDepl



## oyment

VersionControlDep  
loyment:: **create**

VersionControlDep  
loyment:: **delete**

VersionControlDep  
loyment:: **retrieve**

### ▼ WebDisk

WebDisk:: **delete\_**  
**user**

WebDisk:: **set\_ho**  
**medir**

WebDisk:: **set\_pas**  
**sword**

WebDisk:: **set\_per**  
**missions**

### ▼ WebmailApps

WebmailApps:: **list**  
**webmailapps**

### ▼ WebVhosts

WebVhost:: **list\_do**  
**mains**

WebVhost:: **list\_ssl**  
**\_capable\_domains**

### ▼ WordPressBackup

WordPressBackup  
:: **any\_running**

WordPressBackup  
:: **cancel**

WordPressBackup  
:: **cleanup**

WordPressBackup  
:: **get\_available\_ba**  
**ckups**

WordPressBackup  
:: **is\_running**

WordPressBackup  
:: **start**

### ▼ WordPressInstance

#### Manager

WordPressInstanc  
eManager:: **cancel**  
**\_scan**

WordPressInstanc  
eManager:: **cleanu**  
**p\_scan**

WordPressInstanc  
eManager:: **chang**  
**e\_admin\_passwor**  
**d**

WordPressInstanc  
eManager:: **config**  
**ure\_autoupdate**

WordPressInstanc  
eManager:: **get\_ap**

i\_version

WordPressInstanceManager:: **get\_instance\_by\_id**

WordPressInstanceManager:: **get\_instances**

WordPressInstanceManager:: **get\_latest\_wordpress\_version\_from\_wordpress\_org**

WordPressInstanceManager:: **get\_scan\_results**

WordPressInstanceManager:: **is\_installable\_addon\_available**

WordPressInstanceManager:: **start\_scan**

▼ WordPressRestore

WordPressRestore:: **any\_running**

WordPressRestore:: **cleanup**

WordPressRestore:: **start**