

UAPI Functions - Personalization::get

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup:: fullbacku
p_to_ftp

Backup:: fullbacku
p_to_homedir

Backup:: fullbacku
p_to_scp_with_key

Backup:: fullbacku
p_to_scp_with_password

Backup:: list_backups

Bandwidth

Bandwidth:: get_enabled_protocols

Bandwidth:: get_retention_periods

Bandwidth:: query

Batch

Batch:: strict

Brand

Brand:: read

Branding

Branding:: file

Branding:: get_applications

Branding:: get_application_information

Branding:: get_available_applications

Branding:: get_information_for_applications

Description

This function retrieves the data from an NVData file on disk. cPanel NVData is a per-account configuration storage mechanism that you can use to maintain persistent cPanel & WHM settings across multiple sessions. This includes custom settings for your own themes and plugins.

Examples

Raw HTTP Request

```
POST
/cpsess#####/execute/Personalization/get HTTP/1.1
Host:
example.com:2083
Cookie:
#####
#####
Content-Type:
application/json
Content-Length: 33

{ "names": [
  "coffee", "milk" ] }
```

LiveAPI PHP Class

Note:
This method is not supported at this time. We plan to add support for this method in future released of cPanel & WHM.

LiveAPI Perl Module

Note:
This method is not supported at this time. We plan to add support for this method in future released of cPanel & WHM.

Function Information

About this module

The Personalization module manages variables.

About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster
 - CacheBuster:: read
 - CacheBuster:: update
- Chkserverd
 - Chkserverd:: get_exit_ports
 - Chkserverd:: get_exit_ports_ssl
- Chrome
 - Chrome:: get_domain
- Contactus
 - Contactus:: is_enabled
- cPAddons
 - cPAddons:: get_available_addons
 - cPAddons:: get_instance_settings
 - cPAddons:: list_addon_instances
- cPGreyList
 - cPGreyList:: disable_all_domains
 - cPGreyList:: disable_domains
 - cPGreyList:: enable_all_domains
 - cPGreyList:: enable_domains
 - cPGreyList:: has_greylisting_enabled
 - cPGreyList:: list_domains
- DAV
 - DAV:: disable_shared_global_addressbook
 - DAV:: enable_shared_global_addressbook
 - DAV:: get_calendar_contacts_config
 - DAV:: has_shared_global_addressbook
 - DAV:: is_dav_service_enabled

▼ cPanel Template Toolkit

```
<!-- Retrieve the NVData data from the server. -->
[%
    SET results =
    execute(
    'Personalization',
    'get', {
        names => [
        'coffee', 'milk'
        ]});
    %]
```

Note:

For more information, read our [Guide to Template Toolkit documentation](#).

▼ Command Line

```
echo '{"names":
["coffee", "milk"]}'
| uapi
--user=username
--input=json
--output=json
Personalization get
```

Unable to render {include} The included page could not be found.

Notes:

- This function
- This function

Find a function

- cPanel API 2 Functions - NVData::setall
- This function creates a non-volatile data store.

- DAV:: is_horde_enabled
- DCV:: check_domains_via_dns
 - DCV:: check_domains_via_http
 - DCV:: ensure_domains_can_pass_dcv
 - DomainInfo
 - DomainInfo:: domains_data
 - DomainInfo:: list_domains
 - DomainInfo:: main_domain_builtin_subdomain_aliases
 - DomainInfo:: single_domain_data
 - DNS
 - DNS:: ensure_domains_reside_only_locally
 - DNS:: has_local_authority
 - DNSSEC
 - DNSSEC:: disable_dnssec
 - DNSSEC:: enable_dnssec
 - DNSSEC:: fetch_dns_records
 - DNSSEC:: set_nsec3
 - DNSSEC:: unset_nsec3
 - Email
 - Email:: account_name
 - Email:: add_auto_responder
 - Email:: add_domain_forwarder
 - Email:: add_forwarder
 - Email:: add_list
 - Email:: add_mailman_delegates
 - Email:: add_mx
 - Email:: add_pop
 - Email:: add_spam_filter

Output (JSON)

```

{
  "messages": null,
  "warnings": null,
  "errors": null,
  "metadata": {},
  "data": {
    "personalization": {
      "milk": {
        "success": 1,
        "reason": "OK",
        "value": "cold"
      },
      "coffee": {
        "reason": "OK",
        "value": "hot",
        "success": 1
      }
    }
  },
  "status": 1
}

```

Note:
 cPanel's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) does **not** support this function.

Parameters

Parameter	Type	Description	Possible values	Example
names	array	<p>Required</p> <p>A list of NVData keys stored on the server.</p>	<p>A valid array.</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Notes:</p> </div>	

- cPanel API 2 Functions - NVData:: get — This function retrieves data from a non-volatile data store.
 - cPanel API 2 Functions - NVData:: set — This function creates a non-volatile data store.
 - WHM API 0 Functions - nvget — This function retrieves the value of a non-volatile variable.

Email:: browse_mailbox
Email:: change_mx
Email:: check_fastmail
Email:: check_pipe_forwarder
Email:: delete_auto_responder
Email:: delete_domain_forwarder
Email:: delete_filter
Email:: delete_forwarder
Email:: delete_held_messages
Email:: delete_list
Email:: delete_mx
Email:: delete_pop
Email:: disable_filter
Email:: disable_mailbox_autocreate
Email:: disable_spam_assassin
Email:: disable_spam_autodelete
Email:: disable_spam_box
Email:: dispatch_client_settings
Email:: edit_pop_quota
Email:: enable_filter
Email:: enable_mailbox_autocreate
Email:: enable_spam_assassin
Email:: enable_spam_box
Email:: fetch_charmaps
Email:: fts_rescan_mailbox
Email:: generate_mailman_opt
Email:: get_auto_responder
Email:: get_chase

• The array 'sva' uses character 2048 character 2048.

ts

Email:: get_client_settings

Email:: get_default_email_quota

Email:: get_default_email_quota_mib

Email:: get_disk_usage

Email:: get_filter

Email:: get_held_message_count

Email:: get_mailbox_autocreate

Email:: get_mailman_delegates

Email:: get_main_account_disk_usage

Email:: get_main_account_disk_usage_bytes

Email:: get_max_email_quota

Email:: get_max_email_quota_mib

Email:: get_pop_quota

Email:: get_spam_settings

Email:: get_webmail_settings

Email:: has_delegated_mailman_lists

Email:: has_plaintext_authentication

Email:: hold_outgoing

Email:: is_integer

Email:: list_autoresponders

Email:: list_default_address

Email:: list_domain_forwarders

Email:: list_filters

Email:: list_filters_backups

Email:: list_forwarders

Email:: list_forward

• If you do not set a value for these requests, the system will return null.

Returns

Return	Type	Description	Possible values	Example
--------	------	-------------	-----------------	---------

ers_backups
 Email:: list_lists
 Email:: list_mail_domains
 Email:: list_mxns
 Email:: list_pops
 Email:: list_pops_with_disk
 Email:: list_system_filter_info
 Email:: passwd_list
 Email:: passwd_pop
 Email:: release_outgoing
 Email:: remove_mailman_delegates
 Email:: reorder_filters
 Email:: set_always_accept
 Email:: set_default_address
 Email:: set_list_privacy_options
 Email:: stats_db_status
 Email:: store_filter
 Email:: suspend_incoming
 Email:: suspend_login
 Email:: suspend_outgoing
 Email:: trace_filter
 Email:: unsuspend_incoming
 Email:: unsuspend_login
 Email:: unsuspend_outgoing
 Email:: verify_password
 EmailAuth
 EmailAuth:: disable_dkim
 EmailAuth:: enable_dkim
 EmailAuth:: ensure_dkim_keys_exist

personalization	hash	The NVData keys and values stored on the server.	This hash contains the key* hash.	
key*	hash	<p>The retrieved NVData information stored on the server.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : You set this return's name based on the keys that you provide in the personalization parameter with the UAPI Functions - Personalization::set function.</p> </div> <p>This function returns this value in the personalization hash.</p>	A hash that contains the reason, success, and value returns.	
reason	string	<p>The message that describes the failure if the success Boolean returns 0.</p> <p>This function returns this value in the key* hash.</p>	A valid string.	OK

EmailAuth:: fetch_dkim_private_keys

EmailAuth:: install_dkim_private_keys

EmailAuth:: install_spf_records

EmailAuth:: validate_current_dkims

EmailAuth:: validate_current_ptrs

EmailAuth:: validate_current_spfs

ExternalAuthentication

ExternalAuthentication:: add_authn_link

ExternalAuthentication:: configured_modules

ExternalAuthentication:: get_authn_links

ExternalAuthentication:: has_external_auth_modules_configured

ExternalAuthentication:: remove_authn_link

Features

Features:: get_feature_metadata

Features:: has_feature

Features:: list_features

Fileman

Fileman:: autocompletedir

Fileman:: empty_trash

Fileman:: get_file_content

Fileman:: get_file_information

Fileman:: list_files

Fileman:: save_file_content

Fileman:: transcoding

Fileman:: upload_files

<p>s u c c e s s</p>	<p>Boolean</p>	<p>Whether the function successfully retrieved the value from the server.</p> <p>This function returns this value in the key * hash.</p>	<ul style="list-style-type: none"> 1 — Successful. 0 — Unsuccessful. 	<p>1</p>
<p>v a l u e</p>	<p>string/undef</p>	<p>The value stored in the field or undef if the pair does not exist in the store.</p> <p>This function returns this value in the key * hash.</p>	<ul style="list-style-type: none"> A valid string. null 	<p>hot</p>

▼ Ftp

Ftp:: add_ftp

Ftp:: allows_anonymous_ftp

Ftp:: allows_anonymous_ftp_incoming

Ftp:: delete_ftp

Ftp:: ftp_exists

Ftp:: get_ftp_daemon_info

Ftp:: get_port

Ftp:: get_quota

Ftp:: get_welcome_message

Ftp:: kill_session

Ftp:: list_ftp

Ftp:: list_ftp_with_disk

Ftp:: list_sessions

Ftp:: passwd

Ftp:: server_name

Ftp:: set_anonymous_ftp

Ftp:: set_anonymous_ftp_incoming

Ftp:: set_homedir

Ftp:: set_quota

Ftp:: set_welcome_message

▼ Integration

Integration:: fetch_url

▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

▼ LangPHP

LangPHP:: php_get_domain_handler

LangPHP:: php_get_impacted_domains

LangPHP:: php_get_installed_version

s

LangPHP:: php_get_system_default_version

LangPHP:: php_get_vhost_versions

LangPHP:: php_ini_get_user_basic_directives

LangPHP:: php_ini_get_user_content

LangPHP:: php_ini_get_user_paths

LangPHP:: php_ini_set_user_basic_directives

LangPHP:: php_ini_set_user_content

LangPHP:: php_set_vhost_versions

▼ LastLogin

LastLogin:: get_last_or_current_logged_in_ip

▼ Locale

Locale:: get_attributes

▼ Mailboxes

Mailboxes:: expunge_mailbox_messages

Mailboxes:: expunge_messages_for_mailbox_guid

Mailboxes:: get_mailbox_status

Mailboxes:: has_utf8_mailbox_names

Mailboxes:: set_utf8_mailbox_names

▼ Market

Market:: cancel_pending_ssl_certificate

Market:: create_shopping_cart

Market:: get_all_products

Market:: get_certificate_status_details

Market:: get_login_url

Market:: get_pending_ssl_certificates

Market:: get_provider_specific_dcv_constraints

Market:: get_providers_list

Market:: get_ssl_certificate_if_available

Market:: process_ssl_pending_queue

Market:: request_ssl_certificates

Market:: set_status_of_pending_queue_items

Market:: set_url_after_checkout

Market:: validate_login_token

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: delete_handler

Mime:: delete_hotlink

Mime:: delete_mime

Mime:: delete_redirect

Mime:: list_handlers

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirects

Mime:: redirect_info

▼ ModSecurity

ModSecurity:: disable_all_domains

ModSecurity:: disable_domains

ModSecurity:: enable_all_domains

ModSecurity:: enable_domains

ModSecurity:: has
_modsecurity_inst
alled

ModSecurity:: list_
domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_
note

Mysql :: check_dat
abase

Mysql:: create_dat
abase

Mysql:: create_use
r

Mysql:: delete_dat
abase

Mysql:: delete_hos
t

Mysql:: delete_use
r

Mysql:: get_host_n
otes

Mysql:: get_privile
ges_on_database

Mysql:: get_restrict
ions

Mysql:: get_server
_information

Mysql:: locate_ser
ver

Mysql:: rename_d
atabase

Mysql:: rename_us
er

Mysql:: repair_dat
abase

Mysql:: revoke_ac
cess_to_database

Mysql:: set_passw
ord

Mysql:: set_privile
ges_on_database

▼ Notifications

Notifications:: get_
notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_rel
ative_uri

- ▼ PassengerApps
 - PassengerApps:: disable_application
 - PassengerApps:: edit_application
 - PassengerApps:: enable_application
 - PassengerApps:: ensure_deps
 - PassengerApps:: list_applications
 - PassengerApps:: register_application
 - PassengerApps:: unregister_application
- ▼ PasswdStrength
 - PasswdStrength:: get_required_strength
- ▼ Personalization
 - Personalization::set
 - Personalization::get
- ▼ Postgresql
 - Postgresql:: create_database
 - Postgresql:: create_user
 - Postgresql:: delete_database
 - Postgresql:: get_restrictions
 - Postgresql:: grant_all_privileges
 - Postgresql:: rename_database
 - Postgresql:: rename_user
 - Postgresql:: rename_user_no_password
 - Postgresql:: revoke_all_privileges
 - Postgresql:: set_password
- ▼ Pushbullet
 - Pushbullet:: send_test_message
- ▼ Quota
 - Quota:: get_quota_info

- ▼ Resellers
 - Resellers:: list_accounts
- ▼ ResourceUsage
 - ResourceUsage:: get_usages
- ▼ Restore
 - Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- ▼ Session
 - Session:: create_temp_user
- ▼ SiteTemplates
 - SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- ▼ SpamAssassin
 - SpamAssassin :: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key
 - SSL:: delete_ssl
 - SSL :: disable_mail_sni

SSL:: enable_mail
_sni

SSL:: fetch_best_f
or_domain

SSL:: fetch_cert_in
fo

SSL:: fetch_certific
ates_for_fqdns

SSL:: fetch_key_a
nd_cabundle_for_
certificate

SSL:: find_certifica
tes_for_key

SSL:: find_csrs_for
_key

SSL:: generate_ce
rt

SSL:: generate_cs
r

SSL:: generate_ke
y

SSL:: get_autossl_
excluded_domains

SSL:: get_autossl_
pending_queue

SSL:: get_autossl_
problems

SSL:: get_cabundl
e

SSL:: get_cn_nam
e

SSL:: install_ssl

SSL:: installed_ho
st

SSL:: installed_ho
sts

SSL:: is_autossl_c
heck_in_progress

SSL:: is_mail_sni_
supported

SSL:: is_sni_supp
orted

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_item
s

SSL:: mail_sni_sta
tus

SSL:: rebuild_mail
_sni_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete_user

WebDisk:: set_homedir

WebDisk:: set_password

WebDisk:: set_permissions

▼ WebmailApps

WebmailApps:: list_webmailapps

▼ WebVhosts

WebVhost:: list_domains

WebVhost:: list_ssl_capable_domains

▼ WordPressBackup

WordPressBackup:: any_running

WordPressBackup:: cancel

WordPressBackup:: cleanup

WordPressBackup:: get_available_backups

WordPressBackup:: is_running

WordPressBackup:: start

▼ WordPressInstance

Manager

WordPressInstanceManager:: cancel_scan

WordPressInstanceManager:: cleanup_scan

WordPressInstanceManager:: change_admin_password

WordPressInstanceManager:: configure_autoupdate

WordPressInstanceManager:: get_api_version

WordPressInstanceManager:: get_in

stance_by_id

WordPressInstanceManager::get_instances

WordPressInstanceManager::get_latest_wordpress_version_from_wordpress_org

WordPressInstanceManager::get_scan_results

WordPressInstanceManager::is_installable_addon_available

WordPressInstanceManager::start_scan

▼ WordPressRestore

WordPressRestore::any_running

WordPressRestore::cleanup

WordPressRestore::start