

UAPI Functions - Market::set_status_of_pending_queue_items

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup::
fullbacku

p_to_ftp

Backup:: fullbacku
p_to_homedir

Backup:: fullbacku
p_to_scp_with_key

Backup:: fullbacku
p_to_scp_with_pa
ssword

Backup:: list_back
ups

Bandwidth

Bandwidth:: get_e
nabled_protocols

Bandwidth:: get_re
tention_periods

Bandwidth:: query

Batch

Batch:: strict

Brand

Brand:: read

Branding

Branding:: file

Branding:: get_app
lications

Branding:: get_app
lication_informatio
n

Branding:: get_ava
ilable_applications

Branding:: get_info

Description

This function sets the status of an item or items in the cPanel Market pending queue.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/Market/set_status_of_pending_queue_items?provider=cPStore&order_item_id=8675309&status=confirmed
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

Function information

About this module

The Market module manages connections to cPanel Market providers.

information_for_applications

Branding:: image

Branding:: include

Branding:: spritelist

CacheBuster

CacheBuster:: read

CacheBuster:: update

Chkserverd

Chkserverd:: get_exit_ports

Chkserverd:: get_exit_ports_ssl

Chrome

Chrome:: get_domain

Contactus

Contactus:: is_enabled

cPAddons

cPAddons:: get_available_addons

cPAddons:: get_instance_settings

cPAddons:: list_addon_instances

cPGreyList

cPGreyList:: disable_all_domains

cPGreyList:: disable_domains

cPGreyList:: enable_all_domains

cPGreyList:: enable_domains

cPGreyList:: has_greylisting_enabled

cPGreyList:: list_domains

DAV

DAV:: disable_shared_global_addressbook

DAV:: enable_shared_global_addressbook

DAV:: get_calendar_contacts_config

DAV:: has_shared_global_addressbook

LiveAPI PHP Class

```
$cpanel = new CPANEL(); // Connect to cPanel - only do this once.

// Set the status of 8675309 item in the queue to confirmed status.
$ davidbowielives = $cpanel->uapi(
    'Market',
    'set_status_of_pending_queue_items',
    array(
        'provider' => 'CPStore',
        'order_item_id' => '8675309',
        'status' => 'confirmed'
    )
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

About UAPI

UAPI accesses and modifies data for cPanel accounts.

Notes:

- The Fe
- Ur
- mi
- us
- 20
- or
- 20
-).`
- 20
- or
- 20
-).

Find a function

DAV:: is_dav_service_enabled

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# Set the status of  
8675309 item in the  
queue to confirmed  
status  
my $davidbowielives =  
$cpliveapi->uapi(  
  'Market',  
  'set_status_of_pending_queue_items',  
  {  
    'provider'  
=> 'cPStore',  
  
    'order_item_id' =>  
    '8675309',  
    'status'  
=> 'confirmed'  
  }  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

- UAPI Functions - SSL: :delete_ssl — This function removes SSL from a domain.
- UAPI Functions - SSL: :fetch_best_for_domain — This function retrieves the best-available certificate for the domain.
- UAPI Functions - SSL: :fetch_certificate — This function retrieves all of a certificate's available information.

Email:: add_spam_filter
Email:: browse_mailbox
Email:: change_mx
Email:: check_fastmail
Email:: check_pipe_forwarder
Email:: delete_auto_responder
Email:: delete_domain_forwarder
Email:: delete_filter
Email:: delete_forwarder
Email:: delete_held_messages
Email:: delete_list
Email:: delete_mx
Email:: delete_pop
Email:: disable_filter
Email:: disable_mailbox_autocreate
Email:: disable_spam_assassin
Email:: disable_spam_autodelete
Email:: disable_spam_box
Email:: dispatch_client_settings
Email:: edit_pop_quota
Email:: enable_filter
Email:: enable_mailbox_autocreate
Email:: enable_spam_assassin
Email:: enable_spam_box
Email:: fetch_charmaps
Email:: fts_rescan_mailbox
Email:: generate_mailman_otp
Email:: get_auto_r

▼ cPanel Template Toolkit

```
<!-- Set the status of 8675309 item in the queue to confirmed status -->[% execute('Market', 'set_status_of_pending_queue_items', { provider => 'cPStore', 'order_item_id' => '8675309', 'status' => 'confirmed' }) %]
```

Note:

For more information, read our [Guide to Template Toolkit](#) documentation.

▼ Command Line

```
uapi --user=username  
Market  
set_status_of_pending_queue_items  
provider=cPStore  
order_item_id=8675309  
status=confirmed
```

Notes:

- You **must** [URI-encode](#) values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local  
/cpanel/bin/uapi
```

- UAPI Functions - SSL: `:fetch_key_and_certificate` — This function extracts the private key and CA bundle information from a certificate.

esponder

Email:: get_charts

Email:: get_client_settings

Email:: get_default_email_quota

Email:: get_default_email_quota_mib

Email:: get_disk_usage

Email:: get_filter

Email:: get_held_message_count

Email:: get_mailbox_autocreate

Email:: get_mailman_delegates

Email:: get_main_account_disk_usage

Email:: get_main_account_disk_usage_bytes

Email:: get_max_email_quota

Email:: get_max_email_quota_mib

Email:: get_pop_quota

Email:: get_spam_settings

Email:: get_webmail_settings

Email:: has_delegated_mailman_lists

Email:: has_plaintext_authentication

Email:: hold_outgoing

Email:: is_integer

Email:: list_autoresponders

Email:: list_default_address

Email:: list_domain_forwarders

Email:: list_filters

Email:: list_filters_backups

Email:: list_forward

Output (JSON)

Success:

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "metadata": {
  }
}
```

Failure:

```
{
  "data": {
    "error_type": "EntryDoesNotExist",
    "order_item_ids": [
      8675309,
      5551212
    ]
  },
  "messages": null,
  "errors": null,
  "status": 1,
  "metadata": {
  }
}
```

Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

| Parameter | Type | Description | Possible values | Example |
|-----------|------|-------------|-----------------|---------|
|-----------|------|-------------|-----------------|---------|

ers

Email:: list_forward
ers_backups

Email:: list_lists

Email:: list_mail_d
omains

Email:: list_mx

Email:: list_pops

Email:: list_pops_
with_disk

Email:: list_system
_filter_info

Email:: passwd_list

Email:: passwd_po
p

Email:: release_ou
tgoing

Email:: remove_m
ailman_delegates

Email:: reorder_filt
ers

Email:: set_always
_accept

Email:: set_default
_address

Email:: set_list_pri
vacy_options

Email:: stats_db_st
atus

Email:: store_filter

Email:: suspend_in
coming

Email:: suspend_lo
gin

Email:: suspend_o
utgoing

Email:: trace_filter

Email:: unsuspend
_incoming

Email:: unsuspend
_login

Email:: unsuspend
_outgoing

Email:: verify_pass
word

▼ EmailAuth

EmailAuth:: disabl
e_dkim

EmailAuth:: enable
_dkim

| | | | | |
|----------|--------|--|-----------------|---------|
| provider | string | Required The cPanel Market provider's name. | A valid string. | cPStore |
|----------|--------|--|-----------------|---------|

EmailAuth:: ensure_dkim_keys_exist

EmailAuth:: fetch_dkim_private_keys

EmailAuth:: install_dkim_private_keys

EmailAuth:: install_spf_records

EmailAuth:: validate_current_dkims

EmailAuth:: validate_current_ptrs

EmailAuth:: validate_current_spfs

ExternalAuthentication

ExternalAuthentication:: add_authn_link

ExternalAuthentication:: configured_modules

ExternalAuthentication:: get_authn_links

ExternalAuthentication:: has_external_auth_modules_configured

ExternalAuthentication:: remove_authn_link

Features

Features:: get_feature_metadata

Features:: has_feature

Features:: list_features

Fileman

Fileman:: autocomplete_dir

Fileman:: empty_trash

Fileman:: get_file_content

Fileman:: get_file_information

Fileman:: list_files

Fileman:: save_file_content

Fileman:: transcode

| | | | | |
|---------------|--------|---|-----------------|---------|
| order_item_id | string | <p>Required</p> <p>The ID of the ordered item.</p> <div data-bbox="732 243 872 1896" style="border: 1px solid orange; padding: 5px;"> <p>Note</p> <p>: To set the status for multiple items, duplicate or increment the parameter name. For example, to change the status for three certificates, use the order_item_id-1 parameter multiple times or use the order_item_id-2, and order_item_id-3 parameters.</p> </div> | A valid string. | 8675309 |
|---------------|--------|---|-----------------|---------|

- Fileman:: upload_files
- ▼ Ftp
 - Ftp:: add_ftp
 - Ftp:: allows_anonymous_ftp
 - Ftp:: allows_anonymous_ftp_incoming
 - Ftp:: delete_ftp
 - Ftp:: ftp_exists
 - Ftp:: get_ftp_daemon_info
 - Ftp:: get_port
 - Ftp:: get_quota
 - Ftp:: get_welcome_message
 - Ftp:: kill_session
 - Ftp:: list_ftp
 - Ftp:: list_ftp_with_disk
 - Ftp:: list_sessions
 - Ftp:: passwd
 - Ftp:: server_name
 - Ftp:: set_anonymous_ftp
 - Ftp:: set_anonymous_ftp_incoming
 - Ftp:: set_homedir
 - Ftp:: set_quota
 - Ftp:: set_welcome_message
- ▼ Integration
 - Integration:: fetch_url
- ▼ KnownHosts
 - KnownHosts:: create
 - KnownHosts:: delete
 - KnownHosts:: update
 - KnownHosts:: verify
- ▼ LangPHP
 - LangPHP:: php_get_domain_handler
 - LangPHP:: php_get_impacted_domains

| | | | | |
|--------|--------|---|--|-----------|
| status | string | Required The new status of the item in the cPanel Market pending queue. | <ul style="list-style-type: none"> • confirmed — The system confirmed payment for the item with the provider. | confirmed |
|--------|--------|---|--|-----------|

Returns

Note:
The function **only** returns these values if the user or users do **not** have the `order_item_id` item in the cPanel Market pending queue.

| Return | Type | Description | Possible values | Example |
|----------------|--------|--|--|---------|
| error_type | string | The type of error that the function encountered. <div style="border: 1px solid #f0e68c; padding: 5px; width: fit-content; margin: 10px auto;">Note : We introduced this return in cPanel & WHM version 56.1.</div> | <ul style="list-style-type: none"> • EntryDoesNotExist — The returned <code>order_item_ids</code> do not exist in the cPanel Market pending queue for the user. | cpStore |
| order_item_ids | array | An array that lists order item IDs which do not exist in the cPanel Market pending queue for the user. <div style="border: 1px solid #f0e68c; padding: 5px; width: fit-content; margin: 10px auto;">Note : We introduced this return in cPanel & WHM version 56.1.</div> | A list of order item IDs. | 8675309 |

LangPHP:: php_get_installed_versions

LangPHP:: php_get_system_default_version

LangPHP:: php_get_vhost_versions

LangPHP:: php_ini_get_user_basic_directives

LangPHP:: php_ini_get_user_content

LangPHP:: php_ini_get_user_paths

LangPHP:: php_ini_set_user_basic_directives

LangPHP:: php_ini_set_user_content

LangPHP:: php_set_vhost_versions

▼ LastLogin

LastLogin:: get_last_or_current_logged_in_ip

▼ Locale

Locale:: get_attributes

▼ Mailboxes

Mailboxes:: expunge_messages

Mailboxes:: expunge_messages_for_mailbox_guid

Mailboxes:: get_mailbox_status

Mailboxes:: has_utf8_mailbox_names

Mailboxes:: set_utf8_mailbox_names

▼ Market

Market:: cancel_pending_ssl_certificate

Market:: create_shopping_cart

Market:: get_all_products

Market:: get_certificate_status_details

Market:: get_login_url

Market:: get_pending_ssl_certificates

Market:: get_provider_specific_dcv_constraints

Market:: get_providers_list

Market:: get_ssl_certificate_if_available

Market:: process_ssl_pending_queue

Market:: request_ssl_certificates

Market:: set_status_of_pending_queue_items

Market:: set_url_after_checkout

Market:: validate_login_token

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: delete_handler

Mime:: delete_hotlink

Mime:: delete_mime

Mime:: delete_redirect

Mime:: list_handlers

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirects

Mime:: redirect_info

▼ ModSecurity

ModSecurity:: disable_all_domains

ModSecurity:: disable_domains

ModSecurity:: enable_all_domains

ModSecurity:: enable_domains

ModSecurity:: has_modsecurity_installed

ModSecurity:: list_domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_note

Mysql :: check_database

Mysql:: create_database

Mysql:: create_user

Mysql:: delete_database

Mysql:: delete_host

Mysql:: delete_user

Mysql:: get_host_notes

Mysql:: get_privileges_on_database

Mysql:: get_restrictions

Mysql:: get_server_information

Mysql:: locate_server

Mysql:: rename_database

Mysql:: rename_user

Mysql:: repair_database

Mysql:: revoke_access_to_database

Mysql:: set_password

Mysql:: set_privileges_on_database

▼ Notifications

Notifications:: get_notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_relati
ative_uri

▼ PassengerApps

PassengerApps:: d
isable_application

PassengerApps:: e
dit_application

PassengerApps:: e
nable_application

PassengerApps:: e
nsure_deps

PassengerApps:: li
st_applications

PassengerApps:: r
egister_application

PassengerApps:: u
nregister_applicati
on

▼ PasswdStrength

PasswdStrength::
get_required_stren
gth

▼ Personalization

Personalization::se
t

Personalization ::g
et

▼ Postgresql

Postgresql:: create
_database

Postgresql:: create
_user

Postgresql:: delete
_database

Postgresql:: get_re
strictions

Postgresql:: grant_
all_privileges

Postgresql:: renam
e_database

Postgresql:: renam
e_user

Postgresql:: renam
e_user_no_passw
ord

Postgresql:: revok
e_all_privileges

Postgresql:: set_p
assword

▼ Pushbullet

Pushbullet:: send_
test_message

- ▼ Quota
 - Quota:: get_quota_info
- ▼ Resellers
 - Resellers:: list_accounts
- ▼ ResourceUsage
 - ResourceUsage:: get_usages
- ▼ Restore
 - Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- ▼ Session
 - Session:: create_temp_user
- ▼ SiteTemplates
 - SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- ▼ SpamAssassin
 - SpamAssassin :: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key

SSL:: delete_ssl

SSL:: disable_mail_sni

SSL:: enable_mail_sni

SSL:: fetch_best_for_domain

SSL:: fetch_cert_info

SSL:: fetch_certificates_for_fqdns

SSL:: fetch_key_and_bundle_for_certificate

SSL:: find_certificates_for_key

SSL:: find_csrs_for_key

SSL:: generate_certificate

SSL:: generate_csr

SSL:: generate_key

SSL:: get_autossl_excluded_domains

SSL:: get_autossl_pending_queue

SSL:: get_autossl_problems

SSL:: get_bundle

SSL:: get_cn_name

SSL:: install_ssl

SSL:: installed_host

SSL:: installed_hosts

SSL:: is_autossl_check_in_progress

SSL:: is_mail_sni_supported

SSL:: is_sni_supported

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_items

SSL:: mail_sni_status

tus

SSL:: rebuild_mail
_snl_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDepl

oyment

VersionControlDep
loyment:: **create**

VersionControlDep
loyment:: **delete**

VersionControlDep
loyment:: **retrieve**

▼ WebDisk

WebDisk:: **delete_**
user

WebDisk:: **set_ho**
medir

WebDisk:: **set_pas**
sword

WebDisk:: **set_per**
missions

▼ WebmailApps

WebmailApps:: **list**
webmailapps

▼ WebVhosts

WebVhost:: **list_do**
mains

WebVhost:: **list_ssl**
_capable_domains

▼ WordPressBackup

WordPressBackup
:: **any_running**

WordPressBackup
:: **cancel**

WordPressBackup
:: **cleanup**

WordPressBackup
:: **get_available_ba**
ckups

WordPressBackup
:: **is_running**

WordPressBackup
:: **start**

▼ WordPressInstance

Manager

WordPressInstanc
eManager:: **cancel**
_scan

WordPressInstanc
eManager:: **cleanu**
p_scan

WordPressInstanc
eManager:: **chang**
e_admin_passwor
d

WordPressInstanc
eManager:: **config**
ure_autoupdate

WordPressInstanc
eManager:: **get_ap**

i_version

WordPressInstanceManager:: **get_instance_by_id**

WordPressInstanceManager:: **get_instances**

WordPressInstanceManager:: **get_latest_wordpress_version_from_wordpress_org**

WordPressInstanceManager:: **get_scan_results**

WordPressInstanceManager:: **is_installable_addon_available**

WordPressInstanceManager:: **start_scan**

▼ WordPressRestore

WordPressRestore:: **any_running**

WordPressRestore:: **cleanup**

WordPressRestore:: **start**