

# UAPI Functions - Email::get\_filter

## Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup  
Backup:: fullbackup  
p\_to\_ftp

Backup:: fullbackup  
p\_to\_homedir

Backup:: fullbackup  
p\_to\_scp\_with\_key

Backup:: fullbackup  
p\_to\_scp\_with\_password

Backup:: list\_backups

### Bandwidth

Bandwidth:: get\_enabled\_protocols

Bandwidth:: get\_retention\_periods

Bandwidth:: query

### Batch

Batch:: strict

### Brand

Brand:: read

### Branding

Branding:: file

Branding:: get\_applications

Branding:: get\_application\_information

Branding:: get\_available\_applications

Branding:: get\_information\_for\_applications

## Description

This function retrieves an email filter's information.

### Important:

In cPanel & WHM version 76 and later, when you disable the MailReceive role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

## Examples

### ▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess##  
▼ #####/execute/Email/get_filter?account=user%40example.com&filtername=coffee
```

### Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

## Function information

## About this module

The Email module modifies cPanel email account settings.

## About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster
  - CacheBuster:: read
  - CacheBuster:: update
- Chkservd
  - Chkservd:: get\_exim\_ports
  - Chkservd:: get\_exim\_ports\_ssl
- Chrome
  - Chrome:: get\_dom
- Contactus
  - Contactus:: is\_enabled
- cPAddons
  - cPAddons:: get\_available\_addons
  - cPAddons:: get\_instance\_settings
  - cPAddons:: list\_addon\_instances
- cPGreyList
  - cPGreyList:: disable\_all\_domains
  - cPGreyList:: disable\_domains
  - cPGreyList:: enable\_all\_domains
  - cPGreyList:: enable\_domains
  - cPGreyList:: has\_greylisting\_enabled
  - cPGreyList:: list\_domains
- DAV
  - DAV:: disable\_shared\_global\_addressbook
  - DAV:: enable\_shared\_global\_addressbook
  - DAV:: get\_calendar\_contacts\_config
  - DAV:: has\_shared\_global\_addressbook
  - DAV:: is\_dav\_service\_enabled

## LiveAPI PHP Class

```

$cpnl = new
CPANEL(); // Connect
to cPanel - only do
this once.

// List information
for
user@example.com's
coffee filter.
$filter_info =
$cpnl->uapi(
    'Email',
    'get_filter',
    array(
        'account'
=>
'user@example.com',
        'filtername'
=> 'coffee',
    )
);

```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

**Notes:**

- The *Fe*
- Ur  
mu  
us  
20  
or  
20  
)`  
20  
or  
20  
).

## Find a function

The Mailbox module manages email messages.

- UAPI Functions - Email::edit\_pop\_quota — This function changes an address's quota.

DAV:: is\_horde\_enabled

#### ▼ DCV

DCV:: check\_domains\_via\_dns

DCV:: check\_domains\_via\_http

DCV:: ensure\_domains\_can\_pass\_dcv

#### ▼ DomainInfo

DomainInfo:: domains\_data

DomainInfo:: list\_domains

DomainInfo:: main\_domain\_builtin\_subdomain\_aliases

DomainInfo:: single\_domain\_data

#### ▼ DNS

DNS:: ensure\_domains\_reside\_only\_locally

DNS:: has\_local\_authority

#### ▼ DNSSEC

DNSSEC:: disable\_dnssec

DNSSEC:: enable\_dnssec

DNSSEC:: fetch\_dns\_records

DNSSEC:: set\_nsec3

DNSSEC:: unset\_nsec3

#### ▼ Email

Email:: account\_name

Email:: add\_auto\_responder

Email:: add\_domain\_forwarder

Email:: add\_forwarder

Email:: add\_list

Email:: add\_mailman\_delegates

Email:: add\_mx

Email:: add\_pop

Email:: add\_spam\_filter

### ▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
  
# List information  
for  
user@example.com's  
coffee filter.  
my $filter_info =  
$cpliveapi->uapi(  
  'Email',  
  'get_filter',  
  {  
    'account'  
  }  
=>  
  'user@example.com',  
  'filtername'  
=> 'coffee',  
  }  
);
```

#### **Note:**

For more information, read our [Guide to the LiveAPI System](#).

- UAPI Functions - SpamAssassin::get\_user\_preferences

This function lists the Apache SpamAssassin™ settings for the account.

- UAPI Functions - SpamAssassin::clear\_spam\_box

This function clears the spam box of all its contents for all email accounts.

Email: browse\_mailbox  
Email: change\_mx  
Email: check\_fastmail  
Email: check\_pipe\_forwarder  
Email: delete\_auto\_responder  
Email: delete\_domain\_forwarder  
Email: delete\_filter  
Email: delete\_forwarder  
Email: delete\_held\_messages  
Email: delete\_list  
Email: delete\_mx  
Email: delete\_pop  
Email: disable\_filter  
Email: disable\_mailbox\_autocreate  
Email: disable\_spam\_assassin  
Email: disable\_spam\_autodelete  
Email: disable\_spam\_box  
Email: dispatch\_client\_settings  
Email: edit\_pop\_quota  
Email: enable\_filter  
Email: enable\_mailbox\_autocreate  
Email: enable\_spam\_assassin  
Email: enable\_spam\_box  
Email: fetch\_charmaps  
Email: fts\_rescan\_mailbox  
Email: generate\_mailman\_opt  
Email: get\_auto\_responder  
Email: get\_chase

## ▼ cPanel Template Toolkit

```
<!-- Get a hash of data, then display the destination value. -->
[% data = execute(
  'Email',
  'get_filter', {
    'account' =>
      'user@example.com',
    'filtername' =>
      'coffee', } ); %]
[% FOREACH q =
  data.dest %]
  <p>
    [% q %]
  </p>
[% END %]

<!-- Get only the filter destination. -->
[% execute( 'Email',
  'get_filter', {
    'account' =>
      'user@example.com',
    'filtername' =>
      'coffee', }
  ).data.dest %]
```

**Note:**

For more information, read our [Guide to Template Toolkit](#) documentation.

- UAPI Functions - SpamAssassin::update\_preferences — This function sets the Apache SpamAssassin™ settings for the account.

ts

Email: get\_client\_settings

Email: get\_default\_email\_quota

Email: get\_default\_email\_quota\_mib

Email: get\_disk\_usage

Email: get\_filter

Email: get\_held\_message\_count

Email: get\_mailbox\_autocreate

Email: get\_mailman\_delegates

Email: get\_main\_account\_disk\_usage

Email: get\_main\_account\_disk\_usage\_bytes

Email: get\_max\_email\_quota

Email: get\_max\_email\_quota\_mib

Email: get\_pop\_quota

Email: get\_spam\_settings

Email: get\_webmail\_settings

Email: has\_delegated\_mailman\_lists

Email: has\_plaintext\_authentication

Email: hold\_outgoing

Email: is\_integer

Email: list\_autoresponders

Email: list\_default\_address

Email: list\_domain\_forwarders

Email: list\_filters

Email: list\_filters\_backups

Email: list\_forwarders

Email: list\_forward

## Command Line

```
uapi --user=username
Email get_filter
account=user%40example.com
filtername=coffee
```

### Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

ers\_backups  
 Email: list\_lists  
 Email: list\_mail\_domains  
 Email: list\_mx  
 Email: list\_pops  
 Email: list\_pops\_with\_disk  
 Email: list\_system\_filter\_info  
 Email: passwd\_list  
 Email: passwd\_pop  
 Email: release\_outgoing  
 Email: remove\_mailman\_delegates  
 Email: reorder\_filters  
 Email: set\_always\_accept  
 Email: set\_default\_address  
 Email: set\_list\_privacy\_options  
 Email: stats\_db\_status  
 Email: store\_filter  
 Email: suspend\_incoming  
 Email: suspend\_login  
 Email: suspend\_outgoing  
 Email: trace\_filter  
 Email: unsuspend\_incoming  
 Email: unsuspend\_login  
 Email: unsuspend\_outgoing  
 Email: verify\_password

## Output (JSON)

```

{
  "messages": null,
  "errors": null,
  "status": 1,
  "data": {
    "actions": [
      {
        "number": 1,
        "dest":
"/dev/null",
        "action":
"save"
      }
    ],
    "filtername":
"FilterTest",
    "rules": [
      {
        "number": 1,
        "match":
"contains",
        "part":
"$header_from:",
        "opt": "or",
        "val":
"example.com"
      }
    ],
    "metadata": {
      "transformed": 1
    }
  }
}
  
```

**Note:**  
 Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

## Parameters

EmailAuth  
 EmailAuth:: disable\_dkim  
 EmailAuth:: enable\_dkim  
 EmailAuth:: ensure\_dkim\_keys\_exist

Parameter	Type	Description	Possible values	Example
account	string	<b>Required</b> The email address that owns the filter.	A valid email address on the cPanel account.	user@example.com

EmailAuth:: fetch\_dkim\_private\_keys

EmailAuth:: install\_dkim\_private\_keys

EmailAuth:: install\_spf\_records

EmailAuth:: validate\_current\_dkims

EmailAuth:: validate\_current\_ptrs

EmailAuth:: validate\_current\_spfs

#### ExternalAuthentication

ExternalAuthentication:: add\_auth\_link

ExternalAuthentication:: configured\_modules

ExternalAuthentication:: get\_auth\_links

ExternalAuthentication:: has\_external\_auth\_modules\_configured

ExternalAuthentication:: remove\_auth\_link

#### Features

Features:: get\_feature\_metadata

Features:: has\_feature

Features:: list\_features

#### Fileman

Fileman:: autocompletedir

Fileman:: empty\_trash

Fileman:: get\_file\_content

Fileman:: get\_file\_information

Fileman:: list\_files

Fileman:: save\_file\_content

Fileman:: transcode

Fileman:: upload\_files

filtername	string	<b>Required</b> The filter's name.	The name of an email filter.	coffee
------------	--------	---------------------------------------	------------------------------	--------

## Returns

Return	Type	Description	Possible values	Example
actions	array	An array that contains a hash of the filter's actions.	This array's hash contains the number, dest, and action returns.	
number	integer	The filter's position in the order of the account's filters.  The function returns this value in the actions hash.	A positive value.	1
dest	string	The destination to which the filter sends mail.  The function returns this value in the actions hash.	<ul style="list-style-type: none"><li>A file path.</li><li>An application path.</li><li>A valid email address.</li></ul>	/dev/null
action	string	The filter's action.  The function returns this value in the actions hash.	<ul style="list-style-type: none"><li>deliver — The filter sends mail to the dest address.</li><li>fail — The filter forces a delivery failure.</li><li>finish — The filter stops message processing.</li><li>save — The filter saves mail to the dest file.</li><li>pipe — The filter sends mail to the dest application.</li></ul>	
filtername	string	The filter's name.	The filtername input parameter's value.	coffee
rules	array	An array that contains a hash of the filter's rules.	This array's hash contains the number, match, part, opt, and val returns.	

▼ Ftp

- Ftp:: add\_ftp
- Ftp:: allows\_anonymous\_ftp
- Ftp:: allows\_anonymous\_ftp\_incoming
- Ftp:: delete\_ftp
- Ftp:: ftp\_exists
- Ftp:: get\_ftp\_daemon\_info
- Ftp:: get\_port
- Ftp:: get\_quota
- Ftp:: get\_welcome\_message
- Ftp:: kill\_session
- Ftp:: list\_ftp
- Ftp:: list\_ftp\_with\_disk
- Ftp:: list\_sessions
- Ftp:: passwd
- Ftp:: server\_name
- Ftp:: set\_anonymous\_ftp
- Ftp:: set\_anonymous\_ftp\_incoming
- Ftp:: set\_homedir
- Ftp:: set\_quota
- Ftp:: set\_welcome\_message

number	integer	The filter's position in the order of the account's filters.  The function returns this value in the rules hash.	A positive value.	1
match	string	The filter's match type.  The function returns this value in the rules hash.	<ul style="list-style-type: none"> <li>• is</li> <li>• matches</li> <li>• contains</li> <li>• does not contain</li> <li>• begins</li> <li>• does not begin</li> <li>• ends</li> <li>• does not end</li> <li>• does not match</li> <li>• is above</li> <li>• is not above</li> <li>• is below</li> <li>• is not below</li> </ul>	contains

▼ Integration

- Integration:: fetch\_url

▼ KnownHosts

- KnownHosts:: create
- KnownHosts:: delete
- KnownHosts:: update
- KnownHosts:: verify

▼ LangPHP

- LangPHP:: php\_get\_domain\_handler
- LangPHP:: php\_get\_impacted\_domains
- LangPHP:: php\_get\_installed\_version



S

LangPHP:: `php_get_system_default_version`

LangPHP:: `php_get_vhost_versions`

LangPHP:: `php_ini_get_user_basic_directives`

LangPHP:: `php_ini_get_user_content`

LangPHP:: `php_ini_get_user_paths`

LangPHP:: `php_ini_set_user_basic_directives`

LangPHP:: `php_ini_set_user_content`

LangPHP:: `php_set_vhost_versions`

▼ LastLogin

LastLogin:: `get_last_or_current_logged_in_ip`

▼ Locale

Locale:: `get_attributes`

▼ Mailboxes

Mailboxes:: `expunge_mailbox_messages`

Mailboxes:: `expunge_messages_for_mailbox_guid`

Mailboxes:: `get_mailbox_status`

Mailboxes:: `has_utf8_mailbox_names`

Mailboxes:: `set_utf8_mailbox_names`

▼ Market

Market:: `cancel_pending_ssl_certificate`

Market:: `create_shopping_cart`

Market:: `get_all_products`

Market:: `get_certificate_status_details`

Market:: `get_login_url`

Market:: `get_pending_ssl_certificates`

<p>part</p>	<p>string</p>	<p>The queried email section.</p> <p>The function returns this value in the rules hash.</p>	<ul style="list-style-type: none"> <li>• <code>\$header_from: —</code> Matches against the From: section.</li> <li>• <code>\$header_subject: —</code> Matches against the Subject: section.</li> <li>• <code>\$header_to: —</code> Matches against the To: section.</li> <li>• <code>\$reply_address: —</code> Matches against the Reply To: section.</li> <li>• <code>\$message_body —</code> Matches against the message's body.</li> <li>• <code>\$message_headers —</code> Matches against the message's headers.</li> <li>• <code>foranyaddress \$h_to: , \$h_cc: , \$h_bcc: —</code> Matches against all message recipients.</li> <li>• <code>not delivered —</code> Matches if the message is not queued for delivery.</li> <li>• <code>error_message —</code> Matches if the incoming message bounced.</li> </ul>	<p>\$message_body</p>
<p>opt</p>	<p>string</p>	<p>The connection between multiple conditions.</p> <p>The function returns this value in the rules hash.</p>	<ul style="list-style-type: none"> <li>• <code>and —</code> Match both conditions.</li> <li>• <code>or —</code> Match either condition.</li> <li>• <code>null —</code> There is only one condition.</li> </ul>	<p>or</p>

val	string	The matched value.  The function returns this value in the rules hash.	A string value.	coconut
-----	--------	--	-----------------	---------

Market:: get\_provider\_specific\_dcv\_constraints

Market:: get\_providers\_list

Market:: get\_ssl\_certificate\_if\_available

Market:: process\_ssl\_pending\_queue

Market:: request\_ssl\_certificates

Market:: set\_status\_of\_pending\_queue\_items

Market:: set\_url\_after\_checkout

Market:: validate\_login\_token

▼ Mime

Mime:: add\_handler

Mime:: add\_hotlink

Mime:: add\_mime

Mime:: add\_redirect

Mime:: delete\_handler

Mime:: delete\_hotlink

Mime:: delete\_mime

Mime:: delete\_redirect

Mime:: list\_handlers

Mime:: list\_hotlinks

Mime:: list\_mime

Mime:: list\_redirects

Mime:: redirect\_info

▼ ModSecurity

ModSecurity:: disable\_all\_domains

ModSecurity:: disable\_domains

ModSecurity:: enable\_all\_domains

ModSecurity:: enable\_domains

ModSecurity:: has  
\_modsecurity\_inst  
alled

ModSecurity:: list\_  
domains

▼ Mysql

Mysql:: add\_host

Mysql:: add\_host\_  
note

Mysql :: check\_dat  
abase

Mysql:: create\_dat  
abase

Mysql:: create\_use  
r

Mysql:: delete\_dat  
abase

Mysql:: delete\_hos  
t

Mysql:: delete\_use  
r

Mysql:: get\_host\_n  
otes

Mysql:: get\_privile  
ges\_on\_database

Mysql:: get\_restrict  
ions

Mysql:: get\_server\_  
information

Mysql:: locate\_ser  
ver

Mysql:: rename\_d  
atabase

Mysql:: rename\_us  
er

Mysql:: repair\_dat  
abase

Mysql:: revoke\_ac  
cess\_to\_database

Mysql:: set\_passw  
ord

Mysql:: set\_privile  
ges\_on\_database

▼ Notifications

Notifications:: get\_  
notifications\_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile\_rel  
ative\_uri

- ▼ PassengerApps
  - PassengerApps:: disable\_application
  - PassengerApps:: edit\_application
  - PassengerApps:: enable\_application
  - PassengerApps:: ensure\_deps
  - PassengerApps:: list\_applications
  - PassengerApps:: register\_application
  - PassengerApps:: unregister\_application
- ▼ PasswdStrength
  - PasswdStrength:: get\_required\_strength
- ▼ Personalization
  - Personalization::set
  - Personalization::get
- ▼ Postgresql
  - Postgresql:: create\_database
  - Postgresql:: create\_user
  - Postgresql:: delete\_database
  - Postgresql:: get\_restrictions
  - Postgresql:: grant\_all\_privileges
  - Postgresql:: rename\_database
  - Postgresql:: rename\_user
  - Postgresql:: rename\_user\_no\_password
  - Postgresql:: revoke\_all\_privileges
  - Postgresql:: set\_password
- ▼ Pushbullet
  - Pushbullet:: send\_test\_message
- ▼ Quota
  - Quota:: get\_quota\_info

- ▼ Resellers
  - Resellers:: list\_accounts
- ▼ ResourceUsage
  - ResourceUsage:: get\_usages
- ▼ Restore
  - Restore:: directory\_listing
  - Restore:: get\_users
  - Restore:: query\_file\_info
  - Restore:: restore\_file
- ▼ Session
  - Session:: create\_temp\_user
- ▼ SiteTemplates
  - SiteTemplates:: list\_site\_templates
  - SiteTemplates:: list\_user\_settings
  - SiteTemplates:: publish
- ▼ SpamAssassin
  - SpamAssassin :: clear\_spam\_box
  - SpamAssassin:: get\_symbolic\_test\_names
  - SpamAssassin:: get\_user\_preferences
  - SpamAssassin:: update\_user\_preference
- ▼ SSH
  - SSH:: get\_port
- ▼ SSL
  - SSL:: add\_autossl\_excluded\_domains
  - SSL:: can\_ssl\_redirect
  - SSL:: check\_shared\_cert
  - SSL:: delete\_cert
  - SSL:: delete\_csr
  - SSL:: delete\_key
  - SSL:: delete\_ssl
  - SSL :: disable\_mail\_sni

SSL:: enable\_mail  
\_sni

SSL:: fetch\_best\_f  
or\_domain

SSL:: fetch\_cert\_in  
fo

SSL:: fetch\_certific  
ates\_for\_fqdns

SSL:: fetch\_key\_a  
nd\_cabundle\_for\_  
certificate

SSL:: find\_certifica  
tes\_for\_key

SSL:: find\_csrs\_for  
\_key

SSL:: generate\_ce  
rt

SSL:: generate\_cs  
r

SSL:: generate\_ke  
y

SSL:: get\_autossl\_  
excluded\_domains

SSL:: get\_autossl\_  
pending\_queue

SSL:: get\_autossl\_  
problems

SSL:: get\_cabundl  
e

SSL:: get\_cn\_nam  
e

SSL:: install\_ssl

SSL:: installed\_ho  
st

SSL:: installed\_ho  
sts

SSL:: is\_autossl\_c  
heck\_in\_progress

SSL:: is\_mail\_sni\_  
supported

SSL:: is\_sni\_supp  
orted

SSL:: list\_certs

SSL:: list\_csrs

SSL:: list\_keys

SSL:: list\_ssl\_item  
s

SSL:: mail\_sni\_sta  
tus

SSL:: rebuild\_mail  
\_sni\_config

SSL:: rebuildssldb

SSL:: remove\_aut  
ossl\_excluded\_do  
mains

SSL:: set\_autossl\_  
excluded\_domains

SSL:: set\_cert\_frie  
ndly\_name

SSL:: set\_csr\_frien  
dly\_name

SSL:: set\_key\_frie  
ndly\_name

SSL:: set\_primary  
\_ssl

SSL:: set\_ssl\_shar  
e

SSL:: show\_cert

SSL:: show\_csr

SSL:: show\_key

SSL:: start\_autossl\_  
\_check

SSL:: toggle\_ssl\_r  
edirects\_for\_doma  
ins

SSL:: upload\_cert

SSL:: upload\_key

▼ StatsBar

StatsBar:: get\_stat  
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

▼ SubDomain

SubDomain:: adds  
ubdomain

▼ Themes

Themes:: get\_the  
me\_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create\_fu  
ll\_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate\_user\_configuration

TwoFactorAuth:: get\_user\_configuration

TwoFactorAuth:: remove\_user\_configuration

TwoFactorAuth:: set\_user\_configuration

▼ UserManager

UserManager:: check\_account\_conflicts

UserManager:: create\_user

UserManager:: delete\_user

UserManager:: dismiss\_user

UserManager:: edit\_user

UserManager:: list\_users

UserManager:: lookup\_service\_account

UserManager:: lookup\_user

UserManager:: merge\_service\_account

UserManager:: unlink\_service\_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create



VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete\_user

WebDisk:: set\_homedir

WebDisk:: set\_password

WebDisk:: set\_permissions

▼ WebmailApps

WebmailApps:: list\_webmailapps

▼ WebVhosts

WebVhost:: list\_domains

WebVhost:: list\_ssl\_capable\_domains

▼ WordPressBackup

WordPressBackup:: any\_running

WordPressBackup:: cancel

WordPressBackup:: cleanup

WordPressBackup:: get\_available\_backups

WordPressBackup:: is\_running

WordPressBackup:: start

▼ WordPressInstance

Manager

WordPressInstanceManager:: cancel\_scan

WordPressInstanceManager:: cleanup\_scan

WordPressInstanceManager:: change\_admin\_password

WordPressInstanceManager:: configure\_autoupdate

WordPressInstanceManager:: get\_api\_version

WordPressInstanceManager:: get\_in

stance\_by\_id

WordPressInstanceManager::get\_instances

WordPressInstanceManager::get\_latest\_wordpress\_version\_from\_wordpress\_org

WordPressInstanceManager::get\_scan\_results

WordPressInstanceManager::is\_installable\_addon\_available

WordPressInstanceManager::start\_scan

▼ WordPressRestore

WordPressRestore::any\_running

WordPressRestore::cleanup

WordPressRestore::start