

cPanel API 2 Functions - MysqlFE::listusers

Guide to cPanel API 2

Return Data

Filter and Sort Output

Paginate Output

Output Columns

Calls from the WHM API

cPanel Tags (deprecated)

Description

This function lists an account's MySQL® database users.

Warning:

We **strongly** recommend that you use [UAPI](#) instead of cPanel API 2. However, no equivalent UAPI function exists.

Important:

In cPanel & WHM version 76 and later, when you disable the MySQL role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

[AddonDomain](#)

WHM API (JSON)

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?cpanel_jsonapi_user=user&cpanel_jsonapi_api_version=2&cpanel_jsonapi_module=MysqlFE&cpanel_jsonapi_function=listusers
```

Note:

For more information, read our [Calls from the WHM API](#) documentation.

- AddonDomain: addomain
- AddonDomain: deladdondomain
- AddonDomain: listaddondomains
- Backups
 - Backups: listfullbackups
- Bandwidth
 - Bandwidth: addhttpbandwidth
 - Bandwidth: getbwdata
 - Bandwidth: gethourlyaveragebwoveryear
- BoxTrapper
 - BoxTrapper: accountmanagelist
- Branding
 - Branding: addbrandingobj
 - Branding: applist
 - Branding: brandingeditor
 - Branding: createpkg
 - Branding: cssmerge
 - Branding: delbrandingobj
 - Branding: delpkg
 - Branding: gensprites

Function information

About this module

The MysqlFE module manages MySQL® databases, users, and services.

Branding:: getbrandingpkg

Branding:: getbrandingpkgstatus

Branding:: getdefaultbrandingpkg

Branding:: installbrandingpkgs

Branding:: installimages

Branding:: killimages

Branding:: listingtypes

Branding:: listobjecttypes

Branding:: preloadconf

Branding:: resetall

Branding:: resetscripts

Branding:: resethtml

Branding:: resolvefile

Branding:: resolvelocalcss

Branding:: savelocalcss

Branding:: setbrandingpkgstatus

Branding:: showpackages

Branding:: spritelist

▼ CSVImport

CSVImport:: columnchoices

CSVImport:: configimport

CSVImport:: data

CSVImport:: fetchimportdata

CSVImport:: isenabled

CSVImport:: loaddata

CSVImport:: processdata

CSVImport:: sendcontact

CSVImport:: uploadimport

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.
```

```
// List database  
users.  
$list_users =  
$cpanel->api2(  
    'MysqlFE',  
    'listusers'  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# List database  
users.  
my $list_users =  
$cpliveapi->api2(  
    'MysqlFE',  
    'listusers',  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

About cPanel API 2

cPanel API 2 accesses and modifies data for cPanel accounts.

Notes:

- The
Fe

int
• Ur
mu
us
20
or
20
)`
20
or
20
)

Find a function

- ▼ Contactus
 - Contactus:: isenab led
 - Contactus:: sendc ontact
- ▼ Cron
 - Cron:: add_line
 - Cron:: edit_line
 - Cron:: fetchcron
 - Cron:: get_email
 - Cron:: listcron
 - Cron:: remove_line
 - Cron:: set_email
- ▼ CustInfo
 - CustInfo:: contacte mails
 - CustInfo:: contactp refs
 - CustInfo:: displayc ontactinfo
 - CustInfo:: savecon tactinfo
- ▼ DBmap
 - DBmap:: status
 - DBmap:: version
- ▼ DKIMUI
 - DKIMUI:: available
 - DKIMUI:: getrecor ds
 - DKIMUI:: install
 - DKIMUI:: installed
 - DKIMUI:: uninstall
- ▼ Denylp
 - Denylp:: listdenyip s
- ▼ DiskCounter
 - DiskCounter:: disk _counter
- ▼ DiskUsage
 - DiskUsage:: buildc ache
 - DiskUsage:: clearc ache
 - DiskUsage:: fetch_ raw_disk_usage
 - DiskUsage:: fetchd iskusage
 - DiskUsage:: fetchd iskusagewithextras

▼ cPanel Tag System (deprecated)

Warnings:

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecat ed**. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Dep recated cPanel Tag Usage](#) docume ntation.

▼ Command Line

```
cpapi2
--user=username
MysqlFE listusers
```

Notes:

- You **must** [URI-encode](#) values.
- username represents your account-level username.
- You **must** run the `--user=username` command.
- For more information and additional output options, read our [Guide to cPanel API 2](#) documentation or run the `cpapi2 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapi2` command:

```
/usr/local
/cpanel/bi
n/cpapi2
```

▼ Output (JSON)

```
{
  "cpanelresult": {
    "apiversion": 2,
    "data": [
      {
        "dblist": [
          ],

```

- cPan el API 2 Mod ules - Mysq LFE — The Mysq lFE mod ule man ages MyS QL® data base s, user s, and servi ces.
- cPan el API 2 Func tions - Mysq LFE:: auth orize host — This functi on auth orize s a host for remo te acce ss to the acco unt's data base .

- ▼ DnsLookup
 - DnsLookup:: name2ip
- ▼ DomainLookup
 - DomainLookup:: countbaseddomains
 - DomainLookup:: getbaseddomains
 - DomainLookup:: getdocroot
 - DomainLookup:: getdocroots
 - DomainLookup:: getmaindomain
- ▼ Email
 - Email:: accountname
 - Email:: adddomainforward
 - Email:: addforward
 - Email:: addmx
 - Email:: addpop
 - Email:: browseboxes
 - Email:: changemx
 - Email:: checkmaindiscard
 - Email:: clearpopcache
 - Email:: deletefilter
 - Email:: delforward
 - Email:: delmx
 - Email:: delpop
 - Email:: disablefilter
 - Email:: editquota
 - Email:: enablefilter
 - Email:: fetchautosponder
 - Email:: fetchcharmaps
 - Email:: filteractions
 - Email:: filterlist
 - Email:: filtername
 - Email:: filterrules
 - Email:: get_archiving_configuration
 - Email:: get_archiving_default_configu

```

        "shortuser" :
"cpses_ex24NqG8AX",
        "user" :
"cpses_ex24NqG8AX"
    },
    {
        "dblist" : [

        ],
        "shortuser" :
"cpses_exb03uMNZD",
        "user" :
"cpses_exb03uMNZD"
    },
    {
        "dblist" : [

        ],
        "shortuser" :
"bobby",
        "user" :
"example_bobby"
    },
    {
        "dblist" : [
            {
                "db" :
"example_fred",
                "user" :
"example_fred"
            }
        ],
        "shortuser" :
"fred",
        "user" :
"example_fred"
    },
    {
        "dblist" : [
            {
                "db" :
"example_test",
                "user" :
"example_username"
            }
        ],
        "shortuser" :
"username",
        "user" :
"example_username"
    }
],
"func" :

```

- cPanel API 2 Functions - MySQLFE:: changeuserpassword — This function changes a database user's password.
- cPanel API 2 Functions - MySQLFE:: createedb — This function creates a database.

ration
Email: get_archiving_types
Email: get_default_email_quota
Email: get_email_signing
Email: get_max_email_quota
Email: getabsbrowse_dir
Email: getalwaysaccept
Email: getdiskusage
Email: getmxcheck
Email: has_delegated_mailman_lists
Email: list_system_filter_info
Email: listaliasbackups
Email: listautoresponders
Email: listdefaultaddresses
Email: listdomainforwards
Email: listfilterbackups
Email: listfilters
Email: listforwards
Email: listlists
Email: listmaildomains
Email: listmx
Email: listmxs
Email: listpops
Email: listpopssingle
Email: listpopswithdisk
Email: listpopswithimage
Email: loadfilter
Email: passwdpop
Email: reorderfilters

```
"listusers",  
  "event": {  
    "result": 1  
  },  
  "module":  
  "MysqlFE"
```

Email:: `set_archiving_configuration`

Email:: `set_archiving_default_configuration`

Email:: `set_email_signing`

Email:: `setalwaysaccept`

Email:: `setdefaultaddress`

Email:: `setmxcheck`

Email:: `storefilter`

Email:: `tracefilter`

▼ EmailTrack

EmailTrack:: `search`

EmailTrack:: `stats`

EmailTrack:: `trace`

▼ Encoding

Encoding:: `get_encodings`

Encoding:: `guess_file`

Encoding:: `guess_file_opts`

▼ FSTest

FSTest:: `dirisempty`

▼ Fileman

Fileman:: `autocomplete_dir`

Fileman:: `fileop`

Fileman:: `getabsdir`

Fileman:: `getdir`

Fileman:: `getdiractions`

Fileman:: `getdiskinfo`

Fileman:: `getedittype`

Fileman:: `getfileactions`


Fileman:: `getpath`

Fileman:: `listfiles`

Fileman:: `mkdir`

Fileman:: `mkfile`

Fileman:: `savefile`



Parameters

This function does not accept parameters.

Returns

Return	Type	Description	Possible values	Example
<code>dblist</code>	<i>hash</i>	A hash of databases and their authorized users.	A hash that contains the <code>db</code> and <code>user</code> returns.	
<code>db</code>	<i>string</i>	The database name. The function returns this value in the <code>dblist</code> hash.	A valid database name.	<code>example_database</code>
<code>user</code>	<i>string</i>	The database username. The function returns this value in the <code>dblist</code> hash.	A valid database username.	<code>example_user1</code>
<code>shortuser</code>	<i>string</i>	The short version of the database username.	A valid database username, without any database prefix.	<code>user1</code>
<code>user</code>	<i>string</i>	The database username.	A valid database username.	<code>example_user1</code>

- Fileman:: search
- Fileman:: statfiles
- Fileman:: uploadfiles
- Fileman:: viewfile
- ▼ ForcePassword
 - ForcePassword:: get_force_password_flags
 - ForcePassword:: update_force_password_flags
- ▼ Frontpage
 - Frontpage:: fopenabled
 - Frontpage:: list
- ▼ Ftp
 - Ftp:: addftp
 - Ftp:: delftp
 - Ftp:: listftp
 - Ftp:: listftpsessions
 - Ftp:: listftpwithdisk
 - Ftp:: passwd
 - Ftp:: setquota
- ▼ Gpg
 - Gpg:: listgpgkeys
 - Gpg:: listsecretgpgkeys
 - Gpg:: number_of_private_keys
 - Gpg:: number_of_public_keys
- ▼ Htaccess
 - Htaccess:: listuser
 - Htaccess:: listusers
- ▼ HttpUtils
 - HttpUtils:: getdirindices
- ▼ ImageManager
 - ImageManager:: thumbnail
- ▼ LVEInfo
 - LVEInfo:: getUsage
- ▼ LangMods
 - LangMods:: getarcname
 - LangMods:: getkey

reason	string	A reason for failure. <div style="border: 1px solid black; padding: 5px; margin: 5px 0;">Note : This function only returns a reason value if it failed.</div>	A string that describes the error.	This is an error message.
result	Boolean	Whether the function succeeded.	<ul style="list-style-type: none"> • 1 — The function succeeded. • 0 — The function failed. 	1

LangMods:: getpre
fix

LangMods:: install

LangMods:: langlis
t

LangMods:: list_av
ailable

LangMods:: list_in
stalled

LangMods:: magic
_status

LangMods:: pre_ru
n

LangMods:: search

LangMods:: setup

LangMods:: uninst
all

LangMods:: updat
e

▼ LeechProtect

LeechProtect:: set
up

▼ Locale

Locale:: get_encod
ing

Locale:: get_html_
dir_attr

Locale:: get_locale
_name

Locale:: get_user_
ocale

Locale:: get_user_
ocale_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse
r

Logaholic:: adduse
rprofile

Logaholic:: deleteu
ser

Logaholic:: deleteu
serprofile

Logaholic:: edituse
r

Logaholic:: fetchus
er

Logaholic:: listuser
profiles

Logaholic:: logahol
iclink

Logaholic:: proces
sstats

▼ Mime

Mime:: list_hotlinks

Mime:: listhandlers

Mime:: listmime

Mime:: listredirects

Mime:: redirectname

Mime:: redirecturlname

▼ MysqlFE

MysqlFE:: authorizehost

MysqlFE:: change
dbuserpassword

MysqlFE:: created
b

MysqlFE:: created
buser

MysqlFE:: dbuserexists

MysqlFE:: deauthorizehost

MysqlFE:: deleted
b

MysqlFE:: deleted
buser

MysqlFE:: getalldb
sinfo

MysqlFE:: getalldb
usersanddbs

MysqlFE:: getdatabasesprivileges

MysqlFE:: getdatabases

MysqlFE:: gethosts

MysqlFE:: getmysqlprivileges

MysqlFE:: getmysqlserverprivileges

MysqlFE:: has_my
cnf_for_cpuser

MysqlFE:: listdbs

MysqlFE:: listdatabasesackup

MysqlFE:: listhosts

MysqlFE:: listusers

MysqlFE:: listusers
indb

MysqlFE:: revoked
buserprivileges

MysqlFE:: setdbu
erprivileges

MysqlFE:: userdbp
rivs

▼ MysqlOptimizer

MysqlOptimizer:: f
etch_slow_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does_news
_exist

News:: does_news
_type_exist

News:: get_news

▼ PHPINI

PHPINI:: getallopti
ons

PHPINI:: getoption
s

▼ Park

Park:: listaddondo
mains

Park:: listparkeddo
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change_
password

Passwd:: set_dige
st_auth

▼ PasswdStrength

PasswdStrength::
appstrengths

PasswdStrength::
get_password_stre
ngth

PasswdStrength::
get_required_stren
gth

▼ Postgres

Postgres:: listdbs

Postgres:: listusers

Postgres:: listusers
indb

Postgres:: userexi
sts

▼ Rand

Rand:: getranddat
a

▼ Resellers

Resellers:: get_su
b_accounts

▼ RoR

RoR:: addapp

RoR:: changeapp

RoR:: importrails

RoR:: listapps

RoR:: listrewrites

RoR:: needsimport

RoR:: removeapp

RoR:: removerewri
te

RoR:: restartapp

RoR:: setuprewrite

RoR:: softrestartap
p

RoR:: startapp

RoR:: stopapp

▼ SetLang

SetLang:: setlocale

▼ SourceIPCheck

SourceIPCheck:: a
ddip

SourceIPCheck:: d
elip

SourceIPCheck:: g
etaccount

SourceIPCheck:: li
stips

SourceIPCheck:: l
oadsecquestions

SourceIPCheck:: r
esetsecquestions

SourceIPCheck:: s
amplequestions

SourceIPCheck:: s
avesecquestions

▼ SPFUJ

SPFUJ:: available

SPFUJ:: count_sett
ings

SPFUI:: entries_co
mplete

SPFUI:: get_raw_r
ecord

SPFUI:: getmainse
rverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list_settin
gs

SPFUI:: load_curr
ent_values

SPFUI:: uninstall

▼ SSH

SSH:: authkey

SSH:: converttopp
k

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey_leg
acy

SSH:: importkey

SSH:: listkeys

▼ SSL

SSL:: fetchcabundl
e

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcnname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

▼ SSLInfo

SSLInfo:: fetchinfo

▼ StatCache

StatCache:: clearc
ache

▼ Stats

Stats:: getmonthly

bandwidth

Stats:: getmonthly
domainbandwidth

Stats:: getthismont
hsbwusage

Stats:: lastapache
hits

Stats:: lastvisitors

Stats:: listanalog

Stats:: listawstats

Stats:: listlastvisito
rs

Stats:: listrawlogs

Stats:: listurchin

Stats:: listwebalize
r

▼ StatsBar

StatsBar:: getrowc
ounter

StatsBar:: rowcoun
ter

StatsBar:: setrowc
ounter

StatsBar:: stat

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: chan
gedocroot

SubDomain:: delsu
bdomain

SubDomain:: getre
servedsubdomains

SubDomain:: listsu
bdomains

SubDomain:: validr
egex

▼ Themes

Themes:: apply_n
ew_theme

Themes:: does_cp
anel_theme_exist

Themes:: get_avail
able_themes

Themes:: get_the
mes_list

Themes:: restore_
saved_theme

▼ UI

UI:: dynamicinclud
elist

UI:: includelist

UI:: listform

UI:: paginate

UI:: paginate_list

▼ UserHttpUtils

UserHttpUtils:: get
dirindices

▼ WebDisk

WebDisk:: addweb
disk

WebDisk:: delweb
disk

WebDisk:: hasdige
st

WebDisk:: listwebd
isks

WebDisk:: passwd
webdisk

WebDisk:: set_dig
est_auth

WebDisk:: set_ho
mdir

WebDisk:: set_per
ms

WebDisk:: setstatu
s

▼ WebmailApps

WebmailApps:: list
webmailapps

▼ ZoneEdit

ZoneEdit:: add_zo
ne_record

ZoneEdit:: edit_zo
ne_record

ZoneEdit:: fetch_c
panel_generated_
domains

ZoneEdit:: fetchzo
ne

ZoneEdit:: fetchzo
ne_records

ZoneEdit:: fetchzo
nes

ZoneEdit:: get_zon
e_record

ZoneEdit:: remove
_zone_record

ZoneEdit:: resetzo
ne

