

# UAPI Functions -

## DomainInfo::main\_domain\_builtin\_subdomain\_aliases

Function information

### Description

#### Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules
  
- Backup
- Backup::fullbackup
- p\_to\_ftp
- Backup::fullbackup
- p\_to\_homedir
- Backup::fullbackup
- p\_to\_scp\_with\_key
  
- Backup::fullbackup
- p\_to\_scp\_with\_password
  
- Backup::list\_backups
  
- Bandwidth
  - Bandwidth::get\_enabled\_protocols
  - Bandwidth::get\_restriction\_periods
  - Bandwidth::query
  
- Batch
  - Batch::strict
  
- Brand
  - Brand::read
  
- Branding
  - Branding::file
  - Branding::get\_applications
  - Branding::get\_application\_information

This function returns the built-in subdomain aliases for an account's main domain.

**Note:**

This function retrieves data from the `/var/cpanel/userdata/user/domain` file, where `user` represents the cPanel account username and `domain` represents the domain. For this reason, actual output may not contain all of the returns that this document lists.

### Examples

#### ▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess##  
#####/execute/DomainInfo/main_domain_builtin_subdomain_aliases
```

**Note:**

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

About this module

The DomainInfo module accesses domain data.

About UAPI

UAPI accesses and modifies data for cPanel accounts.

Branding:: get\_available\_applications  
Branding:: get\_information\_for\_applications  
Branding:: image  
Branding:: include  
Branding:: spritelist

CacheBuster  
CacheBuster:: read  
CacheBuster:: update

Chkservd  
Chkservd:: get\_exim\_ports  
Chkservd:: get\_exim\_ports\_ssl

Chrome  
Chrome:: get\_dom

Contactus  
Contactus:: is\_enabled

cPAddons  
cPAddons:: get\_available\_addons  
cPAddons:: get\_instance\_settings  
cPAddons:: listAddon\_instances

cPGreyList  
cPGreyList:: disable\_all\_domains  
cPGreyList:: disable\_domains  
cPGreyList:: enable\_all\_domains  
cPGreyList:: enable\_domains  
cPGreyList:: has\_greylisting\_enabled  
cPGreyList:: list\_domains

DAV  
DAV:: disable\_shared\_global\_addressbook  
DAV:: enable\_shared\_global\_addressbook  
DAV:: get\_calendar\_contacts\_config

## LiveAPI PHP Class

```
$cpanel = new CPANEL(); // Connect to cPanel - only do this once.  
  
// Get domain user data.  
$get_userdata = $cpanel->uapi(  
    'DomainInfo',  
    'main_domain_builtin_subdomain_aliases',  
    array(  
        'format'  
    => 'hash',  
        )  
);
```

### Note:

For more information, read our [Guide to the LiveAPI System](#).

- Notes:**
- The Fe  
int  
• Ur m  
us 20  
or 20  
).` 20  
or 20  
).

Find  
a  
funct  
ion

DAV:: has\_shared\_global\_addressbook

DAV:: is\_dav\_service\_enabled

DAV:: is\_horde\_enabled

#### DCV

DCV:: check\_domains\_via\_dns

DCV:: check\_domains\_via\_http

DCV:: ensure\_domains\_can\_pass\_dcv

#### DomainInfo

DomainInfo:: domains\_data

DomainInfo:: list\_domains

DomainInfo:: main\_domain\_builtin\_subdomain\_aliases

DomainInfo:: single\_domain\_data

#### DNS

DNS:: ensure\_domains\_reside\_only\_locally

DNS:: has\_local\_authority

#### DNSSEC

DNSSEC:: disable\_dnssec

DNSSEC:: enable\_dnssec

DNSSEC:: fetch\_domains\_records

DNSSEC:: set\_ns\_ec3

DNSSEC:: unset\_nsec3

#### Email

Email:: account\_name

Email:: add\_auto\_responder

Email:: add\_domain\_forwarder

Email:: add\_forwarder

Email:: add\_list

Email:: add\_mailman\_delegates

## LiveAPI Perl Module

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Get domain user
data.
my $get_userdata =
$cpliveapi->uapi(
    'DomainInfo',
'main_domain_builtin_
subdomain_aliases',
{
    'format'
=> 'hash',
}
);
```

#### Note:

For more information, read our [Guide to the LiveAPI System](#).

- UAPI Functions
  - DomainInfo::main\_domain\_builtin\_subdomain\_aliases
  - This function returns the built-in subdomain aliases for an account's main domain.
- UAPI Modules
  - DomainInfo — The DomainInfo module allows domain data.

Email:: add\_mx  
Email:: add\_pop  
Email:: add\_spam\_filter  
Email:: browse\_mailbox  
Email:: change\_mx  
Email:: check\_fast\_mail  
Email:: check\_pipe\_forwarder  
Email:: delete\_auto\_responder  
Email:: delete\_domain\_forwarder  
Email:: delete\_filter  
Email:: delete\_forwarder  
Email:: delete\_hd\_messages  
Email:: delete\_list  
Email:: delete\_mx  
Email:: delete\_pop  
Email:: disable\_filter  
Email:: disable\_mailbox\_autocreate  
Email:: disable\_spam\_assassin  
Email:: disable\_spam\_autodelete  
Email:: disable\_spam\_box  
Email:: dispatch\_client\_settings  
Email:: edit\_pop\_quota  
Email:: enable\_filter  
Email:: enable\_mailbox\_autocreate  
Email:: enable\_spam\_assassin  
Email:: enable\_spam\_box  
Email:: fetch\_charmaps  
Email:: fts\_rescan\_mailbox

## v cPanel Template Toolkit

```
<!-- Get a hash of  
all the data, then  
display the  
addon_domains values.  
-->  
[% data = execute(  
'DomainInfo',  
'main_domain_builtin_  
subdomain_aliases', {  
format => 'hash' } );  
%]  
[% FOREACH q =  
domains.data.addon_domains %]  
  <p>  
    [% q %]  
  </p>  
[% END %]  
  
<!-- Get only the  
main_domain's domain  
name. -->  
[%  
execute('DomainInfo',  
'main_domain_builtin_  
subdomain_aliases', {  
format => 'hash'  
}).data.main_domain.domain %]
```

- UAPI Modules
  - SubDomain
  - The SubDomain module manages subdomains.
- UAPI Functions
  - SubDomain::addsubdomain
  - This function creates a subdomain.

**Note:**  
For more information, read our [Guide to Template Toolkit documentation](#).

Email:: generate\_mailman\_otp

Email:: get\_auto\_responder

Email:: get\_charge\_ts

Email:: get\_client\_settings

Email:: get\_default\_email\_quota

Email:: get\_default\_email\_quota\_mib

Email:: get\_disk\_usage

Email:: get\_filter

Email:: get\_held\_message\_count

Email:: get\_mailbox\_autocreate

Email:: get\_main\_delegatees

Email:: get\_main\_account\_disk\_usage

Email:: get\_main\_account\_disk\_usage\_bytes

Email:: get\_max\_email\_quota

Email:: get\_max\_email\_quota\_mib

Email:: get\_pop\_quota

Email:: get\_spam\_settings

Email:: get\_webmail\_settings

Email:: has\_delegated\_mailman\_lists

Email:: has\_plaintext\_authentication

Email:: hold\_outgoing

Email:: is\_integer

Email:: list\_auto\_responders

Email:: list\_default\_address

Email:: list\_domain\_forwarders

Email:: list\_filters

## Command Line

```
uapi --user=username
DomainInfo domains
format=hash
```

### Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the uapi --help command.
- If you run CloudLinux™, you **must** use the full path of the uapi command:

```
/usr/local
/cpanel/bin/uapi
```

Email:: `list_filters_backups`

Email:: `list_forwarders`

Email:: `list_forwarders_backups`

Email:: `list_lists`

Email:: `list_mail_domains`

Email:: `list_mxns`

Email:: `list_pops`

Email:: `list_pops_with_disk`

Email:: `list_system_filter_info`

Email:: `passwd_list`

Email:: `passwd_pop`

Email:: `release_outgoing`

Email:: `remove_mailman_delegates`

Email:: `reorder_filters`

Email:: `set_always_accept`

Email:: `set_default_address`

Email:: `set_list_privacy_options`

Email:: `stats_db_status`

Email:: `store_filter`

Email:: `suspend_incoming`

Email:: `suspend_login`

Email:: `suspend_outgoing`

Email:: `trace_filter`

Email:: `unsuspend_incoming`

Email:: `unsuspend_login`

Email:: `unsuspend_outgoing`

Email:: `verify_password`

## Output (JSON)

format=hashformat=list

```
{  
    "messages": null,  
    "errors": null,  
    "status": 1,  
    "metadata": {  
        ...  
    },  
    "data": {  
        "result": {  
            "0": "mail",  
            "1": "www"  
        }  
    }  
}
```

```
{  
    "messages": null,  
    "errors": null,  
    "status": 1,  
    "metadata": {  
        ...  
    },  
    "data": {  
        "result": {  
            "0": "mail",  
            "1": "www"  
        }  
    }  
}
```

### Note:

Use cPanel's [API Shell](#) interface (`cPanel >> Home >> Advanced >> API Shell`) to directly test cPanel API calls.

## Parameters

Email:: `list_filters_backups`  
This function accepts no parameters.

## Returns

### EmailAuth

EmailAuth:: `disable_dkim`

	Return	Type	Description	Possible values	Example
EmailAuth:: enable_dkim	web_subdomain_aliases	array	The type of subdomain alias.	<ul style="list-style-type: none"> <li>• 0 — mail subdomain</li> <li>• 1 — www subdomain</li> </ul>	1

EmailAuth:: install\_dkim\_private\_keys

EmailAuth:: install\_spf\_records

EmailAuth:: validate\_current\_dkims

EmailAuth:: validate\_current\_ptrs

EmailAuth:: validate\_current\_spfs

#### ExternalAuthentication

ExternalAuthentication:: add\_authn\_link

ExternalAuthentication:: configured\_modules

ExternalAuthentication:: get\_authn\_links

ExternalAuthentication:: has\_external\_auth\_modules\_configured

ExternalAuthentication:: remove\_authn\_link

#### Features

Features:: get\_feature\_metadata

Features:: has\_feature

Features:: list\_features

#### Fileman

Fileman:: autocompletedir

Fileman:: empty\_trash

Fileman:: get\_file\_content

Fileman:: get\_file\_information

Fileman:: list\_files

Fileman:: save\_file\_content

Fileman:: **transcod**  
e

Fileman:: **upload\_fi**  
les

✓ **Ftp**

Ftp:: **add\_ftp**

Ftp:: **allows\_anony**  
**mous\_ftp**

Ftp:: **allows\_anony**  
**mous\_ftp\_incomin**  
g

Ftp:: **delete\_ftp**

Ftp:: **ftp\_exists**

Ftp:: **get\_ftp\_daem**  
on\_info

Ftp:: **get\_port**

Ftp:: **get\_quota**

Ftp:: **get\_welcome**  
\_message

Ftp:: **kill\_session**

Ftp:: **list\_ftp**

Ftp:: **list\_ftp\_with\_**  
disk

Ftp:: **list\_sessions**

Ftp:: **passwd**

Ftp:: **server\_name**

Ftp:: **set\_anonymo**  
us\_ftp

Ftp:: **set\_anonymo**  
us\_ftp\_incoming

Ftp:: **set\_homedir**

Ftp:: **set\_quota**

Ftp:: **set\_welcome**  
\_message

✓ **Integration**

Integration:: **fetch\_**  
url

✓ **KnownHosts**

KnownHosts:: **crea**  
te

KnownHosts:: **dele**  
te

KnownHosts:: **upd**  
ate

KnownHosts:: **verif**  
y

✓ **LangPHP**

LangPHP:: **php\_ge**  
t\_domain\_handler

LangPHP:: `php_get_impacted_domains`

LangPHP:: `php_get_installed_versions`

LangPHP:: `php_get_system_default_version`

LangPHP:: `php_get_vhost_versions`

LangPHP:: `php_ini_get_user_basic_directives`

LangPHP:: `php_ini_get_user_content`

LangPHP:: `php_ini_get_user_paths`

LangPHP:: `php_ini_set_user_basic_directives`

LangPHP:: `php_ini_set_user_content`

LangPHP:: `php_set_vhost_versions`

▼ **LastLogin**

LastLogin:: `get_last_or_current_logged_in_ip`

▼ **Locale**

Locale:: `get_attributes`

▼ **Mailboxes**

Mailboxes:: `expunge_mailbox_messages`

Mailboxes:: `expunge_messages_for_mailbox_guid`

Mailboxes:: `get_mailbox_status`

Mailboxes:: `has_utf8_mailbox_names`

Mailboxes:: `set_utf8_mailbox_names`

▼ **Market**

Market:: `cancel_pending_ssl_certificate`

Market:: `create_shopping_cart`

Market:: `get_all_products`

Market:: `get_certificate_status_detail`

s

Market:: **get\_login\_url**

Market:: **get\_pending\_ssl\_certificates**

Market:: **get\_provider\_specific\_dcv\_constraints**

Market:: **get\_providers\_list**

Market:: **get\_ssl\_certificate\_if\_available**

Market:: **process\_ssl\_pending\_queue**

Market:: **request\_ssl\_certificates**

Market:: **set\_status\_of\_pending\_queue\_items**

Market:: **set\_url\_after\_checkout**

Market:: **validate\_login\_token**

⌄ **Mime**

Mime:: **add\_handler**

Mime:: **add\_hotlink**

Mime:: **add\_mime**

Mime:: **add\_redirect**

Mime:: **delete\_handler**

Mime:: **delete\_hotlink**

Mime:: **delete\_mime**

Mime:: **delete\_redirect**

Mime:: **list\_handlers**

Mime:: **list\_hotlinks**

Mime:: **list\_mime**

Mime:: **list\_redirects**

Mime:: **redirect\_info**

⌄ **ModSecurity**

ModSecurity:: **disable\_all\_domains**

ModSecurity:: **disa**

```
ble_domains  
ModSecurity:: ena  
ble_all_domains  
ModSecurity:: ena  
ble_domains  
ModSecurity:: has  
_modsecurity_inst  
alled  
ModSecurity:: list_  
domains
```

#### ▼ Mysql

```
Mysql:: add_host  
Mysql:: add_host_  
note  
Mysql :: check_dat  
abase  
Mysql:: create_dat  
abase  
Mysql:: create_use  
r  
Mysql:: delete_dat  
abase  
Mysql:: delete_hos  
t  
Mysql:: delete_use  
r  
Mysql:: get_host_n  
otes
```

```
Mysql:: get_privile  
ges_on_database
```

```
Mysql:: get_restrict  
ions
```

```
Mysql:: get_server  
_information
```

```
Mysql:: locate_ser  
ver
```

```
Mysql:: rename_d  
atabase
```

```
Mysql:: rename_us  
er
```

```
Mysql:: repair_dat  
abase
```

```
Mysql:: revoke_ac  
cess_to_database
```

```
Mysql:: set_passw  
ord
```

```
Mysql:: set_privile  
ges_on_database
```

#### ▼ Notifications

```
Notifications:: get_  
notifications_count
```

#### ▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile\_rel  
ative\_uri

▼ PassengerApps

PassengerApps:: d  
isable\_application

PassengerApps:: e  
dit\_application

PassengerApps:: e  
nable\_application

PassengerApps:: e  
nsure\_deps

PassengerApps:: li  
st\_applications

PassengerApps:: r  
egister\_application

PassengerApps:: u  
nregister\_applicati  
on

▼ PasswdStrength

PasswdStrength::  
get\_required\_stren  
gth

▼ Personalization

Personalization::se  
t

Personalization ::g  
et

▼ Postgresql

Postgresql:: create  
\_database

Postgresql:: create  
\_user

Postgresql:: delete  
\_database

Postgresql:: get\_re  
strictions

Postgresql:: grant\_  
all\_privileges

Postgresql:: renam  
e\_database

Postgresql:: renam  
e\_user

Postgresql:: renam  
e\_user\_no\_passw  
ord

Postgresql:: revok  
e\_all\_privileges

Postgresql:: set\_p  
assword

▼ Pushbullet

```
Pushbullet:: send_
test_message
```

⌄ Quota

```
Quota:: get_quota
_info
```

⌄ Resellers

```
Resellers:: list_acc
ounts
```

⌄ ResourceUsage

```
ResourceUsage::
get_usages
```

⌄ Restore

```
Restore:: directory
_listing
```

```
Restore:: get_user
s
```

```
Restore:: query_fil
e_info
```

```
Restore:: restore_f
ile
```

⌄ Session

```
Session:: create_t
emp_user
```

⌄ SiteTemplates

```
SiteTemplates:: list
_site_templates
```

```
SiteTemplates:: list
_user_settings
```

```
SiteTemplates:: pu
blish
```

⌄ SpamAssassin

```
SpamAssassin :: cl
ear_spam_box
```

```
SpamAssassin:: g
et_symbolic_test_
names
```

```
SpamAssassin:: g
et_user_preferences
```

```
SpamAssassin:: u
pdate_user_prefer
ence
```

⌄ SSH

```
SSH:: get_port
```

⌄ SSL

```
SSL:: add_autossl
_excluded_domain
s
```

```
SSL:: can_ssl_r
edirect
```

```
SSL:: check_share
d_cert
```

```
SSL:: delete_cert
```

```
SSL:: delete_csr
SSL:: delete_key
SSL:: delete_ssl
SSL:: disable_main_
SSL:: enable_mail_
SSL:: fetch_best_f
SSL:: fetch_cert_in
SSL:: fetch_certific
SSL:: fetch_key_a
SSL:: find_certifica
SSL:: find_csrs_for_
SSL:: generate_ce
SSL:: generate_cs
SSL:: generate_ke
SSL:: get_autossl_
SSL:: get_autossl_
SSL:: get_autossl_
SSL:: get_cabundl
SSL:: get_cn_nam
SSL:: install_ssl
SSL:: installed_ho
SSL:: installed_ho
SSL:: is_autossl_c
SSL:: is_mail_sni_
SSL:: is_sni_supp
SSL:: list_certs
SSL:: list_csrs
SSL:: list_keys
```

SSL:: list\_ssl\_item  
s

SSL:: mail\_sni\_sta  
tus

SSL:: rebuild\_mail  
\_sni\_config

SSL:: rebuildssldb

SSL:: remove\_au  
tossl\_excluded\_d  
omains

SSL:: set\_au\_ssl\_  
excluded\_domains

SSL:: set\_cert\_frie  
ndly\_name

SSL:: set\_csr\_frien  
dly\_name

SSL:: set\_key\_frie  
ndly\_name

SSL:: set\_primary\_  
\_ssl

SSL:: set\_ssl\_shar  
e

SSL:: show\_cert

SSL:: show\_csr

SSL:: show\_key

SSL:: start\_au\_ssl\_  
\_check

SSL:: toggle\_ssl\_r  
edirects\_for\_doma  
ins

SSL:: upload\_cert

SSL:: upload\_key

⌄ **StatusBar**

StatusBar:: get\_stat  
s

⌄ **Styles**

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

⌄ **SubDomain**

SubDomain:: adds  
ubdomain

⌄ **Themes**

Themes:: get\_the  
me\_base

Themes:: list

Themes:: update

⌄ **Tokens**

Tokens:: create\_fu

## ll\_access

Tokens:: **list**

Tokens:: **rename**

Tokens:: **revoke**

## TwoFactorAuth

TwoFactorAuth:: **g  
e  
n  
e  
r  
a  
t  
e  
\_  
u  
s  
e  
r  
\_  
c  
o  
n  
f  
i  
g  
u  
r  
a  
t  
i  
o  
n**

TwoFactorAuth:: **g  
e  
t  
\_  
u  
s  
e  
r  
\_  
c  
o  
n  
f  
i  
g  
u  
r  
a  
t  
i  
o  
n**

TwoFactorAuth:: **re  
m  
o  
v  
e  
\_  
u  
s  
e  
r  
\_  
c  
o  
n  
f  
i  
g  
u  
r  
a  
t  
i  
o  
n**

TwoFactorAuth:: **s  
e  
t  
\_  
u  
s  
e  
r  
\_  
c  
o  
n  
f  
i  
g  
u  
r  
a  
t  
i  
o  
n**

## UserManager

UserManager:: **che  
c  
k  
\_  
a  
c  
c  
o  
u  
n  
t  
c  
o  
n  
f  
l  
i  
c  
t  
s**

UserManager:: **cre  
a  
t  
e  
\_  
u  
s  
e  
r**

UserManager:: **de  
l  
e  
t  
e  
\_  
u  
s  
e  
r**

UserManager:: **dis  
m  
i  
s  
s  
\_  
u  
s  
e  
r**

UserManager:: **edi  
t  
\_  
u  
s  
e  
r**

UserManager:: **lis  
t  
\_  
u  
s  
e  
r**

UserManager:: **loo  
k  
u  
p  
\_  
s  
e  
r  
v  
i  
c  
e  
\_  
a  
c  
c  
o  
u  
n  
t**

UserManager:: **loo  
k  
u  
p  
\_  
u  
s  
e  
r**

UserManager:: **me  
r  
g  
e  
\_  
s  
e  
r  
v  
i  
c  
e  
\_  
a  
c  
c  
o  
u  
n  
t**

UserManager:: **unli  
n  
k  
\_  
s  
e  
r  
v  
i  
c  
e  
\_  
a  
c  
c  
o  
u  
n  
t**

## UserTasks

UserTasks:: **de  
l  
e  
t  
e**

UserTasks:: **retr  
ie  
v  
e**

## VersionControl

VersionControl:: **cr  
e  
a  
t  
e**

VersionControl:: **d  
e  
l  
e  
t  
e**

VersionControl:: **re  
t  
ri  
e  
v  
e**

VersionControl:: **u**  
**pdate**

✓ VersionControlDeployment

VersionControlDeployment:: **create**

VersionControlDeployment:: **delete**

VersionControlDeployment:: **retrieve**

✓ WebDisk

WebDisk:: **delete\_user**

WebDisk:: **set\_home\_dir**

WebDisk:: **set\_password**

WebDisk:: **set\_permissions**

✓ WebmailApps

WebmailApps:: **list\_webmailapps**

✓ WebVhosts

WebVhost:: **list\_domains**

WebVhost:: **list\_ssl\_capable\_domains**

✓ WordPressBackup

WordPressBackup :: **any\_running**

WordPressBackup :: **cancel**

WordPressBackup :: **cleanup**

WordPressBackup :: **get\_available\_backups**

WordPressBackup :: **is\_running**

WordPressBackup :: **start**

✓ WordPressInstance

Manager

WordPressInstanceManager:: **cancel\_scan**

WordPressInstanceManager:: **cleanup\_scan**

WordPressInstanceManager:: **change\_admin\_password**

WordPressInstanceManager:: **config**

ure\_automate

WordPressInstanceManager:: **get\_api\_version**

WordPressInstanceManager:: **get\_instance\_by\_id**

WordPressInstanceManager:: **get\_instances**

WordPressInstanceManager:: **get\_latest\_wordpress\_version\_from\_wordpress\_org**

WordPressInstanceManager:: **get\_scan\_results**

WordPressInstanceManager:: **is\_installable\_addon\_available**

WordPressInstanceManager:: **start\_scan**

✓ **WordPressRestore**

WordPressRestore :: **any\_running**

WordPressRestore :: **cleanup**

WordPressRestore :: **start**