

# UAPI Functions - SSL::list\_ssl\_items

## Guide to UAPI

Return Data  
Filter Output  
Sort Output  
Paginate Output  
Output Columns  
Calls from the WHM API  
Custom UAPI Modules

Backup  
Backup::fullbacku  
p\_to\_ftp

Backup::fullbacku  
p\_to\_homedir

Backup::fullbacku  
p\_to\_scp\_with\_key

Backup::fullbacku  
p\_to\_scp\_with\_password

Backup::list\_backups

Bandwidth  
Bandwidth::get\_enabled\_protocols  
Bandwidth::get\_retention\_periods  
Bandwidth::query

Batch  
Batch::strict

Brand  
Brand::read

Branding  
Branding::file  
Branding::get\_applications  
Branding::get\_application\_information  
Branding::get\_available\_applications  
Branding::get\_info

## Description

This function lists SSL-related items on a domain.

## Examples

### ▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/SSL/list_ssl_items?domains=example.com%7Cexample1.com%7Cexample2.com&items=key%7Ccert%7Ccsr
```

#### Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

### ▼ LiveAPI PHP Class

List keys:

```
$cpanel = new CPANEL(); // Connect to cPanel - only do this once.  
  
// List SSL-related items on the example.com domain.  
$SSL_list_ssl_items = $cpanel->uapi('SSL', 'list_ssl_items', array('domains' => 'example.com', 'items' => 'key', ));
```

List CSRs:

## Function information

## About this module

The SSL module manages certificates, certificate requests, and keys on your server.

## About UAPI

UAPI accesses and modifies data for cPanel accounts.

information\_for\_applications

Branding:: image

Branding:: include

Branding:: spritelist

▼ CacheBuster

CacheBuster:: read

CacheBuster:: update

▼ Chkserverd

Chkserverd:: get\_external\_ports

Chkserverd:: get\_external\_ports\_ssl

▼ Chrome

Chrome:: get\_domain

▼ Contactus

Contactus:: is\_enabled

▼ cPAddons

cPAddons:: get\_available\_addons

cPAddons:: get\_instance\_settings

cPAddons:: list\_addon\_instances

▼ cPGreyList

cPGreyList:: disable\_all\_domains

cPGreyList:: disable\_domains

cPGreyList:: enable\_all\_domains

cPGreyList:: enable\_domains

cPGreyList:: has\_greylisting\_enabled

cPGreyList:: list\_domains

▼ DAV

DAV:: disable\_shared\_global\_addressbook

DAV:: enable\_shared\_global\_addressbook

DAV:: get\_calendar\_contacts\_config

DAV:: has\_shared\_global\_addressbook

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.
```

```
// List SSL-related  
items on the  
example.com domain.  
$SSL_list_ssl_items =  
$cpanel->uapi(  
    'SSL',  
    'list_ssl_items',  
    array(  
        'domains'  
=> 'example.com',  
        'items'  
=> 'csr',  
    )  
);
```

List certificates:

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.
```

```
// List SSL-related  
items on the  
example.com domain.  
$SSL_list_ssl_items =  
$cpanel->uapi(  
    'SSL',  
    'list_ssl_items',  
    array(  
        'domains'  
=> 'example.com',  
        'items'  
=> 'crt',  
    )  
);
```

**Note:**

For more information, read our [Guide to the LiveAPI System](#).

▼ LiveAPI Perl Module

**Notes:**

- The `Fe`
- The `int`
- The `Ur`
- The `mu`
- The `us`
- The `20`
- The `or`
- The `20`
- The `).'`
- The `20`
- The `or`
- The `20`
- The `).`

**Find  
a  
function**

- UAPI Functions - SSL: delete\_ssl — This function removes SSL from a domain.

DAV:: is\_dav\_service\_enabled

DAV:: is\_horde\_enabled

#### ▼ DCV

DCV:: check\_domains\_via\_dns

DCV:: check\_domains\_via\_http

DCV:: ensure\_domains\_can\_pass\_dcv

#### ▼ DomainInfo

DomainInfo:: domains\_data

DomainInfo:: list\_domains

DomainInfo:: main\_domain\_builtin\_subdomain\_aliases

DomainInfo:: single\_domain\_data

#### ▼ DNS

DNS:: ensure\_domains\_reside\_only\_locally

DNS:: has\_local\_authority

#### ▼ DNSSEC

DNSSEC:: disable\_dnssec

DNSSEC:: enable\_dnssec

DNSSEC:: fetch\_dns\_records

DNSSEC:: set\_nsec3

DNSSEC:: unset\_nsec3

#### ▼ Email

Email:: account\_name

Email:: add\_auto\_responder

Email:: add\_domain\_forwarder

Email:: add\_forwarder

Email:: add\_list

Email:: add\_mailman\_delegates

Email:: add\_mx

Email:: add\_pop

List keys:

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# List SSL-related
items on the
example.com domain.
my
$SSL_list_ssl_items =
$cpliveapi->uapi(
  'SSL',
  'list_ssl_items',
  {
    'domains'
=> 'example.com',
    'items'
=> 'key',
  }
);
```

List CSRs:

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# List SSL-related
items on the
example.com domain.
my
$SSL_list_ssl_items =
$cpliveapi->uapi(
  'SSL',
  'list_ssl_items',
  {
    'domains'
=> 'example.com',
    'items'
=> 'csr',
  }
);
```

List certificates:

- UAPI Functions - SSL: fetch\_best\_for\_domain — This function retrieves the best-available certificate for the domain.
- UAPI Functions - SSL: fetch\_certificate\_info — This function retrieves all of a certificate's available information.

Email: add\_spam\_filter  
Email: browse\_mailbox  
Email: change\_mx  
Email: check\_fastmail  
Email: check\_pipe\_forwarder  
Email: delete\_auto\_responder  
Email: delete\_domain\_forwarder  
Email: delete\_filter  
Email: delete\_forwarder  
Email: delete\_held\_messages  
Email: delete\_list  
Email: delete\_mx  
Email: delete\_pop  
Email: disable\_filter  
Email: disable\_mailbox\_autocreate  
Email: disable\_spam\_assassin  
Email: disable\_spam\_autodelete  
Email: disable\_spam\_box  
Email: dispatch\_client\_settings  
Email: edit\_pop\_quota  
Email: enable\_filter  
Email: enable\_mailbox\_autocreate  
Email: enable\_spam\_assassin  
Email: enable\_spam\_box  
Email: fetch\_charmaps  
Email: fts\_rescan\_mailbox  
Email: generate\_mailman\_otp  
Email: get\_auto\_r

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
  
# List SSL-related  
items on the  
example.com domain.  
my  
$SSL_list_ssl_items =  
$cpliveapi->uapi(  
    'SSL',  
    'list_ssl_items',  
    {  
        'domains'  
=> 'example.com',  
        'items'  
=> 'crt',  
    }  
);
```

**Note:**

For more information, read our [Guide to the LiveAPI System](#).

### ▼ cPanel Template Toolkit

List keys:

```
<!-- List SSL-related  
items on the  
example.com domain.  
-->  
[% data = execute(  
    'SSL',  
    'list_ssl_items', {  
        domains =>  
        'example.com', item  
=> 'key' } )]; %]  
[% FOREACH q = data  
%]  
    <p>  
        [% q %]  
    </p>  
[% END %]
```

List CSRs:

- UAPI Functions - SSL: :fetch\_key\_and\_certificate — This function extracts the private key and CA bundle information from a certificate.

esponder

Email: get\_charts

Email: get\_client\_settings

Email: get\_default\_email\_quota

Email: get\_default\_email\_quota\_mib

Email: get\_disk\_usage

Email: get\_filter

Email: get\_held\_message\_count

Email: get\_mailbox\_autocreate

Email: get\_mailman\_delegates

Email: get\_main\_account\_disk\_usage

Email: get\_main\_account\_disk\_usage\_bytes

Email: get\_max\_email\_quota

Email: get\_max\_email\_quota\_mib

Email: get\_pop\_quota

Email: get\_spam\_settings

Email: get\_webmail\_settings

Email: has\_delegated\_mailman\_lists

Email: has\_plaintext\_authentication

Email: hold\_outgoing

Email: is\_integer

Email: list\_autoresponders

Email: list\_default\_address

Email: list\_domain\_forwarders

Email: list\_filters

Email: list\_filters\_backups

Email: list\_forward

```
<!-- List SSL-related
items on the
example.com domain.
-->
[% data = execute(
'SSL',
'list_ssl_items', {
domains =>
'example.com', item
=> 'csr'} ); %]
[% FOREACH q = data
%]
    <p>
        [% q %]
    </p>
[% END %]
```

List certificates:

```
<!-- List SSL-related
items on the
example.com domain.
-->
[% data = execute(
'SSL',
'list_ssl_items', {
domains =>
'example.com', item
=> 'crt'} ); %]
[% FOREACH q = data
%]
    <p>
        [% q %]
    </p>
[% END %]
```

**Note:**

For more information, read our [Guide to Template Toolkit documentation](#).

ers

Email:: list\_forward\_ers\_backups

Email:: list\_lists

Email:: list\_mail\_domains

Email:: list\_mx

Email:: list\_pops

Email:: list\_pops\_with\_disk

Email:: list\_system\_filter\_info

Email:: passwd\_list

Email:: passwd\_pop

Email:: release\_outgoing

Email:: remove\_mailman\_delegates

Email:: reorder\_filters

Email:: set\_always\_accept

Email:: set\_default\_address

Email:: set\_list\_privacy\_options

Email:: stats\_db\_status

Email:: store\_filter

Email:: suspend\_incoming

Email:: suspend\_login

Email:: suspend\_outgoing

Email:: trace\_filter

Email:: unsuspend\_incoming

Email:: unsuspend\_login

Email:: unsuspend\_outgoing

Email:: verify\_password

#### ▼ EmailAuth

EmailAuth:: disable\_dkim

EmailAuth:: enable\_dkim

#### ▼ Command Line

```
uapi --user=username
SSL list_ssl_items
domains=example.com%7
Cexample1.com%7Cexample2.com
items=key%7Ccert%7Ccsr
```

#### Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

#### ▼ Output (JSON)

List keys:

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "metadata": {
    "transformed": 1
  },
  "data": [
    {
      "id":
"example_com_a74f7_9d
ddf_1446659822_eae1ff
43c4ec1991e195877c557
55eff",
      "type": "key",
      "host":
"example.com"
    }
  ]
}
```

EmailAuth:: ensure  
\_dkim\_keys\_exist

EmailAuth:: fetch\_  
dkim\_private\_keys

EmailAuth:: install  
\_dkim\_private\_key  
s

EmailAuth:: install  
\_spf\_records

EmailAuth:: validat  
e\_current\_dkims

EmailAuth:: validat  
e\_current\_ptrs

EmailAuth:: validat  
e\_current\_spfs

ExternalAuthenticat  
ion

ExternalAuthenticat  
ion:: add\_authn\_li  
nk

ExternalAuthenticat  
ion:: configured\_  
modules

ExternalAuthenticat  
ion:: get\_authn\_lin  
ks

ExternalAuthenticat  
ion:: has\_external\_  
\_auth\_modules\_co  
nfigured

ExternalAuthenticat  
ion:: remove\_auth  
n\_link

Features

Features:: get\_feat  
ure\_metadata

Features:: has\_fea  
ture

Features:: list\_feat  
ures

Fileman

Fileman:: autocom  
pletedir

Fileman:: empty\_tr  
ash

Fileman:: get\_file\_  
content

Fileman:: get\_file\_i  
nformation

Fileman:: list\_files

Fileman:: save\_file  
\_content

Fileman:: transcod  
e

List CSRs:

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "metadata": {
    "transformed": 1
  },
  "data": [
    {
      "id":
      "example_com_a74f7_9d
      ddf_1446659822_eae1ff
      43c4ec1991e195877c557
      55eff",
      "type": "csr",
      "host":
      "example.com"
    }
  ]
}
```

List certificates:

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "metadata": {
    "transformed": 1
  },
  "data": [
    {
      "id":
      "example_com_a74f7_9d
      ddf_1446659822_eae1ff
      43c4ec1991e195877c557
      55eff",
      "type": "crt",
      "host":
      "example.com"
    }
  ]
}
```

- Fileman:: upload\_files
- Ftp:: add\_ftp
    - Ftp:: allows\_anonymous\_ftp
    - Ftp:: allows\_anonymous\_ftp\_incoming
    - Ftp:: delete\_ftp
    - Ftp:: ftp\_exists
    - Ftp:: get\_ftp\_daemon\_info
    - Ftp:: get\_port
    - Ftp:: get\_quota
    - Ftp:: get\_welcome\_message
    - Ftp:: kill\_session
    - Ftp:: list\_ftp
    - Ftp:: list\_ftp\_with\_disk
    - Ftp:: list\_sessions
    - Ftp:: passwd
    - Ftp:: server\_name
    - Ftp:: set\_anonymous\_ftp
    - Ftp:: set\_anonymous\_ftp\_incoming
    - Ftp:: set\_homedir
    - Ftp:: set\_quota
    - Ftp:: set\_welcome\_message
  - Integration
    - Integration:: fetch\_url
  - KnownHosts
    - KnownHosts:: create
    - KnownHosts:: delete
    - KnownHosts:: update
    - KnownHosts:: verify
  - LangPHP
    - LangPHP:: php\_get\_domain\_handler
    - LangPHP:: php\_get\_impacted\_domains

**Note:**  
Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

## Parameters

Parameter	Type	Description	Possible values	Example
domains	string	The domain name or names.	A valid domain or pipe-separated list of domains.  <b>Note:</b> To retrieve multiple domains, separate them with the pipe ( ) character.	example.com
item	string	The SSL item type or types.  This parameter defaults to <code>key</code> .	<ul style="list-style-type: none"> <li>• key</li> <li>• csr</li> <li>• crt</li> </ul> <b>Note:</b> To retrieve multiple types, separate them with the pipe ( ) character.	key

## Returns



LangPHP:: php\_get\_installed\_versions

LangPHP:: php\_get\_system\_default\_version

LangPHP:: php\_get\_vhost\_versions

LangPHP:: php\_ini\_get\_user\_basic\_directives

LangPHP:: php\_ini\_get\_user\_content

LangPHP:: php\_ini\_get\_user\_paths

LangPHP:: php\_ini\_set\_user\_basic\_directives

LangPHP:: php\_ini\_set\_user\_content

LangPHP:: php\_set\_vhost\_versions

▼ LastLogin

LastLogin:: get\_last\_or\_current\_logged\_in\_ip

▼ Locale

Locale:: get\_attributes

▼ Mailboxes

Mailboxes:: expunge\_messages

Mailboxes:: expunge\_messages\_for\_mailbox\_guid

Mailboxes:: get\_mailbox\_status

Mailboxes:: has\_utf8\_mailbox\_names

Mailboxes:: set\_utf8\_mailbox\_names

▼ Market

Market:: cancel\_pending\_ssl\_certificate

Market:: create\_shopping\_cart

Market:: get\_all\_products

Market:: get\_certificate\_status\_details

Market:: get\_login\_url

Return	Type	Description	Possible values	Example
id	string	The certificate's ID.	A valid string.	▼ <a href="#">Click to view...</a> example_com_a74f7_9dddf_1446659822_eae1ff43c4ec1991e195877c55755eff
type	string	The type of SSL item.	<ul style="list-style-type: none"><li>key</li><li>csr</li><li>crt</li></ul>	key
host	string	The hostname.	A valid hostname.	example.com

Market:: get\_pending\_ssl\_certificates

Market:: get\_provider\_specific\_dcv\_constraints

Market:: get\_providers\_list

Market:: get\_ssl\_certificate\_if\_available

Market:: process\_ssl\_pending\_queue

Market:: request\_ssl\_certificates

Market:: set\_status\_of\_pending\_queue\_items

Market:: set\_url\_after\_checkout

Market:: validate\_login\_token

#### ▼ Mime

Mime:: add\_handler

Mime:: add\_hotlink

Mime:: add\_mime

Mime:: add\_redirect

Mime:: delete\_handler

Mime:: delete\_hotlink

Mime:: delete\_mime

Mime:: delete\_redirect

Mime:: list\_handlers

Mime:: list\_hotlinks

Mime:: list\_mime

Mime:: list\_redirects

Mime:: redirect\_info

#### ▼ ModSecurity

ModSecurity:: disable\_all\_domains

ModSecurity:: disable\_domains

ModSecurity:: enable\_all\_domains

ModSecurity:: enable\_domains

ModSecurity:: has\_modsecurity\_installed

ModSecurity:: list\_domains

▼ Mysql

Mysql:: add\_host

Mysql:: add\_host\_note

Mysql :: check\_database

Mysql:: create\_database

Mysql:: create\_user

Mysql:: delete\_database

Mysql:: delete\_host

Mysql:: delete\_user

Mysql:: get\_host\_notes

Mysql:: get\_privileges\_on\_database

Mysql:: get\_restrictions

Mysql:: get\_server\_information

Mysql:: locate\_server

Mysql:: rename\_database

Mysql:: rename\_user

Mysql:: repair\_database

Mysql:: revoke\_access\_to\_database

Mysql:: set\_password

Mysql:: set\_privileges\_on\_database

▼ Notifications

Notifications:: get\_notifications\_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile\_rel  
ative\_uri

▼ PassengerApps

PassengerApps:: d  
isable\_application

PassengerApps:: e  
dit\_application

PassengerApps:: e  
nable\_application

PassengerApps:: e  
nsure\_deps

PassengerApps:: li  
st\_applications

PassengerApps:: r  
egister\_application

PassengerApps:: u  
nregister\_applicati  
on

▼ PasswdStrength

PasswdStrength::  
get\_required\_stren  
gth

▼ Personalization

Personalization::se  
t

Personalization ::g  
et

▼ Postgresql

Postgresql:: create  
\_database

Postgresql:: create  
\_user

Postgresql:: delete  
\_database

Postgresql:: get\_re  
strictions

Postgresql:: grant\_  
all\_privileges

Postgresql:: renam  
e\_database

Postgresql:: renam  
e\_user

Postgresql:: renam  
e\_user\_no\_passw  
ord

Postgresql:: revok  
e\_all\_privileges

Postgresql:: set\_p  
assword

▼ Pushbullet

Pushbullet:: send\_  
test\_message

- ▼ Quota
  - Quota:: get\_quota\_info
- ▼ Resellers
  - Resellers:: list\_accounts
- ▼ ResourceUsage
  - ResourceUsage:: get\_usages
- ▼ Restore
  - Restore:: directory\_listing
  - Restore:: get\_users
  - Restore:: query\_file\_info
  - Restore:: restore\_file
- ▼ Session
  - Session:: create\_temp\_user
- ▼ SiteTemplates
  - SiteTemplates:: list\_site\_templates
  - SiteTemplates:: list\_user\_settings
  - SiteTemplates:: publish
- ▼ SpamAssassin
  - SpamAssassin :: clear\_spam\_box
  - SpamAssassin:: get\_symbolic\_test\_names
  - SpamAssassin:: get\_user\_preferences
  - SpamAssassin:: update\_user\_preference
- ▼ SSH
  - SSH:: get\_port
- ▼ SSL
  - SSL:: add\_autossl\_excluded\_domains
  - SSL:: can\_ssl\_redirect
  - SSL:: check\_shared\_cert
  - SSL:: delete\_cert
  - SSL:: delete\_csr
  - SSL:: delete\_key

SSL:: delete\_ssl

SSL:: disable\_mail\_sni

SSL:: enable\_mail\_sni

SSL:: fetch\_best\_for\_domain

SSL:: fetch\_cert\_info

SSL:: fetch\_certificates\_for\_fqdns

SSL:: fetch\_key\_and\_cabundle\_for\_certificate

SSL:: find\_certificates\_for\_key

SSL:: find\_csrs\_for\_key

SSL:: generate\_certificate

SSL:: generate\_csr

SSL:: generate\_key

SSL:: get\_autossl\_excluded\_domains

SSL:: get\_autossl\_pending\_queue

SSL:: get\_autossl\_problems

SSL:: get\_cabundle

SSL:: get\_cn\_name

SSL:: install\_ssl

SSL:: installed\_host

SSL:: installed\_hosts

SSL:: is\_autossl\_check\_in\_progress

SSL:: is\_mail\_sni\_supported

SSL:: is\_sni\_supported

SSL:: list\_certs

SSL:: list\_csrs

SSL:: list\_keys

SSL:: list\_ssl\_items

SSL:: mail\_sni\_status

tus

SSL:: rebuild\_mail  
\_snl\_config

SSL:: rebuildssldb

SSL:: remove\_aut  
ossl\_excluded\_do  
mains

SSL:: set\_autossl\_  
excluded\_domains

SSL:: set\_cert\_frie  
ndly\_name

SSL:: set\_csr\_frien  
dly\_name

SSL:: set\_key\_frie  
ndly\_name

SSL:: set\_primary  
\_ssl

SSL:: set\_ssl\_shar  
e

SSL:: show\_cert

SSL:: show\_csr

SSL:: show\_key

SSL:: start\_autossl\_  
\_check

SSL:: toggle\_ssl\_r  
edirects\_for\_doma  
ins

SSL:: upload\_cert

SSL:: upload\_key

▼ StatsBar

StatsBar:: get\_stat  
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

▼ SubDomain

SubDomain:: adds  
ubdomain

▼ Themes

Themes:: get\_the  
me\_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create\_fu  
ll\_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate\_user\_configuration

TwoFactorAuth:: get\_user\_configuration

TwoFactorAuth:: remove\_user\_configuration

TwoFactorAuth:: set\_user\_configuration

▼ UserManager

UserManager:: check\_account\_conflicts

UserManager:: create\_user

UserManager:: delete\_user

UserManager:: dismiss\_user

UserManager:: edit\_user

UserManager:: list\_users

UserManager:: lookup\_service\_account

UserManager:: lookup\_user

UserManager:: merge\_service\_account

UserManager:: unlink\_service\_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDepl



## oyment

VersionControlDep  
loyment:: **create**

VersionControlDep  
loyment:: **delete**

VersionControlDep  
loyment:: **retrieve**

### ▼ WebDisk

WebDisk:: **delete\_**  
**user**

WebDisk:: **set\_ho**  
**medir**

WebDisk:: **set\_pas**  
**sword**

WebDisk:: **set\_per**  
**missions**

### ▼ WebmailApps

WebmailApps:: **list**  
**webmailapps**

### ▼ WebVhosts

WebVhost:: **list\_do**  
**mains**

WebVhost:: **list\_ssl**  
**\_capable\_domains**

### ▼ WordPressBackup

WordPressBackup  
:: **any\_running**

WordPressBackup  
:: **cancel**

WordPressBackup  
:: **cleanup**

WordPressBackup  
:: **get\_available\_ba**  
**ckups**

WordPressBackup  
:: **is\_running**

WordPressBackup  
:: **start**

### ▼ WordPressInstance

#### Manager

WordPressInstanc  
eManager:: **cancel**  
**\_scan**

WordPressInstanc  
eManager:: **cleanu**  
**p\_scan**

WordPressInstanc  
eManager:: **chang**  
**e\_admin\_passwor**  
**d**

WordPressInstanc  
eManager:: **config**  
**ure\_autoupdate**

WordPressInstanc  
eManager:: **get\_ap**

i\_version

WordPressInstanceManager:: **get\_instance\_by\_id**

WordPressInstanceManager:: **get\_instances**

WordPressInstanceManager:: **get\_latest\_wordpress\_version\_from\_wordpress\_org**

WordPressInstanceManager:: **get\_scan\_results**

WordPressInstanceManager:: **is\_installable\_addon\_available**

WordPressInstanceManager:: **start\_scan**

▼ WordPressRestore

WordPressRestore:: **any\_running**

WordPressRestore:: **cleanup**

WordPressRestore:: **start**