

UAPI Functions - Pushbullet::send_test_message

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

- Backup
- Backup::fullbacku

- p_to_ftp

- Backup::fullbacku
- p_to_homedir

- Backup::fullbacku
- p_to_scp_with_key

- Backup::fullbacku
- p_to_scp_with_password

- Backup::list_backups

Bandwidth

- Bandwidth::get_enabled_protocols

- Bandwidth::get_retention_periods

- Bandwidth::query

Batch

- Batch::strict

Brand

- Brand::read

Branding

- Branding::file

- Branding::get_applications

- Branding::get_application_information

- Branding::get_available_applications

- Branding::get_info

Description

This function sends a Pushbullet™ test message to determine that the token is valid and that the account holder can receive the message.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/Pushbullet/send_test_message?access_token=alb2c3d4e5f6g7h8i9j0
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

Function information

About this module

The Pushbullet module manages user notifications through the Pushbullet service.

About UAPI

UAPI accesses and modifies data for cPanel accounts.

information_for_applications

Branding:: image

Branding:: include

Branding:: spritelist

CacheBuster

CacheBuster:: read

CacheBuster:: update

Chkserverd

Chkserverd:: get_exit_ports

Chkserverd:: get_exit_ports_ssl

Chrome

Chrome:: get_domain

Contactus

Contactus:: is_enabled

cPAddons

cPAddons:: get_available_addons

cPAddons:: get_instance_settings

cPAddons:: list_addon_instances

cPGreyList

cPGreyList:: disable_all_domains

cPGreyList:: disable_domains

cPGreyList:: enable_all_domains

cPGreyList:: enable_domains

cPGreyList:: has_greylisting_enabled

cPGreyList:: list_domains

DAV

DAV:: disable_shared_global_addressbook

DAV:: enable_shared_global_addressbook

DAV:: get_calendar_contacts_config

DAV:: has_shared_global_addressbook

LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// Send test message  
to Pushbullet.  
$test_pushbullet =  
$cpanel->uapi(  
    'Pushbullet',  
    'send_test_message',  
    array(  
  
        'access_token'  
=>  
        'a1b2c3d4e5f6g7h8i9j0'  
    ),  
    );
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Notes:

- The *Fe*
- Ur **mi** us 20 or 20).\ 20 or 20).

Find a function

- UAPI Modules - Pushbullet — The Pushbullet module manages user notifications through the Pushbullet™ service.

DAV:: is_dav_service_enabled

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

▼ LiveAPI Perl Module

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Send test message
to Pushbullet.
my $test_pushbullet =
$cpliveapi->uapi(
    'Pushbullet',
    'send_test_message',
    {
        'access_token'
=>
'a1b2c3d4e5f6g7h8i9j0
',
    }
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

▼ cPanel Template Toolkit

```
<!-- Get an array of
privileges. -->
[% execute(
    'Pushbullet',
    'send_test_message',
    { access_token =>
'a1b2c3d4e5f6g7h8i9j0
' } ); %]
```

Note:

For more information, read our [Guide to Template Toolkit documentation](#).

Email:: add_spam_filter

Email:: browse_mailbox

Email:: change_mx

Email:: check_fastmail

Email:: check_pipe_forwarder

Email:: delete_auto_responder

Email:: delete_domain_forwarder

Email:: delete_filter

Email:: delete_forwarder

Email:: delete_held_messages

Email:: delete_list

Email:: delete_mx

Email:: delete_pop

Email:: disable_filter

Email:: disable_mailbox_autocreate

Email:: disable_spam_assassin

Email:: disable_spam_autodelete

Email:: disable_spam_box

Email:: dispatch_client_settings

Email:: edit_pop_quota

Email:: enable_filter

Email:: enable_mailbox_autocreate

Email:: enable_spam_assassin

Email:: enable_spam_box

Email:: fetch_charmaps

Email:: fts_rescan_mailbox

Email:: generate_mailman_otp

Email:: get_auto_r

Command Line

```
uapi --user=username
Pushbullet
send_test_message
access_token=a1b2c3d4
e5f6g7h8i9j0
```

Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

Output (JSON)

```
{
  "messages":null,
  "errors":null,
  "status":1,
  "metadata":{" },
  "data":{"
    "message_id":"555a399
4-173a4a271062d",
    "payload":{"
      "dismissed":false,
      "body":"This
message confirms that
hostname.example.com
" (192.168.0.20) can
send a message to you
via
Pushbullet.\n\nThis
message was sent on
Monday, May 18, 2015
at 7:12:20 PM UTC.",
```

esponder
Email: get_charts
Email: get_client_settings
Email: get_default_email_quota
Email: get_default_email_quota_mib
Email: get_disk_usage
Email: get_filter
Email: get_held_message_count
Email: get_mailbox_autocreate
Email: get_mailman_delegates
Email: get_main_account_disk_usage
Email: get_main_account_disk_usage_bytes
Email: get_max_email_quota
Email: get_max_email_quota_mib
Email: get_pop_quota
Email: get_spam_settings
Email: get_webmail_settings
Email: has_delegated_mailman_lists
Email: has_plaintext_authentication
Email: hold_outgoing
Email: is_integer
Email: list_auto_responders
Email: list_default_address
Email: list_domain_forwarders
Email: list_filters
Email: list_filters_backups
Email: list_forward

```
"receiver_email": "user@example.com",  
"direction": "self",  
"sender_iden": "ujw5ScArtjU",  
"iden": "ujw5ScArtjUsjAeRXXMLGS",  
"sender_name": "Firstname Lastname",  
"active": true,  
"sender_email": "user@example.com",  
"receiver_email_normalized": "user@example.com",  
"modified": 1431976341.39182,  
"created": 1431976341.38872,  
"sender_email_normalized": "user@example.com",  
"type": "note",  
"receiver_iden": "ujw5ScArtjU",  
"title": "Test message (ID: 555a3994-173a4a271062d)"
```


EmailAuth:: ensure
_dkim_keys_exist

EmailAuth:: fetch_
dkim_private_keys

EmailAuth:: install
_dkim_private_key
s

EmailAuth:: install
_spf_records

EmailAuth:: validat
e_current_dkims

EmailAuth:: validat
e_current_ptrs

EmailAuth:: validat
e_current_spfs

ExternalAuthenticat
ion

ExternalAuthenticat
ion:: add_authn_li
nk

ExternalAuthenticat
ion:: configured_
modules

ExternalAuthenticat
ion:: get_authn_lin
ks

ExternalAuthenticat
ion:: has_external_
_auth_modules_co
nfigured

ExternalAuthenticat
ion:: remove_auth
n_link

Features

Features:: get_feat
ure_metadata

Features:: has_fea
ture

Features:: list_feat
ures

Fileman

Fileman:: autocom
pletedir

Fileman:: empty_tr
ash

Fileman:: get_file_
content

Fileman:: get_file_i
nformation

Fileman:: list_files

Fileman:: save_file_
_content

Fileman:: transcod
e

- Fileman:: upload_files
- Ftp:: add_ftp
 - Ftp:: allows_anonymous_ftp
 - Ftp:: allows_anonymous_ftp_incoming
 - Ftp:: delete_ftp
 - Ftp:: ftp_exists
 - Ftp:: get_ftp_daemon_info
 - Ftp:: get_port
 - Ftp:: get_quota
 - Ftp:: get_welcome_message
 - Ftp:: kill_session
 - Ftp:: list_ftp
 - Ftp:: list_ftp_with_disk
 - Ftp:: list_sessions
 - Ftp:: passwd
 - Ftp:: server_name
 - Ftp:: set_anonymous_ftp
 - Ftp:: set_anonymous_ftp_incoming
 - Ftp:: set_homedir
 - Ftp:: set_quota
 - Ftp:: set_welcome_message
 - Integration
 - Integration:: fetch_url
 - KnownHosts
 - KnownHosts:: create
 - KnownHosts:: delete
 - KnownHosts:: update
 - KnownHosts:: verify
 - LangPHP
 - LangPHP:: php_get_domain_handler
 - LangPHP:: php_get_impacted_domains

g
 • This is confidential information that you reserve the right to send via a secure channel.

Returns

- LangPHP:: php_get_installed_versions
- LangPHP:: php_get_system_default_version
- LangPHP:: php_get_vhost_versions
- LangPHP:: php_ini_get_user_basic_directives
- LangPHP:: php_ini_get_user_content
- LangPHP:: php_ini_get_user_paths
- LangPHP:: php_ini_set_user_basic_directives
- LangPHP:: php_ini_set_user_content
- LangPHP:: php_set_vhost_versions
- ▼ LastLogin
 - LastLogin:: get_last_or_current_logged_in_ip
- ▼ Locale
 - Locale:: get_attributes
- ▼ Mailboxes
 - Mailboxes:: expunge_mailbox_messages
 - Mailboxes:: expunge_messages_for_mailbox_guid
 - Mailboxes:: get_mailbox_status
 - Mailboxes:: has_utf8_mailbox_names
 - Mailboxes:: set_utf8_mailbox_names
- ▼ Market
 - Market:: cancel_pending_ssl_certificate
 - Market:: create_shopping_cart
 - Market:: get_all_products
 - Market:: get_certificate_status_details
 - Market:: get_login_url

Return	Type	Description	Possible values	Example
message_id	string	The test message's ID.	A valid string.	554d2cbd-efe61da3cacb
payload	hash	The payload from the Pushbullet server.	For more information, visit Pushbullet's API documentation . <div style="border: 1px solid red; padding: 5px; margin-top: 10px;"> <p>Warning: This return may contain values that are Boolean primitives. JSON properly represents these, but XML represents them as 0 or 1.</p> </div>	

Market:: get_pending_ssl_certificates

Market:: get_provider_specific_dcv_constraints

Market:: get_providers_list

Market:: get_ssl_certificate_if_available

Market:: process_ssl_pending_queue

Market:: request_ssl_certificates

Market:: set_status_of_pending_queue_items

Market:: set_url_after_checkout

Market:: validate_login_token

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: delete_handler

Mime:: delete_hotlink

Mime:: delete_mime

Mime:: delete_redirect

Mime:: list_handlers

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirects

Mime:: redirect_info

▼ ModSecurity

ModSecurity:: disable_all_domains

ModSecurity:: disable_domains

ModSecurity:: enable_all_domains

ModSecurity:: enable_domains

ModSecurity:: has_modsecurity_installed

ModSecurity:: list_domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_note

Mysql :: check_database

Mysql:: create_database

Mysql:: create_user

Mysql:: delete_database

Mysql:: delete_host

Mysql:: delete_user

Mysql:: get_host_notes

Mysql:: get_privileges_on_database

Mysql:: get_restrictions

Mysql:: get_server_information

Mysql:: locate_server

Mysql:: rename_database

Mysql:: rename_user

Mysql:: repair_database

Mysql:: revoke_access_to_database

Mysql:: set_password

Mysql:: set_privileges_on_database

▼ Notifications

Notifications:: get_notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_rel
ative_uri

▼ PassengerApps

PassengerApps:: d
isable_application

PassengerApps:: e
dit_application

PassengerApps:: e
nable_application

PassengerApps:: e
nsure_deps

PassengerApps:: li
st_applications

PassengerApps:: r
egister_application

PassengerApps:: u
nregister_applicati
on

▼ PasswdStrength

PasswdStrength::
get_required_stren
gth

▼ Personalization

Personalization::se
t

Personalization ::g
et

▼ Postgresql

Postgresql:: create
_database

Postgresql:: create
_user

Postgresql:: delete
_database

Postgresql:: get_re
strictions

Postgresql:: grant_
all_privileges

Postgresql:: renam
e_database

Postgresql:: renam
e_user

Postgresql:: renam
e_user_no_passw
ord

Postgresql:: revok
e_all_privileges

Postgresql:: set_p
assword

▼ Pushbullet

Pushbullet:: send_
test_message

- ▼ Quota
 - Quota:: get_quota_info
- ▼ Resellers
 - Resellers:: list_accounts
- ▼ ResourceUsage
 - ResourceUsage:: get_usages
- ▼ Restore
 - Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- ▼ Session
 - Session:: create_temp_user
- ▼ SiteTemplates
 - SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- ▼ SpamAssassin
 - SpamAssassin :: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key

SSL:: delete_ssl

SSL:: disable_mail_sni

SSL:: enable_mail_sni

SSL:: fetch_best_for_domain

SSL:: fetch_cert_info

SSL:: fetch_certificates_for_fqdns

SSL:: fetch_key_and_cabundle_for_certificate

SSL:: find_certificates_for_key

SSL:: find_csrs_for_key

SSL:: generate_certificate

SSL:: generate_csr

SSL:: generate_key

SSL:: get_autossl_excluded_domains

SSL:: get_autossl_pending_queue

SSL:: get_autossl_problems

SSL:: get_cabundle

SSL:: get_cn_name

SSL:: install_ssl

SSL:: installed_host

SSL:: installed_hosts

SSL:: is_autossl_check_in_progress

SSL:: is_mail_sni_supported

SSL:: is_sni_supported

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_items

SSL:: mail_sni_status

tus

SSL:: rebuild_mail
_snl_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDepl

oyment

VersionControlDep
loyment:: **create**

VersionControlDep
loyment:: **delete**

VersionControlDep
loyment:: **retrieve**

▼ WebDisk

WebDisk:: **delete_**
user

WebDisk:: **set_ho**
medir

WebDisk:: **set_pas**
sword

WebDisk:: **set_per**
missions

▼ WebmailApps

WebmailApps:: **list**
webmailapps

▼ WebVhosts

WebVhost:: **list_do**
mains

WebVhost:: **list_ssl**
_capable_domains

▼ WordPressBackup

WordPressBackup
:: **any_running**

WordPressBackup
:: **cancel**

WordPressBackup
:: **cleanup**

WordPressBackup
:: **get_available_ba**
ckups

WordPressBackup
:: **is_running**

WordPressBackup
:: **start**

▼ WordPressInstance

Manager

WordPressInstanc
eManager:: **cancel**
_scan

WordPressInstanc
eManager:: **cleanu**
p_scan

WordPressInstanc
eManager:: **chang**
e_admin_passwor
d

WordPressInstanc
eManager:: **config**
ure_autoupdate

WordPressInstanc
eManager:: **get_ap**

i_version

WordPressInstanceManager:: **get_instance_by_id**

WordPressInstanceManager:: **get_instances**

WordPressInstanceManager:: **get_latest_wordpress_version_from_wordpress_org**

WordPressInstanceManager:: **get_scan_results**

WordPressInstanceManager:: **is_installable_addon_available**

WordPressInstanceManager:: **start_scan**

▼ WordPressRestore

WordPressRestore:: **any_running**

WordPressRestore:: **cleanup**

WordPressRestore:: **start**