

# UAPI Functions - WordPressInstanceManager::get\_instance\_by\_id

## Description

This function retrieves a WordPress® instance's configuration.

### Notes:

- You **must** install the [WordPress Manager cPanel plugin](#) to access this API function.
- This function retrieves some data that the system stored during the WordPress installation. That data may not reflect the most recent user changes.

## Examples

### ▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess##  
▼ #####/execute/WordPressInstanceManager/  
get_instance_by_id?id=cPanel__Blogs__WordPressX.0.1528208546
```

### Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

## Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

### Backup

Backup::fullbackup

p\_to\_ftp

Backup::fullbackup\_to\_homedir

Backup::fullbackup\_to\_scp\_with\_key

Backup::fullbackup\_to\_scp\_with\_password

Backup::list\_backups

### ▼ Bandwidth

Bandwidth::get\_enabled\_protocols

Bandwidth::get\_retention\_periods

Bandwidth::query

### ▼ Batch

Batch::strict

### ▼ Brand

Brand::read

### ▼ Branding

Branding::file

Branding::get\_applications

Branding::get\_application\_information

Branding::get\_available\_applications

## Function information

## About this module

The WordPressInstanceManager module manages cPanel's WordPress® cPAddon instances. The system installs this module with the WordPress Instance Manager cPanel plugin.

Branding:: get\_information\_for\_applications

Branding:: image

Branding:: include

Branding:: spritelist

▼ CacheBuster

CacheBuster:: read

CacheBuster:: update

▼ Chkservd

Chkservd:: get\_external\_ports

Chkservd:: get\_external\_ports\_ssl

▼ Chrome

Chrome:: get\_domain

▼ Contactus

Contactus:: is\_enabled

▼ cPAddons

cPAddons:: get\_available\_addons

cPAddons:: get\_instance\_settings

cPAddons:: list\_addon\_instances

▼ cPGreyList

cPGreyList:: disable\_all\_domains

cPGreyList:: disable\_domains

cPGreyList:: enable\_all\_domains

cPGreyList:: enable\_domains

cPGreyList:: has\_greylisting\_enabled

cPGreyList:: list\_domains

▼ DAV

DAV:: disable\_shared\_global\_addressbook

DAV:: enable\_shared\_global\_addressbook

DAV:: get\_calendar\_contacts\_config

DAV:: has\_shared\_global\_addressbook

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// Retrieve a single  
WordPress instance by  
ID.  
$instances =  
$cpanel->uapi(  
  
    'WordPressInstanceMan  
ager',  
    'get_instance_by_id',  
    array(  
        'id'  
    )  
=>  
    'cPanel__Blogs__WordP  
ressX.0.1528208546',  
    )  
);
```

**Note:**

For more information, read our [Guide to the LiveAPI System](#).

## About UAPI

UAPI accesses and modifies data for cPanel accounts.

**Notes:**

- The *Fe* int
- Ur *mi* us 20 or 20 ).` 20 or 20 ).

## Find a function

ok

DAV:: is\_dav\_service\_enabled

DAV:: is\_horde\_enabled

▾ DCV

DCV:: check\_domains\_via\_dns

DCV:: check\_domains\_via\_http

DCV:: ensure\_domains\_can\_pass\_dcv

▾ DomainInfo

DomainInfo:: domains\_data

DomainInfo:: list\_domains

DomainInfo:: main\_domain\_builtin\_subdomain\_aliases

DomainInfo:: single\_domain\_data

▾ DNS

DNS:: ensure\_domains\_reside\_only\_locally

DNS:: has\_local\_authority

▾ DNSSEC

DNSSEC:: disable\_dnssec

DNSSEC:: enable\_dnssec

DNSSEC:: fetch\_dns\_records

DNSSEC:: set\_nsec3

DNSSEC:: unset\_nsec3

▾ Email

Email:: account\_name

Email:: add\_auto\_responder

Email:: add\_domain\_forwarder

Email:: add\_forwarder

Email:: add\_list

Email:: add\_mailman\_delegates

Email:: add\_mx

▾ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# Retrieve a single  
WordPress instance by  
ID.
```

```
my $instances =  
$cpliveapi->uapi(  
  
'WordPressInstanceMan  
ager',  
'get_instance_by_id',  
{  
    'id'  
  
=>  
'cPanel__Blogs__WordP  
ressX.0.1528208546',  
}  
  
);
```

**Note:**

For more information, read our [Guide to the LiveAPI System](#).

▾ cPanel Template Toolkit

```
<!-- Retrieve a  
single WordPress  
instance by ID. -->  
[% data = execute(  
'WordPressInstanceMan  
ager',  
'get_instance_by_id' {  
'id' =>  
'cPanel__Blogs__WordP  
ressX.0.1528208546',  
} )]; %]
```

**Note:**

For more information, read our [Guide to Template Toolkit](#) documentation.

- UAPI Functions - cPanel addons::list\_addon\_instances — This function lists an account's deployed cPanel addons instances.
- UAPI Functions - cPanel addons::get\_instance\_settings — This function lists a cPanel addons instance's settings.
- UAPI Modules - cPanel addons — The cPanel addons module accesses cPanel's cPanel addons system.

Email:: add\_pop

Email:: add\_spam\_filter

Email:: browse\_mailbox

Email:: change\_mx

Email:: check\_fastmail

Email:: check\_pipe\_forwarder

Email:: delete\_auto\_responder

Email:: delete\_domain\_forwarder

Email:: delete\_filter

Email:: delete\_forwarder

Email:: delete\_help\_messages

Email:: delete\_list

Email:: delete\_mx

Email:: delete\_pop

Email:: disable\_filter

Email:: disable\_mailbox\_autocreate

Email:: disable\_spam\_assassin

Email:: disable\_spam\_autodelete

Email:: disable\_spam\_box

Email:: dispatch\_client\_settings

Email:: edit\_pop\_quota

Email:: enable\_filter

Email:: enable\_mailbox\_autocreate

Email:: enable\_spam\_assassin

Email:: enable\_spam\_box

Email:: fetch\_charmaps

Email:: fts\_rescan\_mailbox

Email:: generate\_mailman\_opt

## Command Line

```
uapi --user=username
WordPressInstanceManager
get_instance_by_id
id=cPanel__Blogs__WordPressX.0.1528208546
```

### Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

## Output (JSON)

```
{
  "metadata": {},
  "warnings": null,
  "status": 1,
  "data": {
    "addon_config":
      "/home/example/.cpaddons/cPanel::Blogs::WordPressX.0.yaml",
    "db_type": "mysql",
    "created_on":
      "1525876559",
    "db_prefix": "wp",
    "db_server":
      "localhost",

    "autoupdate.core.has_filter": false,
    "db_username":
      "example_wp2",
    "current_version":
      "4.9.5",
```

Email: get\_auto\_responder  
Email: get\_charts  
Email: get\_client\_settings  
Email: get\_default\_email\_quota  
Email: get\_default\_email\_quota\_mib  
Email: get\_disk\_usage  
Email: get\_filter  
Email: get\_held\_message\_count  
Email: get\_mailbox\_autocreate  
Email: get\_mailman\_delegates  
Email: get\_main\_account\_disk\_usage  
Email: get\_main\_account\_disk\_usage\_bytes  
Email: get\_max\_email\_quota  
Email: get\_max\_email\_quota\_mib  
Email: get\_pop\_quota  
Email: get\_spam\_settings  
Email: get\_webmail\_settings  
Email: has\_delegated\_mailman\_lists  
Email: has\_plaintext\_authentication  
Email: hold\_outgoing  
Email: is\_integer  
Email: list\_auto\_responders  
Email: list\_default\_address  
Email: list\_domain\_forwarders  
Email: list\_filters  
Email: list\_filters\_backups

```
"domain":  
"example.com",  
  "full_path":  
"/home/example/public_html",  
  "rel_path": "",  
  "admin_username":  
"admin",  
  "addon_type":  
"modern",  
  "site_url":  
"example.com",  
  
"available_version":  
"4.9.6",  
  
"autoupdate.core.major": false,  
  "id":  
"cPanel__Blogs__WordPressX.0.1528208546",  
  "admin_url":  
"example.com/wp-login.php",  
  "autoupdate": true,  
  
"initial_install_version": "4.9.5",  
  
"autoupdate.core.minor": true,  
  "db_name":  
"example_wp2",  
  "recent": 0,  
  "addon_name":  
"cPanel::Blogs::WordPressX",  
  "admins": [{  
    "display_name":  
"admin",  
    "user_nicename":  
"admin",  
    "user_login":  
"admin",  
    "ID": 1,  
    "user_status":  
"0",  
    "user_email":  
"admin@example.com"  
  }],  
  "homedir":  
"/home/example"  
},
```

Email:: list\_forwarders

Email:: list\_forwarders\_backups

Email:: list\_lists

Email:: list\_mail\_domains

Email:: list\_mxns

Email:: list\_pops

Email:: list\_pops\_with\_disk

Email:: list\_system\_filter\_info

Email:: passwd\_list

Email:: passwd\_pop

Email:: release\_outgoing

Email:: remove\_mailman\_delegates

Email:: reorder\_filters

Email:: set\_always\_accept

Email:: set\_default\_address

Email:: set\_list\_privacy\_options

Email:: stats\_db\_status

Email:: store\_filter

Email:: suspend\_incoming

Email:: suspend\_login

Email:: suspend\_outgoing

Email:: trace\_filter

Email:: unsuspend\_incoming

Email:: unsuspend\_login

Email:: unsuspend\_outgoing

Email:: verify\_password

▼ EmailAuth

EmailAuth:: disable\_dkim

EmailAuth:: enable\_dkim

```
"errors": null,
"messages": null
}
```

**Note:**

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

### Parameters

Parameter	Type	Description	Possible values	Example
id	string	<p><b>Required</b></p> <p>The WordPress instance's unique ID.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <p><b>Note</b> : You can retrieve an instance ID with the <code>get_instances</code> function.</p> </div>	A valid instance ID.	cPanel_Blogs_WordPressX.0.1528208546

### Returns

Return	Type	Description	Possible values	Example
addon_config	string	The WordPress instance's configuration file location.	An absolute filepath.	<p>▼ <a href="#">Click to view...</a></p> <p>/home/example/.cpaddons/cPanel::Blogs::WordPressX.0.yaml</p>

EmailAuth:: ensure\_dkim\_keys\_exist

EmailAuth:: fetch\_dkim\_private\_keys

EmailAuth:: install\_dkim\_private\_keys

EmailAuth:: install\_spf\_records

EmailAuth:: validate\_current\_dkims

EmailAuth:: validate\_current\_ptrs

EmailAuth:: validate\_current\_spfs

ExternalAuthentication

ExternalAuthentication:: add\_authn\_link

ExternalAuthentication:: configured\_modules

ExternalAuthentication:: get\_authn\_links

ExternalAuthentication:: has\_external\_auth\_modules\_configured

ExternalAuthentication:: remove\_authn\_link

Features

Features:: get\_feature\_metadata

Features:: has\_feature

Features:: list\_features

Fileman

Fileman:: autocompletdir

Fileman:: empty\_trash

Fileman:: get\_file\_content

Fileman:: get\_file\_information

Fileman:: list\_files

Fileman:: save\_file\_content

Fileman:: transcode

addon_name	string	The WordPress cPAddon used to install the instance.	<ul style="list-style-type: none"> <li>cPanel::Blogs::WordPress</li> <li>cPanel::Blogs::WordPressX</li> <li>cPanel::Blogs::WordPressUnmanaged</li> </ul>	cPanel::Blogs::WordPressX
addon_type	string	The WordPress instance's installation method.	<ul style="list-style-type: none"> <li>modern — Installed by RPM-managed WordPress cPAddon.</li> <li>legacy — Installed by legacy cPAddon.</li> <li>unmanaged — Installed by third-party tool or the WordPress installer.</li> </ul>	modern
admin_url	string	The URL to the instance's administration interface.	A valid URL.	example.com/wp-login.php
admin_username	string	The administrator username configured at the time of installation.	A valid string.	admin
admins	array of hashes	<p>A list of the WordPress instance's administrators.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p><b>Note</b> : We introduced this return in WordPress Instance Manager version 1.1.</p> </div> <p>The function returns the value in the admins array of hashes.</p>	This array of hashes contains the id, display_name, user_email, nice_name, and user_status returns.	

- Fileman:: upload\_files
- Ftp:: add\_ftp
    - Ftp:: allows\_anonymous\_ftp
    - Ftp:: allows\_anonymous\_ftp\_incoming
    - Ftp:: delete\_ftp
    - Ftp:: ftp\_exists
    - Ftp:: get\_ftp\_daemon\_info
    - Ftp:: get\_port
    - Ftp:: get\_quota
    - Ftp:: get\_welcome\_message
    - Ftp:: kill\_session
    - Ftp:: list\_ftp
    - Ftp:: list\_ftp\_with\_disk
    - Ftp:: list\_sessions
    - Ftp:: passwd
    - Ftp:: server\_name
    - Ftp:: set\_anonymous\_ftp
    - Ftp:: set\_anonymous\_ftp\_incoming
    - Ftp:: set\_homedir
    - Ftp:: set\_quota
    - Ftp:: set\_welcome\_message
  - Integration
    - Integration:: fetch\_url
  - KnownHosts
    - KnownHosts:: create
    - KnownHosts:: delete
    - KnownHosts:: update
    - KnownHosts:: verify
  - LangPHP
    - LangPHP:: php\_get\_domain\_handler
    - LangPHP:: php\_get\_impacted\_domains

id	<i>integer</i>	<p>The user's automatically generated identifier.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p><b>Note</b> : We introduced this return in WordPress Instance Manager version 1.1.</p> </div> <p>The function returns the value in the <code>admins</code> array of hashes.</p>	A positive integer.	1
display_name	<i>string</i>	<p>The user's display name.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p><b>Note</b> : We introduced this return in WordPress Instance Manager version 1.1.</p> </div> <p>The function returns the value in the <code>admins</code> array of hashes.</p>	A valid string.	admin



LangPHP:: php\_get\_installed\_versions

LangPHP:: php\_get\_system\_default\_version

LangPHP:: php\_get\_vhost\_versions

LangPHP:: php\_ini\_get\_user\_basic\_directives

LangPHP:: php\_ini\_get\_user\_content

LangPHP:: php\_ini\_get\_user\_paths

LangPHP:: php\_ini\_set\_user\_basic\_directives

LangPHP:: php\_ini\_set\_user\_content

LangPHP:: php\_set\_vhost\_versions

▼ LastLogin

LastLogin:: get\_last\_or\_current\_logged\_in\_ip

▼ Locale

Locale:: get\_attributes

▼ Mailboxes

Mailboxes:: expunge\_mailbox\_messages

Mailboxes:: expunge\_messages\_for\_mailbox\_guid

Mailboxes:: get\_mailbox\_status

Mailboxes:: has\_utf8\_mailbox\_names

Mailboxes:: set\_utf8\_mailbox\_names

▼ Market

Market:: cancel\_pending\_ssl\_certificate

Market:: create\_shopping\_cart

Market:: get\_all\_products

Market:: get\_certificate\_status\_details

Market:: get\_login\_url

<p>nice_name</p>	<p>string</p>	<p>The user's simplified username, which you can use as an HTML ID or similar.</p> <div data-bbox="740 296 878 772" style="border: 1px solid orange; padding: 5px;"> <p><b>Note</b> : We introduced this return in WordPress Instance Manager version 1.1.</p> </div> <p>The function returns the value in the <code>admins</code> array of hashes.</p>	<p>A valid string.</p>	<p>admin</p>
<p>user_email</p>	<p>string</p>	<p>The user's email address.</p> <div data-bbox="740 968 878 1444" style="border: 1px solid orange; padding: 5px;"> <p><b>Note</b> : We introduced this return in WordPress Instance Manager version 1.1.</p> </div> <p>The function returns the value in the <code>admins</code> array of hashes.</p>	<p>A valid email address.</p>	<p>admin@example.com</p>

Market:: get\_pending\_ssl\_certificates

Market:: get\_provider\_specific\_dcv\_constraints

Market:: get\_providers\_list

Market:: get\_ssl\_certificate\_if\_available

Market:: process\_ssl\_pending\_queue

Market:: request\_ssl\_certificates

Market:: set\_status\_of\_pending\_queue\_items

Market:: set\_url\_after\_checkout

Market:: validate\_login\_token

▼ Mime

Mime:: add\_handler

Mime:: add\_hotlink

Mime:: add\_mime

Mime:: add\_redirect

Mime:: delete\_handler

Mime:: delete\_hotlink

Mime:: delete\_mime

Mime:: delete\_redirect

Mime:: list\_handlers

Mime:: list\_hotlinks

Mime:: list\_mime

Mime:: list\_redirects

Mime:: redirect\_info

▼ ModSecurity

ModSecurity:: disable\_all\_domains

ModSecurity:: disable\_domains

ModSecurity:: enable\_all\_domains

user_status	string	<p>The user's verified status.</p> <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;"> <p><b>Note</b> : We introduced this return in WordPress Instance Manager version 1.1.</p> </div> <p>The function returns the value in the admins array of hashes.</p>	<ul style="list-style-type: none"> <li>• 1 — Verified.</li> <li>• 0 — Unverified.</li> </ul>	0
autoupdate	Boolean	Whether the user enabled automatic updates.	<ul style="list-style-type: none"> <li>• true — Enabled.</li> <li>• false — Disabled.</li> </ul>	true
autoupdate.core.has_filter	Boolean	Whether one or more filters modify the core autoupdate settings.	<ul style="list-style-type: none"> <li>• true — Filter(s) applied.</li> <li>• false — No filters applied.</li> </ul>	false
		<div style="border: 1px solid orange; padding: 5px;"> <p><b>Notes:</b></p> </div>		

ModSecurity:: enable\_domains

ModSecurity:: has\_modsecurity\_installed

ModSecurity:: list\_domains

▼ Mysql

Mysql:: add\_host

Mysql:: add\_host\_note

Mysql :: check\_database

Mysql:: create\_database

Mysql:: create\_user

Mysql:: delete\_database

Mysql:: delete\_host

Mysql:: delete\_user

Mysql:: get\_host\_notes

Mysql:: get\_privileges\_on\_database

Mysql:: get\_restrictions

Mysql:: get\_server\_information

Mysql:: locate\_server

Mysql:: rename\_database

Mysql:: rename\_user

Mysql:: repair\_database

Mysql:: revoke\_access\_to\_database

Mysql:: set\_password

Mysql:: set\_privileges\_on\_database

▼ Notifications

Notifications:: get\_notifications\_count

▼ NVData

NVData:: get

NVData:: set

• Typically, plugins apply filters to the output data sets.

- Parser: firstfile\_relative\_uri
- PassengerApps:: disable\_application
  - PassengerApps:: edit\_application
  - PassengerApps:: enable\_application
  - PassengerApps:: ensure\_deps
  - PassengerApps:: list\_applications
  - PassengerApps:: register\_application
  - PassengerApps:: unregister\_application
- PasswdStrength:: get\_required\_strength
- Personalization::set
  - Personalization::get
- Postgresql:: create\_database
  - Postgresql:: create\_user
  - Postgresql:: delete\_database
  - Postgresql:: get\_restrictions
  - Postgresql:: grant\_all\_privileges
  - Postgresql:: rename\_database
  - Postgresql:: rename\_user
  - Postgresql:: rename\_user\_no\_password
  - Postgresql:: revoke\_all\_privileges
  - Postgresql:: set\_password
- Pushbullet:: send\_test\_message

		<ul style="list-style-type: none"> <li>• We introduced this return in WordPress 1.1.</li> </ul>		
autoupdate_core.major	<i>Boolean</i>	Whether the user enabled automatic updates for major releases.	<ul style="list-style-type: none"> <li>• true — Enabled.</li> <li>• false — Disabled.</li> </ul>	false
autoupdate_core.minor	<i>Boolean</i>	Whether the user enabled automatic updates for minor releases.	<ul style="list-style-type: none"> <li>• true — Enabled.</li> <li>• false — Disabled.</li> </ul>	true

- Quota:: `get_quota_info`
  - Resellers
    - Resellers:: `list_accounts`
  - ResourceUsage
    - ResourceUsage:: `get_usages`
  - Restore
    - Restore:: `directory_listing`
    - Restore:: `get_users`
    - Restore:: `query_file_info`
    - Restore:: `restore_file`
  - Session
    - Session:: `create_temp_user`
  - SiteTemplates
    - SiteTemplates:: `list_site_templates`
    - SiteTemplates:: `list_user_settings`
    - SiteTemplates:: `publish`
  - SpamAssassin
    - SpamAssassin:: `clear_spam_box`
    - SpamAssassin:: `get_symbolic_test_names`
    - SpamAssassin:: `get_user_preferences`
    - SpamAssassin:: `update_user_preference`
  - SSH
    - SSH:: `get_port`
  - SSL
    - SSL:: `add_autossl_excluded_domains`
    - SSL:: `can_ssl_redirect`
    - SSL:: `check_shared_cert`
    - SSL:: `delete_cert`
    - SSL:: `delete_csr`
    - SSL:: `delete_key`

available_version	<i>string</i>	<p>The latest WordPress instance's version.</p> <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;"> <p><b>Note</b> : We introduced this return in WordPress Instance Manager version 2.0</p> </div>	A WordPress version number.	4.9.6
created_on	<i>integer</i>	<p>The WordPress instance's installation date.</p> <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;"> <p><b>Note</b> : We introduced this return in WordPress Instance Manager version 2.0</p> </div>	A valid timestamp, in Unix Epoch time.	1528208546
current_version	<i>string</i>	<p>The WordPress instance's version.</p> <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;"> <p><b>Note</b> : This function retrieves this return's value directly from the WordPress instance.</p> </div>	A WordPress version number.	4.9.5

SSL:: delete\_ssl  
 SSL:: disable\_mail\_sni  
 SSL:: enable\_mail\_sni  
 SSL:: fetch\_best\_for\_domain  
 SSL:: fetch\_certificate\_for\_fqdns  
 SSL:: fetch\_key\_and\_certificate\_for\_certificate  
 SSL:: find\_certificates\_for\_key  
 SSL:: find\_csrs\_for\_key  
 SSL:: generate\_certificate  
 SSL:: generate\_certificate  
 SSL:: generate\_key  
 SSL:: get\_autossl\_excluded\_domains  
 SSL:: get\_autossl\_pending\_queue  
 SSL:: get\_autossl\_problems  
 SSL:: get\_certificate  
 SSL:: get\_certificate\_name  
 SSL:: install\_ssl  
 SSL:: installed\_hosts  
 SSL:: installed\_hosts  
 SSL:: is\_autossl\_check\_in\_progress  
 SSL:: is\_mail\_sni\_supported  
 SSL:: is\_sni\_supported  
 SSL:: list\_certs  
 SSL:: list\_csrs  
 SSL:: list\_keys  
 SSL:: list\_ssl\_items  
 SSL:: mail\_sni\_status

db_name	string	The WordPress instance's database name.	A database name.	example_wp2
db_prefix	string	The WordPress instance's database prefix.	A database table prefix.	wp
db_server	string	The WordPress instance's database server hostname.	A valid hostname.	localhost
db_type	string	The WordPress instance's database type.	mysql	mysql
db_username	string	The WordPress instance's database username.	A database username.	example_wp
domain	string	The WordPress instance's installation domain.	A domain the cPanel account owns.	example.com
full_path	string	The WordPress instance's full installation path.	An absolute filepath.	/home/example/public_html
homedir	string	The cPanel account's home directory.	An absolute filepath.	/home/example
id	string	The WordPress instance's unique identifier.	A valid string.	cPanel_Blogs_WordPress_X.0.1528208546
initial_install_version	string	The WordPress instance's version at installation.	A WordPress version number.	4.7.2
rel_path	string	The WordPress instance's installation path.	A valid filepath, relative to the domain's document root.	<div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <p><b>Note</b> : This function returns an empty value if the relative path is the document root.</p> </div>
site_url	string	The WordPress instance's home page URL.	A valid URL.	example.com/wordpress

tus

SSL:: rebuild\_mail  
\_snl\_config

SSL:: rebuildssldb

SSL:: remove\_aut  
ossl\_excluded\_do  
mains

SSL:: set\_autossl\_  
excluded\_domains

SSL:: set\_cert\_frie  
ndly\_name

SSL:: set\_csr\_frien  
dly\_name

SSL:: set\_key\_frie  
ndly\_name

SSL:: set\_primary  
\_ssl

SSL:: set\_ssl\_shar  
e

SSL:: show\_cert

SSL:: show\_csr

SSL:: show\_key

SSL:: start\_autossl\_  
\_check

SSL:: toggle\_ssl\_r  
edirects\_for\_doma  
ins

SSL:: upload\_cert

SSL:: upload\_key

▼ StatsBar

StatsBar:: get\_stat  
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

▼ SubDomain

SubDomain:: adds  
ubdomain

▼ Themes

Themes:: get\_the  
me\_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create\_fu  
ll\_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate\_user\_configuration

TwoFactorAuth:: get\_user\_configuration

TwoFactorAuth:: remove\_user\_configuration

TwoFactorAuth:: set\_user\_configuration

▼ UserManager

UserManager:: check\_account\_conflicts

UserManager:: create\_user

UserManager:: delete\_user

UserManager:: dismiss\_user

UserManager:: edit\_user

UserManager:: list\_users

UserManager:: lookup\_service\_account

UserManager:: lookup\_user

UserManager:: merge\_service\_account

UserManager:: unlink\_service\_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDepl



## oyment

VersionControlDep  
loyment:: **create**

VersionControlDep  
loyment:: **delete**

VersionControlDep  
loyment:: **retrieve**

### ▼ WebDisk

WebDisk:: **delete\_**  
**user**

WebDisk:: **set\_ho**  
**medir**

WebDisk:: **set\_pas**  
**sword**

WebDisk:: **set\_per**  
**missions**

### ▼ WebmailApps

WebmailApps:: **list**  
**webmailapps**

### ▼ WebVhosts

WebVhost:: **list\_do**  
**mains**

WebVhost:: **list\_ssl**  
**\_capable\_domains**

### ▼ WordPressBackup

WordPressBackup  
:: **any\_running**

WordPressBackup  
:: **cancel**

WordPressBackup  
:: **cleanup**

WordPressBackup  
:: **get\_available\_ba**  
**ckups**

WordPressBackup  
:: **is\_running**

WordPressBackup  
:: **start**

### ▼ WordPressInstance

#### Manager

WordPressInstanc  
eManager:: **cancel**  
**\_scan**

WordPressInstanc  
eManager:: **cleanu**  
**p\_scan**

WordPressInstanc  
eManager:: **chang**  
**e\_admin\_passwor**  
**d**

WordPressInstanc  
eManager:: **config**  
**ure\_autoupdate**

WordPressInstanc  
eManager:: **get\_ap**

i\_version

WordPressInstanceManager:: **get\_instance\_by\_id**

WordPressInstanceManager:: **get\_instances**

WordPressInstanceManager:: **get\_latest\_wordpress\_version\_from\_wordpress\_org**

WordPressInstanceManager:: **get\_scan\_results**

WordPressInstanceManager:: **is\_installable\_addon\_available**

WordPressInstanceManager:: **start\_scan**

▼ WordPressRestore

WordPressRestore:: **any\_running**

WordPressRestore:: **cleanup**

WordPressRestore:: **start**