

# UAPI Functions - UserManager::delete\_user

## Guide to UAPI

Return Data

Filter Output

Sort Output

Paginate Output

Output Columns

Calls from the WHM API

Custom UAPI Modules

Backup  
Backup::fullbackup

p\_to\_ftp

Backup::fullbackup  
p\_to\_homedir

Backup::fullbackup  
p\_to\_scp\_with\_key

Backup::fullbackup  
p\_to\_scp\_with\_password

Backup::list\_backups

### Bandwidth

Bandwidth::get\_enabled\_protocols

Bandwidth::get\_retention\_periods

Bandwidth::query

### Batch

Batch::strict

### Brand

Brand::read

### Branding

Branding::file

Branding::get\_applications

Branding::get\_application\_information

Branding::get\_available\_applications

Branding::get\_information\_for\_applications

## Description

This function deletes a Subaccount. This function returns only metadata if no other service accounts exist with the same username and domain.

- If one service account uses the same username and domain, the function returns the service account's information.
- If two or more service accounts use the same username and domain, the function returns a hypothetical Subaccount.

### Note:

A hypothetical Subaccount consists of two or more service accounts that use the same username and domain.

## Examples

### cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/UserManager/delete_user?username=example1&domain=example.com
```

### Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

## Function information

## About this module

The UserManager module modifies a cPanel account's Subaccounts.

## About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster
  - CacheBuster:: read
  - CacheBuster:: update
- Chkservd
  - Chkservd:: get\_exim\_ports
  - Chkservd:: get\_exim\_ports\_ssl
- Chrome
  - Chrome:: get\_dom
- Contactus
  - Contactus:: is\_enabled
- cPAddons
  - cPAddons:: get\_available\_addons
  - cPAddons:: get\_instance\_settings
  - cPAddons:: list\_addon\_instances
- cPGreyList
  - cPGreyList:: disable\_all\_domains
  - cPGreyList:: disable\_domains
  - cPGreyList:: enable\_all\_domains
  - cPGreyList:: enable\_domains
  - cPGreyList:: has\_greylisting\_enabled
  - cPGreyList:: list\_domains
- DAV
  - DAV:: disable\_shared\_global\_addressbook
  - DAV:: enable\_shared\_global\_addressbook
  - DAV:: get\_calendar\_contacts\_config
  - DAV:: has\_shared\_global\_addressbook
  - DAV:: is\_dav\_service\_enabled

## LiveAPI PHP Class

```

$cpnl = new
CPANEL(); // Connect
to cPanel - only do
this once.

// Deletes the
Subaccount.
$Usermanager =
$cpnl->uapi(
    'UserManager',
    'delete_user',
    array(
        'username'
=> 'example1',
        'domain'
=> 'example.com',
    )
);

```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

**Notes:**

- The
- Ur
- int
- us
- 20
- or
- 20
- ).'
- 20
- or
- 20
- ).

## Find a function

- UAPI Functions - DomainInfo::list\_domains — This function lists the cPanel account's domains.

DAV:: is\_horde\_enabled

#### ▼ DCV

DCV:: check\_domains\_via\_dns

DCV:: check\_domains\_via\_http

DCV:: ensure\_domains\_can\_pass\_dcv

#### ▼ DomainInfo

DomainInfo:: domains\_data

DomainInfo:: list\_domains

DomainInfo:: main\_domain\_builtin\_subdomain\_aliases

DomainInfo:: single\_domain\_data

#### ▼ DNS

DNS:: ensure\_domains\_reside\_only\_locally

DNS:: has\_local\_authority

#### ▼ DNSSEC

DNSSEC:: disable\_dnssec

DNSSEC:: enable\_dnssec

DNSSEC:: fetch\_dns\_records

DNSSEC:: set\_nsec3

DNSSEC:: unset\_nsec3

#### ▼ Email

Email:: account\_name

Email:: add\_auto\_responder

Email:: add\_domain\_forwarder

Email:: add\_forwarder

Email:: add\_list

Email:: add\_mailman\_delegates

Email:: add\_mx

Email:: add\_pop

Email:: add\_spam\_filter

### ▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# Deletes the  
Subaccount.  
my $Usermanager =  
$cpliveapi->uapi(  
    'UserManager',  
    'delete_user',  
    {  
        'username'  
=> 'example1',  
        'domain'  
=> 'example.com',  
    }  
);
```

#### Note:

For more information, read our [Guide to the LiveAPI System](#).

### ▼ cPanel Template Toolkit

```
<!-- Deletes the  
Subaccount. -->  
[%  
execute('UserManager'  
, 'delete_user',  
{ 'username' =>  
'example1', 'domain'  
=> 'example.com', } )  
%]
```

#### Note:

For more information, read our [Guide to Template Toolkit documentation](#).

- UAPI Functions - `Contac`  
`actus::is_enabled` — This function checks whether the account's contact option is enabled.
- UAPI Functions - `Chkser`  
`verd:get_exim_ports` — This function lists the ports on which Exim listens.
- UAPI Functions - `Chkser`  
`verd:get_exim_ports_ssl` — This function retrieves Exim's SSL port.

Email: browse\_mailbox  
Email: change\_mx  
Email: check\_fastmail  
Email: check\_pipe\_forwarder  
Email: delete\_auto\_responder  
Email: delete\_domain\_forwarder  
Email: delete\_filter  
Email: delete\_forwarder  
Email: delete\_held\_messages  
Email: delete\_list  
Email: delete\_mx  
Email: delete\_pop  
Email: disable\_filter  
Email: disable\_mailbox\_autocreate  
Email: disable\_spam\_assassin  
Email: disable\_spam\_autodelete  
Email: disable\_spam\_box  
Email: dispatch\_client\_settings  
Email: edit\_pop\_quota  
Email: enable\_filter  
Email: enable\_mailbox\_autocreate  
Email: enable\_spam\_assassin  
Email: enable\_spam\_box  
Email: fetch\_charmaps  
Email: fts\_rescan\_mailbox  
Email: generate\_mailman\_opt  
Email: get\_auto\_responder  
Email: get\_chase

## Command Line

```
uapi --user=username  
UserManager  
delete_user  
username=example1  
domain=example.com
```

### Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local  
/cpanel/bin/uapi
```

## Output (JSON)

```
{  
  "errors":null,  
  "messages":null,  
  "status":1,  
  "metadata":{  
  
  },  
  "data":{  
    "has_invite":0,  
  
    "has_siblings":0,  
  
    "username":"example1"  
  },  
  
  "invite_expiration":null,  
  
  "can_set_password":0,  
  
  "merge_candidates":[  
  
    {
```

ts

Email: get\_client\_settings

Email: get\_default\_email\_quota

Email: get\_default\_email\_quota\_mib

Email: get\_disk\_usage

Email: get\_filter

Email: get\_held\_message\_count

Email: get\_mailbox\_autocreate

Email: get\_mailman\_delegates

Email: get\_main\_account\_disk\_usage

Email: get\_main\_account\_disk\_usage\_bytes

Email: get\_max\_email\_quota

Email: get\_max\_email\_quota\_mib

Email: get\_pop\_quota

Email: get\_spam\_settings

Email: get\_webmail\_settings

Email: has\_delegated\_mailman\_lists

Email: has\_plaintext\_authentication

Email: hold\_outgoing

Email: is\_integer

Email: list\_autoresponders

Email: list\_default\_address

Email: list\_domain\_forwarders

Email: list\_filters

Email: list\_filters\_backups

Email: list\_forwarders

Email: list\_forward

"dismissed":0,

"phone\_number":null,

"avatar\_url":null,

"domain":"example.com",

"guid":"EXAMPLE1:EXAMPLE.COM:577D1AF6:E9897AA23C50E177FEEDB5168B240A3458334E6DC955653D3FBBB24538F1F807",

"type":"service",

"real\_name":null,

"sub\_account\_exists":0,

"full\_username":"example1@example.com",

"alternate\_email":null,

"can\_set\_quota":1,

"parent\_type":null,

"services":{

"webdisk":{

"enabled":0},

"ftp":{

"enabled":0},

"email":{

"enabled":1,

"quota":0},

},

ers\_backups  
Email: list\_lists  
Email: list\_mail\_domains  
Email: list\_mx  
Email: list\_pops  
Email: list\_pops\_with\_disk  
Email: list\_system\_filter\_info  
Email: passwd\_list  
Email: passwd\_pop  
Email: release\_outgoing  
Email: remove\_mailman\_delegates  
Email: reorder\_filters  
Email: set\_always\_accept  
Email: set\_default\_address  
Email: set\_list\_privacy\_options  
Email: stats\_db\_status  
Email: store\_filter  
Email: suspend\_incoming  
Email: suspend\_login  
Email: suspend\_outgoing  
Email: trace\_filter  
Email: unsuspend\_incoming  
Email: unsuspend\_login  
Email: unsuspend\_outgoing  
Email: verify\_password  
▼ EmailAuth  
EmailAuth: disable\_dkim  
EmailAuth: enable\_dkim  
EmailAuth: ensure\_dkim\_keys\_exist

```
"special":0,  
"can_delete":1,  
"can_set_password":1,  
"invite_expiration":null,  
"has_siblings":0,  
"username":"example1",  
"has_invite":0,  
"issues":[  
    ],  
"dismissed_merge_candidates":[  
    ],  
"has_expired_invite":0,  
"merge_candidates":[  
    ],  
"synced_password":0  
    },  
    {  
"issues":[  
    ],  
"synced_password":0,  
"merge_candidates":[  
    ],  
"has_expired_invite":0,  
"dismissed_merge_candidates":[
```

EmailAuth: fetch\_ dkim\_private\_keys

EmailAuth: install\_ dkim\_private\_key s

EmailAuth: install\_ spf\_records

EmailAuth: validat e\_current\_dkims

EmailAuth: validat e\_current\_ptrs

EmailAuth: validat e\_current\_spfs

ExternalAuthenticat ion

ExternalAuthenticat ion: add\_auth\_li nk

ExternalAuthenticat ion: configured\_ modules

ExternalAuthenticat ion: get\_authn\_lin ks

ExternalAuthenticat ion: has\_external\_ auth\_modules\_co nfigured

ExternalAuthenticat ion: remove\_auth n\_link

Features

Features: get\_feat ure\_metadata

Features: has\_fea ture

Features: list\_feat ures

Fileman

Fileman: autocom pletedir

Fileman: empty\_tr ash

Fileman: get\_file\_ content

Fileman: get\_file\_i nformation

Fileman: list\_files

Fileman: save\_file\_ content

Fileman: transcod e

Fileman: upload\_fi les

```
    ],  
    "invite_expiration":null,  
    "can_set_password":1,  
    "has_invite":0,  
    "username":"example1",  
    ,  
    "has_siblings":0,  
    "can_set_quota":1,  
    "alternate_email":null,  
    "can_delete":1,  
    "special":0,  
    "services":{  
      "email":{  
        },  
      "ftp":{  
        "quota":"42.00",  
        "homedir":"example1@example.com",  
        "enabled":1  
      },  
      "webdisk":{  
        "enabled":0  
      }  
    },  
    "parent_type":null,  
    "domain":"example.com",  
    ,  
    "avatar_url":null,
```

<ul style="list-style-type: none"> <li>▼ Ftp <ul style="list-style-type: none"> <li>Ftp:: add_ftp</li> <li>Ftp:: allows_anonymous_ftp</li> <li>Ftp:: allows_anonymous_ftp_incoming</li> <li>Ftp:: delete_ftp</li> <li>Ftp:: ftp_exists</li> <li>Ftp:: get_ftp_daemon_info</li> <li>Ftp:: get_port</li> <li>Ftp:: get_quota</li> <li>Ftp:: get_welcome_message</li> <li>Ftp:: kill_session</li> <li>Ftp:: list_ftp</li> <li>Ftp:: list_ftp_with_disk</li> <li>Ftp:: list_sessions</li> <li>Ftp:: passwd</li> <li>Ftp:: server_name</li> <li>Ftp:: set_anonymous_ftp</li> <li>Ftp:: set_anonymous_ftp_incoming</li> <li>Ftp:: set_homedir</li> <li>Ftp:: set_quota</li> <li>Ftp:: set_welcome_message</li> </ul> </li> <li>▼ Integration <ul style="list-style-type: none"> <li>Integration:: fetch_url</li> </ul> </li> <li>▼ KnownHosts <ul style="list-style-type: none"> <li>KnownHosts:: create</li> <li>KnownHosts:: delete</li> <li>KnownHosts:: update</li> <li>KnownHosts:: verify</li> </ul> </li> <li>▼ LangPHP <ul style="list-style-type: none"> <li>LangPHP:: php_get_domain_handler</li> <li>LangPHP:: php_get_impacted_domains</li> <li>LangPHP:: php_get_installed_version</li> </ul> </li> </ul>	<pre> "phone_number":null,  "dismissed":0,  "full_username":"example1@example.com",  "sub_account_exists":0,  "real_name":null,  "type":"service",  "guid":"EXAMPLE1:EXAMPLE.COM:577D1AF6:D7DC771B2C35109DC57FC7ED4257D7EEA4F4F06FDCB5203E5DB7BD1863C407B0"         },         {  "has_expired_invite":0,  "dismissed_merge_candidates":[          ],  "synced_password":0,  "merge_candidates":[          ],  "issues":[          ],  "has_siblings":0,  "username":"example1",  "has_invite":0,  "can_set_password":1,  "invite_expiration":null, </pre>
--	--



s

LangPHP:: php\_get\_system\_default\_version

LangPHP:: php\_get\_vhost\_versions

LangPHP:: php\_ini\_get\_user\_basic\_directives

LangPHP:: php\_ini\_get\_user\_content

LangPHP:: php\_ini\_get\_user\_paths

LangPHP:: php\_ini\_set\_user\_basic\_directives

LangPHP:: php\_ini\_set\_user\_content

LangPHP:: php\_set\_vhost\_versions

▼ LastLogin

LastLogin:: get\_last\_or\_current\_logged\_in\_ip

▼ Locale

Locale:: get\_attributes

▼ Mailboxes

Mailboxes:: expunge\_mailbox\_messages

Mailboxes:: expunge\_messages\_for\_mailbox\_guid

Mailboxes:: get\_mailbox\_status

Mailboxes:: has\_utf8\_mailbox\_names

Mailboxes:: set\_utf8\_mailbox\_names

▼ Market

Market:: cancel\_pending\_ssl\_certificate

Market:: create\_shopping\_cart

Market:: get\_all\_products

Market:: get\_certificate\_status\_details

Market:: get\_login\_url

Market:: get\_pending\_ssl\_certificates

```
"services":{
  "email":{
    },
  "webdisk":{
    "enabledigest":1,
    "homedir":"home/example/public_html/webdav",
    "perms":"rw",
    "enabled":1,
    "private":0
  },
  "ftp":{
    },
  "parent_type":null,
  "can_delete":1,
  "special":0,
  "can_set_quota":1,
  "alternate_email":null,
  "type":"service",
  "guid":"EXAMPLE1:EXAMPLE.COM:577D1AF6:C2F3566DCE80D6B1A3B25512E73C64BF6B7B4FA7E791A8E89DF091FE2242ECB6",
  "full_username":"example1@example.com",
  "sub_account_exists":0,
  "real_name":null,
```

Market:: get\_provider\_specific\_dcvc\_constraints  
Market:: get\_providers\_list  
Market:: get\_ssl\_certificate\_if\_available  
Market:: process\_ssl\_pending\_queue  
Market:: request\_ssl\_certificates  
Market:: set\_status\_of\_pending\_queue\_items  
Market:: set\_url\_after\_checkout  
Market:: validate\_login\_token  
▼ Mime  
Mime:: add\_handler  
Mime:: add\_hotlink  
Mime:: add\_mime  
Mime:: add\_redirect  
Mime:: delete\_handler  
Mime:: delete\_hotlink  
Mime:: delete\_mime  
Mime:: delete\_redirect  
Mime:: list\_handlers  
Mime:: list\_hotlinks  
Mime:: list\_mime  
Mime:: list\_redirects  
Mime:: redirect\_info  
▼ ModSecurity  
ModSecurity:: disable\_all\_domains  
ModSecurity:: disable\_domains  
ModSecurity:: enable\_all\_domains  
ModSecurity:: enable\_domains

```
"avatar_url":null,  
"phone_number":null,  
"dismissed":0,  
"domain":"example.com"  
},  
],  
"synced_password":0,  
"dismissed_merge_candidates":[  
],  
"has_expired_invite":0,  
"issues":[  
],  
"real_name":null,  
"full_username":"example1@example.com",  
"sub_account_exists":0,  
"guid":"EXAMPLE1:EXAMPLE.COM:577D1AF6:BA8D199D4AB1DF97B69EE912B9607B4EF2558AE0D743510F98062E1CC5ACD698",  
"type":"hypothetical",  
"domain":"example.com",  
"dismissed":0,  
"phone_number":null,  
"avatar_url":null,  
"can_delete":0,  
"special":0,  
"parent_type":null,  
"services":{
```

ModSecurity:: has  
\_modsecurity\_inst  
alled

ModSecurity:: list\_  
domains

▼ Mysql

Mysql:: add\_host

Mysql:: add\_host\_  
note

Mysql :: check\_dat  
abase

Mysql:: create\_dat  
abase

Mysql:: create\_use  
r

Mysql:: delete\_dat  
abase

Mysql:: delete\_hos  
t

Mysql:: delete\_use  
r

Mysql:: get\_host\_n  
otes

Mysql:: get\_privile  
ges\_on\_database

Mysql:: get\_restrict  
ions

Mysql:: get\_server  
\_information

Mysql:: locate\_ser  
ver

Mysql:: rename\_d  
atabase

Mysql:: rename\_us  
er

Mysql:: repair\_dat  
abase

Mysql:: revoke\_ac  
cess\_to\_database

Mysql:: set\_passw  
ord

Mysql:: set\_privile  
ges\_on\_database

▼ Notifications

Notifications:: get\_  
notifications\_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile\_rel  
ative\_uri

```
"email":{  
  "enabled":0  
  },  
  "ftp":{  
    "enabled":0  
    },  
    "webdisk":{  
      "enabled":0  
      }  
    },  
    "alternate_email":nul  
l,
```

- ▼ PassengerApps
  - PassengerApps:: disable\_application
  - PassengerApps:: edit\_application
  - PassengerApps:: enable\_application
  - PassengerApps:: ensure\_deps
  - PassengerApps:: list\_applications
  - PassengerApps:: register\_application
  - PassengerApps:: unregister\_application

```
"can_set_quota": 0
  }
}
```

**Note:**  
 Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

- ▼ PasswdStrength
  - PasswdStrength:: get\_required\_strength
- ▼ Personalization
  - Personalization::set
  - Personalization::get

## Parameters

- ▼ Postgresql
  - Postgresql:: create\_database
  - Postgresql:: create\_user
  - Postgresql:: delete\_database
  - Postgresql:: get\_restrictions
  - Postgresql:: grant\_all\_privileges
  - Postgresql:: rename\_database
  - Postgresql:: rename\_user
  - Postgresql:: rename\_user\_no\_password
  - Postgresql:: revoke\_all\_privileges
  - Postgresql:: set\_password

Parameter	Type	Description	Possible values	Example
username	string	<b>Required</b> The Subaccount's username.	A username that meets the account name limitations. <ul style="list-style-type: none"> <li>• Length — 64 characters</li> <li>• Character set — a-z, A-Z, 0-9, dot (.), hyphen (-), underscore (_)</li> </ul>	example
domain	string	<b>Required</b> The Subaccount's associated domain.	A domain that the cPanel account owns. <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p><b>Note:</b> This value does <b>not</b> include the domain name.</p> </div>	example.com

- ▼ Pushbullet
  - Pushbullet:: send\_test\_message
- ▼ Quota
  - Quota:: get\_quota\_info

- Resellers:: list\_accounts
- ResourceUsage:: get\_usages
- Restore:: directory\_listing
  - Restore:: get\_users
  - Restore:: query\_file\_info
  - Restore:: restore\_file
- Session:: create\_temp\_user
- SiteTemplates:: list\_site\_templates
  - SiteTemplates:: list\_user\_settings
  - SiteTemplates:: publish
- SpamAssassin:: clear\_spam\_box
  - SpamAssassin:: get\_symbolic\_test\_names
  - SpamAssassin:: get\_user\_preferences
  - SpamAssassin:: update\_user\_preference
- SSH:: get\_port
- SSL:: add\_autossl\_excluded\_domains
  - SSL:: can\_ssl\_redirect
  - SSL:: check\_shared\_cert
  - SSL:: delete\_cert
  - SSL:: delete\_csr
  - SSL:: delete\_key
  - SSL:: delete\_ssl
  - SSL:: disable\_mail\_sni

## Returns

**Note:**  
This function returns only metadata if the specified username and domain do **not** match any service accounts or hypothetical Subaccounts.

Return	Type	Description	Possible values	Example
alternate_email	string	An alternate email address for the account's user.	A valid email address.	user@example.com
avatar_url	string	The user's account profile photo.	A valid HTTPS URL that points to an image file.	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li><a href="#">Click to view...</a></li> </ul> </li> <li>https://img.example.com/avatars/example.jpg</li> </ul>
can_delete	Boolean	Whether the cPanel account user can delete the account.	<ul style="list-style-type: none"> <li>• 1 — Can delete.</li> <li>• 0 — <b>Cannot</b> delete.</li> </ul>	0
can_set_password	Boolean	Whether the cPanel account user can change the account's password.	<ul style="list-style-type: none"> <li>• 1 — Can change password.</li> <li>• 0 — <b>Cannot</b> change password.</li> </ul> <div style="border: 1px solid #f0e68c; padding: 5px; margin-top: 10px;"> <p><b>Note:</b> The function returns 0 for accounts that inherit their password from the cPanel account.</p> </div>	1

SSL:: enable\_mail\_sni  
 SSL:: fetch\_best\_for\_domain  
 SSL:: fetch\_cert\_info  
 SSL:: fetch\_certificates\_for\_fqdns  
 SSL:: fetch\_key\_and\_bundle\_for\_certificate  
 SSL:: find\_certificates\_for\_key  
 SSL:: find\_csrs\_for\_key  
 SSL:: generate\_certificate  
 SSL:: generate\_certificate  
 SSL:: generate\_key  
 SSL:: get\_autossl\_excluded\_domains  
 SSL:: get\_autossl\_pending\_queue  
 SSL:: get\_autossl\_problems  
 SSL:: get\_bundle  
 SSL:: get\_cn\_name  
 SSL:: install\_ssl  
 SSL:: installed\_hosts  
 SSL:: installed\_hosts  
 SSL:: is\_autossl\_check\_in\_progress  
 SSL:: is\_mail\_sni\_supported  
 SSL:: is\_sni\_supported  
 SSL:: list\_certs  
 SSL:: list\_csrs  
 SSL:: list\_keys  
 SSL:: list\_ssl\_items  
 SSL:: mail\_sni\_status  
 SSL:: rebuild\_mail\_sni\_config

can_set_quota	<i>Boolean</i>	Whether the cPanel account user can change the account's disk usage quota.	<ul style="list-style-type: none"> <li>1 — Can change quota.</li> <li>0 — <b>Cannot</b> change quota.</li> </ul>	0
dismissed	<i>Boolean</i>	Whether the cPanel account user dismissed the merge prompt for the service account.	<ul style="list-style-type: none"> <li>1 — Dismissed prompt.</li> <li>0 — Did <b>not</b> dismiss prompt.</li> </ul> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p><b>Note</b> : <b>Only</b> service accounts return this value.</p> </div>	1
dismissed_merge_candidates	<i>array of hashes</i>	An array of hashes that represent the service accounts that the user dismissed the merge prompt for.	<p>This array will always return empty.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p><b>Note</b> : We reserved this return for future use.</p> </div>	
domain	<i>string</i>	The account user's associated domain.	A domain that the cPanel account owns.	example.com
full_username	<i>string</i>	The account's username and domain name.	A valid username, the @ character, and the associated domain.	user@example.com

SSL:: rebuildssldb

SSL:: remove\_autossl\_excluded\_domains

SSL:: set\_autossl\_excluded\_domains

SSL:: set\_cert\_friendly\_name

SSL:: set\_csrfriendly\_name

SSL:: set\_key\_friendly\_name

SSL:: set\_primary\_ssl

SSL:: set\_ssl\_share

SSL:: show\_cert

SSL:: show\_csrf

SSL:: show\_key

SSL:: start\_autossl\_check

SSL:: toggle\_ssl\_redirects\_for\_domains

SSL:: upload\_cert

SSL:: upload\_key

▼ StatsBar

StatsBar:: get\_stats

▼ Styles

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

▼ SubDomain

SubDomain:: add\_subdomain

▼ Themes

Themes:: get\_theme\_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create\_full\_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

guid	string	The account unique identifier.	The system-assigned unique value.	<p>▼ <a href="#">Click to view...</a></p> <p>N4641:EXAMPLE.COM:564CC8A7:A82EA007D8348AC631C0170F9418EC1DEB0D164CC5A722A87C55EF5DD2AD98D4</p>
has_expired_invite	Boolean	Whether the Subaccount owns an expired invitation.	<ul style="list-style-type: none"> <li>1 — Owns an expired invitation.</li> <li>0 — Does <b>not</b> own an expired invitation.</li> </ul>	0
has_invite	Boolean	Whether the Subaccount owns an active invitation.	<ul style="list-style-type: none"> <li>1 — Owns an invitation.</li> <li>0 — Does <b>not</b> own an invitation.</li> </ul>	0

**Note**  
: We introduced this return in cPanel & WHM version 60.

**Note**  
: We introduced this return in cPanel & WHM version 60.

- TwoFactorAuth
  - TwoFactorAuth:: generate\_user\_configuration
  - TwoFactorAuth:: get\_user\_configuration
  - TwoFactorAuth:: remove\_user\_configuration
  - TwoFactorAuth:: set\_user\_configuration
- UserManager
  - UserManager:: check\_account\_conflicts
  - UserManager:: create\_user
  - UserManager:: delete\_user
  - UserManager:: dismiss\_user
  - UserManager:: edit\_user
  - UserManager:: list\_users
  - UserManager:: lookup\_service\_account
  - UserManager:: lookup\_user
  - UserManager:: merge\_service\_account
  - UserManager:: unlink\_service\_account
- UserTasks
  - UserTasks:: delete
  - UserTasks:: retrieve
- VersionControl
  - VersionControl:: create
  - VersionControl:: delete
  - VersionControl:: retrieve
  - VersionControl:: update
- VersionControlDeployment
  - VersionControlDeployment:: create

has_siblings	<i>Boolean</i>	Whether the service account shares a full_username value with another service account.	<ul style="list-style-type: none"> <li>• 1 — Shares.</li> <li>• 0 — Does not share.</li> </ul>	0
invite_expiration	<i>integer</i>	<p>The time at which the new Subaccount invitation will expire.</p> <p>If the account does not own an active invitation, this value returns null.</p> <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;"> <p><b>Note</b> : We introduced this return in cPanel &amp; WHM version 60.</p> </div>	<ul style="list-style-type: none"> <li>• A valid Unix epoch time.</li> <li>• null</li> </ul>	1466258282
issues	<i>array</i>	Information about any issues or problems with the account.	This array includes the type, area, service, message, used, and limit returns.	
type	<i>string</i>	<p>The type of issue.</p> <p>The function returns this value in the issues array.</p>	<ul style="list-style-type: none"> <li>• error</li> <li>• warning</li> <li>• info</li> </ul>	info
area	<i>string</i>	The affected section of cPanel & WHM.	quota	quota
service	<i>string</i>	<p>The affected service.</p> <p>The function returns this value in the issues array.</p>	<ul style="list-style-type: none"> <li>• email</li> <li>• ftp</li> <li>• webdisk</li> </ul>	email



- VersionControlDeployment:: **delete**
- VersionControlDeployment:: **retrieve**
- WebDisk:: **delete\_user**
  - WebDisk:: **set\_homedir**
  - WebDisk:: **set\_password**
  - WebDisk:: **set\_permissions**
- WebmailApps:: **list\_webmailapps**
- WebVhosts:: **list\_domains**
  - WebVhosts:: **list\_ssl\_capable\_domains**
- WordPressBackup:: **any\_running**
  - WordPressBackup:: **cancel**
  - WordPressBackup:: **cleanup**
  - WordPressBackup:: **get\_available\_backups**
  - WordPressBackup:: **is\_running**
  - WordPressBackup:: **start**
- WordPressInstanceManager:: **cancel\_scan**
  - WordPressInstanceManager:: **cleanup\_scan**
  - WordPressInstanceManager:: **change\_admin\_password**
  - WordPressInstanceManager:: **configure\_autoupdate**
  - WordPressInstanceManager:: **get\_api\_version**
  - WordPressInstanceManager:: **get\_in**

message	string	The description of the issue.  The function returns this value in the issues array.	A string value.	Your account is over quota.
used	integer	The number of Megabytes (MB) that the account currently uses.  The function returns this value in the issues array.	A positive integer.	2000
limit	integer	The set quota Megabyte (MB) limit for the affected account.  The function returns this value in the issues array.	A positive integer.	1500
merge_candidates	array	The service accounts that the system could merge for this account.  <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;"> <p><b>Note</b> : You can find descriptions for this array's returns within this table.</p> </div>	This array includes the alternate_email, avatar_url, can_delete, can_set_password, can_set_quota, dismissed, domain, full_username, guid, has_siblings, issues, merge_candidates, parent_type, phone_number, real_name, services, special, sub_account_exists, synced_password, type, and username returns.	

stance\_by\_id

WordPressInstanceManager::get\_instances

WordPressInstanceManager::get\_latest\_wordpress\_version\_from\_wordpress\_org

WordPressInstanceManager::get\_scan\_results

WordPressInstanceManager::is\_installeable\_addon\_available

WordPressInstanceManager::start\_scan

WordPressRestore

WordPressRestore::any\_running

WordPressRestore::cleanup

WordPressRestore::start

parent_type	string	The type of account that could own the service account.	<ul style="list-style-type: none"><li>sub — An account.</li><li>hypothetical — A hypothetical account that does <b>not</b> yet exist, but that the user could create as part of a merge.</li><li>null — <b>Not</b> a merge candidate.</li></ul>	hypothetical
phone_number	string	The account user's phone number.	A valid phone number that conforms to ITU-T's <a href="#">E.164</a> -recommended standard for the representation of telephone numbers.	+15551234567
real_name	string	The name of the account's user.	<ul style="list-style-type: none"><li>A first name, a last name, or a first name and last name.</li><li>An empty string.</li></ul>	John Doe
services	hash	Information about the account's access to email, FTP, and Web Disk.	This hash includes the email, ftp, and webdisk returns.	
email	hash	Information that indicates the account's email status.  The function returns this value in the services hash.	This hash includes the enabled and quota returns.	
enabled	Boolean	Whether the account can access Webmail, POP, and IMAP services.  The function returns this value in the email hash.	<ul style="list-style-type: none"><li>1 — Can access.</li><li>0 — <b>Cannot</b> access.</li></ul>	1

quota	<i>string</i>	<p>The account's email disk space quota.</p> <p>The function returns this value in the <code>email hash</code>.</p>	<ul style="list-style-type: none"> <li>A positive integer between 1 and 999999 that represents the maximum disk space that the account may use, in Megabytes (MB).</li> <li>0 — Unlimited.</li> </ul>	100
ftp	<i>hash</i>	<p>Information about the account's FTP status.</p> <p>The function returns this value in the <code>services hash</code>.</p>	<p>This hash includes the <code>enabled</code>, <code>quota</code>, and <code>homedir</code> returns.</p>	
enabled	<i>Boolean</i>	<p>Whether the account can access FTP.</p> <p>The function returns this value in the <code>ftp hash</code>.</p>	<ul style="list-style-type: none"> <li>1 — Can access.</li> <li>0 — <b>Cannot</b> access.</li> </ul>	0
quota	<i>integer</i>	<p>The account's FTP disk space quota.</p> <p>The function returns this value in the <code>ftp hash</code>.</p>	<ul style="list-style-type: none"> <li>An integer that represents the account's maximum FTP disk usage, in Megabytes (MB).</li> <li>0 — Unlimited.</li> </ul>	100
homedir	<i>string</i>	<p>The account's FTP home directory.</p> <p>The function returns this value in the <code>ftp hash</code>.</p>	<p>A valid path, relative to the cPanel account's home directory.</p>	/account
webdisk	<i>hash</i>	<p>Information about the account's Web Disk status.</p> <p>The function returns this value in the <code>services hash</code>.</p>	<p>This hash includes the <code>enabled</code>, <code>homedir</code>, <code>perms</code>, and <code>private</code> returns.</p>	

enabled	<i>Boolean</i>	<p>Whether the account can access Web Disk.</p> <p>The function returns this value in the <code>web disk</code> hash.</p>	<ul style="list-style-type: none"> <li>• 1 — Can access.</li> <li>• 0 — <b>Cannot</b> access.</li> </ul>	0
home_dir	<i>string</i>	<p>The account's Web Disk directory.</p> <p>The function returns this value in the <code>web disk</code> hash.</p>	A valid path, relative to the cPanel account's home directory.	/bob
perms	<i>string</i>	<p>Whether to grant write permissions to the account.</p> <p>The function returns this value in the <code>web disk</code> hash.</p>	<ul style="list-style-type: none"> <li>• <code>ro</code> — Read-only permissions.</li> <li>• <code>rw</code> — Read and write permissions.</li> </ul>	<code>rw</code>
private	<i>Boolean</i>	<p>Whether to set the Web Disk directory's permissions to public or private.</p> <p>The function returns this value in the <code>web disk</code> hash.</p>	<ul style="list-style-type: none"> <li>• 1 — Private (0700).</li> <li>• 0 — Public (0755).</li> </ul>	0
special	<i>Boolean</i>	<p>Whether the account is a system-created special account that the user <b>cannot</b> remove.</p>	<ul style="list-style-type: none"> <li>• 1 — A special account.</li> <li>• 0 — <b>Not</b> a special account.</li> </ul>	1

sub_account_exists	<i>Boolean</i>	Whether an account exists with the same username.	<ul style="list-style-type: none"> <li>• 1 — Exists.</li> <li>• 0 — Does not exist.</li> </ul> <div data-bbox="891 268 1029 831" style="border: 1px solid black; padding: 5px;"> <p><b>Note</b> : The function returns a null value if the account is <b>not</b> a service account.</p> </div>	0
synced_password	<i>Boolean</i>	Whether the user has synchronized the passwords for each of the account's service accounts.	<ul style="list-style-type: none"> <li>• 1 — Synchronized.</li> <li>• 0 — <b>Not</b> synchronized.</li> </ul> <div data-bbox="891 1058 1029 1591" style="border: 1px solid black; padding: 5px;"> <p><b>Note</b> : The function returns a null value if the account is <b>not</b> a Sub account.</p> </div>	0

type	<i>string</i>	The type of account.	<ul style="list-style-type: none"> <li>• hypothetical — A hypothetical account that does not exist, but that the user could create as part of a merge.</li> <li>• service — A service account.</li> </ul>	sub
username	<i>string</i>	The account username.	<p>A username that meets the account name limitations.</p> <ul style="list-style-type: none"> <li>• Length — 64 characters</li> <li>• Characters — a-z, A-Z, 0-9, dot (.), hyphen (-), underscore (_)</li> </ul> <div data-bbox="891 1020 1029 1446" style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p><b>Note</b> : This value does <b>not</b> include the domain name.</p> </div>	example