

# UAPI Functions - Email::remove\_mailman\_delegates

## Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup  
Backup::  
fullbacku

p\_to\_ftp

Backup:: fullbacku  
p\_to\_homedir

Backup:: fullbacku  
p\_to\_scp\_with\_key

Backup:: fullbacku  
p\_to\_scp\_with\_password

Backup:: list\_backups

### Bandwidth

Bandwidth:: get\_enabled\_protocols

Bandwidth:: get\_retention\_periods

Bandwidth:: query

### Batch

Batch:: strict

### Brand

Brand:: read

### Branding

Branding:: file

Branding:: get\_applications

Branding:: get\_application\_information

Branding:: get\_available\_applications

Branding:: get\_information\_for\_applications

## Description

This function removes an account's mailing list administrative privileges.

## Examples

### ▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/Email/remove_mailman_delegates?list=mylist&delegates=user%40example.com%2Cadmin%40example.com
```

#### Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

## Function information

## About this module

The Email module modifies cPanel email account settings.

## About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster
  - CacheBuster:: read
  - CacheBuster:: update
- Chkserverd
  - Chkserverd:: get\_exim\_ports
  - Chkserverd:: get\_exim\_ports\_ssl
- Chrome
  - Chrome:: get\_dom
- Contactus
  - Contactus:: is\_enabled
- cPAddons
  - cPAddons:: get\_available\_addons
  - cPAddons:: get\_instance\_settings
  - cPAddons:: list\_addon\_instances
- cPGreyList
  - cPGreyList:: disable\_all\_domains
  - cPGreyList:: disable\_domains
  - cPGreyList:: enable\_all\_domains
  - cPGreyList:: enable\_domains
  - cPGreyList:: has\_greylisting\_enabled
  - cPGreyList:: list\_domains
- DAV
  - DAV:: disable\_shared\_global\_addressbook
  - DAV:: enable\_shared\_global\_addressbook
  - DAV:: get\_calendar\_contacts\_config
  - DAV:: has\_shared\_global\_addressbook
  - DAV:: is\_dav\_service\_enabled

## LiveAPI PHP Class

```

$cpanel = new
CPANEL(); // Connect
to cPanel - only do
this once.

// Remove
user@example.com and
admin@example.com as
admins.
$delete_admin =
$cpanel->uapi(
    'Email',
    'remove_mailman_deleg
ates',
    array(
        'list'
=> 'mylist',
        'delegate'
=>
'user@example.com,adm
in@example.com',
    )
);

```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

**Notes:**

- Th  
Fe
- Ur  
mu  
us  
20  
or  
20  
)`  
20  
or  
20  
)

## Find a function

The Mailbox module manages email messages.

- UAPI Functions - Email::edit\_pop\_quota — This function changes an email address's quota.

- DAV:: is\_horde\_enabled
- ▼ DCV
  - DCV:: check\_domains\_via\_dns
  - DCV:: check\_domains\_via\_http
  - DCV:: ensure\_domains\_can\_pass\_dcv
- ▼ DomainInfo
  - DomainInfo:: domains\_data
  - DomainInfo:: list\_domains
  - DomainInfo:: main\_domain\_builtin\_subdomain\_aliases
  - DomainInfo:: single\_domain\_data
- ▼ DNS
  - DNS:: ensure\_domains\_reside\_only\_locally
  - DNS:: has\_local\_authority
- ▼ DNSSEC
  - DNSSEC:: disable\_dnssec
  - DNSSEC:: enable\_dnssec
  - DNSSEC:: fetch\_dns\_records
  - DNSSEC:: set\_nsec3
  - DNSSEC:: unset\_nsec3
- ▼ Email
  - Email:: account\_name
  - Email:: add\_auto\_responder
  - Email:: add\_domain\_forwarder
  - Email:: add\_forwarder
  - Email:: add\_list
  - Email:: add\_mailman\_delegates
  - Email:: add\_mx
  - Email:: add\_pop
  - Email:: add\_spam\_filter

## ▼ LiveAPI Perl Module

```

my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Remove
user@example.com and
admin@example.com as
admins.
my $delete_admin =
$cpliveapi->uapi(
'Email',
'remove_mailman_deleg
ates',
{
'list'
=> 'mylist',
'delegate'
=>
'user@example.com,adm
in@example.com',
}
);

```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

- UAPI Functions - SpamAssassin::get\_user\_preferences — This function lists the Apache SpamAssassin™ settings for the account.
- UAPI Functions - SpamAssassin::clear\_spam\_box — This function clears the spam box of all its contents for all email accounts.

Email: browse\_mailbox  
Email: change\_mx  
Email: check\_fast\_mail  
Email: check\_pipe\_forwarder  
Email: delete\_auto\_responder  
Email: delete\_domain\_forwarder  
Email: delete\_filter  
Email: delete\_forwarder  
Email: delete\_help\_messages  
Email: delete\_list  
Email: delete\_mx  
Email: delete\_pop  
Email: disable\_filter  
Email: disable\_mailbox\_autocreate  
Email: disable\_spam\_assassin  
Email: disable\_spam\_autodelete  
Email: disable\_spam\_box  
Email: dispatch\_client\_settings  
Email: edit\_pop\_quota  
Email: enable\_filter  
Email: enable\_mailbox\_autocreate  
Email: enable\_spam\_assassin  
Email: enable\_spam\_box  
Email: fetch\_charmaps  
Email: fts\_rescan\_mailbox  
Email: generate\_mailman\_opt  
Email: get\_auto\_responder  
Email: get\_chase

## ▼ cPanel Template Toolkit

```
<!-- Remove user@example.com and admin@example.com as admins. -->[% execute('Email', 'remove_mailman_delegates', { 'list' => 'mylist', 'delegate' => 'user@example.com,admin@example.com', }) %]
```

### Note:

For more information, read our [Guide to Template Toolkit documentation](#).

## ▼ Command Line

```
uapi --user=username Email remove_mailman_delegates list=mylist delegates=user%40example.com%2Cadmin%40example.com
```

### Notes:

- You **must** [URI-encode](#) values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI documentation](#) or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local/cpanel/bin/uapi
```

- UAPI Functions - SpamAssassin::update\_user\_preference — This function sets the Apache SpamAssassin™ settings for the account.

ts

Email: get\_client\_settings

Email: get\_default\_email\_quota

Email: get\_default\_email\_quota\_mib

Email: get\_disk\_usage

Email: get\_filter

Email: get\_held\_message\_count

Email: get\_mailbox\_autocreate

Email: get\_mailman\_delegates

Email: get\_main\_account\_disk\_usage

Email: get\_main\_account\_disk\_usage\_bytes

Email: get\_max\_email\_quota

Email: get\_max\_email\_quota\_mib

Email: get\_pop\_quota

Email: get\_spam\_settings

Email: get\_webmail\_settings

Email: has\_delegated\_mailman\_lists

Email: has\_plaint\_authentication

Email: hold\_outgoing

Email: is\_integer

Email: list\_autoresponders

Email: list\_default\_address

Email: list\_domain\_forwarders

Email: list\_filters

Email: list\_filters\_backups

Email: list\_forwarders

Email: list\_forward

### Output (JSON)

```

{
  "messages": null,
  "errors": null,
  "status": 1,
  "data": {
    "delegates": [
      "secondadmin@example.com",
    ],
    "metadata": {
      "transformed": 1
    }
  }
}

```

**Note:**  
 Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

## Parameters

Parameter	Type	Description	Possible values	Example
list	string	<b>Required</b> The mailing list.	The name of a Mailman mailing list on the cPanel account.	mylist
delegates	string	<b>Required</b> A list of the administrators to remove.	One or more email addresses.  <b>Note</b> : Separate multiple email addresses with commas.	user@example.com, admin@example.com

ers\_backups

Email:: list\_lists

Email:: list\_mail\_domains

Email:: list\_mx

Email:: list\_pops

Email:: list\_pops\_with\_disk

Email:: list\_system\_filter\_info

Email:: passwd\_list

Email:: passwd\_pop

Email:: release\_outgoing

Email:: remove\_mailman\_delegates

Email:: reorder\_filters

Email:: set\_always\_accept

Email:: set\_default\_address

Email:: set\_list\_privacy\_options

Email:: stats\_db\_status

Email:: store\_filter

Email:: suspend\_incoming

Email:: suspend\_login

Email:: suspend\_outgoing

Email:: trace\_filter

Email:: unsuspend\_incoming

Email:: unsuspend\_login

Email:: unsuspend\_outgoing

Email:: verify\_password

#### ▼ EmailAuth

EmailAuth:: disable\_dkim

EmailAuth:: enable\_dkim

EmailAuth:: ensure\_dkim\_keys\_exist

## Returns

Return	Type	Description	Possible values	Example
delegates	<i>array</i>	An array of the mailing list's administrators.	One or more email addresses.	secondadmin@example.com

EmailAuth:: fetch\_  
dkim\_private\_keys

EmailAuth:: install  
\_dkim\_private\_key  
s

EmailAuth:: install  
\_spf\_records

EmailAuth:: validat  
e\_current\_dkims

EmailAuth:: validat  
e\_current\_ptrs

EmailAuth:: validat  
e\_current\_spfs

ExternalAuthenticat  
ion

ExternalAuthentic  
ation:: add\_auth\_li  
nk

ExternalAuthentic  
ation:: configured\_  
modules

ExternalAuthentic  
ation:: get\_auth\_lin  
ks

ExternalAuthentic  
ation:: has\_external  
\_auth\_modules\_co  
nfigured

ExternalAuthentic  
ation:: remove\_auth  
n\_link

Features

Features:: get\_feat  
ure\_metadata

Features:: has\_fea  
ture

Features:: list\_feat  
ures

Fileman

Fileman:: autocom  
pletedir

Fileman:: empty\_tr  
ash

Fileman:: get\_file\_  
content

Fileman:: get\_file\_i  
nformation

Fileman:: list\_files

Fileman:: save\_file  
\_content

Fileman:: transcod  
e

Fileman:: upload\_fi  
les

▼ Ftp

Ftp:: add\_ftp

Ftp:: allows\_anonymous\_ftp

Ftp:: allows\_anonymous\_ftp\_incoming

Ftp:: delete\_ftp

Ftp:: ftp\_exists

Ftp:: get\_ftp\_daemon\_info

Ftp:: get\_port

Ftp:: get\_quota

Ftp:: get\_welcome\_message

Ftp:: kill\_session

Ftp:: list\_ftp

Ftp:: list\_ftp\_with\_disk

Ftp:: list\_sessions

Ftp:: passwd

Ftp:: server\_name

Ftp:: set\_anonymous\_ftp

Ftp:: set\_anonymous\_ftp\_incoming

Ftp:: set\_homedir

Ftp:: set\_quota

Ftp:: set\_welcome\_message

▼ Integration

Integration:: fetch\_url

▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

▼ LangPHP

LangPHP:: php\_get\_domain\_handler

LangPHP:: php\_get\_impacted\_domains

LangPHP:: php\_get\_installed\_version



s

LangPHP:: php\_get\_system\_default\_version

LangPHP:: php\_get\_vhost\_versions

LangPHP:: php\_ini\_get\_user\_basic\_directives

LangPHP:: php\_ini\_get\_user\_content

LangPHP:: php\_ini\_get\_user\_paths

LangPHP:: php\_ini\_set\_user\_basic\_directives

LangPHP:: php\_ini\_set\_user\_content

LangPHP:: php\_set\_vhost\_versions

▼ LastLogin

LastLogin:: get\_last\_or\_current\_logged\_in\_ip

▼ Locale

Locale:: get\_attributes

▼ Mailboxes

Mailboxes:: expunge\_mailbox\_messages

Mailboxes:: expunge\_messages\_for\_mailbox\_guid

Mailboxes:: get\_mailbox\_status

Mailboxes:: has\_utf8\_mailbox\_names

Mailboxes:: set\_utf8\_mailbox\_names

▼ Market

Market:: cancel\_pending\_ssl\_certificate

Market:: create\_shopping\_cart

Market:: get\_all\_products

Market:: get\_certificate\_status\_details

Market:: get\_login\_url

Market:: get\_pending\_ssl\_certificates

Market:: get\_provi  
der\_specific\_dcv\_  
constraints

Market:: get\_provi  
ders\_list

Market:: get\_ssl\_c  
ertificate\_if\_availa  
ble

Market:: process\_s  
sl\_pending\_queue

Market:: request\_s  
sl\_certificates

Market:: set\_status  
\_of\_pending\_queu  
e\_items

Market:: set\_url\_af  
ter\_checkout

Market:: validate\_l  
ogin\_token

#### ▼ Mime

Mime:: add\_handl  
er

Mime:: add\_hotlink

Mime:: add\_mime

Mime:: add\_redire  
ct

Mime:: delete\_han  
dler

Mime:: delete\_hotli  
nk

Mime:: delete\_mim  
e

Mime:: delete\_redi  
rect

Mime:: list\_handler  
s

Mime:: list\_hotlinks

Mime:: list\_mime

Mime:: list\_redirect  
s

Mime:: redirect\_inf  
o

#### ▼ ModSecurity

ModSecurity:: disa  
ble\_all\_domains

ModSecurity:: disa  
ble\_domains

ModSecurity:: ena  
ble\_all\_domains

ModSecurity:: ena  
ble\_domains

ModSecurity:: has  
\_modsecurity\_inst  
alled

ModSecurity:: list\_  
domains

▼ Mysql

Mysql:: add\_host

Mysql:: add\_host\_  
note

Mysql :: check\_dat  
abase

Mysql:: create\_dat  
abase

Mysql:: create\_use  
r

Mysql:: delete\_dat  
abase

Mysql:: delete\_hos  
t

Mysql:: delete\_use  
r

Mysql:: get\_host\_n  
otes

Mysql:: get\_privile  
ges\_on\_database

Mysql:: get\_restrict  
ions

Mysql:: get\_server  
\_information

Mysql:: locate\_ser  
ver

Mysql:: rename\_d  
atabase

Mysql:: rename\_us  
er

Mysql:: repair\_dat  
abase

Mysql:: revoke\_ac  
cess\_to\_database

Mysql:: set\_passw  
ord

Mysql:: set\_privile  
ges\_on\_database

▼ Notifications

Notifications:: get\_  
notifications\_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile\_rel  
ative\_uri

- ▼ PassengerApps
  - PassengerApps:: disable\_application
  - PassengerApps:: edit\_application
  - PassengerApps:: enable\_application
  - PassengerApps:: ensure\_deps
  - PassengerApps:: list\_applications
  - PassengerApps:: register\_application
  - PassengerApps:: unregister\_application
- ▼ PasswdStrength
  - PasswdStrength:: get\_required\_strength
- ▼ Personalization
  - Personalization::set
  - Personalization::get
- ▼ Postgresql
  - Postgresql:: create\_database
  - Postgresql:: create\_user
  - Postgresql:: delete\_database
  - Postgresql:: get\_restrictions
  - Postgresql:: grant\_all\_privileges
  - Postgresql:: rename\_database
  - Postgresql:: rename\_user
  - Postgresql:: rename\_user\_no\_password
  - Postgresql:: revoke\_all\_privileges
  - Postgresql:: set\_password
- ▼ Pushbullet
  - Pushbullet:: send\_test\_message
- ▼ Quota
  - Quota:: get\_quota\_info

- ▼ Resellers
  - Resellers:: list\_accounts
- ▼ ResourceUsage
  - ResourceUsage:: get\_usages
- ▼ Restore
  - Restore:: directory\_listing
  - Restore:: get\_users
  - Restore:: query\_file\_info
  - Restore:: restore\_file
- ▼ Session
  - Session:: create\_temp\_user
- ▼ SiteTemplates
  - SiteTemplates:: list\_site\_templates
  - SiteTemplates:: list\_user\_settings
  - SiteTemplates:: publish
- ▼ SpamAssassin
  - SpamAssassin :: clear\_spam\_box
  - SpamAssassin:: get\_symbolic\_test\_names
  - SpamAssassin:: get\_user\_preferences
  - SpamAssassin:: update\_user\_preference
- ▼ SSH
  - SSH:: get\_port
- ▼ SSL
  - SSL:: add\_autossl\_excluded\_domains
  - SSL:: can\_ssl\_redirect
  - SSL:: check\_shared\_cert
  - SSL:: delete\_cert
  - SSL:: delete\_csr
  - SSL:: delete\_key
  - SSL:: delete\_ssl
  - SSL :: disable\_mail\_sni

SSL:: enable\_mail  
\_sni

SSL:: fetch\_best\_f  
or\_domain

SSL:: fetch\_cert\_in  
fo

SSL:: fetch\_certific  
ates\_for\_fqdns

SSL:: fetch\_key\_a  
nd\_cabundle\_for\_  
certificate

SSL:: find\_certifica  
tes\_for\_key

SSL:: find\_csrs\_for  
\_key

SSL:: generate\_ce  
rt

SSL:: generate\_cs  
r

SSL:: generate\_ke  
y

SSL:: get\_autossl\_  
excluded\_domains

SSL:: get\_autossl\_  
pending\_queue

SSL:: get\_autossl\_  
problems

SSL:: get\_cabundl  
e

SSL:: get\_cn\_nam  
e

SSL:: install\_ssl

SSL:: installed\_ho  
st

SSL:: installed\_ho  
sts

SSL:: is\_autossl\_c  
heck\_in\_progress

SSL:: is\_mail\_sni\_  
supported

SSL:: is\_sni\_supp  
orted

SSL:: list\_certs

SSL:: list\_csrs

SSL:: list\_keys

SSL:: list\_ssl\_item  
s

SSL:: mail\_sni\_sta  
tus

SSL:: rebuild\_mail  
\_sni\_config

SSL:: rebuildssldb

SSL:: remove\_aut  
ossl\_excluded\_do  
mains

SSL:: set\_autossl\_  
excluded\_domains

SSL:: set\_cert\_frie  
ndly\_name

SSL:: set\_csr\_frien  
dly\_name

SSL:: set\_key\_frie  
ndly\_name

SSL:: set\_primary  
\_ssl

SSL:: set\_ssl\_shar  
e

SSL:: show\_cert

SSL:: show\_csr

SSL:: show\_key

SSL:: start\_autossl\_  
\_check

SSL:: toggle\_ssl\_r  
edirects\_for\_doma  
ins

SSL:: upload\_cert

SSL:: upload\_key

▼ StatsBar

StatsBar:: get\_stat  
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

▼ SubDomain

SubDomain:: adds  
ubdomain

▼ Themes

Themes:: get\_the  
me\_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create\_fu  
ll\_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate\_user\_configuration

TwoFactorAuth:: get\_user\_configuration

TwoFactorAuth:: remove\_user\_configuration

TwoFactorAuth:: set\_user\_configuration

▼ UserManager

UserManager:: check\_account\_conflicts

UserManager:: create\_user

UserManager:: delete\_user

UserManager:: dismiss\_user

UserManager:: edit\_user

UserManager:: list\_users

UserManager:: lookup\_service\_account

UserManager:: lookup\_user

UserManager:: merge\_service\_account

UserManager:: unlink\_service\_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create



VersionControlDeployment:: **delete**

VersionControlDeployment:: **retrieve**

▼ **WebDisk**

WebDisk:: **delete\_user**

WebDisk:: **set\_homedir**

WebDisk:: **set\_password**

WebDisk:: **set\_permissions**

▼ **WebmailApps**

WebmailApps:: **list\_webmailapps**

▼ **WebVhosts**

WebVhost:: **list\_domains**

WebVhost:: **list\_ssl\_capable\_domains**

▼ **WordPressBackup**

WordPressBackup:: **any\_running**

WordPressBackup:: **cancel**

WordPressBackup:: **cleanup**

WordPressBackup:: **get\_available\_backups**

WordPressBackup:: **is\_running**

WordPressBackup:: **start**

▼ **WordPressInstance**

**Manager**

WordPressInstanceManager:: **cancel\_scan**

WordPressInstanceManager:: **cleanup\_scan**

WordPressInstanceManager:: **change\_admin\_password**

WordPressInstanceManager:: **configure\_autoupdate**

WordPressInstanceManager:: **get\_api\_version**

WordPressInstanceManager:: **get\_in**

stance\_by\_id

WordPressInstanceManager::get\_instances

WordPressInstanceManager::get\_latest\_wordpress\_version\_from\_wordpress\_org

WordPressInstanceManager::get\_scan\_results

WordPressInstanceManager::is\_installable\_addon\_available

WordPressInstanceManager::start\_scan

▼ WordPressRestore

WordPressRestore::any\_running

WordPressRestore::cleanup

WordPressRestore::start