

cPanel API 2 Functions - Branding::delpkg

Guide to cPanel API 2

Return Data

Filter and Sort Output

Paginate Output

Output Columns

Calls from the WHM API

cPanel Tags (deprecated)

AddonDomain:: adddomain

omain

AddonDomain:: deladdondomain

AddonDomain:: listaddondomains

Backups

Backups:: listfullbackups

Bandwidth

Bandwidth:: addhttpbandwidth

Bandwidth:: getbwdata

Bandwidth:: gethourlyaveragebwoveryear

BoxTrapper

BoxTrapper:: accountmanagelist

Branding

Branding:: addbrandingobj

Branding:: applist

Branding:: brandingeditor

Branding:: createpkg

Branding:: cssmerge

Branding:: delbrandingobj

Branding:: delpkg

Description

This function deletes a branding package.

Note:

cPanel API 2's `Branding` module **only** modifies data for the x3 theme. To customize the Paper Lantern theme, use `UAPI` functions. For more information, read our [Guide to cPanel Interface Customization and Branding](#) documentation.

Warning:

We **strongly** recommend that you use `UAPI` instead of cPanel API 2. However, no equivalent `UAPI` function exists.

`AddonDomain`

Examples

WHM API (JSON)

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?cpanel_jsonapi_user=user&cpanel_jsonapi_api_version=2&cpanel_jsonapi_module=Branding&cpanel_jsonapi_function=delpkg&pkg="mypkg"
```

Note:

For more information, read our [Calls from the WHM API](#) documentation.

Function information

About this module

The `Branding` module accesses cPanel's theming system.

- CSVImport:: uploadimport
- Contactus:: isenabled
 - Contactus:: sendcontact
 - Cron:: add_line
 - Cron:: edit_line
 - Cron:: fetchcron
 - Cron:: get_email
 - Cron:: listcron
 - Cron:: remove_line
 - Cron:: set_email
 - CustInfo:: contactemails
 - CustInfo:: contactprefs
 - CustInfo:: displaycontactinfo
 - CustInfo:: savecontactinfo
 - DBmap:: status
 - DBmap:: version
 - DKIMUI:: available
 - DKIMUI:: getrecords
 - DKIMUI:: install
 - DKIMUI:: installed
 - DKIMUI:: uninstall
 - DenyIp:: listdenyips
 - DiskCounter:: disk_counter
 - DiskUsage:: buildcache
 - DiskUsage:: clearcache
 - DiskUsage:: fetch_raw_disk_usage
 - DiskUsage:: fetchdiskusage

LiveAPI Perl Module

```

my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Delete the mypkg
branding package.
my
$delete_branding_pkg
= $cpliveapi->api2(
  'Branding',
  'delpkg',
  {
    'pkg' =>
'mypkg',
  }
);

```

Note:
For more information, read our [Guide to the LiveAPI System](#).

cPanel Tag System (deprecated)

Warnings:

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Deprecated cPanel Tag Usage](#) documentation.

- cPanel API 2 Functions - Branding: showpackages — This function lists available branding packages.
- cPanel API 2 Functions - Branding: createpkg — This function creates a branding package's directory.
- cPanel API 2 Functions - Branding: delpkg — This function deletes a branding package.

DiskUsage:: fetchdiskusagewithextras

▼ DnsLookup

DnsLookup:: name2ip

▼ DomainLookup

DomainLookup:: countbaseddomains

DomainLookup:: getbaseddomains

DomainLookup:: getdocroot

DomainLookup:: getdocroots

DomainLookup:: getmaindomain

▼ Email

Email:: accountname

Email:: adddomainforward

Email:: addforward

Email:: addmx

Email:: addpop

Email:: browseboxes

Email:: changemx

Email:: checkmaindiscard

Email:: clearpopcache

Email:: deletefilter

Email:: delforward

Email:: delmx

Email:: delpop

Email:: disablefilter

Email:: editquota

Email:: enablefilter

Email:: fetchautosponder

Email:: fetchcharmaps

Email:: filteractions

Email:: filterlist

Email:: filtername

Email:: filterrules

Email:: get_archiving_configuration

▼ Command Line

```
cpapi2
--user=username
Branding delpkg
pkg=mypkg
```

Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- You **must** run the `--user=username` command.
- For more information and additional output options, read our [Guide to cPanel API 2](#) documentation or run the `cpapi2 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapi2` command:

```
/usr/local
/cpanel/bin/cpapi2
```

▼ Output (JSON)

```
{
  "cpanelresult": {
    "apiversion": 2,
    "func": "delpkg",
    "data": [
      {
        "pkg":
"mypkg"
      }
    ],
    "event": {
      "result": 1
    },
    "module":
"Branding"
  }
}
```

- cPanel API 2 Functions - Branding: getbrandingpkg — This function retrieves the current branding package's name.

Email: [get_archiving_default_configuration](#)

Email: [get_archiving_types](#)

Email: [get_default_email_quota](#)

Email: [get_email_signing](#)

Email: [get_max_email_quota](#)

Email: [getabsbrowsedir](#)

Email: [getalwaysaccept](#)

Email: [getdiskusage](#)

Email: [getmxcheck](#)

Email: [has_delegated_mailman_lists](#)

Email: [list_system_filter_info](#)

Email: [listaliasbackups](#)

Email: [listautoresponders](#)

Email: [listdefaultaddresses](#)

Email: [listdomainforwards](#)

Email: [listfilterbackups](#)

Email: [listfilters](#)

Email: [listforwards](#)

Email: [listlists](#)

Email: [listmaildomains](#)

Email: [listmx](#)

Email: [listmxs](#)

Email: [listpops](#)

Email: [listpopssingle](#)

Email: [listpopswithdisk](#)

Email: [listpopswithimage](#)

Email: [loadfilter](#)

Email: [passwdpop](#)

Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

Input	Type	Description	Possible values	Example
pkg	string	Required The branding package name.	The name of a branding package that the cPanel account owns.	mypkg

Returns

Return	Type	Description	Possible values	Example
error	string	An error message. Note : This function only returns an error value if it failed.	A string that describes the error.	/home/example/cpanelbranding/x3/mypkg does not exist!
pkg	string	The branding package name.	The pkg parameter's value.	mypkg
result	Boolean	Whether the function succeeded.	<ul style="list-style-type: none">1 — The function succeeded.0 — The function failed.	1

Email:: reorderfilter
s

Email:: set_archivi
ng_configuration

Email:: set_archivi
ng_default_configu
ration

Email:: set_email_
signing

Email:: setalwaysa
ccept

Email:: setdefaulta
ddress

Email:: setmxchec
k

Email:: storefilter

Email:: tracefilter

▼ EmailTrack

EmailTrack:: searc
h

EmailTrack:: stats

EmailTrack:: trace

▼ Encoding

Encoding:: get_en
codings

Encoding:: guess_
file

Encoding:: guess_
file_opts

▼ FSTest

FSTest:: dirisempt
y

▼ Fileman

Fileman:: autocom
pletedir

Fileman:: fileop

Fileman:: getabsdir

Fileman:: getdir

Fileman:: getdiracti
ons

Fileman:: getdiskin
fo

Fileman:: geteditty
pe

Fileman:: getfileact
ions

Fileman:: getpath

Fileman:: listfiles

Fileman:: mkdir

Fileman:: mkfile

Fileman:: savefile

Fileman:: search

Fileman:: statfiles

Fileman:: uploadfiles

Fileman:: viewfile

▼ ForcePassword

ForcePassword:: get_force_password_flags

ForcePassword:: update_force_password_flags

▼ Frontpage

Frontpage:: fpenabled

Frontpage:: list

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: listftp

Ftp:: listftpsessions

Ftp:: listftpwithdisk

Ftp:: passwd

Ftp:: setquota

▼ Gpg

Gpg:: listgpgkeys

Gpg:: listsecretgpgkeys

Gpg:: number_of_private_keys

Gpg:: number_of_public_keys

▼ Htaccess

Htaccess:: listuser

Htaccess:: listusers

▼ HttpUtils

HttpUtils:: getdirindices

▼ ImageManager

ImageManager:: thumbnail

▼ LVEInfo

LVEInfo:: getUsage

▼ LangMods

LangMods:: getarchname

LangMods:: getkey

LangMods:: getpre
fix

LangMods:: install

LangMods:: langlis
t

LangMods:: list_av
ailable

LangMods:: list_in
stalled

LangMods:: magic
_status

LangMods:: pre_ru
n

LangMods:: search

LangMods:: setup

LangMods:: uninst
all

LangMods:: updat
e

▼ LeechProtect

LeechProtect:: set
up

▼ Locale

Locale:: get_encod
ing

Locale:: get_html_
dir_attr

Locale:: get_locale
_name

Locale:: get_user_
ocale

Locale:: get_user_
ocale_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse
r

Logaholic:: adduse
rprofile

Logaholic:: deleteu
ser

Logaholic:: deleteu
serprofile

Logaholic:: edituse
r

Logaholic:: fetchus
er

Logaholic:: listuser
profiles

Logaholic:: logahol

iclink

Logaholic:: proces
sstats

▼ Mime

Mime:: list_hotlinks

Mime:: listhandlers

Mime:: listmime

Mime:: listredirects

Mime:: redirectna
me

Mime:: redirecturln
ame

▼ MysqlFE

MysqlFE:: authoriz
ehost

MysqlFE:: change
dbuserpassword

MysqlFE:: created
b

MysqlFE:: created
buser

MysqlFE:: dbusere
xists

MysqlFE:: deautho
rizehost

MysqlFE:: deleted
b

MysqlFE:: deleted
buser

MysqlFE:: getalldb
sinfo

MysqlFE:: getalldb
usersanddbs

MysqlFE:: getdbus
erprivileges

MysqlFE:: getdbus
ers

MysqlFE:: gethosts

MysqlFE:: getmys
qlprivileges

MysqlFE:: getmys
qlserverprivileges

MysqlFE:: has_my
cnf_for_cpuser

MysqlFE:: listdbs

MysqlFE:: listdbsb
ackup

MysqlFE:: listhosts

MysqlFE:: listusers

MysqlFE:: listusers

indb

MysqlFE:: revoked
buserprivileges

MysqlFE:: setdbu
erprivileges

MysqlFE:: userdbp
rivs

▼ MysqlOptimizer

MysqlOptimizer:: f
etch_slow_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does_news
_exist

News:: does_news
_type_exist

News:: get_news

▼ PHPINI

PHPINI:: getallopti
ons

PHPINI:: getoption
s

▼ Park

Park:: listaddondo
mains

Park:: listparkeddo
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change_
password

Passwd:: set_dige
st_auth

▼ PasswdStrength

PasswdStrength::
appstrengths

PasswdStrength::
get_password_stre
ngth

PasswdStrength::
get_required_stren
gth

▼ Postgres

Postgres:: listdbs

Postgres:: listusers

Postgres:: listusers
indb

Postgres:: userexists

▼ Rand

Rand:: getranddata

▼ Resellers

Resellers:: get_sub_accounts

▼ RoR

RoR:: addapp

RoR:: changeapp

RoR:: importrails

RoR:: listapps

RoR:: listrewrites

RoR:: needsimport

RoR:: removeapp

RoR:: removerewrite

RoR:: restartapp

RoR:: setuprewrite

RoR:: softrestartapp

RoR:: startapp

RoR:: stopapp

▼ SetLang

SetLang:: setlocale

▼ SourceIPCheck

SourceIPCheck:: addip

SourceIPCheck:: delip

SourceIPCheck:: getaccount

SourceIPCheck:: listips

SourceIPCheck:: loadsecquestions

SourceIPCheck:: resetsecquestions

SourceIPCheck:: samplequestions

SourceIPCheck:: savequestions

▼ SPFUI

SPFUI:: available

SPFUI:: count_settings

SPFUI:: entries_complete

SPFUI:: get_raw_record

SPFUI:: getmainserverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list_settings

SPFUI:: load_current_values

SPFUI:: uninstall

▼ SSH

SSH:: authkey

SSH:: converttopk

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey_legacy

SSH:: importkey

SSH:: listkeys

▼ SSL

SSL:: fetchcertificate

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcnname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

▼ SSLInfo

SSLInfo:: fetchinfo

▼ StatCache

StatCache:: clearcache

▼ Stats

- Stats:: getmonthly bandwidth
- Stats:: getmonthly domainbandwidth
- Stats:: getthismont hsbwusage
- Stats:: lastapache hits
- Stats:: lastvisitors
- Stats:: listanalog
- Stats:: listawstats
- Stats:: listlastvisitors
- Stats:: listrawlogs
- Stats:: listurchin
- Stats:: listwebalizer

▼ StatsBar

- StatsBar:: getrowcounter
- StatsBar:: rowcounter
- StatsBar:: setrowcounter
- StatsBar:: stat

▼ SubDomain

- SubDomain:: adds ubdomain
- SubDomain:: changedocroot
- SubDomain:: delsubdomain
- SubDomain:: getservedsubdomains
- SubDomain:: listsubdomains
- SubDomain:: validregex

▼ Themes

- Themes:: apply_new_theme
- Themes:: does_cpanel_theme_exist
- Themes:: get_available_themes
- Themes:: get_themes_list
- Themes:: restore_saved_theme

▼ UI

- UI:: dynamicincludelist
- UI:: includelist
- UI:: listform
- UI:: paginate
- UI:: paginate_list

▼ UserHttpUtils

- UserHttpUtils:: getdirindices

▼ WebDisk

- WebDisk:: addwebdisk
- WebDisk:: delwebdisk
- WebDisk:: hasdigest
- WebDisk:: listwebdisks
- WebDisk:: passwdwebdisk
- WebDisk:: set_digest_auth
- WebDisk:: set_home_dir
- WebDisk:: set_perms
- WebDisk:: setstatus

▼ WebmailApps

- WebmailApps:: listwebmailapps

▼ ZoneEdit

- ZoneEdit:: add_zone_record
- ZoneEdit:: edit_zone_record
- ZoneEdit:: fetch_cpanel_generated_domains
- ZoneEdit:: fetchzone
- ZoneEdit:: fetchzone_records
- ZoneEdit:: fetchzones
- ZoneEdit:: get_zone_record
- ZoneEdit:: remove_zone_record
- ZoneEdit:: resetzone

