

UAPI Functions - Themes::get_theme_base

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup::fullbacku
p_to_ftp

Backup::fullbacku
p_to_homedir

Backup::fullbacku
p_to_scp_with_key

Backup::fullbacku
p_to_scp_with_password

Backup::list_backups

Bandwidth

Bandwidth::get_enabled_protocols

Bandwidth::get_retention_periods

Bandwidth::query

Batch

Batch::strict

Brand

Brand::read

Branding

Branding::file

Branding::get_applications

Branding::get_application_information

Branding::get_available_applications

Branding::get_info

Description

This function returns the cPanel account's base theme. If you have modified the current theme, this function returns the name of the theme that you modified.

Note:

In cPanel & WHM version 66 and later, the `/scripts/modify_accounts` script allows you to modify the style and theme for many or all accounts on the server. For more information, read our [The modify_accounts Script documentation](#).

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/Themes/get_theme_base
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI documentation](#).

Function information

About this module

The Themes module manages the account's theme.

About UAPI

UAPI accesses and modifies data for cPanel accounts.

information_for_applications

Branding:: image

Branding:: include

Branding:: spritelist

▼ CacheBuster

CacheBuster:: read

CacheBuster:: update

▼ Chkserverd

Chkserverd:: get_exit_ports

Chkserverd:: get_exit_ports_ssl

▼ Chrome

Chrome:: get_domain

▼ Contactus

Contactus:: is_enabled

▼ cPAddons

cPAddons:: get_available_addons

cPAddons:: get_instance_settings

cPAddons:: list_addon_instances

▼ cPGreyList

cPGreyList:: disable_all_domains

cPGreyList:: disable_domains

cPGreyList:: enable_all_domains

cPGreyList:: enable_domains

cPGreyList:: has_greylisting_enabled

cPGreyList:: list_domains

▼ DAV

DAV:: disable_shared_global_addressbook

DAV:: enable_shared_global_addressbook

DAV:: get_calendar_contacts_config

DAV:: has_shared_global_addressbook

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.
```

```
// List the account's  
current theme.  
$get_theme_base =  
$cpanel->uapi(  
    'Themes',  
    'get_theme_base'  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# List the account's  
current theme.  
my $get_theme_base =  
$cpliveapi->uapi(  
    'Themes',  
    'get_theme_base',  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Notes:

- Theme
- Username

Find
a
function

DAV:: is_dav_service_enabled

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

▼ cPanel Template Toolkit

```
<!-- List the
account's current
theme. -->
[% data = execute(
'Themes',
'get_theme_base' );
%]
[% FOREACH q = data
%]
    <p>
        [% q %]
    </p>
[% END %]
```

Note:

For more information, read our [Guide to Template Toolkit](#) documentation.

▼ Command Line

```
uapi --user=username
Themes get_theme_base
```

Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/
uapi
```

- [Change Style](#)
- [Web Template Editor](#)
- [Customization](#)
- [Tutorial - Customize the WHM User Interface with CSS](#)
— This tutorial customizes the appearance of a WHM interface theme.
- [cPanel API 1 Functions - Branding:file](#)
— This function searches for a file within a theme and returns its URL.

Email:: add_spam_filter

Email:: browse_mailbox

Email:: change_mx

Email:: check_fast_mail

Email:: check_pipe_forwarder

Email:: delete_auto_responder

Email:: delete_domain_forwarder

Email:: delete_filter

Email:: delete_for_warder

Email:: delete_held_messages

Email:: delete_list

Email:: delete_mx

Email:: delete_pop

Email:: disable_filter

Email:: disable_mailbox_autocreate

Email:: disable_spam_assassin

Email:: disable_spam_autodelete

Email:: disable_spam_box

Email:: dispatch_client_settings

Email:: edit_pop_quota

Email:: enable_filter

Email:: enable_mailbox_autocreate

Email:: enable_spam_assassin

Email:: enable_spam_box

Email:: fetch_charmaps

Email:: fts_rescan_mailbox

Email:: generate_mailman_otp

Email:: get_auto_r

Output (JSON)

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "metadata": {},
  "data":
  "paper_lantern"
}
```

Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

This function does not accept parameters.

Returns

Return	Type	Description	Possible values	Example
data	string	The cPanel account's base theme.	The function returns only one of the following strings: <ul style="list-style-type: none"> paper_lantern unknown 	paper_lantern

Note: The function returns unknown

esponder
Email:: get_charts
Email:: get_client_settings
Email:: get_default_email_quota
Email:: get_default_email_quota_mib
Email:: get_disk_usage
Email:: get_filter
Email:: get_held_message_count
Email:: get_mailbox_autocreate
Email:: get_mailman_delegates
Email:: get_main_account_disk_usage
Email:: get_main_account_disk_usage_bytes
Email:: get_max_email_quota
Email:: get_max_email_quota_mib
Email:: get_pop_quota
Email:: get_spam_settings
Email:: get_webmail_settings
Email:: has_delegated_mailman_lists
Email:: has_plaintext_authentication
Email:: hold_outgoing
Email:: is_integer
Email:: list_auto_responders
Email:: list_default_address
Email:: list_domain_forwarders
Email:: list_filters
Email:: list_filters_backups
Email:: list_forward

n
k
n
o
w
n
w
h
e
n
i
t
c
a
n
n
o
t
d
e
t
e
r
m
i
n
e
t
h
e
b
a
s
e
t
h
e
m
e
t
h
a
t
y
o
u
m
o
d
i
f
i
e
d
t
o
c
r
e
a
t
e
t
h
e
c
u
s
t
o
m
t
h
e
m

ers

Email:: list_forward
ers_backups

Email:: list_lists

Email:: list_mail_d
omains

Email:: list_mxs

Email:: list_pops

Email:: list_pops_
with_disk

Email:: list_system
_filter_info

Email:: passwd_list

Email:: passwd_po
p

Email:: release_ou
tgoing

Email:: remove_m
ailman_delegates

Email:: reorder_filt
ers

Email:: set_always
_accept

Email:: set_default
_address

Email:: set_list_pri
vacy_options

Email:: stats_db_st
atus

Email:: store_filter

Email:: suspend_in
coming

Email:: suspend_lo
gin

Email:: suspend_o
utgoing

Email:: trace_filter

Email:: unsuspend
_incoming

Email:: unsuspend
_login

Email:: unsuspend
_outgoing

Email:: verify_pass
word

▼ EmailAuth

EmailAuth:: disabl
e_dkim

EmailAuth:: enable
_dkim

			e .	
--	--	--	--------	--

EmailAuth:: ensure
_dkim_keys_exist

EmailAuth:: fetch_
dkim_private_keys

EmailAuth:: install
_dkim_private_key
s

EmailAuth:: install
_spf_records

EmailAuth:: validat
e_current_dkims

EmailAuth:: validat
e_current_ptrs

EmailAuth:: validat
e_current_spfs

ExternalAuthenticat ion

ExternalAuthentic
ation:: add_authn_li
nk

ExternalAuthentic
ation:: configured_
modules

ExternalAuthentic
ation:: get_authn_lin
ks

ExternalAuthentic
ation:: has_external
_auth_modules_co
nfigured

ExternalAuthentic
ation:: remove_auth
n_link

Features

Features:: get_feat
ure_metadata

Features:: has_fea
ture

Features:: list_feat
ures

Fileman

Fileman:: autocom
pletedir

Fileman:: empty_tr
ash

Fileman:: get_file_
content

Fileman:: get_file_i
nformation

Fileman:: list_files

Fileman:: save_file
_content

Fileman:: transcod
e

Fileman:: upload_files

▼ Ftp

Ftp:: add_ftp

Ftp:: allows_anonymous_ftp

Ftp:: allows_anonymous_ftp_incoming

Ftp:: delete_ftp

Ftp:: ftp_exists

Ftp:: get_ftp_daemon_info

Ftp:: get_port

Ftp:: get_quota

Ftp:: get_welcome_message

Ftp:: kill_session

Ftp:: list_ftp

Ftp:: list_ftp_with_disk

Ftp:: list_sessions

Ftp:: passwd

Ftp:: server_name

Ftp:: set_anonymous_ftp

Ftp:: set_anonymous_ftp_incoming

Ftp:: set_homedir

Ftp:: set_quota

Ftp:: set_welcome_message

▼ Integration

Integration:: fetch_url

▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

▼ LangPHP

LangPHP:: php_get_domain_handler

LangPHP:: php_get_impacted_domains

LangPHP:: php_get_installed_versions

LangPHP:: php_get_system_default_version

LangPHP:: php_get_vhost_versions

LangPHP:: php_ini_get_user_basic_directives

LangPHP:: php_ini_get_user_content

LangPHP:: php_ini_get_user_paths

LangPHP:: php_ini_set_user_basic_directives

LangPHP:: php_ini_set_user_content

LangPHP:: php_set_vhost_versions

▼ LastLogin

LastLogin:: get_last_or_current_logged_in_ip

▼ Locale

Locale:: get_attributes

▼ Mailboxes

Mailboxes:: expunge_messages

Mailboxes:: expunge_messages_for_mailbox_guid

Mailboxes:: get_mailbox_status

Mailboxes:: has_utf8_mailbox_names

Mailboxes:: set_utf8_mailbox_names

▼ Market

Market:: cancel_pending_ssl_certificate

Market:: create_shopping_cart

Market:: get_all_products

Market:: get_certificate_status_details

Market:: get_login_url

Market:: get_pending_ssl_certificates

Market:: get_provider_specific_dcv_constraints

Market:: get_providers_list

Market:: get_ssl_certificate_if_available

Market:: process_ssl_pending_queue

Market:: request_ssl_certificates

Market:: set_status_of_pending_queue_items

Market:: set_url_after_checkout

Market:: validate_login_token

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: delete_handler

Mime:: delete_hotlink

Mime:: delete_mime

Mime:: delete_redirect

Mime:: list_handlers

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirects

Mime:: redirect_info

▼ ModSecurity

ModSecurity:: disable_all_domains

ModSecurity:: disable_domains

ModSecurity:: enable_all_domains

ModSecurity:: enable_domains

ModSecurity:: has_modsecurity_installed

ModSecurity:: list_domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_note

Mysql :: check_database

Mysql:: create_database

Mysql:: create_user

Mysql:: delete_database

Mysql:: delete_host

Mysql:: delete_user

Mysql:: get_host_notes

Mysql:: get_privileges_on_database

Mysql:: get_restrictions

Mysql:: get_server_information

Mysql:: locate_server

Mysql:: rename_database

Mysql:: rename_user

Mysql:: repair_database

Mysql:: revoke_access_to_database

Mysql:: set_password

Mysql:: set_privileges_on_database

▼ Notifications

Notifications:: get_notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_relati
ative_uri

▼ PassengerApps

PassengerApps:: d
isable_application

PassengerApps:: e
dit_application

PassengerApps:: e
nable_application

PassengerApps:: e
nsure_deps

PassengerApps:: li
st_applications

PassengerApps:: r
egister_application

PassengerApps:: u
nregister_applicati
on

▼ PasswdStrength

PasswdStrength::
get_required_stren
gth

▼ Personalization

Personalization::se
t

Personalization ::g
et

▼ Postgresql

Postgresql:: create
_database

Postgresql:: create
_user

Postgresql:: delete
_database

Postgresql:: get_re
strictions

Postgresql:: grant_
all_privileges

Postgresql:: renam
e_database

Postgresql:: renam
e_user

Postgresql:: renam
e_user_no_passw
ord

Postgresql:: revok
e_all_privileges

Postgresql:: set_p
assword

▼ Pushbullet

Pushbullet:: send_
test_message

- ▼ Quota
 - Quota:: get_quota_info
- ▼ Resellers
 - Resellers:: list_accounts
- ▼ ResourceUsage
 - ResourceUsage:: get_usages
- ▼ Restore
 - Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- ▼ Session
 - Session:: create_temp_user
- ▼ SiteTemplates
 - SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- ▼ SpamAssassin
 - SpamAssassin :: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key

SSL:: delete_ssl

SSL:: disable_mail_sni

SSL:: enable_mail_sni

SSL:: fetch_best_for_domain

SSL:: fetch_cert_info

SSL:: fetch_certificates_for_fqdns

SSL:: fetch_key_and_cabundle_for_certificate

SSL:: find_certificates_for_key

SSL:: find_csrs_for_key

SSL:: generate_certificate

SSL:: generate_csr

SSL:: generate_key

SSL:: get_autossl_excluded_domains

SSL:: get_autossl_pending_queue

SSL:: get_autossl_problems

SSL:: get_cabundle

SSL:: get_cn_name

SSL:: install_ssl

SSL:: installed_host

SSL:: installed_hosts

SSL:: is_autossl_check_in_progress

SSL:: is_mail_sni_supported

SSL:: is_sni_supported

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_items

SSL:: mail_sni_status

tus

SSL:: rebuild_mail
_snl_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDepl

oyment

VersionControlDep
loyment:: **create**

VersionControlDep
loyment:: **delete**

VersionControlDep
loyment:: **retrieve**

▼ WebDisk

WebDisk:: **delete_**
user

WebDisk:: **set_ho**
medir

WebDisk:: **set_pas**
sword

WebDisk:: **set_per**
missions

▼ WebmailApps

WebmailApps:: **list**
webmailapps

▼ WebVhosts

WebVhost:: **list_do**
mains

WebVhost:: **list_ssl**
_capable_domains

▼ WordPressBackup

WordPressBackup
:: **any_running**

WordPressBackup
:: **cancel**

WordPressBackup
:: **cleanup**

WordPressBackup
:: **get_available_ba**
ckups

WordPressBackup
:: **is_running**

WordPressBackup
:: **start**

▼ WordPressInstance

Manager

WordPressInstanc
eManager:: **cancel**
_scan

WordPressInstanc
eManager:: **cleanu**
p_scan

WordPressInstanc
eManager:: **chang**
e_admin_passwor
d

WordPressInstanc
eManager:: **config**
ure_autoupdate

WordPressInstanc
eManager:: **get_ap**

i_version

WordPressInstanceManager:: **get_instance_by_id**

WordPressInstanceManager:: **get_instances**

WordPressInstanceManager:: **get_latest_wordpress_version_from_wordpress_org**

WordPressInstanceManager:: **get_scan_results**

WordPressInstanceManager:: **is_installable_addon_available**

WordPressInstanceManager:: **start_scan**

▼ WordPressRestore

WordPressRestore:: **any_running**

WordPressRestore:: **cleanup**

WordPressRestore:: **start**